Suppose users share a 100 Mbps link. Also suppose each user requires 10 Mbps when transmitting, but each user transmits only 25% of the time.

- (a) When circuit switching is used, how many users can be supported?
- (b) For the remainder of the problem, suppose packet switching is used. Find the probability that a given user is transmitting.
- (c) Suppose there are 100 users. Find the probability that at any given time, exactly n users are transmitting simultaneously. (Hint: Use the binomial distribution)
- (d) Find the probability that there are 21 or more users transmitting simultaneously (Hint: only the formula is required).

Queuing delay.

- (a) Suppose N packets arrive simultaneously to a link at which no packets are currently being transmitted or queued. Each packet is of length L and the link has transmission rate R. What is the average queuing delay for N packets?
- (b) Now suppose that a batch of packets arrives to the link every  $\frac{LN}{R}$  seconds and each batch has N packets. What is the average queuing delay of a packet?

Review the car-caravan analogy in lecture #1 slides (for Chapter 1). Assume a propagation speed of 100 km/h.

- (a) Suppose the caravan (5 cars) travels 100 km, beginning in front of one tollbooth, passing through a second tollbooth, and finishing just after a third tollbooth. The distance between two tollbooths is 50 km. Each car takes 12 sec to serve. The caravan can only dispatch a tollbooth after all cars in the caravan are served. What is the end-to-end delay (from when the caravan is lined up before 1st tollbooth till the caravan is served by the 3rd tollbooth)?
- (b) Repeat (a), now assuming that there are 8 cars in the caravan instead of 5.

In this problem, we consider sending real-time voice from Host A to Host B over a packet-switched network (VoIP). Host A converts analog voice to a digital 64 Kbps bit stream on the fly, which means it take 1 second to create 64K bits from the analog signal. Host A then groups the bits into 56-byte packets. There is one link between Hosts A and B; its transmission rate is 2 Mbps and its propagation delay is 10 msec. As soon as Host A gathers a 56-byte packet, it sends it to Host B. As soon as Host B receives an entire packet, it converts the packet's bits to an analog signal. How much time elapses from the time the first bit of one packet is created (from the original analog signal at Host A) until the packet is received at Host B)?

