

AURORA SV Red

New Generation Aurora series

G2G's new generation Aurora SV LED modules are innovatively designed as an optimal solution for outdoor and indoor lighting. Ideal for channel letters, illuminated light boxes, and decorative architectural lighting.



5 Year



RECOMMENDED COVERAGE CHART

Depth	5"	6"	7"	8"
Spacing	6"	7"	8"	9"

-40° to +60°C

LED MODULE SPECIFICATIONS

Working mode Constant Voltage Technology **Fastening** 3M VHB double face tape and Max Mods (Series) Full 50W load mechanical mounting options. **Viewing Angle** 120° UV or IR Protected **Optical Structure** CT Red 200 modules per bag, 5 bags per case **Packaging** CRI >70 **Protection Grade** IP68 wet-Location **LEDs Per Module** Certifications UL and cUL Recognized

Warranty

LED Module Dimension 2.2"L x 0.57"W x 0.26"H

LED MODULE PRODUCT OPTIONS LIST

Model	Voltage	Power	Current	Modules Per Ft	CT	Lumens	Qty 60W Power Supply	Viewing Angle
Aurora SV Red	12VDC	0.50W/Module	42mA	3	Red	35 Lm/Ft	120Modules/31Ft	120 °

LED MODULE DIMENSIONS

Operating Temp





