G2G ArRay SF
Sign Box Lighting
Easier Than Ever Before

Bringing you a revolution in sign box lighting, G2G introduces the ArRay system. Our goal is to help you reduce energy consumption and maintenance costs in applications where a high quality sign box lighting replacement is required. ArRay SF module is designed for cabinets as shallow as 3".

E344189

IP66

RECOMMENDED COVERAGE CHART

Depth	4"	5"	6"	7"	8"
Spacing	12"	12"	12-15"	12-15"	12-15"

LED MODULE SPECIFICATIONS

Working mode	Constant Voltage Technology	**LED Module Dimension**	9.45"L x 4.45"W x 0.25"H
Max Mods (Series)	Full 30W load	**Optical Structure**	UV or IR Protected
Viewing Angle	160°	**Packaging**	60 modules per case
CT	7500K	**Protection Grade**	IP66 wet-Location
CRI	>70	**Certifications**	UL and cUL Recognized
LEDs Per Module	3	**Warranty**	5 Year
Operating Temp	-40° to +60°C		

LED MODULE PRODUCT OPTIONS LIST

Model	Voltage	Power	Current	Modules Per Ft	CT	Lumens	Qty 60W Power Supply	Viewing Angle
ArRay SF	12VDC	1.0W/Module	83mA	3	7500K	105 Lm/Module	60 Modules	160°

LED MODULE DIMENSIONS

0.41"

0.43"

4.45"

0.90"

0.25"

9.45"