

G2G AnPro 160

AnPro series G2G Led product

G2G's AnPro LED modules provide a 155° wide viewing angle. This design offers an energy efficient and cost effective solution to sign lighting, and enables the sign designer to control operating costs. Because of it's high lumen output, the AnPro helps you create brighter and more evenly illuminated sign using less product. Bringing you more flexibility in installation, the AnPro makes custom sign designs simpler than ever before.



cULus IP67
E344189

RECOMMENDED COVERAGE CHART

| Depth | 4" | 5" | 6" | 7" | 8" |
|---------|----|----|-----|-----|-----|
| Spacing | 6" | 8" | 10" | 12" | 15" |

LED MODULE SPECIFICATIONS

| | |
|-----------------------------|-----------------------------|
| Working mode | Constant Voltage Technology |
| Max Mods (Series) | Full 90W load |
| Viewing Angle | 160° |
| CT | 6300K/7500K |
| CRI | >70 |
| LEDs Per Module | 2 |
| Operating Temp | -40° to +60°C |
| LED Module Dimension | 2.75"L x 0.78"W x 0.23"H |

| | |
|--------------------------|--|
| Fastening | 3M VHB double face tape and mechanical mounting options. |
| Optical Structure | UV or IR Protected |
| Packaging | 150 modules per bag, 5 bags per case |
| Protection Grade | IP67 wet-Location |
| Certifications | UL and cUL Recognized |
| Warranty | 5 Year |

LED MODULE PRODUCT OPTIONS LIST

| Model | Voltage | Power | Current | Modules Per Ft | CT | Lumens | Qty 60W Power Supply | Viewing Angle |
|---------------|---------|-------------|---------|----------------|-------------|-----------|----------------------|---------------|
| G2G AnPro 160 | 12VDC | 1.2W/Module | 100mA | 2 | 7500K/6300K | 270 Lm/Ft | 50 Mods/25 Ft | 160° |

LED MODULE DIMENSIONS

