

G2GFL10W

LED Flood Light Series

With its integrated applications of LED light sources and its unique circuit control design, G2G's Floodlight models conserve more than 80% of energy consumption. Given its ultra-bright, high color rendering index, our Floodlight fixtures are the latest style in efficient outdoor lighting, all while demonstrating a long lasting product life of over 50,000 hours. Ideal for outdoor decorative building and monument lighting, industrial lighting, advertisement illumination, increasing sign visibility, road lighting and street lamp distribution, our LED Floodlights satisfy a variety of applications.



IP65

LED FLOOD LIGHT SPECIFICATIONS

Lifetime	≥50,000 hours
Working Environment	-37°C-55°C
Working Humidity	≤95%
CRI	≥75
Material	Aluminum + Tempered glass
LED Quantity	1PC Integrated Bridgelux SMD LEDs

Fixture Dimension	4.52*3.38*3.22 in
Net Weight	0.5kg/pc
Packaging	24pcs/ctn
Protection Grade	IP65 wet-Location
Warranty	3 Years

LED FLOOD LIGHT PRODUCT OPTIONS LIST

Model No.	Power	Input Voltage	Input Current	Max Lighting Distance	Lumens	Beam Angle	CCT
G2GFL10W	10W	100-240VAC, 50/60Hz	0.04A-0.10A	4.92Ft	900 Lm	120°	3000-3500K 4000-4500K 6000-6500K

LED FLOOD LIGHT DIMENSIONS

