

## G2GFL50W

### LED Flood Light Series

With its integrated applications of LED light sources and its unique circuit control design, G2G's Floodlight models conserve more than 80% of energy consumption. Given its ultra-bright, high color rendering index, our Floodlight fixtures are the latest style in efficient outdoor lighting, all while demonstrating a long lasting product life of over 50,000 hours. Ideal for outdoor decorative building and monument lighting, industrial lighting, advertisement illumination, increasing sign visibility, road lighting and street lamp distribution, our LED Floodlights satisfy a variety of applications.



**IP65**

### LED FLOOD LIGHT SPECIFICATIONS

<b>Lifetime</b>	≥50,000 hours
<b>Working Environment</b>	-37°C-55°C
<b>Working Humidity</b>	≤95%
<b>CRI</b>	≥75
<b>Material</b>	Aluminum + Tempered glass
<b>LED Quantity</b>	1PC Integrated Bridgelux SMD LEDs

<b>Fixture Dimension</b>	11.1*9.13*5.23 in
<b>Net Weight</b>	2.6kg/pc
<b>Packaging</b>	6pcs/ctn
<b>Protection Grade</b>	IP65 wet-Location
<b>Warranty</b>	3 Years

### LED FLOOD LIGHT PRODUCT OPTIONS LIST

Model No.	Power	Input Voltage	Input Current	Max Lighting Distance	Lumens	Beam Angle	CCT
G2GFL50W	50W	100-277VAC, 50/60Hz	0.2A-0.5A	8.20Ft	4500 Lm	120°	3000-3500K 4000-4500K 6000-6500K

### LED FLOOD LIGHT DIMENSIONS

