

# AURORA SV White

New Generation Aurora series

G2G's new generation Aurora SV LED modules are innovatively designed as an optimal solution for outdoor and indoor lighting. Ideal for channel letters, illuminated light boxes, and decorative architectural lighting.



cUL<sup>®</sup>us IP68  
E344189

## RECOMMENDED COVERAGE CHART

Depth	5"	6"	7"	8"
Spacing	6"	7"	8"	9"

## LED MODULE SPECIFICATIONS

<b>Working mode</b>	Constant Voltage Technology	<b>Fastening</b>	3M VHB double face tape and mechanical mounting options.
<b>Max Mods (Series)</b>	Full 63W load	<b>Optical Structure</b>	UV or IR Protected
<b>Viewing Angle</b>	120°	<b>Packaging</b>	200 modules per bag, 5 bags per case
<b>CT</b>	7500K	<b>Protection Grade</b>	IP68 wet-Location
<b>CRI</b>	>70	<b>Certifications</b>	UL and cUL Recognized
<b>LEDs Per Module</b>	3	<b>Warranty</b>	5 Year
<b>Operating Temp</b>	-40° to +60°C		
<b>LED Module Dimension</b>	2.2"L x 0.57"W x 0.26"H		

## LED MODULE PRODUCT OPTIONS LIST

Model	Voltage	Power	Current	Modules Per Ft	CT	Lumens	Qty 60W Power Supply	Viewing Angle
Aurora SV White	12VDC	0.63W/Module	53mA	3	7500K	190 Lm/Ft	93Modules/31Ft	120°

## LED MODULE DIMENSIONS

