

G2G Slim SiDe Bar

Engineered For Shallow Or Narrow Cabinets

Uniquely engineered for shallow or narrow sign cabinets, G2G's Slim SiDe Bar optic lenses optimize light from the edge to the center, delivering bright and even illumination in a revolutionary way. For application of both single and double-sided cabinets. Installation options include 3M VHB double-sided tape and mechanical mounting.



cUL[®]us **IP65**
E344189

RECOMMENDED COVERAGE CHART

Model from the face	3"	4"	5"	6"
Coverage Cabinet Length	30"	40"	48"	48"

LED MODULE SPECIFICATIONS

Working mode	Constant Current Technology (CCT)	Fastening	3M VHB double face tape and mechanical mounting options.
Max Mods (Series)	Full 100W load	Optical Structure	UV or IR Protected
Viewing Angle	12 x 56°	Packaging	20 modules per bag, 10 bags per case
CT	7500K	Protection Grade	IP67 wet-Location
CRI	>70	Certifications	UL and cUL Recognized
LEDs Per Module	12	Warranty	5 Year
Operating Temp	-40° to +60°C		
LED Module Dimension	11.81"L x 0.63"W x 0.43"H		

LED MODULE PRODUCT OPTIONS LIST

Model	Voltage	Power	Current	Modules Per Ft	CT	Lumens	Qty 60W Power Supply	Viewing Angle
G2G Slim SiDe Bar	12VDC	5.0W/Module	416mA	1	7500K	500 Lm/Module	12 Modules/12Ft	12 x 56°

LED MODULE DIMENSIONS

