

# AURORA Red

New Generation Aurora series

G2G's new generation Aurora R LED modules are innovatively designed as an optimal solution for outdoor and indoor lighting. Ideal for channel letters, illuminated light boxes, and decorative architectural lighting.



cULus  
E344189

IP68

## RECOMMENDED COVERAGE CHART

Depth	5"	6"	7"	8"
Spacing	6"	7"	8"	9"

## LED MODULE SPECIFICATIONS

Working mode	Constant Voltage Technology
Max Mods (Series)	Full 40W load
Viewing Angle	120°
CT	Red
CRI	>70
LEDs Per Module	4
Operating Temp	-40° to +60°C
LED Module Dimension	2.56"L x 0.78"W x 0.51"H

Fastening	3M VHB double face tape and mechanical mounting options.
Optical Structure	UV or IR Protected
Packaging	100 modules per tray, 5 trays per case
Protection Grade	IP68 wet-Location
Certifications	UL and cUL Recognized
Warranty	5 Year

## LED MODULE PRODUCT OPTIONS LIST

Model	Voltage	Power	Current	Modules Per Ft	CT	Lumens	Qty 60W Power Supply	Viewing Angle
Aurora Red	12VDC	0.40W/Module	35mA	3	Red	150 Lm/Ft	150Modules/50Ft	120°

## LED MODULE DIMENSIONS

