

G2G ArRay DF **Sign Box Lighting**

Easier Than Ever Before

Bringing you a revolution in sign box lighting, G2G introduces the ArRay system. Our goal is to help you reduce energy consumption and maintenance costs in applications where a high quality sign box lighting replacement is required. The ArRay PRO DF, and the ArRay ECO DF are designed for double-sided cabinets with a depth of 8" or greater.



RECOMMENDED COVERAGE CHART

Depth	8"	10"	12"	14"	16"	
Spacing	12"	12"	12"	12-15"	12-15"	

LED MODULE SPECIFICATIONS

Working mode Constant Voltage Technology for ArRay DF ECO

Constant Current Technology for ArRay DF PRO

Max Mods (Series) ArRay DF PRO Full 108W load

ArRay DF ECO Full 54W load

Viewing Angle 120° CT 7500K CRI >70

LEDs Per Module

Operating Temp -40° to +60°C

LED Module Dimension 10.23"L x 4.45"W x 0.43"H

Optical Structure UV or IR Protected **Packaging** 60 modules per case **Protection Grade** IP66 wet-Location Certifications UL and cUL Recognized

Warranty 5 Year

LED MODULE PRODUCT OPTIONS LIST

6

Model	Voltage	Power	Current	Modules Per Ft	CT	Lumens	Qty 60W Power Supply	Viewing Angle
ArRay DF PRO	12VDC	3.6W/Module	300mA	3	7500K	360 Lm/Module	16 Modules	120 °
ArRay DF ECO	12VDC	1.8W/Module	150mA	3	7500K	180 Lm/Module	33 Modules	120 °





