

# G2G Slim SiDe Bar

## Engineered For Shallow Or Narrow Cabinets

Uniquely engineered for shallow or narrow sign cabinets, G2G's SiDe optic lenses optimize light from the edge to the center, delivering bright and even illumination in a revolutionary way. For application of both single and double-sided cabinets. Installation options include 3M VHB double-sided tape and mechanical mounting.



**cULus** IP65  
E344189

### RECOMMENDED COVERAGE CHART

Model from the face	3"	4"	5"	6"
Coverage Cabinet Length	30"	40"	48"	48"

### LED MODULE SPECIFICATIONS

<b>Working mode</b>	Constant Current Technology (CCT)	<b>Fastening</b>	3M VHB double face tape and mechanical mounting options.
<b>Max Mods (Series)</b>	Full 100W load	<b>Optical Structure</b>	UV or IR Protected
<b>Viewing Angle</b>	12 x 56°	<b>Packaging</b>	20 modules per bag, 10 bags per case
<b>CT</b>	7500K	<b>Protection Grade</b>	IP67 wet-Location
<b>CRI</b>	>70	<b>Certifications</b>	UL and cUL Recognized
<b>LEDs Per Module</b>	12	<b>Warranty</b>	5 Year
<b>Operating Temp</b>	-40° to +60°C		
<b>LED Module Dimension</b>	11.81"L x 0.63"W x 0.43"H		

### LED MODULE PRODUCT OPTIONS LIST

Model	Voltage	Power	Current	Modules Per Ft	CT	Lumens	Qty 60W Power Supply	Viewing Angle
G2G Slim SiDe Bar	12VDC	5.0W/Module	416mA	1	7500K	500 Lm/Module	21 Modules	12 x 56°

### LED MODULE DIMENSIONS

