

AURORA Mini White

New Generation Aurora series

Lighting a large space has now become easier than ever before. G2G's Aurora MINI modules promise to be not only eye-catchingly bright, but unquestionably easy to mount. Lasting up to 50,000 hours with an input voltage of 12VDC, the MINI offers the best quality in LED technology today. Undeniably one of our best lighting units, the Aurora MINI transforms a space from glowing to striking.



cUL[®]us
E344189

IP67

RECOMMENDED COVERAGE CHART

Depth	5"	6"	7"	8"
Spacing	6"	7"	8"	9"

LED MODULE SPECIFICATIONS

Working mode	Constant Voltage Technology
Max Mods (Series)	Full 60W load
Viewing Angle	120°
CT	7500K
CRI	>70
LEDs Per Module	2
Operating Temp	-40° to +60°C
LED Module Dimension	1.18"L x 0.43"W x 0.29"H

Fastening	3M VHB double face tape and mechanical mounting options.
Optical Structure	UV or IR Protected
Packaging	100 modules per tray, 10 trays per case
Protection Grade	IP67 wet-Location
Certifications	UL and cUL Recognized
Warranty	5 Year

LED MODULE PRODUCT OPTIONS LIST

Model	Voltage	Power	Current	Modules Per Ft	CT	Lumens	Qty 60W Power Supply	Viewing Angle
Aurora Mini White	12VDC	0.60W/Module	50mA	4	7500K	170 Lm/Ft	100Modules/25Ft	120°

LED MODULE DIMENSIONS

