

G2G AnPro 160

AnPro Series G2G LED Product

G2G's AnPro LED modules provide a 160° wide viewing angle. This design offers an energy efficient and cost effective solution to sign lighting, and enables the sign designer to control operating costs. Because of it's high lumen output, the AnPro helps you create brighter and more evenly illuminated sign using less product. Bringing you more flexibility in installation, the AnPro makes custom sign designs simpler than ever before.



cULus
E344189 **IP67**

RECOMMENDED COVERAGE CHART

Depth	4"	5"	6"	7"	8"
Spacing	6"	8"	10"	12"	15"

LED MODULE SPECIFICATIONS

Working mode	Constant Voltage Technology	LED Module Dimension	2.75"L x 0.78"W x 0.23"H
Max Mods (Series)	Full 90W load	Fastening	3M VHB double face tape and mechanical mounting options.
Viewing Angle	160°	Optical Structure	UV or IR Protected
CT	6300K/7500K	Packaging	750pcs/carton, 150pcs/tray
CRI	>70	Protection Grade	IP67 wet-Location
LEDs Per Module	2	Certifications	UL and cUL Recognized
Operating Temp	-40° to +60°C	Warranty	5 Years
LEDs Lifetime	L70 rating of 50,000 hours		

LED MODULE PRODUCT OPTIONS LIST

Model	Voltage	Power	Current	Modules Per Ft	CT	Lumens	Qty 60W Power Supply	Viewing Angle
G2G AnPro 160	12VDC	1.2W/Module	100mA	2	7500K/6300K	270 Lm/Ft	50 Mods/25 Ft	160°

LED MODULE DIMENSIONS

