

AURORA Mini White

New Generation Aurora Series

Lighting a large space has now become easier than ever before. G2G's Aurora MINI modules promise to be not only eye-catchingly bright, but unquestionably easy to mount. Lasting up to 50,000 hours with an input voltage of 12DVC, the MINI offers the best quality in LED technology today. Undeniably one of our best lighting units, the Aurora MINI transforms a space from glowing to striking.



cULus
E344189

IP67

RECOMMENDED COVERAGE CHART

Depth	5"	6"	7"	8"
Spacing	6"	7"	8"	9"

LED MODULE SPECIFICATIONS

Working mode	Constant Voltage Technology	LED Module Dimension	1.18"L x 0.43"W x 0.29"H
Max Mods (Series)	Full 60W load	Fastening	3M VHB double face tape and mechanical mounting options.
Viewing Angle	120°	Optical Structure	UV or IR Protected
CT	7500K	Packaging	100 modules per tray, 10 trays per case
CRI	>70	Protection Grade	IP67 wet-Location
LEDs Per Module	2	Certifications	UL and cUL Recognized
Operating Temp	-40° to +60°C	Warranty	5 Years
LEDs Lifetime	L70 rating of 50,000 hours		

LED MODULE PRODUCT OPTIONS LIST

Model	Voltage	Power	Current	Modules Per Ft	CT	Lumens	Qty 60W Power Supply	Viewing Angle
Aurora Mini White	12VDC	0.60W/Module	50mA	4	7500K	170 Lm/Ft	100Modules/25Ft	120°

LED MODULE DIMENSIONS

