AURORA Red
New Generation   Aurora Series

G2G's new generation Aurora R LED modules are innovatively designed as an optimal solution for outdoor and indoor lighting. Ideal for channel letters, illuminated light boxes, and decorative architectural lighting.

IP68

c ℞ us
E344189

RECOMMENDED COVERAGE CHART

Depth	5"	6"	7"	8"
Spacing	6"	7"	8"	9"

LED MODULE SPECIFICATIONS

Working mode	Constant Voltage Technology	**LED Module Dimension**	2.56"L x 0.78"W x 0.51"H
Max Mods (Series)	Full 40W load	**Fastening**	3M VHB double face tape and mechanical mounting options.
Viewing Angle	120°		
CT	Red	**Optical Structure**	UV or IR Protected
CRI	>70	**Packaging**	100 modules per tray, 5 trays per case
LEDs Per Module	4	**Protection Grade**	IP68 wet-Location
Operating Temp	-40° to +60°C	**Certifications**	UL and cUL Recognized
LEDs Lifetime	L70 rating of 50,000 hours	**Warranty**	5 Years

LED MODULE PRODUCT OPTIONS LIST

Model	Voltage	Power	Current	Modules Per Ft	CT	Lumens	Qty 60W Power Supply	Viewing Angle
Aurora Red	12VDC	0.40W/Module	35mA	3	Red	150 Lm/Ft	150Modules/50Ft	120°

LED MODULE DIMENSIONS

2.56"
0.78"
2.75"
0.51"