


Trident DF Premier Stick

Trident Stick Series







RECOMMENDED COVERAGE CHART

Depth	10"	12"	14"	16"	
Spacing	10"	12"	12"	12"	

LED STICK SPECIFICATIONS

Input 12VDC LED Module Dimension 7.07"L x 1.14"W x 0.37"H **Power Per Module** 6.5W **Module Per Stick See Product Options**

Power Per Stick See Product Options Fastening Peel & Stick / Mechanical screw hole

Viewing Angle 160° **Operating Temp** -40° to +60°C

CT 6500K **Packaging** 12 Stick per case (6 stick per Tray, 2Tray per case)

Protection Grade CRI >70 IP66 wet-Location Certifications **LEDs Per Module** 12 UL and cUL Recognized

LEDs Lifetime 5 Years L70 rating of 50,000 hours Warranty

LED STICK PRODUCT OPTIONS LIST

LED Sign Module	Power	Lumens	Dimensions	Module/Stick	Stick Accessories
1 FT add on parts	6.5W	682.5 Lm/Stick	9.91"	1 Modules	Joining Bkt
Trident DF Premier Stick 18IN	6.5W	682.5 Lm/Stick	15.91"	1 Modules	HO Stick Plug/The Stabilizer
Trident DF Premier Stick 42IN	26W	2730 Lm/Stick	39.91"	4 Modules	HO Stick Plug/The Stabilizer
Trident DF Premier Stick 64IN	32.5W	3412.5 Lm/Stick	61.91"	5 Modules	HO Stick Plug/The Stabilizer /Joining Bkt
Trident DF Premier Stick 2FT	13W	1365 Lm/Stick	21.91"	2 Modules	HO Stick Plug/The Stabilizer
Trident DF Premier Stick 4FT	26W	2730 Lm/Stick	45.91"	4 Modules	HO Stick Plug/The Stabilizer
Trident DF Premier Stick 6FT	39W	4095 Lm/Stick	69.91"	6 Modules	HO Stick Plug/The Stabilizer /Joining Bkt
Trident DF Premier Stick 8FT	52W	5460 Lm/Stick	93.91"	8 Modules	HO Stick Plug/The Stabilizer /Joining Bkt
Trident DF Premier Stick 10FT	65W	6825 Lm/Stick	117.91"	10 Modules	Joining Bkt /Trident Mtg Bkt





