

Yo Module Series

180° Optical lenses

The Yo module provides a wide 180° viewing angle. This design offers an energy efficient and cost effective solution to sign lighting. The high lumen output of the Yo module helps you to build brighter and more evenly illuminated signs with less product.



cULus IP67
E344189

RECOMMENDED COVERAGE CHART

Depth	2.5"	3"	4"	5"	6-8"
Spacing	5"(4Modules/Ft)	7"	10"	15"	15"

LED MODULE SPECIFICATIONS

Working mode	Constant Voltage Technology	LED Module Dimension	1.126"L x 0.807"W x 0.374"H
Max Mods (Series)	Full 54W load	Fastening	3M VHB double face tape and mechanical mounting options.
Viewing Angle	180°	Optical Structure	UV or IR Protected
CT	7500K	Packaging	750pcs/box, 75pcs/bag
CRI	>70	Protection Grade	IP67 wet-Location
LEDs Per Module	3	Certifications	UL and cUL Recognized
LEDs Lifetime	L70 rating of 50,000 hours	Warranty	5 Years
Operating Temp	-40° to +60°C		

LED MODULE PRODUCT OPTIONS LIST

Model	Power	Current	Modules Per Ft	CT	Lumens	Qty 60W Power Supply	Viewing Angle
Yo	0.5W/Module	42mA	2.5	7500K	150 Lm/Ft	120Mods/40Ft	180°

LED MODULE DIMENSIONS

