

G2G Micro

New Generation Of Mini Module

G2G Micro LED module is the new generation of mini module. With the low lumen decay technology and compact size design, G2G Micro helps you create brighter and more evenly illuminated signs. Also it is the perfect solution for small channel letter and sign cabinets, etc.



RECOMMENDED COVERAGE CHART

| Depth | 5" | 6" | 7" | 8" |
|---------|----|----|----|----|
| Spacing | 6" | 7" | 8" | 9" |

LED MODULE SPECIFICATIONS

| | | | |
|-------------------|-----------------------------|----------------------|--|
| Working mode | Constant Voltage Technology | LED Module Dimension | 0.78"L x 0.27"W x 0.22"H |
| Max Mods (Series) | Full 26W load | Fastening | 3M VHB double face tape and mechanical mounting options. |
| Viewing Angle | 120° | Optical Structure | UV or IR Protected |
| CT | 7500K | Packaging | 60 modules per bag, 5 bags per case |
| CRI | >70 | Protection Grade | IP67 wet-Location |
| LEDs Per Module | 2 | Certifications | UL and cUL Recognized |
| Operating Temp | -40° to +60°C | Warranty | 5 Years |
| LEDs Lifetime | L70 rating of 50,000 hours | | |

LED MODULE PRODUCT OPTIONS LIST

| Model | Voltage | Power | Current | Modules Per Ft | CT | Lumens | Qty 60W Power Supply | Viewing Angle |
|-----------|---------|--------------|---------|----------------|-------|-----------|----------------------|---------------|
| G2G Micro | 12VDC | 0.42W/Module | 35mA | 6 | 7500K | 168 Lm/Ft | 140 Modules/23FT | 120° |

LED MODULE DIMENSIONS

