



# ***SIMPLE SOLUTIONS FOR COMMERCIAL LIGHTING***

*Catalog March 2018*

## LED Commercial Fixture

LED Flood Light  
LED Wall Washer  
LED Tape Light  
LED Retrofit Kits  
LED Corn Bulb  
LED Shoe Box Light  
LED High Bay  
LED Wall Pack Light  
LED Street Light



---

1829 Underwood Blvd, Unit 5, Delran Twp, NJ 08075  
Phone: (973) 575-2600 Fax: (973) 575-2603  
[www.g2glighting.com](http://www.g2glighting.com)

# G2G LED Commercial Fixture

## LED Flood Light

### TF4 SERIES

#### LED Flood Light

Solve the problem of uneven lighting in indoor illumination.  
Solve the problem of uneven lighting in outdoor illumination.  
Solve the problem of short-distance irradiation of LED lamps.  
Solve the problem of glare of high-power LED.

- 50000 Hours Avg Rated Life
- 90-277 Volts
- IP65 waterproof Rating
- 3000K-6500K Color Temperature
- ETL Listed - Wet Location
- 5 Years Warranty



Item	Fixture Dimension	Watt	Current(AC)	Lumen	Beam Angle	Case Qty	Dimensions(In)
G2G-FL-TF4-200W	10.75" x 6.70" x 10.85"	200W	2.2A (max)	26,000LM	15°/38°/60°/120°	1Pcs	12.80" x 13.24" x 11.02"
G2G-FL-TF4-300W	10.75" x 13.30" x 10.85"	300W	3.3A (max)	42,000LM	15°/38°/60°/120°	1Pcs	14.57" x 11.81" x 11.02"
G2G-FL-TF4-400W	16.5" x 8.70" x 10.85"	400W	4.4A (max)	56,000LM	15°/38°/60°/120°	1Pcs	18.5" x 14.41" x 11.81"



### TF4 SERIES

#### LED Flood Light

- 50000 Hours Avg Rated Life
- 100-277 Volts
- IP65 waterproof Rating
- 3000K-6500K Color Temperature
- 5 Years Warranty

Item	Fixture Dimension	Watt	Current(AC)	Lumen	Beam Angle	Case Qty	Dimensions(In)
G2G-FL-TF4-10W	4.52" x 3.38" x 3.22"	10W	0.04-0.1A	900LM	120°	24Pcs/ctns	19.88" x 11.42" x 8.46"
G2G-FL-TF4-20W	7.08" x 5.51" x 4.85"	20W	0.07-0.2A	1800LM	60°/120°	12Pcs/ctns	23.42" x 18.9" x 12.6"
G2G-FL-TF4-30W	8.86" x 7.28" x 4.96"	30W	0.1-0.3A	2700LM	60°/120°	8Pcs/ctns	23.24" x 19.53" x 14.96"
G2G-FL-TF4-50W	11.1" x 9.12" x 5.23"	50W	0.2-0.5A	4500LM	60°/120°	6Pcs/ctns	33.7" x 13.29" x 16.14"
G2G-FL-TF4-100W	11.22" x 14.1" x 13.94"	100W	0.36-1.0A	9000LM	60°/120°	4Pcs/ctns	26.57" x 19.29" x 13.98"
G2G-FL-TF4-150W	17.91" x 12.59" x 7.28"	150W	0.54-1.5A	13500LM	60°/120°	2Pcs/ctns	28.95" x 15.31" x 19.78"

# G2G LED Commercial Fixture

## LED Wall Washer

### Oona Slim Wall Washer

- 50000 Hours Avg Rated Life
- 24 Volts
- OSLWW48P(RGB)
- OSLWW48P(monochromatic)
- ETL Listed - Wet Location
- 5 Years Warranty

**CREE**  **CE** **IP67**



Powerfully structured, the Oona Slim Wall Washer is designed to dramatically illuminate buildings, monuments, fountains and create breathtaking outdoor displays.



Red Blue Amber Yellow White

Item	Fixture Dimension	Watt	Lumen	DLC	Lens	Case Qty	Dimension(in)
OSLWW48P	48" x1.4" x2.2"	20W	2000Lms	—	25 x35"	18pcs/case	50.5" x14.37" x18.63"
OSLWW48P	48" x1.4" x2.2"	13W	494Lms	—	30" x30 x30"	18pcs/case	50.5" x14.37" x18.63"



### 2 & 5 SERIES LED Wall Washer

- 50000 Hours Avg Rated Life
- 120-240 Volts
- RGB & White Color
- ETL Listed - Wet Location
- 5 Years Warranty

**ETL** **CE** **IP65**  **CREE** 

Item	Fixture Dimension	Watt	Color	Lens	Max Lighting Distance(Ft)	Case Qty	Dimension(in)
G2GLWW2-16P	13" x5.9" x6.7"	40W	W,R,G,B	18"/38"/45"/15X50"	32.6/26.24/16.4	4pcs/case	31.89" x19.29" x19.23"
G2GLWW2-17P	25.1" x5.9" x6.7"	80W	W,R,G,B	18"/38"/45"/15X50"	65.6/49.2/32.8	2pcs/case	37.99" x19.29" x19.23"
G2GLWW2-144P	47.2" x5.9" x6.7"	150W	W,R,G,B	18"/38"/45"/15X50"	98.4/65.6/32.8	1pc/case	52.75" x19.06" x19.84"

Item	Fixture Dimension	Watt	Color	Lens	Max Lighting Distance(Ft)	Case Qty	Dimension(in)
G2GLWW5B-18P-L500	22.8" x5.8" x2.8"	20W	W,R,G,B	10"/20"/45"	35.26/19.68/9.84	4pcs/case	25.78" x12" x14.56"
G2GLWW5B-16P-L1100	44" x5.8" x2.8"	40W	W,R,G,B	10"/20"/45"	32.8/19.68/16.4	4pcs/case	40.04" x12.80" x14.56"

# G2G LED Commercial Fixture

## LED Wall Washer

### 1 & 6 SERIES

#### LED Wall Washer

- 50000 Hours Avg Rated Life
- 120-240 Volts
- RGB & White Color
- ETL Listed - Wet Location
- 5 Years Warranty



G2GLWW-1C-36P



G2GLWW-6B-36P

Item	Fixture Dimension	Watt	Color	Lens	Max Lighting Distance(Ft)	Case Qty	Dimensions(In)
G2GLWW1C-36P	15" x15.8" x11.5"	48W	W,R,G,B	15°/38°/45°	32.8/19.68/16.4	4pc/case	36.70" x16.14" x11.03"
G2GLWW6B-36P	D6.3" x17.1"	36W	W,R,G,B	15°/38°/45°	36.24/19.68/16.4	4pc/case	29.87" x26.69" x12.6"
G2GLWW6B-36P	D6.3" x17.5"	48W	W,R,G,B	15°/38°/45°/15845°	32.8 /19.68/16.4	4pc/case	23.25" x23.25" x12.6"

G2GLWW-8C-216P



G2GLWW7-72P

### 7 & 8 SERIES

#### LED Wall Washer

- 50000 Hours Avg Rated Life
- 120-240 Volts
- RGB & White Color
- ETL Listed - Wet Location
- 5 Years Warranty



Item	Fixture Dimension	Watt	Color	Lens	Max Lighting Distance(Ft)	Case Qty	Dimensions(In)
G2GLWW7-36P	15.4" x12.6" x11.8"	72W	W,R,G,B	15°/38°/45°	98.4/65.6/32.8	1pc/case	15.75" x14.96" x15.74"
G2GLWW7-72P	15.7" x12.6" x11.8"	150W	W,R,G,B	15°/38°/45°	164/131.2/98.4	1pc/case	19.29" x15.74" x15.74"
G2GLWW8C-108P	12.6" x24.4" x14.1"	216W	W,R,G,B	15°/38°/45°	262.4/196.8/131.2	1pc/case	23.43" x13.99" x15.74"
G2GLWW8C-216P	26.3" x24.4" x17.3"	432W	W,R,G,B	15°/38°/45°	328/262.4/196.8	1pc/case	27.76" x27.77" x19.69"

# G2G LED Commercial Fixture

## LED Tape Light

### LED Tape Light

DC 12/24V low-voltage power supply, security and energy efficiency. High brightness low power consumption. Dimmable by using dimmer controller.



#### SPECIFICATIONS

Life time	50,000 hours	Led quantity	18 Leds/FT
Working mode	Constant Voltage Technology	Packaging	15FT per roll, 1roll per bag
Input voltage	12V	Protection Grade	IP65/IP68 wet-location
Viewing Angle	120°	Fastening	3M Double-sided tape
CRI	>80	Certifications	UL and cUL Recognized
Operating Temp	-20°C - 50°C	Warranty	5 Years

#### PRODUCT OPTIONS LIST

Products	IP Rate	Color Temperature	Power	LED Tape	LEDs/FT	Lumens	Cutout
G2G-TL-52835R-012-405	IP65	3000K/5000K/6500K	4.4W/FT	5M02835	18	328LM/FT~396LM/FT	14.17"Lx3.44"Wx0.44"H
G2G-TL-52835R-012-405	IP68	3000K/5000K/6500K	4.4W/FT	5M02835	18	328LM/FT~396LM/FT	14.17"Lx3.44"Wx0.44"H
G2G-TL-53528R-012-405	IP65	3000K/5000K/6500K	1.5W/FT	5M03528	18	117LM/FT~132LM/FT	14.17"Lx3.44"Wx0.44"H
G2G-TL-53528R-012-405	IP68	3000K/5000K/6500K	1.5W/FT	5M03528	18	117LM/FT~132LM/FT	14.17"Lx3.44"Wx0.44"H
G2G-TL-55050R-012-405	IP65	RGB	4.4W/FT	5M05050	18	846LM/FTG:107LM/FTB:238LM/FT	14.17"Lx3.44"Wx0.44"H
G2G-TL-55050R-012-405	IP68	RGB	4.4W/FT	5M05050	18	835LM/FTG:93LM/FTB:226LM/FT	14.17"Lx3.44"Wx0.44"H

#### DIMENSIONS

2835 Silicone-cased Series



3528 Silicone-cased Series




5050 Silicone-cased Series



# G2G LED Commercial Fixture

## LED Retrofit Kits

- All led retrofit kits are equipped with Meanwell driver HLG Series
- We are the first one to use Cree-XTE for led retrofit kits ,other factories only use Cree-XBDt
- Fixture Material Die-cast aluminum
- Fan Equipped Taiwan Sunon brand
- Color Temperature:2700-8000K
- 6years warranty for all led retrofit kits



Item	Input Power	Input Voltage	Lumen	LED Source	Case Qty	Dimension(LxWxH)
G2GR6-15W-A1	15W	AC108-277V	3300-3600lm	14PCS CREE SMD LEDS	4pcs/ctn	D4.7" x H1.3"
G2GR6-15W-A1	15W	AC108-277V	4300-4500lm	21PCS CREE SMD LEDS	4pcs/ctn	D4.7" x H1.3"
G2GR6-60W-A1	60W	AC108-277V	5900-6100lm	28PCS CREE SMD LEDS	4pcs/ctn	6.8" x4.9" x1.2"
G2GR6-60W-A1	60W	AC108-277V	6400-6800lm	38PCS CREE SMD LEDS	4pcs/ctn	D4.7" xH1.28"
G2GR6-60W-A1	60W	AC108-277V/347WAC/480WAC	7600-8300lm	42PCS CREE SMD LEDS	4pcs/ctn	6.8" x4.9" x1.2"
G2GR6-185W-A1	185W	AC108-277V/347WAC/480WAC	9600-18500lm	48PCS CREE SMD LEDS	4pcs/ctn	6.8" x4.9" x1.2"
G2GR6-120W-A1	120W	AC108-277V/347WAC/480WAC	11800-12500lm	56PCS CREE SMD LEDS	4pcs/ctn	6.8" x4.9" x1.2"
G2GR6-150W-A1	150W	AC108-277V/347WAC/480WAC	14800-15500lm	77PCS CREE SMD LEDS	4pcs/ctn	10.4" x8.3" x2.4"
G2GR6-200W-A1	200W	AC108-277V	19800-21000lm	105PCS CREE SMD LEDS	4pcs/ctn	10.4" x8.3" x2.4"
G2GR6-240W-A1	240W	AC108-277V/347WAC/480WAC	24800-25000lm	112PCS CREE SMD LEDS	4pcs/ctn	10.4" x8.3" x2.4"
G2GR6-320W-A1	320W	AC108-277V	32000-36000lm	154PCS CREE SMD LEDS	4pcs/ctn	12.6" x8.3" x3"
G2GR6-480W-A1	480W	AC108-277V/347WAC/480WAC	39500-43000lm	210PCS CREE SMD LEDS	4pcs/ctn	12.6" x8.3" x3"

## LED Retrofit Kits Components



The short support can only be used in the high bay light.  
long support can be used in the other lights except the high bay light.



# G2G LED Commercial Fixture

## LED Corn Bulb

- Replaces 110W-400W HID
- E26, E39 or EX39 base available
- Direct line voltage 100-277V— bypass ballast
- Integral 2.5KV-4kV surge protection
- Unique reliable structure design to minimize heat dissipation Built-in temperature control against over-heating over 194°F/90°C UL listed for damp locations
- CR1 80+
- Bm 360°
- Life Hrs 50,000hrs
- UL1598C – Existing fixtures retain UL certification
- Backed up by a 5-year warranty



Item	Watt	Lumen	Chips	Base	CCT	Case Qty	Dimensions(DxH)
G2GC9-120W-A	120W	15000Lms	Samyang 5638	E39/EX39	100-277V	4pcs/cdn	5.75" x 12"
G2GC9-120W-B		14000Lms	Epistar 2835				
G2GC8-100W-A	100W	12500Lms	Samyang 5638	E39/EX39	100-277V	4pcs/cdn	5.75" x 11.2"
G2GC8-100W-B		12000Lms	Epistar 2835				
G2GC8-80W-A	80W	10000Lms	Samyang 5638	E39/EX39	100-277V	4pcs/cdn	5.75" x 10.8"
G2GC8-80W-B		9200Lms	Epistar 2835				
G2GC9-60W-A	60W	8100Lms	Samyang 5638	E26	100-277V		
G2GC9-60W-B		7500Lms	Epistar 2835				
G2GC8-54W-A	54W	7200Lms	Samyang 5638	E39/EX39	100-277V	12pcs/cdn	3.58" x 10.43"
G2GC8-54W-B		6700Lms	Epistar 2835				
G2GC8-45W-A	45W	6000Lms	Samyang 5638	E26	100-277V	12pcs/cdn	3.58" x 10.43"
G2GC8-45W-B		5600Lms	Epistar 2835				
G2GC9-36W-A	36W	4800Lms	Samyang 5638	E26	100-277V	12pcs/cdn	3.58" x 9.25"
G2GC9-36W-B		4500Lms	Epistar 2835				
G2GC8-27W-A	27W	3600Lms	Samyang 5638	E26	100-277V	12pcs/cdn	3.58" x 8.07"
G2GC8-27W-B		3300Lms	Epistar 2835				
G2GC8-22W-A	22W	2530Lms	Epistar 2835	E27	100-277V	24pcs/cdn	2.72" x 7.32"
G2GC8-22W-B		2070Lms	Epistar 2835				
G2GC9-18W-A	18W	2070Lms	Epistar 2835	E27	100-277V	24pcs/cdn	2.72" x 6.54"
G2GC9-18W-B		1610Lms	Epistar 2835				
G2GC8-18W-A	10W	1150Lms	Epistar 2835	E27	100-277V	48pcs/cdn	2.3" x 5.63"
G2GC8-18W-B		920Lms	Epistar 2835				



## Hi SERIES LED Shoe Box Light

### Reliable LED Lighting Technology

The special G2G Reliable LED Lighting Technology provides significant advantages in terms of luminous efficiency, minimizing losses/refraction and reflection inside the optical system. This system ensures a lower density of dirt and maintaining the luminaire performance for a very long period.

### Protect the LED Source

As the key to guarantee the total life span of the luminaire, the protection of the LED source is the core topic in the designing of G2G luminaire. The carefully selected Mitsubishi PC cover and waterproof rubber ring ensured the total IP of the whole product. And it also protect the LED chip from the external agents and impact.

### Temperature Control

G2G Hi Series is designed with superb heat radiation technique. The heat and air can go through the whole luminaire via the gaps between the modules. This product also has a self-clean ability. When the rain come, the fixture will be washed and the dirt automatically goes out. By the excellent heat radiation ability, the temperature rising of i series high bay light is only <26 °C. And the lamp can work in the environment from -40 °C to 50 °C. If the environment is 40 °C, the maximize temperature on the lamp is 66 °C. But the Philips Luxeon T chips can afford 110 °C. This



- 62000 Hours Avg Rated Life
- 90-305 Volts & 277-480Volts
- IP65 (IP67 optional) & IK10

- 3000K-6500K Color Temperature
- ETL Listed - Wet Location
- 5 Years Warranty



Item	Fixture Dimension	Watt	Current(AC)	Lumen	Lens	DLC	Case Qty	Dimension(In)
G2G-SB-HB-43W	11.9" x 5.9" x 7.2"	40W	0.45A (max)	4,400lm	30°/60°/90°/180°/120°	—	1Pcs	15.35" x 9.45" x 10.24"
G2G-SB-HB-80W	11.9" x 9.1" x 7.2"	80W	0.9A (max)	8,800lm	30°/60°/90°/180°/120°	—	1Pcs	15.35" x 12.8" x 10.24"
G2G-SB-HB-120W	11.9" x 12.2" x 7.2"	120W	1.35A (max)	13,200lm	30°/60°/90°/180°/120°	—	1Pcs	15.35" x 15.35" x 10.24"
G2G-SB-HB-160W	11.9" x 15.4" x 7.2"	160W	1.86A (max)	17,600lm	30°/60°/90°/180°/120°	—	1Pcs	18.5" x 15.35" x 10.24"
G2G-SB-HB-200W	11.9" x 18.6" x 7.2"	200W	2.25A (max)	22,000lm	30°/60°/90°/180°/120°	—	1Pcs	22.05" x 15.35" x 10.24"
G2G-SB-HB-240W	11.9" x 21.8" x 7.2"	240W	2.66A (max)	26,400lm	30°/60°/90°/180°/120°	—	1Pcs	25.2" x 15.35" x 10.24"
G2G-SB-HB-280W	11.9" x 25" x 7.2"	280W	3.16A (max)	30,800lm	30°/60°/90°/180°/120°	—	1Pcs	28.34" x 15.35" x 10.24"
G2G-SB-HB-320W	11.9" x 28.2" x 7.2"	320W	3.58A (max)	35,200lm	30°/60°/90°/180°/120°	—	1Pcs	31.88" x 15.35" x 10.24"
G2G-SB-HB-360W	11.9" x 31.4" x 7.2"	360W	4.16A (max)	39,600lm	30°/60°/90°/180°/120°	—	1Pcs	35.43" x 15.35" x 10.24"
G2G-SB-HB-400W	11.9" x 35" x 7.2"	400W	4.46A (max)	44,000lm	30°/60°/90°/180°/120°	—	1Pcs	38.98" x 15.35" x 10.24"

# G2G LED Commercial Fixture

## LED High Bay

### UF SERIES

#### LED High Bay

- Easy installation, free maintenance
- Advanced optics for reduced glare
- IP65 waterproof Rating
- CRI: >70
- Saving over 75% energy comparing with traditional lamps
- Lamp surface treated with anodization, corrosion-resistant
- Scientifically-designed heat dissipater with much better cooling effect
- Improved thermal management to withstand up to 40 °C



**Input Voltage:** 100-277VAC

**Driver Brand:** UL cUL Sosen Driver

**Lumen Efficiency:** >130LM/W

**CCT:** Warm White (2700-3500K)

Neutral White (4000-4500K)

Cool White (5000-5700K)

**Chip Brand:** Philips 3030 SMD


**Material:** Aluminum+Tough Glasses

**Housing color:** Black

**PF Rate:** >0.9

**Lifespan:** >50000hours

**Warranty:** 3 Years



Item	Fixture Dimension	Watt	Current(AC)	Lumen	Lens	Case Qty	Dimensions(In)
G2G-HB-100W	12.81" x 12.81" x 7.03"	100W	1.0A (max)	13,000LM	60°/90°/120°	2Pcs	15.95" x 15.95" x 7.13"
G2G-HB-150W	12.81" x 12.81" x 7.03"	150W	1.5A (max)	19,500LM	60°/90°/120°	2Pcs	15.95" x 15.95" x 7.13"
G2G-HB-200W	15.28" x 15.28" x 7.93"	200W	2.0A (max)	26,000LM	60°/90°/120°	2Pcs	18.31" x 18.31" x 8.7"
G2G-HB-240W	15.28" x 15.28" x 7.93"	240W	2.4A (max)	31,200LM	60°/90°/120°	2Pcs	18.31" x 18.31" x 8.7"

# G2G LED Commercial Fixture

## LED Wall Pack Light

The LWP Series distills the benefits of the latest in LED technology into a high performance, high efficacy, long-life luminaire. The energy savings, long life and easy-to-install design of the Wallpack make it the smart choice for building-mounted doorway and pathway illumination for nearly any facility. Replaces 175-400W MH or HID fixtures, either case, with energy-savings of up to 75%.



### 1 SERIES

- 50000 Hours Avg Rated Life
- 120-277 Volts
- 5000K Color Temperature
- ETL Listed - Wet Location
- 5 Years Warranty



IP67



Item	Fixture Dimension	Watt	Lumen	DLC	Case Qty	Dimensions(in)
G2G-WP1-45W	14.2" x9.2" x7.4"	45W	4981Lms	—	1Pcs	15.16" x8.26" x10.84"
G2G-WP1-60W	14.2" x9.2" x7.4"	60W	6669Lms	—	1Pcs	15.16" x8.26" x10.84"
G2G-WP1-80W	14.2" x9.2" x7.4"	80W	9183Lms	—	1Pcs	15.16" x8.26" x10.84"



### 2 SERIES

#### LED Wall Pack Light

- 50000 Hours Avg Rated Life
- 120-277 Volts
- 5000K Color Temperature
- ETL Listed - Wet Location
- 5 Years Warranty



PHILIPS

Item	Fixture Dimension	Watt	Lumen	DLC	Case Qty	Dimensions(in)
G2G-WP2-25W	8.27" x5.51" x3.54"	25W	2500Lms	—	1Pcs	9.65" x5.9" x3.39"
G2G-WP2-30W	8.27" x5.51" x3.54"	30W	3000Lms	—	1Pcs	9.65" x5.9" x3.39"
G2G-WP2-40W	8.27" x5.51" x3.54"	40W	4000Lms	—	1Pcs	9.65" x5.9" x3.39"

### Hii SERIES LED Street Light

- Multiple brackets optional
- Fishbone style high efficiency heat sink
- Super slim design
- Specilized designed for outdoor parking lot and wide area



The new Hii series LED street light, This light is a perfect solution for outdoor parking lot and area lighting. Considering the preference of the installation styles in different countries in Europe, North American, and Australia, the Hii series come with 4 main variants: style A-D, to mostly suit the local demand and easier for our customer in making project.


The body of the Hii series is just so slim. But behind it is the superb system efficacy, heat radiation ability, and though endurance for brutal working environment.

The new Hii series is from 75W to 265W, can replace up to 1000W traditional luminaire.



Brackets optional

- 62000 Hours Avg Rated Life
- 90-305 Volts & 277-480Volts
- IP65 (IP67 optional) & IK10
- 3000K-6500K Color Temperature
- ETL Listed - Wet Location
- 5 Years Warranty



Item	Fixture Dimension	Watt	Current(AC)	Lumen	Lens	DLC	Case Qty	Dimension(m)
G2G-SL-H1075W	25.1" x13.8" x3"	75W	0.85A (max)	9,700lm	75°130°	—	1Pcs	28.74" x14.57" x7.48"
G2G-SL-H1108W	25.1" x13.8" x3"	119W	1.23A (max)	14,300lm	75°130°	—	1Pcs	28.74" x14.57" x7.48"
G2G-SL-H11508W	25.1" x13.8" x3"	159W	1.67A (max)	18,500lm	75°130°	—	1Pcs	29.53" x17.32" x7.09"
G2G-SL-H11808W	25.1" x13.8" x3"	189W	2.0A (max)	22,500lm	75°130°	—	1Pcs	29.53" x17.32" x7.09"
G2G-SL-H12508W	25.1" x13.8" x3"	259W	2.5A (max)	28,125lm	75°130°	—	1Pcs	29.53" x17.32" x7.09"
G2G-SL-H12658W	25.1" x13.8" x3"	265W	2.95A (max)	33,125lm	75°130°	—	1Pcs	29.53" x17.32" x7.09"



---

☎ 973-675-2600

📠 973-675-2603

📍 1829 Underwood Blvd, Unit 5, DeFran Twp., NJ 08075

[www.g2glighting.com](http://www.g2glighting.com)