

AURORA SV II

New Generation Aurora Series

G2G's new generation Aurora SV II LED modules are innovatively designed as an optimal solution for outdoor and indoor lighting. Ideal for channel letters, illuminated light boxes, and decorative architectural lighting.



cULus IP68
E344189

RECOMMENDED COVERAGE CHART

Depth	5"	6"	7"	8"
Spacing	6"	7"	8"	9"

LED MODULE SPECIFICATIONS

Working mode	Constant Voltage Technology	LED Module Dimension	2.2"L x 0.57"W x 0.26"H
Max Mods (Series)	Full 63W load	Fastening	3M VHB double face tape and mechanical mounting options.
Viewing Angle	120°	Optical Structure	UV or IR Protected
CT	7500K	Packaging	200 modules per bag, 5 bags per case
CRI	>70	Protection Grade	IP68 wet-Location
LEDs Per Module	3	Certifications	UL and cUL Recognized
Operating Temp	-40° to +60°C	Warranty	5 Years
LEDs Lifetime	L70 rating of 50,000 hours		

LED MODULE PRODUCT OPTIONS LIST

Model	Voltage	Power	Current	Modules Per Ft	CT	Lumens	Qty 60W Power Supply	Viewing Angle
Aurora SV II	12VDC	0.63W/Module	53mA	3	7500K	190 Lm/Ft	93Modules/31Ft	120°

LED MODULE DIMENSIONS

