

G2G ArRay DF

Sign Box Lighting

Easier Than Ever Before

Bringing you a revolution in sign box lighting, G2G introduces the ArRay system. Our goal is to help you reduce energy consumption and maintenance costs in applications where a high quality sign box lighting replacement is required. The ArRay PRO DF, and the ArRay ECO DF are designed for double-sided cabinets with a depth of 8" or greater.



6

RECOMMENDED COVERAGE CHART

Depth	8"	10"	12"	14"	16"	
Spacing	12"	12"	12"	12-15"	12-15"	

LED MODULE SPECIFICATIONS

LEDs Per Module Working mode Constant Voltage Technology for ArRay DF ECO

> Constant Current Technology for ArRay DF PRO **Operating Temp** -40° to +60°C

Max Mods (Series) ArRay DF PRO Full 108W load **LED Module Dimension** 10.23"L x 4.45"W x 0.43"H

> ArRay DF ECO Full 54W load **Optical Structure** UV or IR Protected 120° **Packaging**

Viewing Angle 60 modules per case CT 7500K **Protection Grade** IP66 wet-Location CRI Certifications >70 UL and cUL Recognized

LEDs Lifetime L70 rating of 50,000 hours Warranty 5 Years

LED MODULE PRODUCT OPTIONS LIST

Model	Voltage	Power	Current	Modules Per Ft	СТ	Lumens	Qty 60W Power Supply	Viewing Angle
ArRay DF PRO	12VDC	3.6W/Module	300mA	3	7500K	360 Lm/Module	16 Modules	120 °
ArRay DF ECO	12VDC	1.8W/Module	150mA	3	7500K	180 Lm/Module	33 Modules	120°

LED MODULE DIMENSIONS (0)G2G ArRay $(\bigcirc$ 10.23

