

Week 11

Disks, File Systems and the Linux FHS

Melvyn Ian Drag

November 16, 2019

Abstract

We will explore how physical disks are formatted in Linux, discuss (some of) your options for formatting your disks, learn about swap space, and have a look at some of the most important directories that exist on your Linux machine.

1 Before Class

Try to ssh into digital ocean on another port so people don't need to use their data to get into their servers.

2 Motivation for Today's lecture

You might be studying to become any of the following:

1. Sysadmin
2. Programmer
3. DevOps
4. Network engineer
5. More educated person
6. A power user of your personal laptop
7. Did I miss anything?

In any one of these situations, you need to be able to add and remove ssds, usb drives, and hdds from Linux machines. It is somewhat scary to learn how to do this on your own - it's a good thing you're here today!

3 Filesystem Hierarchy Standard

Let's start with the easiest bit. Turn on your Linux machine and navigate to the root of your filesystem. List the files and directories there. If you have a laptop and a digital ocean server you might want to fire both up. If you have a mac, a linux laptop and a server, maybe look at all three. You will see what they have in common, and what is different.

```
1 user@machine$ sudo su -
2 root@machine$ cd /
3 root@machine$ ls
4 # The subject of the coming discussion is here in the stdout.
```

3.1 The important Directories

/ - root of your Linux install

/bin - programs needed for single user mode, for bringing a system up in maintenance mode. I've never had to do this for maintenance, but the utilities it provides are simple standard commands like 'cat', 'ls', etc.

/boot - files to be used for booting the system. These are low level things you won't worry much about as a general desktop user, application developer, or web programmer. This is lowlevel stuff for getting the OS up and running between the time you plug it in and hit the power button and start using Linux. You'll see the Linux kernel, the bootloader (on your system you'll probably see grub, but on an embedded project you'll probably see uboot.) We'll compile the kernel in this class and maybe poke at the bootloader, but it might be more instructive to poke at the bootloader of a physical pc sitting in front of you.

/dev - devices and things. you'll see your harddrive/sdd for example as something like /dev/sda. There are a bunch of ttys. What a tty is and how you use it is of particular interest to me, and maybe during office hours I'll show you some stuff I do with those devices.

/etc - config files. We had to edit config files for apache2 and postgresql before. This is where you find config files for various applications.

/home - user home directories. Your homework will be to put this on a separate physical drive. This is where users put their data. Photos, downloads, video games, etc.

/lib - libraries for booting the system and used by programs on your computer.

/lib<qual > You'll see 32 and 64 bit variants of the various libraries. If you don't know what "dynamic" vs. "Static" linking means, and have never used static vs dynamic libraries, this will be outside of your understanding.

/media - where auto mounted media goes. When you stick a usb stick in, or a CDROM, it will generally appear here.

/mnt - where you will manually mount filesystems for your use. We'll explore some use cases of this today.

/opt - a place for "add on packages". Stuff you want to install goes here. The use of this directory is debatable and I leave it up to you to decide what you put here and what philosophical stance you choose on what ought to go here.

/proc - we already looked at this when we looked at stdin/stdout/stderr. We'll revisit that quickly. Write a little python program:

```
1 import time
2
3 while True:
4     time.sleep(10)
5     pass
```

Run it in the back ground

```
1 user@machine$ python program.py & [outputs pid]
2 user@machine$ ls /proc/$pid/fd 0 1 2
```

you see the file descriptors for stdin, stdout, stderr. the /proc has information about running processes. There is much more to see besides the file descriptors, but that's the only example I'm going to provide.

/root - the home directory for the root user. The root user doesn't get a directory in /home.

/sbin - programs for booting and maintaining the system, but not used by regular users.

1. <https://ma.ttias.be/understanding-the-bin-sbin-usr-bin-and-usr-sbin-split/>

2. <http://landley.net/writing/hackermothly-issue022-pg33.pdf>

the difference between sbin and bin has history behind it, and I've linked a few quick and interesting reads explaining the differences.

Do take a moment to

```
1 user@machine$ ls -l /sbin
```

and notice that many of the commands there are actually links to the commands in /bin. What's a link? In general it's like a windows shortcut. The actual program isn't in /sbin, it's in /bin, but when you call the one in /bin, it calls the one in /sbin. 'bash' isn't linked, however, bash is in /bin you'll see.

```
1 $ which bash /bin/bash
2 $ ls -l /sbin/b*
3 # bash is not there
```

doesn't matter, just showing you.

/srv - I haven't ever used this. It might be relevant to you, I don't know

/sys - don't worry about it

/tmp - temporary files. Depending on the distro you use these might or might not be deleted on reboot. They might be cleaned up before reboot. They are temporary files, and the longevity and uses of them differs and depends on you.

For example,

```
1
2 ls /tmp
3 # some stuff about ssh
```

that's temporary info about your ssh login. Don't worry about the details.

/usr - another location for executables, libraries, etc, typically read-only stuff that isn't essential to booting the system. There's a lot of argument about what goes in here. If you're a sysadmin or linux application developer you will work on this.

Notice that tmux isn't essential to your system.

```
1 $apt-get install tmux
2 $which tmux #/usr/bin/tmux
```

If you want to feel confused for a bit, look at this post:

<https://unix.stackexchange.com/questions/8656/usr-bin-vs-usr-local-bin-on-linux>

people discuss the uses of /bin, /sbin, /usr/bin, /usr/sbin, /usr/local/bin, /bin, etc.

It hasn't mattered to me in my career what goes where, but depending on the depth you go into Linux you may develop a passionate opinion.

3.2 Need your help

Many of you likely have tmux installed already. What are some other fun packages we can install that will serve for the above example?

3.3 Want to learn more?

There is a popular youtube channel called 'Engineer man' or the like. The videos feature a guy sitting in the lower right corner of the screen talking about interesting Linux/Programming stuff with his terminal taking up most of the screen so you can see what stuff he's typing. There is a good video about the filesystem hierarchy standard.

4 Drives, Partitions, Mounting, and Partitioning.

The idea of this part of the lecture is that sometimes you want to add storage space to your machine. You might have a 250GB SSD and you just bought a 1TB drive and you want to add it to your machine so you can download more movies, save more pictures, store more code, whatever.

4.1 Look at what storage space you already have.

```
1
2 $lsblk
3 sda      disk
4 --sda1   part
```

sda is a physical drive on your computer, like a harddrive connected to the machine. sda1 is a partition of the drive, it's a chunk of memory you formatted in a particular way to become useable by your machine.

4.2 Now we will add another drive

Here's how you do it on Digital Ocean. The process is the same on your laptop with a USB stick, SSD, HDD, or whatever persistent storage device you use. We'll all just use Digital Ocean to make the experience easy and avoid accidentally destroying something on the laptop.

Images/addVolume01 Images/addVolume02 Images/addVolume03

Note that there are instructions on Digital Ocean about how to format. Ignore that. I'm going to explain how formatting and partitioning work and then you can go back and see what Digital Ocean is telling you to do and you'll understand and maybe want to modify what they've asked you to do.

```
1 $lsblk
2 # theres an unpartitioned disk called sda ( or something else! )
```

Windows normally gives your drives names like 'C:', 'D:', 'E:', right? I'm not a Windows expert but I know that this is what it looks like on a Windows computer.

5 What is a Filesystem

They are fantastically interesting things. There are many different types of them. A filesystem is a very low-level thing that describes the layout of a physical disk in terms of where the ones and zeros go on the disk and what they mean when they are in different locations. You will work mostly with ext3 and ext4 in your life on Linux, but there are others. We could discuss the differences between them, compare performance of different file systems, but I feel like that would take away from the flow of this lecture.

Write on board: Do not confuse the Linux filesystem hierarchy (which we have described above) with a filesystem, which is more low level concept of where 1s and 0s are stored on a physical disk. Some filesystems are ext3 and ext4, fat. We will use refer to filesystems in this class, you now know that it is a thing. It is your responsibility to go read about them because we simply don't have time here and it isn't just a Linux concept - it is a computer concept. Windows, BSD, Linux, etc. all use filesystems.

After this class, go out and research what ZFS, EXT4, EXT3, FAT32, etc. are for yourself. It will be enlightening for you as a computer professional.

Have a look at the file systems your disks use with:

```
1 user@machine$ df -TH
```

6 Looking at Partitions, Partitioning and Mounting

6.1 Introduction

Let's look at the two drives we added, the one had a partition on it, the other one didn't. What does that mean??

lsblk -h shows us options for showing information about our drives. There's a lot to take in. Let's focus on this command:

6.2 parted

If you happen to miss class and are reading these notes, here's a good reference to get you started

<https://www.digitalocean.com/community/tutorials/how-to-partition-and-format-storage-devices-in-linux>
These notes ought to be good, but sometimes it helps to have another reference.

You may notice that drive sda is 10G and the partition sda1 takes up the full 10G, whereas sda2 takes up only 4XX GB of the 500GB on the disk, and then sdc is a 500GB drive with no partition. There are some weird things happening here and I'm going to explain the basics to you.

We are going to format and add some space to our machine under /mnt, just to do it as an exercise.

```

1 # below I refer to /dev/sdc. The added disk will likely have a different name
2 # like sda or sdb on your machine! Be careful!
3 sudo parted /dev/sdc mklabel gpt # sdc is the name of the drive, not a
4 partition.
5 sudo parted /dev/sdc mkpart primary ext4 0% 100% # same as above
6 lsblk
7 # now its there
8 sudo mkfs.ext4 /dev/sdc1
9 sudo mkdir -p /mnt/newdrive
10 sudo mount /dev/sdc1 /mnt/newdrive
11 lsblk
12 # now the partition is mounted
13 lsblk --output NAME,FSTYPE,SIZE,MOUNTPOINT

```

You can also unmount the drive

```

1 # note the command is umount, NOT unmount!
2 user@machine$ #sudo umount mountpoint
3 user@machine$ sudo umount /mnt/newdrive

```

6.3 Again step by step

```

1 sudo parted /dev/sdc mklabel gpt

```

We first label the disk. This layouts the structure of the disk. There are other names for the label - partition table and partition map are other names. The disk has some metadata about the partitions it contains and how they are structured, that's what this is for. You will mainly be interested in mbr/msdos or gpt partition tables. There's plenty to be said about mbr vs gpt partition tables. If you want to leave class knowing something, though maybe not understanding it fully - MBR is good for drives up to 2TB. Past that you need GPT. GPT is associated with UEFI whereas MBR is associated with BIOS. If you're confused, keep studying. In the meantime, just use gpt on Linux.

```

1 root@machine$ parted -l
2 # you can look through here to verify that you have labeled your disk as gpt.
3 # The label is also referred to as a Partition table!

```

Now to add a partition to the labeled disk. So far the disk is not useable for storage.

```

1 sudo parted /dev/sdc mkpart primary ext4 0% 100%

```

This command puts a partition on the labeled disk. The partition can be extended/logical or primary. For us we will make a primary partition. We also tell parted what file system type we are going to put in the partition. We will use ext4. There are many file system types, and you can read in depth about them if you're interested. ext4 is "the best file system type in Linux" in some senses, and not as good as file system types in other senses. It's up to you how much you want to know. Here's a reference to get you started:

1. <https://opensource.com/article/17/5/introduction-ext4-filesystem>
2. <https://askubuntu.com/questions/44908/what-is-the-difference-between-ext3-ext4-from-a-generic-users-p>

We also made the partition start at 0% and go all the way to the end of the drive.

```

1 sudo mkfs.ext4 /dev/sdc1

```

This puts the ext4 filesystem on the partition you created. A good question to ask yourself is "why did we type ext4 in the command to create the partition?" We'll ignore that question for now and continue on our quest to add some more disk space to our machines.

```

1 sudo mkdir -p /mnt/newdrive

```

create a mount point for your new disk. You can put it in mnt for now.

```
1 sudo mount /dev/sdc1 /mnt/newdrive
```

Now mount your disk.
You can see it with

```
1 lsblk
```

or also with

```
1 user@machine$ df
```

Now mount/unmount the drive a few times to check it out.
Add some stuff to the partition, unmount it, remount it. see stuff is still there.
unmount it and mount it somewhere else.
see the stuff you created is still there under the mount point.

6.4 Restarting machine makes this go away

```
1 user@machine$ sudo reboot
2 #new terminal
3 user@machine$ lsblk
4 #mounted disk not there anymore.
```

to make the disk permanently mounted, update `/etc/fstab`. You know it makes sense for this information to be in `/etc`, because of our previous discussion of the purpose of `/etc`.

```
# part          mounnt_point fstype ignore  ignore ignore
UUID goes here /mnt/data      ext4  defaults 0       2
```

Here's a good reference. It explains what the last three parameters are. Not relevant to us now, but they are important. We won't discuss them because that would take us off track.

<https://help.ubuntu.com/community/Fstab>

6.5 How to get the UUID to add to `/etc/fstab` ?

```
1 user@machine$ sudo blkid
2 # outputs all the blkids along with UUIDs for some of them.
3 user@machine$ cat /etc/fstab
4 # you should see some of those UUIDs already there I havent tested this on
5 # digital ocean yet, but that's how it needs to be I've checked this on my
6 # laptop and pc and that is how it is. If digital ocean does this a different
7 # way that is some cloud machine weirdness and not indicative of a standard
8 # linux experience.
```

To modify your `fstab` file as shown above to remember your new disk, open `/etc/fstab` with `vim` from a `sudo` privileges.

Or you can use this shorthand:

```
1 user@machine$ sudo -e /etc/fstab
2 # opens in editor note the editor might not be vim
```

To change the editor to `vim`, use `update-alternatives` like this:

```
1 user@machine$ sudo update-alternatives --config editor
2 # and chose vim. if vim isn't offered, cancel. then apt install vim then try
3 # again. vi should always be there on any linux/bsd/*nix system, I'm putting
4 # this note here just in case.
```

6.6 Verify the Partition Now Mounts Automatically

TO SEE that it is now mounted even after reboot, reboot your machine!

```
1 sudo reboot
```

Log back in and see the partition is present using *lsblk*.

6.7 Move opt to separate partition

```
1 root@machine$ mkdir -p /mnt/tmpLocation
2 root@machine$ sudo mount /dev/sdc1 /mnt/tmpLocation
3 root@machine$ cp -aR /opt/* /mnt/tmpLocation
4 root@machine$ umount /mnt/tmpLocation
5 root@machine$ mount /dev/sdc1 /opt
6 # now the stuff that was in /opt is stored on /dev/sdc1, which is mounted at
7 # /opt.
8 root@machine$ lsblk
```

Note that */dev/sdc1* is now mounted at */opt*. Notice that the contents of that partition are now visible under */opt*.

Unmount the drive. Put some stuff in */opt*. Remount the drive. Notice that the stuff you put in *opt* are hidden, but the drive stuff is there. The stuff is still there, if you unmount the drive you will see the files there - but when you mount the partition there those files are hidden by the stuff in the partition.

There may be ways to change this behavior, but that's not the way Linux works.

6.8 What does *cp -aR* do?

This command means that the copy retains all privileges and permissions as they were in the original. If you run *cp* without these options, it will give the ownership to the user performing the copy. We don't want that, because there might be files that belong to certain users in */opt* that we don't want to assign to the user making the copy.

Note that when I was taught I learned *-aR*, but it seems to me by reading the man page that *cp -aR* is redundant because *-a* means *-dR*, so *-aR* is like *-dRR* which is redundant

7 fdisk & gparted

There are a bunch of popular tools for doing what we have done today. Two of the popular ones are *fdisk* and *gparted*. You should learn and use them.

8 Swap Space

Now we know a bit about formatting disks and what a partition is. Let's look at an interesting thing called Swap Space.

What is swap space? Your computer has RAM, Random access memory, where programs are loaded in and run from. This is volatile memory, as soon as you power off your machine everything in RAM is gone. This is different from non volatile memory, like a HDD or SSD, where files are permanently stored - things like your pictures, etc. We've seen in this class how to add more non volatile memory to your system, now we're going to ask the question - "what happens if you run out of RAM??" What if you want to have 10000 browser tabs open and not just 5, but your measly 8GB RAM stick in your laptop won't handle that kind of abuse? What if you want to run chrome, pycharm, vscode, inkscape, blender, steam, and a few other things at one time?? You can add more memory as swap space!

Swap space is some space on disk - on your HDD or SSD or USB or whatever that the OS uses to store data from RAM when there is no more space! Collectively you refer to the swap space + the ram space on your system as the virtual memory.

8.1 Overloading the memory on your system

We're going to use a stress testing utility to fill up the memory on the system. I could also have written a little program to fill memory, but this tool exists so we'll just use it.

```
1 apt-get install stress
```

Run tmux, split the pane. Run this

```
1 stress --vm-bytes $(awk '/MemAvailable/{printf "%d\n", $2 * 0.9;}') < /proc/meminfo)k
   --vm-keep -m 1
```

in one pane and run 'top' in the other. Watch how the memory is filled up. When you've had enough fun looking at your computer's ram get filled up, then kill the process and move on to the next section. Now you have a new tool! The *stress* command is super useful when you just want to beat your machine up and see if it crashes. This is a thing you do a lot in software testing. Perhaps you wrote a desktop application and you want to make sure that it doesn't crash if some other process starts gobbling up memory.

Make sure to kill the stress process and let's move on. We'll use that tool later.

8.2 Let's add some swap space.

Is there any swap space yet?

```
1 sudo swapon --show
2 # no
3 free -h
4 # only ram is shown
```

Shouldn't be. By default you don't get any in your debian 9 google cloud vm.

```
1 sudo fallocate -l 1G /swapfile
```

Install fallocate if it isn't installed.

This just allocates 1GB for a file called "swapfile" located at "/". Then change permissions and configure it as swap.

```
1 sudo chmod 600 /swapfile
2 sudo mkswap /swapfile
3 sudo swapon /swapfile
4 sudo swapon --show
5 # you will see that you have swap space now
6 free -h
7 # you will see you have swap space
```

You can play with this a few times to see for yourself how easy it is to add / remove swap space.

```
1 sudo swapoff /swapfile
2 free -h
3 sudo swapon /swapfile
4 free -h
5 # do this a few times to develop muscle memory
```

8.3 Playing around with swap space a bit

Notice that

```
1 cat /proc/meminfo | grep MemAvailable
```

reports available RAM, and not swap space. Let's try and allocate more memory than fits in RAM, by trying to put more than "MemAvailable" bytes into memory. We'll get the MemAvailable from /proc/meminfo and then multiply it by 1.1, and then try to stress our system by allocating that much memory. Then we'll look at top and see that some swap space was used.

BTW - if you want to see swap space in /proc/meminfo you can grep for Swap

Run two vertical tmux panes, in the left put 'top' in the right, run this command. Notice that swap space is used.


```
1 stress --vm-bytes $(awk '/MemAvailable/{printf "%d\n", $2 *  
2 1.1;}' < /proc/meminfo)k --vm-keep -m 1
```

Try to turn swap off and notice that the OS yells at you because it can't allocate the memory to bring the stuff out of swap back to RAM. Then kill the stress test with CTRL C. Look at top. Notice that alot of stuff has stayed in swap space. That's an operating system thing. It could have been programmed to detect when there is space in RAM and always bring the swap stuff back to ram when possible, but it doesnt. You can force it to now by turning swap off. Maybe the OS does eventually pull it back to RAM I don't know. Maybe it waits an hour, or maybe there's another trigger, you'd have to look at the guts of the code to know for sure.

Use top and htop when showing these memory examples

8.4 Making the swap space permanent between reboot

You know how to do this! Which file must we edit to make the swap space endure? You have to edit '/etc/fstab' just like with adding disks / partitions.

```
1 /swapfile swap swap defaults 0 0
```

8.5 Swap space can be on it's own partition too

Add a disk to your machine.

```
1 parted /dev/sdX mklabel gpt  
2 mkpart primary linux-swap 0% 100%  
3 sudo mkswap /dev/sdXN  
4 sudo swapon /dev/sdXN
```

Then play with the swap space as we did with the swap file, you can update fstab too.

Assuming you had a drive called 'sdc' and the partition you create is called '/dev/sdc1' you would type the above commands as:

```
1 parted /dev/sdc mklabel gpt  
2 mkpart primary linux-swap 0% 100%  
3 mkswap /dev/sdc1  
4 swapon /dev/sdc1
```

You need to make the swap space last between reboots on your computer, so you need a UUID for it to put in your /etc/fstab.

8.6 How much swap space to use?

Note that above we used hundreds of gigabytes for swap space. Do not do this. Typically you give a few Gigabytes. There are a few rules of thumb out there about swap space and to be honest I've never had the time to do any performance testing to see the effects of different amounts of swap space. Since I have no expertise in swap space, and you can read the manuals just as good as I can, you can go out and read opinions about how much swap space to use (if any at all) and then make your own expert judgement.

I've had you use a ridiculous amount of swap space because I want us to go in depth into disk partitioning in a coming lecture and tell you about partition alignment and boot sectors.

I hope your brains feel sufficiently stimulated by these few exercises we've done using swap space so that you don't mind that I've omitted some information.

9 Warning

Make sure to delete the drive you allocated in class after you are done with it! It is only \$ a month, so even if you forget it for a year its still cheaper than lunch for 2 at mcdonalds - nevertheless, don't waste your hard earned money!


10 If Extra Time, Do The Homework

If there is extra time in class, just start the homework with students.


11 Week 11 Homework - How to get a 100%

I've run through and done the homework. As you can see by the time stamps on the images (my laptop clock is in the center-top of most images) I did the work, took screen shots, and typed up this document in about 15 minutes. If you are confused about the assignment, make sure to look at what I've done in each image carefully and reproduce the steps on your own machine.


11.1 Go to the 'Volumes' page on your digital ocean account




11.2 Add a Tiny Volume for Swap Space



11.3 Add a Tiny Volume for /home



11.4 Make Sure You Have Two Disks


A terminal window titled 'Terminal' showing the output of the 'lsblk' command. The output lists several disks: sda (2G), sdb (2G), vda (25G), vda1 (25G part), and vdb (450K disk). The terminal is running on a system with the hostname 'debian-s-1vcpu-1gb-nyc3-01'.

```
root@debian-s-1vcpu-1gb-nyc3-01:~# lsblk
NAME MAJ:MIN RM SIZE RO TYPE MOUNTPOINT
sda   8:0    0   2G  0 disk
sdb   8:16   0   2G  0 disk
vda   254:0   0  25G  0 disk
└─vda1 254:1   0  25G  0 part /
vdb   254:16  0 450K  1 disk
root@debian-s-1vcpu-1gb-nyc3-01:~#
```

Note

*I have disks /dev/sda and /dev/sdb in my **lsblk** results. Those are the two disks added in the previous step.*

11.5 Format one disk for /home

A terminal window showing the steps to format a disk for use as a home partition. The user runs 'lsblk' to confirm disk availability, then 'parted /dev/sda mklabel gpt' to create a GPT partition table, 'parted /dev/sda mkpart primary ext4 0% 100%' to create a primary partition, and 'mkfs.ext4 /dev/sda1' to format it with the ext4 filesystem. The output shows the successful creation of the filesystem with a UUID and superblock backups.

```
root@debian-s-1vcpu-1gb-nyc3-01:~# lsblk
NAME MAJ:MIN RM SIZE RO TYPE MOUNTPOINT
sda   8:0    0   2G  0 disk
sdb   8:16   0   2G  0 disk
vda   254:0   0  25G  0 disk
└─vda1 254:1   0  25G  0 part /
vdb   254:16  0 450K  1 disk
root@debian-s-1vcpu-1gb-nyc3-01:~# parted /dev/sda mklabel gpt
Information: You may need to update /etc/fstab.

root@debian-s-1vcpu-1gb-nyc3-01:~# parted /dev/sda mkpart primary ext4 0% 100%
Information: You may need to update /etc/fstab.

root@debian-s-1vcpu-1gb-nyc3-01:~# mkfs.ext4 /dev/sda1
mke2fs 1.44.5 (15-Dec-2018)
Discarding device blocks: done
Creating filesystem with 523776 4k blocks and 131072 inodes
Filesystem UUID: c6ad5c8c-f36e-43d1-a8e3-608ac34369d3
Superblock backups stored on blocks:
    32768, 98304, 163840, 229376, 294912


Allocating group tables: done
Writing inode tables: done
Creating journal (8192 blocks): done
Writing superblocks and filesystem accounting information: done

root@debian-s-1vcpu-1gb-nyc3-01:~#
```

I

chose to use /dev/sda for my home partition. It makes no difference which you chose.

11.6 Format one disk for swap space

A terminal window showing the process of formatting a disk for swap space. The user runs 'parted /dev/sdb mklabel gpt' and 'parted /dev/sdb mkpart primary linux-swap 0% 100%'. Then they run 'lsblk' to see the disk layout. Next, they run 'mkswap /dev/sdb1' and 'swapon /dev/sdb1'. Finally, they run 'lsblk' again to confirm the swap partition is active.

```
root@debian-s-1vcpu-1gb-nyc3-01:~# parted /dev/sdb mklabel gpt &>/dev/null
root@debian-s-1vcpu-1gb-nyc3-01:~# parted /dev/sdb mkpart primary linux-swap 0% 100%
Information: You may need to update /etc/fstab.


root@debian-s-1vcpu-1gb-nyc3-01:~# lsblk
NAME        MAJ:MIN RM  SIZE RO TYPE MOUNTPOINT
sda          8:0    0   2G  0 disk 
└─sda1       8:1    0   2G  0 part 
sdb          8:16   0   2G  0 disk 
└─sdb1       8:17   0   2G  0 part 
vda        254:0    0  25G  0 disk 
└─vda1      254:1    0  25G  0 part /
vdb        254:16   0 450K  1 disk 

root@debian-s-1vcpu-1gb-nyc3-01:~# mkswap /dev/sdb1
Setting up swapspace version 1, size = 2 GiB (2145382400 bytes)
no label, UUID=980686a9-47c0-4353-900c-b113468ef599
root@debian-s-1vcpu-1gb-nyc3-01:~# swapon /dev/sdb1
root@debian-s-1vcpu-1gb-nyc3-01:~# lsblk
NAME        MAJ:MIN RM  SIZE RO TYPE MOUNTPOINT
sda          8:0    0   2G  0 disk 
└─sda1       8:1    0   2G  0 part 
sdb          8:16   0   2G  0 disk 
└─sdb1       8:17   0   2G  0 part [SWAP]
vda        254:0    0  25G  0 disk 
└─vda1      254:1    0  25G  0 part /
vdb        254:16   0 450K  1 disk 

root@debian-s-1vcpu-1gb-nyc3-01:~#
```

Format /dev/sdb for swap space and turn swap on so you can verify it worked.

11.7 Modify /etc/fstab

A terminal window showing the output of the 'blkid' command and the contents of the '/etc/fstab' file. The 'blkid' output shows details for /dev/vda1, /dev/vdb, /dev/sda1, and /dev/sdb1. The /etc/fstab file shows entries for /, /home, and swap.


```
root@debian-s-1vcpu-1gb-nyc3-01:~# blkid
/dev/vda1: UUID="65b4bbd6-39d1-49da-b0af-65261fa0b4a8" TYPE="ext4"
/dev/vdb:  UUID="2019-11-15-03-09-26-00" LABEL="config-2" TYPE="iso9660"
/dev/sda1: UUID="c6ad5c8c-f36e-43d1-a8e3-608ac34369d3" TYPE="ext4" PARTLABEL="primary" PARTUUID="00505dbf-61f0-4889-bfcc-d1900d8c64e2"
/dev/sdb1: UUID="980686a9-47c0-4353-900c-b113468ef599" TYPE="swap" PARTLABEL="primary" PARTUUID="64cceb6-6e9c-4ef8-b5aa-9737b32761ec"
root@debian-s-1vcpu-1gb-nyc3-01:~#

# /etc/fstab: static file system information.
UUID=65b4bbd6-39d1-49da-b0af-65261fa0b4a8    /      ext4    errors=remount-ro    0    1
UUID=c6ad5c8c-f36e-43d1-a8e3-608ac34369d3    /home  ext4    defaults              0    2
UUID=980686a9-47c0-4353-900c-b113468ef599    swap   swap    defaults              0    0
```

Edit

/etc/fstab so that the new disks are mounted on reboot. Pay careful attention to the contents of this file - we already saw in class how a typo can be catastrophic!


11.8 To be thorough, lets add a user (so */home* isn't empty)



```
root@debian-s-1vcpu-1gb-nyc3-01:~# ls /home
root@debian-s-1vcpu-1gb-nyc3-01:~# adduser melvyn
Adding user `melvyn' ...
Adding new group `melvyn' (1000) ...
Adding new user `melvyn' (1000) with group `melvyn' ...
Creating home directory `/home/melvyn' ...
Copying files from `/etc/skel' ...
New password:
Retype new password:
passwd: password updated successfully
Changing the user information for melvyn
Enter the new value, or press ENTER for the default
  Full Name []:
  Room Number []:
  Work Phone []:
  Home Phone []:
  Other []:
Is the information correct? [Y/n] Y
root@debian-s-1vcpu-1gb-nyc3-01:~#
```

/home is empty. Let's add a user so there's some stuff in /home.

11.9 Let's add one more user for good measure




```
root@debian-s-1vcpu-1gb-nyc3-01:~# ls /home
melvyn
root@debian-s-1vcpu-1gb-nyc3-01:~# adduser yousir
Adding user `yousir' ...
Adding new group `yousir' (1001) ...
Adding new user `yousir' (1001) with group `yousir' ...
Creating home directory `/home/yousir' ...
Copying files from `/etc/skel' ...
New password:
Retype new password:
passwd: password updated successfully
Changing the user information for yousir
Enter the new value, or press ENTER for the default
  Full Name []:
  Room Number []:
  Work Phone []:
  Home Phone []:
  Other []:
Is the information correct? [Y/n] root@debian-s-1vcpu-1gb-nyc3-01:~#
root@debian-s-1vcpu-1gb-nyc3-01:~# ls /home
melvyn yousir
root@debian-s-1vcpu-1gb-nyc3-01:~#
```

Kind

of boring to add just one user. Let's add another one so /home has two users' home directories.

11.10 Have a peek at `/home` permissions before moving to new disk


A terminal window titled 'Terminal' showing the command `ls -l /home` and its output. The output shows two directories, 'melvyn' and 'yousir', both with permissions `drwxr-xr-x`, owned by 'melvyn' and 'yousir' respectively, and created on Nov 15. The terminal is running on a system with the hostname 'debian-s-1vcpu-1gb-nyc3-01'.

```
root@debian-s-1vcpu-1gb-nyc3-01:~# ls -l /home
total 8
drwxr-xr-x 2 melvyn melvyn 4096 Nov 15 14:51 melvyn
drwxr-xr-x 2 yousir yousir 4096 Nov 15 14:52 yousir
root@debian-s-1vcpu-1gb-nyc3-01:~#
```

Now

/home is more interesting.


11.11 Move `/home` and verify permissions are still correct.

A terminal window titled 'Terminal' showing a series of commands to move the `/home` directory to a new partition. The commands include creating a temporary mount point, mounting the partition, copying the contents of `/home` to the new location, removing the old `/home` directory, and finally mounting the partition at `/home`. The output of `lsblk` shows the disk layout, and the output of `ls -l /mnt/tmpmount/` shows the copied files with their permissions.

```
root@debian-s-1vcpu-1gb-nyc3-01:~# export PS1=">"
>mkdir /mnt/tmpmount
>mount /dev/sda1 /mnt/tmpmount/
>lsblk
NAME MAJ:MIN RM SIZE RO TYPE MOUNTPOINT
sda 8:0 0 2G 0 disk
└─sda1 8:1 0 2G 0 part /mnt/tmpmount
sdb 8:16 0 2G 0 disk
└─sdb1 8:17 0 2G 0 part [SWAP]
vda 254:0 0 25G 0 disk
└─vda1 254:1 0 25G 0 part /
vdb 254:16 0 450K 1 disk
>cp -a /home/* /mnt/tmpmount
>ls -l /mnt/tmpmount/
total 24
drwx----- 2 root root 16384 Nov 15 14:45 lost+found
drwxr-xr-x 2 melvyn melvyn 4096 Nov 15 14:51 melvyn
drwxr-xr-x 2 yousir yousir 4096 Nov 15 14:52 yousir
>rm -r /home/*
>ls /home
>umount /mnt/tmpmount
>mount /dev/sda1 /home
>ls /home
lost+found melvyn yousir
>
```

Move the home directory to the new partition. Just take a quick peek to see that the move went successfully.

11.12 Reboot and verify that the swap space and home partition are still mounted



```
Activities  Terminal  Fri 09:56
Terminal
File Edit View Search Terminal Tabs Help
Terminal
>reboot
>Connection to 167.172.230.194 closed by remote host.
Connection to 167.172.230.194 closed.
melvyn$ ssh root@167.172.230.194
Linux debian-s-1vcpu-1gb-nyc3-01 4.19.0-6-cloud-amd64 #1 SMP Debian 4.19.67-2+deb10u1 (2019-09-20) x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
Last login: Fri Nov 15 14:55:47 2019 from 174.225.139.19
root@debian-s-1vcpu-1gb-nyc3-01:~# uptime
14:56:24 up 0 min, 1 user, load average: 0.13, 0.03, 0.01
root@debian-s-1vcpu-1gb-nyc3-01:~# lsblk
NAME MAJ:MIN RM SIZE RO TYPE MOUNTPOINT
sda 8:0 0 2G 0 disk
└─sda1 8:1 0 2G 0 part [SWAP]
sdb 8:16 0 2G 0 disk
└─sdb1 8:17 0 2G 0 part /home
vda 254:0 0 25G 0 disk
└─vda1 254:1 0 25G 0 part /
vdb 254:16 0 450K 1 disk
root@debian-s-1vcpu-1gb-nyc3-01:~# ls /home
lost+found melvyn yousir
root@debian-s-1vcpu-1gb-nyc3-01:~#
```

voila! It worked!

12 References

Follow these excellent online tutorials.: 1. <https://linuxize.com/post/how-to-add-swap-space-on-debian-9/> 2. <https://opensource.space-linux-systems>