

Real-Time Garbage Classification Using Lightweight CNN and Webcam

- This presentation explores an innovative, low-resource solution utilizing a lightweight CNN and webcam technology for sustainable waste management. Presented by Hang Zhao from Northeastern University.

Hang Zhao, Northeastern University, Boston, MA, USA

March 31, 2025

ORGANIC

PAPER

PLASTIC


GLASS

Overview of the presentation

- Introduction
- Related Work
- Methods - Data and Model
- Methods - Real-Time Classification
- Experiments and Results
- Demo
- Discussion and Summary

Introduction

- Garbage classification is crucial for effective waste management.
- Manual sorting is inefficient and error-prone.
- Project Goal: Develop a lightweight real-time garbage classification system using a webcam and CNN.
- Input: Webcam video frames; Output: Garbage category labels (Recyclable, Wet, Dry).




Related Work

- Yang et al. (CVPR 2019): TrashNet dataset, 87% accuracy, complex model.
- Bircanoğlu et al. (ICCV 2018): RecycleNet, 91% accuracy, high computational demand.
- Chu et al. (WACV 2018): CNN-SVM hybrid model, 88% accuracy, high complexity.
- Our Work: Lightweight model, real-time CPU performance.


Methods - Data and Model

- Data: Subset of TrashNet (300 images: plastic, paper, wet waste), 64x64 pixels.
- Data Augmentation: Random flips, brightness adjustments.
- Model: Lightweight CNN (2 conv layers, 2 fully connected layers).
- Training: SGD optimizer, 10 epochs, batch size 16.



Methods - Real-Time Classification

- Frame Preprocessing: Grayscale, binarization, contour detection, resize to 64x64.
- Inference: Predict category using trained CNN.
- Display: Overlay label (e.g., “Recyclable”) on video frame.
- Performance: 15-20 FPS (Intel i5 CPU).



Experiments and Results

- Test Accuracy: 86.7% (300 images).
- Training Time: 90.5 seconds (10 epochs).
- Real-Time Performance: 15-20 FPS, correctly classifies common garbage (plastic bottles, food scraps).
- Comparison with Prior Work: Slightly below Yang et al. (87%), but smaller dataset, lower resource needs.

Training and Testing Accuracy on Garbage Dataset




TABLE I
COMPARISON OF GARBAGE CLASSIFICATION ACCURACY.

Method	Dataset Size	Test Accuracy (%)
Yang et al. [1]	2527	87.0
Bircanoğlu et al. [2]	5000	91.0
Chu et al. [3]	1500	88.0
Ours	300	86.7

Demo



Discussion and Summary

- Successfully achieved real-time classification, 86.7% accuracy, 15-20 FPS.
- Strengths: Lightweight, suitable for low-resource environments.
- Limitations: Small dataset, misclassification in complex backgrounds.
- Future Work: Larger dataset, improved preprocessing, stronger models (e.g., MobileNet).
- Contribution: Practical tool for sustainable waste management.