

Step 1: Study 1135 Connecting Cities With Minimum Cost (local copy) – Medium

×

↺

```
from collections import defaultdict
from heapq import heappop, heappush

class Solution:
    def minimumCost(self, N: int, connections: List[List[int]]) -> int:
        neighbor = defaultdict(list)
        for i, j, c in connections:
            neighbor[i].append((j, c))
            neighbor[j].append((i, c))
        #print(nbrs)
        res = 0
        mini_heap = [(0, 1)]
        visited = set()
        while mini_heap:
            c, i = heappop(mini_heap)
            if i in visited:
                continue
            else:
                visited.add(i)
                res += c
                if len(visited) == N:
                    return res
                else:
                    for j, c in neighbor[i]:
                        if j in visited:
                            continue
                        else:
                            heappush(mini_heap, (c, j))
        return -1
```

Console ^

⌘

Run

Submit


^ ↺ 🗨

ENG

📶 🔊 🔋

7:11 PM
6/21/2023 3

Step 2: Use Prim approach to find Minimum Spanning Tree of this question




Step 3: Ask ChatGPT: "How to use Prim approach to implement a Python code to solve the LeetCode question: '1135 Connecting Cities With Minimum Cost', with the test data: 'Input: n = 3, connections = [[1, 2, 5],[1,3,6],[2,3,1]], Output: 6'"

To solve the LeetCode question "Connecting Cities With Minimum Cost" using Prim's algorithm in Python, you can follow these steps:

1. Initialize a list, `graph`, to represent the graph where each index represents a city and the value at that index represents a list of connections from that city. Initialize another list, `visited`, to keep track of visited cities, initially filled with `False` values.
2. Create a helper function, `add_connection`, to add connections to the `graph` list. This function takes the city `u`, destination city `v`, and the cost of the connection `cost`. It appends a tuple `(v, cost)` to the list at index `u` and vice versa since the connections are bidirectional.
3. Create a helper function, `minimum_cost`, to calculate the minimum cost using Prim's algorithm. This function takes the total number of cities `n` and the `graph` as input.
4. Initialize a priority queue, `pq`, to store the edges with their costs in increasing order. You can use the `heapq` module to implement the priority queue.
5. Start from any city, `start_city`, and mark it as visited by setting `visited[start_city] = True`. Then, iterate over the connections from the `start_city` and add them to the priority queue.
6. While the priority queue is not empty, perform the following steps:
 - Pop the edge with the minimum cost from the priority queue.
 - If the destination city of the edge is not visited:
 - Mark the destination city as visited.
 - Add the cost of the connection to the `minimum_cost` variable.
 - Iterate over the connections from the destination city and add them to the priority queue.
7. After the loop ends, check if all cities are visited. If not, return -1 since it means the graph is not connected.
8. Finally, return the `minimum_cost` variable, which represents the minimum cost to connect all cities.

Here's the Python code implementing the Prim's algorithm for the given test data:

python

 Copy code

```
import heapq

def add_connection(graph, u, v, cost):
    graph[u].append((v, cost))
    graph[v].append((u, cost))

def minimum_cost(n, connections):
    graph = [[] for _ in range(n + 1)]
    visited = [False] * (n + 1)

    for u, v, cost in connections:
        add_connection(graph, u, v, cost)

    start_city = 1
    visited[start_city] = True

    pq = []
    minimum_cost = 0

    for v, cost in graph[start_city]:
        heapq.heappush(pq, (cost, v))
```

```

while pq:
    cost, u = heapq.heappop(pq)

    if not visited[u]:
        visited[u] = True
        minimum_cost += cost

        for v, cost in graph[u]:
            heapq.heappush(pq, (cost, v))

    if not all(visited[1:]):
        return -1

    return minimum_cost

# Test data
n = 3
connections = [[1, 2, 5], [1, 3, 6], [2, 3, 1]]
output = minimum_cost(n, connections)
print(output) # Output: 6

```

The code above should solve the given LeetCode question using Prim's algorithm and provide the correct output for the provided test data.

Step 4: Implement the Python code created by ChatGPT


```
q1.py > ...
1  import heapq
2
3  def add_connection(graph, u, v, cost):
4      graph[u].append((v, cost))
5      graph[v].append((u, cost))
6
7  def minimum_cost(n, connections):
8      graph = [[] for _ in range(n + 1)]
9      visited = [False] * (n + 1)
10
11     for u, v, cost in connections:
12         add_connection(graph, u, v, cost)
13
14     start_city = 1
15     visited[start_city] = True
16
17     pq = []
18     minimum_cost = 0
19
20     for v, cost in graph[start_city]:
21         heapq.heappush(pq, (cost, v))
22
23     while pq:
24         cost, u = heapq.heappop(pq)
25
26         if not visited[u]:
27             visited[u] = True
28             minimum_cost += cost
29
30             for v, cost in graph[u]:
31                 heapq.heappush(pq, (cost, v))
32
33     if not all(visited[1:]):
34         return -1
35
36     return minimum_cost
37
38 # Test data
39 n = 3
40 connections = [[1, 2, 5], [1, 3, 6], [2, 3, 1]]
41 output = minimum_cost(n, connections)
42 print(output) # Output: 6
43
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL Python + - [] [x] ... ^

```
PS D:\MSCS\CS455 Algorithm\w5> & C:/Users/odody/AppData/Local/Programs/Python/Python311/python.exe "d:/MSCS/CS455 Algorithm/w5/q1.py"
6
PS D:\MSCS\CS455 Algorithm\w5>
```

ve Share Column Selection Ln 43, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.3 64-bit Go Live 10:21 PM 6/21/2023

q1.py > ...

```
1 import heapq
2
3 def add_connection(graph, u, v, cost):
4     graph[u].append((v, cost))
5     graph[v].append((u, cost))
6
7 def minimum_cost(n, connections):
8     graph = [[] for _ in range(n + 1)]
9     visited = [False] * (n + 1)
10
11     for u, v, cost in connections:
12         add_connection(graph, u, v, cost)
13
14     start_city = 1
15     visited[start_city] = True
16
17     pq = []
18     minimum_cost = 0
19
20     for v, cost in graph[start_city]:
21         heapq.heappush(pq, (cost, v))
22
23     while pq:
24         cost, u = heapq.heappop(pq)
```

```
26         if not visited[u]:
27             visited[u] = True
28             minimum_cost += cost
29
30             for v, cost in graph[u]:
31                 heapq.heappush(pq, (cost, v))
32
33     if not all(visited[1:]):
34         return -1
35
36     return minimum_cost
37
38 # Test data
39 n = 4
40 connections = [[1,2,3],[3,4,4]]
41 output = minimum_cost(n, connections)
42 print(output) # Output: -1
43
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

Python + - [] [] ... ^

```
PS D:\MSCS\CS455 Algorithm\w5> & C:/Users/odody/AppData/Local/Programs/Python/Python311/python.exe "d:/MSCS/CS455 Algorithm/w5/q1.py"
-1
PS D:\MSCS\CS455 Algorithm\w5>
```

ve Share

Column Selection

Ln 40, Col 32

Spaces: 4

UTF-8

CRLF

{ } Python

3.11.3 64-bit

Go Live

10:22 PM

6/21/2023