

Package ‘fbi’

July 25, 2020

Type Package

Title Factor-Based Imputation and FRED-MD Data Set

Version 0.2.0

Date 2020-07-24

Author Yankang (Bennie) Chen [aut, cre],
Serena Ng [aut],
Jushan Bai [aut]

Maintainer Yankang (Bennie) Chen <yankang.chen@columbia.edu>

Description Factor-Based imputation of missing values in panel data and manipulation of the FRED-MD Data Set. It estimates the factor model in the panel data based on the methods in Bai and Ng (2002) <doi:10.1111/1468-0262.00273> and Bai and Ng (2017) <doi:10.1016/j.jeconom.2019.04.021>. It then computes the missing values using the Tall-Wide method (Bai and Ng (2019) <arXiv:1910.06677>) or the Tall-Project method (Bai, Cahan, and Ng (2019), unpublished manuscript). It also facilitates loading, preparing, and interpreting the FRED-MD data set <https://research.stlouisfed.org/econ/mccracken/fred-databases>.

URL <https://github.com/cykbennie/fbi>

Depends R (>= 3.5.0)

Imports stats, readr, pracma

License GPL-3 + LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Suggests knitr, rmarkdown

VignetteBuilder knitr

R topics documented:

fbi-package	2
apc	3
demeanXY	4
describe_md	4

describe_qd	5
fredmd	6
fredmd_description	7
fredqd	7
fredqd_description	8
removeFE	9
rm_outliers.fredmd	10
rpca	10
se.rpca	12
tnt	12
tp_apc	13
tw_apc	14
Index	15

fbi-package

Factor-Based Imputation and FRED-MD/QD Data Set

Description

The fbi package contains functions to estimate factor models and impute missing data based on factor models. It also includes functions to load and prepare the FRED-MD/QD data set.

Details

See `vignette("factor_fred", package = "fbi")` for an example using the FRED-MD dataset (<https://research.stlouisfed.org/econ/mccracken/fred-databases/>).

Author(s)

Yankang (Bennie) Chen <yankang.chen@columbia.edu>

Serena Ng <serena.ng@columbia.edu>

Jushan Bai <jushan.bai@columbia.edu>

References

Jushan Bai and Serena Ng (2002), *Determining the number of factors in approximate factor models*. <https://onlinelibrary.wiley.com/doi/pdf/10.1111/1468-0262.00273>

Jushan Bai and Serena Ng (2017), *Rank regularized estimation of approximate factor models*. <https://www.sciencedirect.com/science/article/pii/S0304407619300764>

apc

Factor Model of Balanced Panel Data

Description

apc estimates the factor model of a given balanced panel data.

Usage

```
apc(X, r)
```

Arguments

X	a matrix of size T by N.
r	integer, indicating the maximum number of factors.

Value

a list of elements:

Fhat

Lamhat

d

d0

ehat

Author(s)

Yankang (Bennie) Chen <yankang.chen@columbia.edu>

Serena Ng <serena.ng@columbia.edu>

Jushan Bai <jushan.bai@columbia.edu>

References

Jushan Bai and Serena Ng (2002), *Determining the number of factors in approximate factor models*.
<https://doi.org/10.1111/1468-0262.00273>

demeanXY	<i>Demean Panel Data</i>
----------	--------------------------

Description

demeanXY demeans the panel data.

Usage

```
demeanXY(X, N, T, N0, T0)
```

Arguments

X	detaframe or matrix of the original panel data.
N	integer, total number of columns of the panel data.
T	integer, total number of rows of the panel data.
N0	integer, the number of columns in the panel data with full data availability.
T0	integer, the number of rows in the panel data with full data availability.

Value

a list of elements:

X1	demeaned data
FE	estimated fixed effects matrix

Author(s)

Yankang (Bennie) Chen <yankang.chen@columbia.edu>
 Serena Ng <serena.ng@columbia.edu>
 Jushan Bai <jushan.bai@columbia.edu>

describe_md	<i>Describe selected variables in the FRED-MD Data Set</i>
-------------	--

Description

describe_md provides a description of the selected variables in the FRED-MD data set.

Usage

```
describe_md(varname, name.only = TRUE, verbose = FALSE)
```

Arguments

varname	string or a vector strings of the format "X1" to "X135".
name.only	logical. If TRUE, return a dataframe with variable names and types of transformation only; if FALSE, return a dataframe with more details.
verbose	logical, indicating whether or not descriptions should be printed.

Value

a vector of variable names, or a data frame with detailed descriptions.

Author(s)

Yankang (Bennie) Chen <yankang.chen@columbia.edu>

References

Michael W. McCracken and Serena Ng (2015), *FRED-MD Updated Appendix*. https://s3.amazonaws.com/files.fred.stlouisfed.org/fred-md/Appendix_Tables_Update.pdf

Examples

```
library(fbi)
varnames <- describe_md(c("X32", "X56"), name.only = TRUE, verbose = FALSE)
```

describe_qd	<i>Describe selected variables in the FRED-QD Data Set</i>
-------------	--

Description

describe_qd provides a description of the selected variables in the FRED-QD data set.

Usage

```
describe_qd(varname, name.only = TRUE, verbose = FALSE)
```

Arguments

varname	string or a vector strings of the format "X1" to "X135".
name.only	logical. If TRUE, return a dataframe with variable names and types of transformation only; if FALSE, return a dataframe with more details.
verbose	logical, indicating whether or not descriptions should be printed.

Value

a vector of variable names, or a data frame with detailed descriptions.

Author(s)

Yankang (Bennie) Chen <yankang.chen@columbia.edu>

References

Michael W. McCracken and Serena Ng (2020), *FRED-QD Updated Appendix*. https://s3.amazonaws.com/files.fred.stlouisfed.org/fred-md/FRED-QD_appendix.pdf

Examples

```
library(fbi)
varnames <- describe_qd(c("X32", "X56"), name.only = TRUE, verbose = FALSE)
```

fredmd

*Loading FRED-MD Data Set***Description**

fredmd loads the official FRED-MD data set and provides a few tools to manipulate the data set.

Usage

```
fredmd(date_start = NULL, date_end = NULL, transform = TRUE, local = FALSE)
```

Arguments

date_start	Date or NULL, the start date (included) of the data selection. If NULL, select till the latest data available.
date_end	Date or NULL, the end date (included) of the data selection. If NULL, select up to the earliest data available.
transform	logical, indicating Whether or not the FRED-MD data set should be transformed according to the transformation code.
local	logical, indicating Whether or not the FRED-MD data set should be loaded from the local files or downloaded online

Value

a subset of the (transformed) FRED-MD data of class fredmd.

Author(s)

Yankang (Bennie) Chen <yankang.chen@columbia.edu>

References

Michael W. McCracken and Serena Ng (2015), *FRED-MD and FRED-QD: Monthly and Quarterly Databases for Macroeconomic Research*. <https://research.stlouisfed.org/econ/mccracken/fred-databases/>

Examples

```
library(fbi)
data <- fredmd(date_start = NULL, date_end = NULL, transform = TRUE, local = FALSE)
```

fredmd_description	<i>FRED-MD Data Set Description</i>
--------------------	-------------------------------------

Description

A description of the FRED-MD data set.

Usage

```
data(fredmd_description)
```

Format

A data frame with 135 rows and 9 variables. The variables are as follows:

id series ID number

tcode code of transformation

ttype type of transformation

fred variable name used in the FRED-MD data set

description description of the series

gsi variable name used in the Global Insights Basic Economics Database (GSI)

gsi:description description of the series in GSI

group group of the series

edited logical, indicating if the data has been edited

varname "X" + id

Source

The fredmd_description data were obtained from Michael W. McCracken and Serena Ng (2015), *FRED-MD Updated Appendix*. https://s3.amazonaws.com/files.fred.stlouisfed.org/fred-md/Appendix_Tables_Update.pdf

fredqd	<i>Loading FRED-QD Data Set</i>
--------	---------------------------------

Description

fredqd loads the official FRED-QD data set and provides a few tools to manipulate the data set.

Usage

```
fredqd(date_start = NULL, date_end = NULL, transform = TRUE, local = FALSE)
```

Arguments

<code>date_start</code>	Date or NULL, the start date (included) of the data selection. If NULL, select till the latest data available.
<code>date_end</code>	Date or NULL, the end date (included) of the data selection. If NULL, select up to the earliest data available.
<code>transform</code>	logical, indicating Whether or not the FRED-QD data set should be transformed according to the transformation code.
<code>local</code>	logical, indicating Whether or not the FRED-QD data set should be loaded from the local files or downloaded online

Value

a subset of the (transformed) FRED-QD data of class `fredqd`.

Author(s)

Yankang (Bennie) Chen <yankang.chen@columbia.edu>

References

Michael W. McCracken and Serena Ng (2015), *FRED-MD and FRED-QD: Monthly and Quarterly Databases for Macroeconomic Research*. <https://research.stlouisfed.org/econ/mccracken/fred-databases/>

Examples

```
library(fbi)
data <- fredqd(date_start = NULL, date_end = NULL, transform = TRUE, local = FALSE)
```

<code>fredqd_description</code>	<i>FRED-QD Data Set Description</i>
---------------------------------	-------------------------------------

Description

A description of the FRED-QD data set.

Usage

```
data(fredqd_description)
```

Format

A data frame with 248 rows and 10 variables. The variables are as follows:

id series ID number

sw_id series ID number in SW (2012)

tcode code of transformation

ttype type of transformation

sw_factors logical, indicating whether a series was used in SW (2012) when constructing factors

fred_mnemonic mnemonic in FRED-QD

sw_mnemonic mnemonic used in SW (2012)

description a brief definition of the series

group group of the series

varname "X" + id

Source

The fredqd_description data were obtained from Michael W. McCracken and Serena Ng (2020), *FRED-QD Updated Appendix*. https://s3.amazonaws.com/files.fred.stlouisfed.org/fred-md/FRED-QD_appendix.pdf

removeFE

Remove Fixed Effects from the Panel Data

Description

removeFE removes fixed effects from the panel data.

Usage

```
removeFE(X, N, T, N0, T0)
```

Arguments

X	detaframe or matrix of the original panel data.
N	integer, total number of columns of the panel data.
T	integer, total number of rows of the panel data.
N0	integer, the number of columns in the panel data with full data availability.
T0	integer, the number of rows in the panel data with full data availability.

Value

a list of elements:

X1	demeaned data
FE	estimated fixed effects matrix

Author(s)

Yankang (Bennie) Chen <yankang.chen@columbia.edu>

Serena Ng <serena.ng@columbia.edu>

Jushan Bai <jushan.bai@columbia.edu>

<code>rm_outliers.fredmd</code>	<i>Remove outliers of the FRED-MD Data Set</i>
---------------------------------	--

Description

`rm_outliers.fredmd` removes outliers of the FRED-MD data set produced by the `fredmd` function.

Usage

```
rm_outliers.fredmd(object)
```

Arguments

`object` an object of class `fredmd`.

Value

FRED-MD data of class `fredmd` with outliers removed.

Author(s)

Yankang (Bennie) Chen <yankang.chen@columbia.edu>

References

Michael W. McCracken and Serena Ng (2015), *FRED-MD and FRED-QD: Monthly and Quarterly Databases for Macroeconomic Research*. <https://research.stlouisfed.org/econ/mccracken/fred-databases/>

Examples

```
library(fbi)
data <- fredmd(date_start = NULL, date_end = NULL, transform = TRUE)
newdata <- rm_outliers.fredmd(data)
```

<code>rpca</code>	<i>Estimation of Approximate Factor Models</i>
-------------------	--

Description

`rpca` estimates the approximate factor models of the given matrix.

Usage

```
rpca(X, kmax, standardize = FALSE, tau = 0)
```

Arguments

X	a matrix of size T by N.
kmax	integer, indicating the maximum number of factors.
standardize	logical, indicating Whether or not X should be centered and scaled.
tau	numeric, specifying the parameter in the rank-regularized estimation. If $\tau = 0$, then rank regularization is not used.

Value

a list of elements:

X
kmax
standardize
tau
ic2
pc2k
pc20
Fhat
Lamhat
Chat
Sigma
IC2
PC2k
PC20
fhat
lamhat
d
d0

Author(s)

Yankang (Bennie) Chen <yankang.chen@columbia.edu>

Serena Ng <serena.ng@columbia.edu>

Jushan Bai <jushan.bai@columbia.edu>

References

- Jushan Bai and Serena Ng (2002), *Determining the number of factors in approximate factor models*.
<https://doi.org/10.1111/1468-0262.00273>
- Jushan Bai and Serena Ng (2017), *Rank regularized estimation of approximate factor models*.
<https://doi.org/10.1016/j.jeconom.2019.04.021>

se.rpca	<i>Standard Error of C^{hat}</i>
---------	--

Description

se.rpca produces the estimated standard error of C^{hat} produced by the `rpca` function.

Usage

```
se.rpca(object, xpoints, qq)
```

Arguments

object	an object of class <code>rpca</code> .
xpoints	placeholder.
qq	placeholder.

Value

standard error of C^{hat}

Author(s)

Yankang (Bennie) Chen <yankang.chen@columbia.edu>
 Serena Ng <serena.ng@columbia.edu>
 Jushan Bai <jushan.bai@columbia.edu>

References

Jushan Bai and Serena Ng (2002), *Determining the number of factors in approximate factor models*.
<https://doi.org/10.1111/1468-0262.00273>
 Jushan Bai and Serena Ng (2017), *Rank regularized estimation of approximate factor models*.
<https://doi.org/10.1016/j.jeconom.2019.04.021>

tnt	<i>Estimate Treatment Effect</i>
-----	----------------------------------

Description

tnt estimates the treatment effect.

Usage

```
tnt(data, param)
```

Arguments

data	list containing x1, x2, y0, y1, N0, N1, T0, and T1.
param	list containing K, r, do_FE, do_IFE, and maxit1.

Value

a list of elements:

est

SE

V

it1

Author(s)

Yankang (Bennie) Chen <yankang.chen@columbia.edu>

Serena Ng <serena.ng@columbia.edu>

Jushan Bai <jushan.bai@columbia.edu>

References

Jushan Bai and Serena Ng (2019), *Matrix Completion, Counterfactuals, and Factor Analysis of Missing Data*. <https://arxiv.org/abs/1910.06677>

tp_apc	<i>Tall-Project Imputation of Missing Value in Panel Data</i>
--------	---

Description

tp_apc imputates the missing values in a given panel data using the method of "Tall-Project".

Usage

```
tp_apc(X1, r1, center = FALSE, standardize = FALSE, re_estimate = TRUE)
```

Arguments

X1	a matrix of size T by N.
r1	integer, indicating the maximum number of factors.
center	logical, indicating whether or not X1 should be demeaned
standardize	logical, indicating whether or not X1 should be scaled.
re_estimate	logical, indicating whether or not output factors, 'Fhat', 'Lamhat', and 'Chat', should be re-estimated from the imputed data.

Value

a list of elements:

Fhat

Lamhat

Chat

data

Author(s)

Yankang (Bennie) Chen <yankang.chen@columbia.edu>

Serena Ng <serena.ng@columbia.edu>

Jushan Bai <jushan.bai@columbia.edu>

References

Cahan, E., Bai, J. and Ng, S. 2019, Factor Based Imputation of Missing Data and Covariance Matrix Estimation. unpublished manuscript, Columbia University

tw_apc

Tall-Wide Imputation of Missing Value in Panel Data

Description

tw_apc imputates the missing values in a given panel data using the method of "Tall-Wide".

Usage

```
tw_apc(X1, r1, center = FALSE, standardize = FALSE, re_estimate = TRUE)
```

Arguments

X1	a matrix of size T by N.
r1	integer, indicating the maximum number of factors.
center	logical, indicating whether or not X1 should be demeaned
standardize	logical, indicating whether or not X1 should be scaled.
re_estimate	logical, indicating whether or not output factors, 'Fhat', 'Lamhat', and 'Chat', should be re-estimated from the imputed data.

Value

a list of elements:

Fhat

Lamhat

Chat

data

Author(s)

Yankang (Bennie) Chen <yankang.chen@columbia.edu>

Serena Ng <serena.ng@columbia.edu>

Jushan Bai <jushan.bai@columbia.edu>

References

Jushan Bai and Serena Ng (2019), *Matrix Completion, Counterfactuals, and Factor Analysis of Missing Data*. <https://arxiv.org/abs/1910.06677>

Index

* datasets

fredmd_description, [7](#)

fredqd_description, [8](#)

apc, [3](#)

demeanXY, [4](#)

describe_md, [4](#)

describe_qd, [5](#)

fbi (fbi-package), [2](#)

fbi-package, [2](#)

fredmd, [6](#), [10](#)

fredmd_description, [7](#)

fredqd, [7](#)

fredqd_description, [8](#)

removeFE, [9](#)

rm_outliers.fredmd, [10](#)

rpca, [10](#), [12](#)

se.rpca, [12](#)

tnt, [12](#)

tp_apc, [13](#)

tw_apc, [14](#)