

# Programming Practices

**Prof. Dr. Dirk Riehle**

**Friedrich-Alexander University Erlangen-Nürnberg**

**AMOS E02**

Licensed under CC BY 4.0 International

**KISS**

**(Keep It Simple, Silly)**

**YAGNI**

**(You Ain't Gonna Need It)**

# DRY

(Don't Repeat Yourself)

- 1. Make it run**
- 2. Make it right**
- 3. Make it fast**



## Definition of Big Ball of Mud [FY97]

A Big Ball of Mud is a haphazardly structured, sprawling, sloppy, duct-tape-and-baling-wire, spaghetti-code jungle. These systems show unmistakable signs of unregulated growth, and repeated, expedient repair. Information is shared promiscuously among distant elements of the system, often to the point where nearly all the important information becomes global or duplicated. The overall structure of the system may never have been well defined. If it was, it may have eroded beyond recognition. Programmers with a shred of architectural sensibility shun these quagmires. Only those who are unconcerned about architecture, and, perhaps, are comfortable with the inertia of the day-to-day chore of patching the holes in these failing dikes, are content to work on such systems.

# Benefits of Good (“Well-Factored”) Code

- 1. Maintainability**  
(Easier to understand)
- 2. Extensibility**  
(Easier to adapt and evolve)
- 3. Predictability**  
(Improves planning ability)



## Technical Debt (Ward Cunningham)

[1] See <https://youtu.be/Jp5japiHAs4>

# Video Lessons

- Technical Debt is a Metaphor
  - Communicates well to manager
  - (Certainly in financial services)
- Taking on debt can speed up development
  - It may be justified to learn faster
  - But you have to pay up later
- If you don't pay back debt you'll slow down
  - Paying up means refactoring
  - Still, never write poor code deliberately

- 1. Identify problem**  
(So-called “code smells”)
- 2. Identify need to act**  
(Correlate occurrences)
- 3. Know how to act**  
(Refactor code)

# Code Smell

- According to Fowler [F99]
  - “smells are certain structures in the code that indicate violation of fundamental design principles and negatively impact design quality”
  - also, “a code smell is a surface indication that usually corresponds to a deeper problem in the system”
- Code smells are not bugs

# Example Code Smells

- Duplicated Code
- Long Method
- Large Class
- ...

# Refactoring (Practice)

- Definition and purpose
  - Is a behavior-preserving transformation of existing source code
  - It is a change made to the internal structure of software to make it easier to understand and cheaper to modify without changing its observable behavior
- More on refactoring
  - Change the structure of code without changing behavior
  - Focus on non-functional features within range of specification
  - Are defined techniques that are typically language specific
  - Are ideally supported by IDEs, for example, the Eclipse JDT
- Defined by Opdyke [O92], popularized by Fowler [F99]

# Example Refactorings

- Rename class
- Pull-up field
- Extract method
- ...
- More at <http://refactoring.com>

# Example Extract-Method Refactoring 1 / 2

```
public class PhotoManager extends ObjectManager {
    protected Map<PhotoId, Photo> allPhotos = new HashMap<PhotoId, Photo>();

    public void addPhoto(Photo photo) {
        PhotoId id = photo.getId();
        assertIsNewPhoto(id);
        allPhotos.put(id, photo);
        ...
    }

    public Photo getPhotoFromId(PhotoId id) {
        Photo result = doGetPhotoFromId(id);
        if (result == null) {
            ...
            if (result != null) { allPhotos.put(id, result); }
        }
        return result;
    }

    public Set<Photo> findPhotosByOwner(String ownerName) {
        ...
        for (Iterator<Photo> i = r.iterator(); i.hasNext();) {
            Photo photo = i.next();
            allPhotos.put(photo.getId(), photo);
        }
        return r;
    }
    ...
}
```



# Example Extract-Method Refactoring 2 / 2

```
public class PhotoManager extends ObjectManager {  
    public void addPhoto(Photo photo) {  
        ...  
        doAddPhoto(photo);  
        ...  
    }  
  
    public Photo getPhotoFromId(PhotoId id) {  
        ...  
        doAddPhoto(photo);  
        ...  
    }  
  
    public Set<Photo> findPhotosByOwner(String ownerName) {  
        ...  
        for (Iterator<Photo> i=r.iterator(); i.hasNext(); ) {  
            doAddPhoto(i.next());  
        }  
        ...  
    }  
  
    protected void doAddPhoto(Photo myPhoto) {  
        allPhotos.put(myPhoto.getId(), myPhoto);  
    }  
  
    ...  
}
```


## The “three strikes” rule

**1st time: Just do it**

**2nd time: Wince at duplication**


**3rd time: Refactor**

# Refactoring Process (Two Hats)



# Code Smells and Refactorings

- Duplicated code
- Long method
- Large class
- ...



# Example Refactoring Process

- The refactoring process can become complex
  - It may turn into a series of refactorings
- Example Removal of Switch Statement
  - Extract Method
  - Move Method
  - Replace Type Code ...
    - with Subclass or
    - with State / Strategy
  - Replace Conditional ...
    - with Polymorphism

**PhotoManager.java**

```
public void addPhoto(Photo photo) {
    PhotoId id = photo.getId();
    assertIsNewPhoto(id);
    doAddPhoto(photo);

    try {
        createObject(photo, getReadingStatement("INSERT INTO photos(id) VALUES
        Wahlzeit.saveGlobals();
    } catch (SQLException sex) {
        SysLog.logThrowable(sex);
    }
}

/**
 *
 */
protected void doAddPhoto(Photo myPhoto) {
    photoCache.put(myPhoto.getId(), myPhoto);
}

/**
 *
 */
public void loadPhotos(Collection<Photo> result) {
    try {
        readObjects(result, getReadingStatement("SELECT * FROM photos"));
        for (Iterator<Photo> i = result.iterator(); i.hasNext(); ) {
            Photo photo = i.next();
            if (!doHasPhoto(photo.getId())) {
                doAddPhoto(photo);
            } else {
            }
        }
    }
}
```

**Outline**

- org.wahlzeit.model
- import declaration
- PhotoManager 11
  - instance : Photo
  - photoCache : Ma
  - photoTagCollect
  - getInstance() : Pl
  - hasPhoto(String)
  - hasPhoto(Photo)
  - getPhoto(String)
  - getPhoto(Photo)
  - PhotoManager()
  - doHasPhoto(Phc
  - getPhotoFromId
  - doGetPhotoFor
  - createObject(Re
  - addPhoto(Photo
  - doAddPhoto(Ph
  - loadPhotos(Coll
  - savePhoto(Phot
  - savePhotos()

**Problems** @ Javadoc Declaration Console Search

<terminated> Wahlzeit [Java Application] /usr/lib/jvm/java-6-openjdk/bin/java (Feb 18, 2012 10:57:44 AM)

INFO: Started org.mortbay.http.HttpServer@10000000

2012-02-18 10:57:45 542, level=sl, context=system, dbconnection=dbc0, threadid=1, client=system, logtype=info,

2012-02-18 10:57:45 545, level=sl, context=system, dbconnection=dbc0, threadid=1, client=system, logtype=info,

2012-02-18 10:57:45 546, level=sl, context=agent0, dbconnection=nodbc, threadid=16, client=system, logtype=info

org.wahlzeit.model.PhotoManager.doAddPhoto(Photo myPhoto) : void - wahlzeit/src

# Quiz on Refactoring

- Your code smells. All signs for refactoring are given. Under which circumstances should you not start a refactoring?

# Review / Summary of Session

- Agile principles of programming
  - KISS, YAGNI, DRY
  - Make it run, right, fast
- Technical debt and refactoring
  - Principles, two hats
  - Example refactorings and tools



# Thank you! Questions?

**[dirk.riehle@fau.de](mailto:dirk.riehle@fau.de) – <http://osr.cs.fau.de>**

**[dirk@riehle.org](mailto:dirk@riehle.org) – <http://dirkriehle.com> – [@dirkriehle](#)**

# Credits and License

- Original version
  - © 2012-2019 Dirk Riehle, some rights reserved
  - Licensed under [Creative Commons Attribution 4.0 International License](#)
- Contributions
  - ...

# Programming Practices

**Prof. Dr. Dirk Riehle**

**Friedrich-Alexander University Erlangen-Nürnberg**

**AMOS E02**

Licensed under CC BY 4.0 International

It is Friedrich-Alexander University Erlangen-Nürnberg – FAU, in short.  
Corporate identity wants us to say “Friedrich-Alexander University”.

**KISS**  
(Keep It Simple, Silly)

**YAGNI**  
**(You Ain't Gonna Need It)**

**DRY**  
(Don't Repeat Yourself)

- 1. Make it run**
- 2. Make it right**
- 3. Make it fast**





## Definition of Big Ball of Mud [FY97]

A Big Ball of Mud is a haphazardly structured, sprawling, sloppy, duct-tape-and-baling-wire, spaghetti-code jungle. These systems show unmistakable signs of unregulated growth, and repeated, expedient repair. Information is shared promiscuously among distant elements of the system, often to the point where nearly all the important information becomes global or duplicated. The overall structure of the system may never have been well defined. If it was, it may have eroded beyond recognition. Programmers with a shred of architectural sensibility shun these quagmires. Only those who are unconcerned about architecture, and, perhaps, are comfortable with the inertia of the day-to-day chore of patching the holes in these failing dikes, are content to work on such systems.

## Benefits of Good (“Well-Factored”) Code

- 1. Maintainability**  
(Easier to understand)
- 2. Extensibility**  
(Easier to adapt and evolve)
- 3. Predictability**  
(Improves planning ability)



## Video Lessons

- Technical Debt is a Metaphor
  - Communicates well to manager
  - (Certainly in financial services)
- Taking on debt can speed up development
  - It may be justified to learn faster
  - But you have to pay up later
- If you don't pay back debt you'll slow down
  - Paying up means refactoring
  - Still, never write poor code deliberately

- 1. Identify problem**  
(So-called “code smells”)
- 2. Identify need to act**  
(Correlate occurrences)
- 3. Know how to act**  
(Refactor code)

## Code Smell

- According to Fowler [F99]
  - “smells are certain structures in the code that indicate violation of fundamental design principles and negatively impact design quality”
  - also, “a code smell is a surface indication that usually corresponds to a deeper problem in the system”
- Code smells are not bugs

## Example Code Smells

- Duplicated Code
- Long Method
- Large Class
- ...

## Refactoring (Practice)

- Definition and purpose
  - Is a behavior-preserving transformation of existing source code
  - It is a change made to the internal structure of software to make it easier to understand and cheaper to modify without changing its observable behavior
- More on refactoring
  - Change the structure of code without changing behavior
  - Focus on non-functional features within range of specification
  - Are defined techniques that are typically language specific
  - Are ideally supported by IDEs, for example, the Eclipse JDT
- Defined by Opdyke [O92], popularized by Fowler [F99]



## Example Refactorings

- Rename class
- Pull-up field
- Extract method
- ...
- More at <http://refactoring.com>

## Example Extract-Method Refactoring 1 / 2

```
public class PhotoManager extends ObjectManager {
    protected Map<PhotoId, Photo> allPhotos = new HashMap<PhotoId, Photo>();

    public void addPhoto(Photo photo) {
        PhotoId id = photo.getId();
        assertIsNewPhoto(id);
        allPhotos.put(id, photo);
        ...
    }

    public Photo getPhotoFromId(PhotoId id) {
        Photo result = doGetPhotoFromId(id);
        if (result == null) {
            ...
            if (result != null) { allPhotos.put(id, result); }
        }
        return result;
    }

    public Set<Photo> findPhotosByOwner(String ownerName) {
        ...
        for (Iterator<Photo> i = r.iterator(); i.hasNext();) {
            Photo photo = i.next();
            allPhotos.put(photo.getId(), photo);
        }
        return r;
    }
    ...
}
```

## Example Extract-Method Refactoring 2 / 2

```
public class PhotoManager extends ObjectManager {  
    public void addPhoto(Photo photo) {  
        ...  
        doAddPhoto(photo);  
        ...  
    }  
  
    public Photo getPhotoFromId(PhotoId id) {  
        ...  
        doAddPhoto(photo);  
        ...  
    }  
  
    public Set<Photo> findPhotosByOwner(String ownerName) {  
        ...  
        for (Iterator<Photo> i=r.iterator(); i.hasNext(); ) {  
            doAddPhoto(i.next());  
        }  
        ...  
    }  
  
    protected void doAddPhoto(Photo myPhoto) {  
        allPhotos.put(myPhoto.getId(), myPhoto);  
    }  
    ...  
}
```


## **The “three strikes” rule**

**1st time: Just do it**

**2nd time: Wince at duplication**


**3rd time: Refactor**

## Refactoring Process (Two Hats)




## Code Smells and Refactorings

- Duplicated code
- Long method
- Large class
- ...



## Example Refactoring Process

- The refactoring process can become complex
  - It may turn into a series of refactorings
- Example Removal of Switch Statement
  - Extract Method
  - Move Method
  - Replace Type Code ...
    - with Subclass or
    - with State / Strategy
  - Replace Conditional ...
    - with Polymorphism





## Quiz on Refactoring

- Your code smells. All signs for refactoring are given. Under which circumstances should you not start a refactoring?

The code will be abandoned (no business value in refactoring)

You are already in the middle of a refactoring---finish that first

## Review / Summary of Session

- Agile principles of programming
  - KISS, YAGNI, DRY
  - Make it run, right, fast
- Technical debt and refactoring
  - Principles, two hats
  - Example refactorings and tools

# Thank you! Questions?

**[dirk.riehle@fau.de](mailto:dirk.riehle@fau.de) – <http://osr.cs.fau.de>**

**[dirk@riehle.org](mailto:dirk@riehle.org) – <http://dirkriehle.com> – [@dirkriehle](#)**

DR

## Credits and License

- Original version
  - © 2012-2019 Dirk Riehle, some rights reserved
  - Licensed under [Creative Commons Attribution 4.0 International License](#)
- Contributions
  - ...