Benchmarking Minimax, Imitation, Self-Play Reinforcement Learning, and Monte Carlo Tree Search in a Multi-Agent Xiangqi (象棋) League

Alma Nurul Salma (诺艾玛)
Nanjing Xiaozhuang University (南京晓庄学院)
Student ID: L25020007
Email: almanurulsalma@gmail.com

***Abstract*—Modern game-playing agents are built from three ideas validated on Go and chess at cluster scale: imitation of human experts, reinforcement learning by self-play, and tree search over a learned network. It is unknown which of these paradigms is worth its cost for *Xiangqi* (象棋, Chinese Chess) when the compute budget is held fixed as an experimental control, whether imitation pretraining still helps the subsequent reinforcement learning, and what factor ultimately bounds playing strength. Existing Xiangqi deep-learning work consists of a few single-system papers and provides no controlled, like-for-like comparison. We propose a controlled, equal-compute study that places four paradigms—classical alpha–beta search, pure-self-play Proximal Policy Optimization, imitation-initialised Proximal Policy Optimization, and AlphaZero-style Monte Carlo Tree Search—on a single shared Xiangqi engine, a fixed 2086-move action space, one policy–value network, and one Elo scale, so the paradigm is the only variable. We rank the agents by fitted Elo with 95% confidence intervals, quantify the effect of imitation pretraining on the subsequent reinforcement learning, and run a four-lever ablation (search, epochs, teacher, network size) to identify the binding constraint. A complete, tested implementation and preliminary runs over a 9.3M-position training split (113k of 141,356 human games, 11.6M positions in all) already exist, making the study a rigorous formalisation rather than a speculative build. The expected contributions are a reusable multi-agent evaluation framework, to our knowledge the first controlled paradigm comparison for Xiangqi under constraint, and reproducibility guidance for self-play reinforcement learning.**

***Index Terms*—Xiangqi, Chinese Chess, deep reinforcement learning, Monte Carlo Tree Search, imitation learning, Proximal Policy Optimization, Elo rating, empirical software engineering, reproducibility.**

I. Introduction

THE dominant recipe for superhuman board-game play was established on Go by AlphaGo, which combined supervised (imitation) learning of expert moves, reinforcement learning by self-play, and Monte Carlo Tree Search [1]. AlphaGo Zero removed the human-data stage and learned *tabula rasa* [2], and AlphaZero generalised the same algorithm to chess, shogi, and Go, replacing alpha–beta search with general Monte Carlo Tree Search [3]. These landmark results share two properties that limit their guidance for most practitioners: they were obtained on large tensor-processing clusters, and each reports a single successful pipeline rather than a controlled comparison of the paradigms it combines.

Motivation and problem. When the compute budget is held fixed as an experimental control, the practical questions are unanswered, especially for *Xiangqi* (象棋, Chinese Chess)—a culturally major but academically under-served game with a larger 9×10 board, higher branching than chess, a cannon that captures by jumping a screen, and the unusual rule that *stalemate is a loss* (Fig. 1). The published deep-learning work on Xiangqi is recent and sparse: an AlphaZero-style player that searches with Monte Carlo Tree Search [4], a population method that tackles strategic non-transitivity [5], and a language-model approach trained with policy optimization [6]. Each builds *one* maximally strong system; none measures, under a fixed budget, how the distinct learning paradigms compare, whether imitation pretraining helps the reinforcement learning that follows, or which factor limits strength.

Significance. Deep reinforcement-learning results are known to be fragile and hard to reproduce when reported from single runs without variance analysis [7]. A controlled, confidence-interval-backed comparison on one rule engine therefore yields decision-relevant, reproducible evidence that cluster-scale, single-system papers do not.

Research questions. We pose three questions, each answerable by the methodology below:

- **RQ1 (ranking):** under a fixed single-GPU budget, how do the four paradigms rank in Xiangqi playing strength on a common Elo scale?
- **RQ2 (effect of imitation pretraining):** does imitation pretraining improve the subsequent Proximal Policy Optimization self-play under that budget, or can reinforcement learning fine-tuning *degrade* the imitation policy?
- **RQ3 (binding constraint):** which factor—play-time search, model capacity, training data or teacher, or the learning algorithm—most limits playing strength at this scale?

Proposed solution. We hold the environment, action space, network, and Elo scale fixed and swap *only* the learning paradigm, so a like-for-like ranking isolates the effect of the paradigm itself.

II. Related Work

Deep learning, search, and imitation. The AlphaGo family established the two levers we compare—imitation pretraining and search over a learned network [1]–[3]—with Monte Carlo Tree Search surveyed by Browne *et al.* [8], whose selection rules our search agent builds on; classical Xiangqi engines instead use alpha–beta search with handcrafted evaluation, the tradition our Minimax baseline represents. A known limitation of the imitation stage is that an imitator cannot surpass its




Fig. 1. *Left:* the 9 × 10 Xiangqi (象棋) board with its river and two palaces, the opening position, and the seven piece types (Red moves first). *Right:* how each piece moves and captures—the cannon's jump-the-screen capture and the horse's blockable leg give Xiangqi tactics without a chess analogue, enlarging the branching factor the agents must search.

TABLE I
WHERE PRIOR WORK LEAVES THE GAP THIS STUDY FILLS.

Work	Xiangqi	Cross-paradigm comparison	Equal-compute
AlphaGo family [1]–[3]	no	no	no
Monte Carlo Tree Search survey [8]	n/a	n/a	n/a
Proximal Policy Optimization [9]	no	partial	no
Reproducibility [7]	no	no	yes
AlphaStar [10]	no	no	no
JiangJun [5]	yes	no	no
Yilmaz *et al.* [4]	yes	no	partial
Xiangqi-R1 [6]	yes	no	partial
This study	**yes**	**yes**	**yes**

demonstrators—the usual justification for the reinforcement-learning stage—but whether that stage helps *under a fixed budget* is untested for Xiangqi, and our preliminary data suggest it can hurt.

Policy gradients and reproducibility. Proximal Policy Optimization [9] is our reinforcement-learning optimizer, chosen for stability; yet Henderson *et al.* [7] show policy-gradient results vary sharply with seeds and implementation, motivating our interval-based evaluation and a training-stability analysis.

Populations and Xiangqi-specific work. AlphaStar rated a league of adapting agents on an Elo ladder [10], a framing we adopt for *heterogeneous* agents. The directly comparable Xiangqi systems each optimise one pipeline at cluster scale or without cross-paradigm comparison: an AlphaZero-style player [4], JiangJun, which combines Monte Carlo Tree Search with Policy-Space Response Oracles over >10,000 human games to address non-transitivity [5], and a language-model approach [6]. Table I summarises the resulting gap.

Research gap. No controlled, equal-compute, Elo-anchored comparison of classical search, pure Proximal Policy Optimization, imitation-initialised Proximal Policy Optimization, and AlphaZero-style Monte Carlo Tree Search exists for Xiangqi under a single-GPU budget; consequently the direction of the imitation-pretraining effect and the binding constraint on strength are both unquantified for this game at this scale. This is primarily an *evaluation/methodological* gap, with secondary *performance* and *application* dimensions.

III. Proposed Methodology

Design. A controlled comparative study: the independent variable is the paradigm (or the one ablated lever); the dependent variable is Elo; everything else is fixed by a shared stack (Fig. 2), so differences in strength are attributable to the decision function alone. "Equal effort" is operationalised as a matched number of self-play environment steps per reinforcement-learning agent, reported beside every result so the comparison is fair rather than open-ended.

Shared components. (1) A tested Xiangqi rule engine exposed through a Gymnasium interface, with a fixed 2086-move action space and legal masking, and a $14 \times 10 \times 9$ side-to-move-relative board encoding. (2) One AlphaZero-style policy–value network reused by imitation, by Proximal Policy Optimization (as actor and critic), and by Monte Carlo Tree Search (as priors and leaf value); its width and depth are configurable for the ablation (Fig. 3).

The four agents. *Minimax*: alpha–beta (negamax) search with a material evaluation. *From-scratch Proximal Policy Optimization*: action-masked self-play from random initialisation. *Imitation-initialised Proximal Policy Optimization*: supervised imitation of 113k human games, then action-masked self-play refinement from that checkpoint. *Monte Carlo Tree Search agent*: a best-first search that uses the network's priors to guide selection and its value head to evaluate leaves, choosing moves by visit count. A random agent is included as a floor.

Data. 141,356 legal human games (≈11.6M positions) are split at the game level into 113k/14k/14k train/validation/test sets, recorded in a committed manifest for reproducibility; an engine self-play corpus supports the teacher-distillation lever.

Procedure. Each reinforcement-learning paradigm is trained to a matched single-GPU budget with periodic checkpointing. *Experiment 1 (RQ1)* runs a colour-balanced round-robin among all four agents plus the random agent and fits Elo with 95% confidence intervals using (1) and a head-to-head matrix. *Experiment 2 (RQ2)* isolates imitation-only, imitation-initialised Proximal Policy Optimization, and from-scratch




Fig. 2. The controlled apparatus. One shared engine, action space, and policy–value network feed four interchangeable decision functions—the only variable—and all agents are rated on a single Elo scale by a colour-balanced round-robin anchored to Pikafish.




Fig. 3. The board is encoded as a $14 \times 10 \times 9$ tensor—one 10×9 binary plane per piece type and side, from the side-to-move's perspective, shared by every agent.

Proximal Policy Optimization and reports the signed Elo differences plus learning proxies (imitation top-1 accuracy; self-play reward and value traces). *Experiment 3 (RQ3)* varies one lever at a time—search simulations $\in \{100, 200, 400, 800\}$, imitation epochs, teacher (human versus engine distillation), and network size (1.15M versus 4.85M parameters)—each re-entered into the round-robin, reporting each lever's Elo effect. A stability study compares fragmented, continuous, and replay-buffer-persisted training.

Evaluation metrics. The expected score of a rating difference is

$$E_A = \frac{1}{1 + 10^{(R_B - R_A)/400}}, \tag{1}$$

inverted and fitted over round-robin results to obtain each agent's rating; confidence intervals follow the delta method. The imitation stage minimises the policy–value loss $\mathcal{L}_{\text{IL}}$=CE$(\pi_\theta, a_{\text{human}})$+MSE$(v_\theta, z)$, and the search agent selects the move maximising the prior-weighted PUCT score. Reported metrics are fitted and absolute Elo (with 95% confidence interval), head-to-head win rates, the signed Elo difference between the imitation-only and imitation-initialised agents, per-lever Elo effects, top-1 move accuracy, value-loss trajectories, and GPU-hour cost. Differences are called significant only when confidence intervals do not overlap; non-transitivity is handled by full round-robins and fitted Elo rather than single matches [5]. Fixed seeds, the committed manifest, and per-run configuration, seed, and commit logging address known reproducibility pitfalls [7].

Threats to validity. Relative Elo depends on the pool (mitigated by an absolute Pikafish anchor and full round-robins); few games per pair widen the intervals (mitigated by rerunning decisive comparisons with more games); the shared-stack design keeps the comparison internally valid, since only the decision function varies.

IV. Expected Results and Contributions

Expected outcomes. We hypothesise that (H1) the Monte Carlo Tree Search agent attains the highest Elo; (H2) imitation pretraining raises *starting* strength but, under the constrained budget, self-play reinforcement learning does *not* raise the ceiling and may lower it; and (H3) model capacity and training data—not search depth or the learning algorithm—bind strength. Preliminary runs on the existing implementation are consistent with all three and establish feasibility (Fig. 4); these are *preliminary, confidence-interval-wide* measurements that the proposed study will formalise with more games and tighter intervals, not final results.

Contributions. (1) *Technical*: a reusable, single-interface multi-agent evaluation league for comparing heterogeneous game-playing paradigms on one rule engine, runnable on a single consumer GPU. (2) *Research*: a controlled, equal-budget, Elo-anchored comparison of the four paradigms for Xiangqi, a quantified answer to whether imitation pretraining helps the subsequent reinforcement learning under constraint, and a multi-lever capacity-bottleneck analysis. (3) *Software engineering*: evidence that training-stability engineering—replay-buffer continuity and best-checkpoint selection—materially affects learned-model quality, yielding reproducibility guidance for self-play reinforcement learning.

Timeline. The apparatus and preliminary runs already exist; the remaining work to the thesis defence (end of May 2027) is scheduled in Table II.

V. Conclusion

We have proposed a controlled, Elo-anchored comparison of four deep-learning paradigms for Xiangqi (象棋) under a




Fig. 4. Preliminary feasibility measurements. *Left:* fitted relative Elo (anchor 1500) with 95% confidence intervals from a round-robin of the four paradigms plus a random agent; a stabilised rerun reproduced the same top rank (Monte Carlo Tree Search ≈1691). *Right:* head-to-head win rates (row agent vs. column opponent)—the Monte Carlo Tree Search agent dominates its column and the ladder is largely transitive, with many draws under the 300-ply cap.

TABLE II
SCHEDULE FROM THIS PROPOSAL TO THE THESIS DEFENCE (END OF MAY 2027).

Period	Milestone
Nov 2026	Finalise proposal; quantitative test-set analysis
Dec 2026	Scale round-robins for tighter CIs; add Pikafish anchor
Jan 2027	Write Chapters 1–3 (intro, related work, method)
Feb 2027	Write Chapter 4 (results); complete the ablations
Mar 2027	Write Chapter 5 (discussion); full draft to advisor
Apr 2027	Revisions; reproducibility check; defence slides
May 2027	Rehearse and **defend**

fixed compute budget, built on a shared environment, action space, and network so that only the decision function varies. The study answers which paradigm is strongest, whether imitation pretraining helps subsequent reinforcement learning, and what factor bounds strength—questions left open by a Xiangqi literature of single, mostly cluster-scale systems. Because a complete, tested implementation and preliminary results already exist, the work is a rigorous, reproducible formalisation whose contributions—a reusable comparison framework, a constrained-budget paradigm comparison for Xiangqi, and training-stability guidance—are defensible and honestly scoped, including where the evidence is negative.

REFERENCES

[1] D. Silver, A. Huang, C. J. Maddison, A. Guez, L. Sifre, G. van den Driessche, J. Schrittwieser, I. Antonoglou, V. Panneershelvam, M. Lanctot, S. Dieleman, D. Grewe, J. Nham, N. Kalchbrenner, I. Sutskever, T. Lillicrap, M. Leach, K. Kavukcuoglu, T. Graepel, and D. Hassabis, "Mastering the game of Go with deep neural networks and tree search," *Nature*, vol. 529, no. 7587, pp. 484–489, 2016.

[2] D. Silver, J. Schrittwieser, K. Simonyan, I. Antonoglou, A. Huang, A. Guez, T. Hubert, L. Baker, M. Lai, A. Bolton, Y. Chen, T. Lillicrap, F. Hui, L. Sifre, G. van den Driessche, T. Graepel, and D. Hassabis, "Mastering the game of Go without human knowledge," *Nature*, vol. 550, no. 7676, pp. 354–359, 2017.

[3] D. Silver, T. Hubert, J. Schrittwieser, I. Antonoglou, M. Lai, A. Guez, M. Lanctot, L. Sifre, D. Kumaran, T. Graepel, T. Lillicrap, K. Simonyan, and D. Hassabis, "A general reinforcement learning algorithm that masters chess, shogi, and Go through self-play," *Science*, vol. 362, no. 6419, pp. 1140–1144, 2018.

[4] B. Yilmaz, J. Hu, and J. Liu, "Deep reinforcement learning Xiangqi player with Monte Carlo tree search," *arXiv preprint arXiv:2506.15880*, 2025.

[5] Y. Li, K. Xiong, Y. Zhang, J. Zhu, S. McAleer, W. Pan, J. Wang, Z. Dai, and Y. Yang, "Mastering Xiangqi by tackling non-transitivity in two-player zero-sum games," *Transactions on Machine Learning Research (TMLR), arXiv:2308.04719*, 2023.

[6] Y. Chen, S. Liu, Y. Lyu, C. Zhang, J. Shi, and T. Xu, "Xiangqi-R1: Enhancing spatial strategic reasoning in LLMs for Chinese Chess via reinforcement learning," *arXiv preprint arXiv:2507.12215*, 2025.

[7] P. Henderson, R. Islam, P. Bachman, J. Pineau, D. Precup, and D. Meger, "Deep reinforcement learning that matters," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 32, no. 1, 2018.

[8] C. B. Browne, E. Powley, D. Whitehouse, S. M. Lucas, P. I. Cowling, P. Rohlfshagen, S. Tavener, D. Perez, S. Samothrakis, and S. Colton, "A survey of Monte Carlo tree search methods," *IEEE Transactions on Computational Intelligence and AI in Games*, vol. 4, no. 1, pp. 1–43, 2012.

[9] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov, "Proximal policy optimization algorithms," *arXiv preprint arXiv:1707.06347*, 2017.

[10] O. Vinyals, I. Babuschkin, W. M. Czarnecki, M. Mathieu, A. Dudzik, J. Chung, D. H. Choi, R. Powell, T. Ewalds, P. Georgiev *et al.*, "Grandmaster level in StarCraft II using multi-agent reinforcement learning," *Nature*, vol. 575, pp. 350–354, 2019.