








# Lecture 2

## Introduction to Python




lecturer Alexander Gorbunov  
Email: [agorbunov@hse.ru](mailto:agorbunov@hse.ru)



# 1.4 Basic Objects II:

## Booleans, Tuples, and Dictionaries

☒ TRUE  
☒ FALSE





# Booleans 1

A boolean is one of the simplest Python objects, and it can have two values:

True









and

False

(Note the uppercase T and F)

In [1]:

```
a = True  
b = False
```



# Booleans 2

Booleans can be combined with logical operators to give other booleans

operators are **not**, **and**, or

**And:**

True and True = True

True and False = False

False and True = False

False and False = False

**Or:**

True or True = True

True or False = True







False or True = True

False or False = False

**not:**

not True = False

not False = True



# Booleans 3

In [2]: `True and False`

Out[2]: `False`

In [3]: `True or False`



Out[3]: `True`

In [4]: `(False and (True or False)) or (False and True)`

Out[4]: `False`

In [6]: `not True`

Out[6]: `False`





# Booleans 4

Comparison operators can also produce booleans:

"x is equal to y"  $x == y$







"x is greater than y"  $x > y$

"x is less than y"  $x < y$

"x is not equal to y"  $x != y$

"x is greater than equal to y"  $x >= y$

"x is less than equal to y"  $x <= y$



# Booleans 5

In [7]: `1 == 3`

Out[7]: `False`

In [8]: `1 != 3`



Out[8]: `True`

In [9]: `3 > 2`

Out[9]: `True`

In [10]: `3 <= 3.4`

Out[10]: `True`





# Booleans 6

There are often multiple ways to express the same condition:

```
In [11]: not (1 == 3)
```

```
Out[11]: True
```

```
In [33]: 1 != 3
```

```
Out[33]: True
```



With sequences the `in` function can be used

```
In [34]: x = [1, 2, 3, 4, 5]
         3 in x
```

```
Out[34]: True
```

```
In [35]: 6 in x
```









```
Out[35]: False
```





# Exercise 1.4a

Write an expression that returns True if  $x$  is strictly greater than 3.4 and smaller or equal to 6.6, or if it is 2, and try changing  $x$  to see if it works





# Solution 1.4a

Write an expression that returns True if x is strictly greater than 3.4 and smaller or equal to 6.6, or if it is 2, and try changing x to see if it works

```
In [13]: x = 6.1  
          ((x > 3.4) and (x <= 6.6)) or (x == 2)
```

```
Out[13]: True
```





# Tuples 1

tuples are, like lists, a type of sequence, but they use round parentheses rather than square brackets:

```
In [14]: t = (1, 2, 3)
```

They can contain heterogeneous types like lists:

```
In [15]: t = (1, 2.3, 'Fred')
```



and also support item access and slicing like lists:

```
In [16]: t[1]
```

```
Out[16]: 2.3
```

```
In [18]: t[:2]
```

```
Out[18]: (1, 2.3)
```



# Tuples 2

The main difference is that they are **immutable**, like strings:

```
In [19]: t[1] = 2
```

```
-----  
-----  
TypeError
```



Traceback (most recent call last)

```
<ipython-input-19-9d97237db197> in <module>()  
----> 1 t[1] = 2
```

```
TypeError: 'tuple' object does not support item assignment
```

Tuples tend to be used to hold collections of different types of objects, and lists tend to be used for objects of the same type.

(We will not go into the details right now of why this is useful, but you should know that these exist as you may encounter them in examples.)





# Dictionaries 1

One of the data types that we have not talked about yet is called *dictionaries* (dict).

One way of thinking about a dictionary is like a real dictionary - It is a list of words and there is a definitions of each word.

In python we call the words **keywords** and the definition their **values**

Dictionaries are defined using curly brackets {} or the dict() object.

```
In [20]: d = {'a':1, 'b':2, 'c':3}
```



Items are accessed using square brackets using the key

```
In [21]: d['a']
```

```
Out[21]: 1
```

```
In [22]: d['c']
```

```
Out[22]: 3
```











# Dictionaries 2

Values can also be set this way:

```
In [23]: d['r'] = 2.2
```

```
In [24]: print (d)
```

```
{'a': 1, 'c': 3, 'b': 2, 'r': 2.2}
```





# Dictionaries 3

The keywords don't have to be strings, they can be many (but not all) Python objects:



```
In [26]: e = dict()
          e['a_string'] = 3.3
          e[3445] = 2.2
          e[complex(2, 1.0)] = 'value'
```

```
In [27]: print(e)

{3445: 2.2, (2+1j): 'value', 'a_string': 3.3}
```

```
In [28]: e[3445]
```

```
Out[28]: 2.2
```



# Dictionaries 4

If you try and access an element that does not exist, you will get a `KeyError`:

In [29]:

```
e[4]
```

```
-----  
-----  
KeyError
```

Traceback (most recent call

```
last)
```

```
<ipython-input-29-a79b29c56d88> in <module>()  
----> 1 e[4]
```









```
KeyError: 4
```

Also, note that dictionaries do **NOT** know about order, so there is no 'first' or 'last' element



# Exercise 1.4b

Try making a dictionary to translate numbers (1-12) into the corresponding name of the month (January-December).





# Solution 1.4b

Try making a dictionary to translate numbers (1-12) into the corresponding name of the month (January-December).

```
In [31]: months = {1:'January', 2:'February',  
                  3:'March', 4:'April',  
                  5:'May', 6:'June',  
                  7:'July', 8:'August',  
                  9:'September', 10:'October',  
                  11:'November', 12:'December'}
```









```
In [32]: months[9]
```

```
Out[32]: 'September'
```





# 1.5 Boolean Algebra











# Boolean Algebra

In the field of mathematical logic, Boolean algebra is a sub-area of algebra in which the values of the variables only have two values: **True** and **False**.

Boolean algebra is important because everything in a computer is represented by "bits", i.e. binary pieces of information which are either **True (1)** or **False (0)**. Hence the algebra underpins many of the internal workings of today's hard- and software.

Boolean algebra is named after the English mathematician George Boole, who first introduced the concept in 1847.





# Booleans in Python 1

We have already seen that the Python syntax knows about the boolean values:

```
In [1]: print True
```

```
True
```



```
In [2]: print False
```

```
False
```

Which are variables of type bool:

```
In [3]: print type(True)
```

```
<type 'bool'>
```



# Booleans in Python 2



Be aware that True and False are case-sensitive words, i.e. this does not work:

```
In [4]: print true
```

```
-----  
-----  
NameError                                Traceback (most recent call  
1 last)
```

```
<ipython-input-4-a2a21570fba6> in <module>()  
----> 1 print true
```

```
NameError: name 'true' is not defined
```





# Booleans in Python 3

True and False behave like the number 1 and 0, respectively, and can be used as such.

For example:

```
In [5]: print True * 5
```

5



```
In [6]: print False + 10
```

10

```
In [7]: print True == 1
```

True

Though please don't try doing maths with Booleans!











# Basic Operations 1

There are three basic operations

$x$  and  $y$ : True only if both  $x$  and  $y$  are True; False otherwise.  $x$  or  $y$ : only False if both  $x$  and  $y$  are False; True otherwise. not  $x$ : True if  $x$  is False, and False if  $x$  is True.

These operations can be illustrated using a so-called truth table, in which we use the numeric values for readability:

$x$	$y$	$x$ and $y$	$x$ or $y$	not $x$
0	0	0	0	1
0	1	0	1	1
1	0	0	1	0
1	1	1	1	0





# Basic Operations 2

x	y	x and y	x or y	not x
0	0	0	0	1
0	1	0	1	1
1	0	0	1	0
1	1	1	1	0







Note that and/or resemble the multiplication and addition operators of ordinary algebra, respectively:

- $x \text{ and } y == x * y$
- $x \text{ or } y == x + y - (x \text{ and } y)$

# Laws

The following laws from ordinary algebra apply:

- commutativity
  - $(y \text{ and } x) == (x \text{ and } y)$
  - $(x \text{ or } y) == (y \text{ or } x)$
- associativity
  - $x \text{ and } (y \text{ and } z) == (x \text{ and } y) \text{ and } z$
  - $x \text{ or } (y \text{ or } z) == (x \text{ or } y) \text{ or } z$
- distributivity
  - $x \text{ and } (y \text{ or } z) == (x \text{ and } y) \text{ or } (x \text{ and } z)$





# Order of Operations 1

Like in the usual algebra of real numbers, the order of the operations matters. The order of precedence is:

1. Comparison operator (e.g. `==`, `>`, `<`)
2. `not`
3. `and`
4. `or`

You can always override the order using round brackets:



```
In [10]: not False or True
```

```
Out[10]: True
```

```
In [12]: not (False or True)
```

```
Out[12]: False
```

Recall from your maths: BODMAS



# Order of Operations 2

You can always override the order using round brackets:



```
In [10]: not False or True
```

```
Out[10]: True
```

```
In [12]: not (False or True)
```

```
Out[12]: False
```

Recall from your maths: BODMAS











# Rewriting Expressions

There are often multiple ways to write the same expression.  
In such case, the least complicated one is usually the better one!

For example:

- "x and y" is identical to "not(not x or not y)"
- "x or y" is identical to "not(not x and not y)"





# Set

An unordered collection, without duplicates (like Java).  
Syntax is like dictionary, but no ":" between key-value.

```
>>> aset = { 'a', 'b', 'c' }  
>>> aset  
{ 'a', 'c', 'b' }  
>>> aset.add('c')           # no effect,  
                             'c' already in set  
>>> aset  
{ 'a', 'c', 'b' }
```





```
set.discard('cat')
```

remove cat. No error if not in set.

```
set.remove('cat')
```

remove cat. Error if not in set.

```
set3 =  
set1.union(set2)
```

doesn't change set1.

```
set4 =  
set1.intersection(s  
et2)
```

doesn't change set1.

```
set2.issubset( set1  
)
```

```
set2.issuperset(  
set1 )
```

```
set1.difference(  
set2 )
```




element in set1 not set2


```
set1.symmetric_diff  
erence(set2)
```

xor

```
set1.clear( )
```

remove everything







```
>>> aset = { 'a', 'b', 'c' }
```

```
>>> 'a' in aset
```


```
True
```

```
>>> 'A' in aset
```

```
False
```







```
if condition :  
    body  
elif condition :  
    body  
else:  
    body
```



```
while condition:  
    body
```

```
for name in  
    iterable:  
    body
```

```
if x%2 == 0:  
    y = y + x  
else:  
    y = y - x
```

```
while count <  
    10:  
    count =  
    2*count
```

```
for x in  
    [1,2,3]:  
    sum = sum + x
```



**range:** create a sequence

`range([start,] stop[, step])`

Generate a list of numbers from `start` to  
`stop` stepping every `step`

`start` defaults to 0, `step` defaults to 1

Example

```
>>> range(5)
```







```
[0, 1, 2, 3, 4]
```

```
>>> range(1, 9)
```

```
[1, 2, 3, 4, 5, 6, 7, 8]
```

```
>>> range(2, 20, 5)
```

```
[2, 7, 12, 17]
```





# for loop using range( )







Use `range` to generate values to use in for loop

```
>>> for i in range(1,4):  
      print (i)
```

1

2



3



# loop iteration using `continue`

```
for x in range(10):  
    if x%2 == 0:  
        continue  
    print x
```

1  
3  
5  
7





# break

```
for number in range(10):  
    if number == 4:  
        print 'Breaking'  
        break  
    else:  
        print (number)
```



0

1

2

3

**Breaking**



# `dir`: show all methods & attributes

`dir` returns all methods for a class or object







```
>>> lst = [1, 3, 2]
```

```
>>> dir(lst)
```

```
['__add__', '__class__', '__contains__', '__delattr__',  
 '__delitem__', '__delslice__', '__doc__', '__eq__',  
 '__ge__', '__getattribute__', '__getitem__',  
 '__getslice__', ...  
  
 '__setitem__', '__setslice__', '__str__', 'append',  
 'count', 'extend', 'index', 'insert', 'pop', 'remove',  
 'reverse', 'sort']
```

```
>>> dir( math )      # import math first
```

```
['__doc__', '__name__', '__package__', 'acos', 'asin',  
 'atan',  
 'atan2', 'ceil', 'copysoign', 'cos', 'degrees', 'e',  
 'exp',  
 'factorial', 'floor', 'fmod', 'frexp', 'fsum',  
 'hypot', ...]
```







# Getting Help







```
>>> help(str)
```

```
Help on class str in module __builtin__:
```

```
class str(basestring)
|   str(object)-> string
|
|   Return a nice string representation of the
|   object.
|
|   Method resolution order:
|       str
|       basestring
|       object
|
|   Methods defined here:
|       ...
```



# Functions





# Defining Functions







Syntax: `def func(arg1, ...):`

`body`

Body of function must be indented

If no value is returned explicitly, function will return `None`

```
def average(num1, num2, num3):  
    sum = num1 + num2 + num3  
    avg = sum / 3.0  
    return avg
```



# Function Parameters

Parameters can be any type

A function can take any number of parameters or none at all

```
def usage(programName, version):  
    print("%s Version %i" % (programName,  
version))  
    print("Usage: %s arg1 arg2" %  
programName)
```

```
>>> usage('Test', 1.0)
```

```
Test Version 1.0
```

```
Usage: Test arg1 arg2
```



# Function Default Parameter values

Parameters can be given a default values

```
split(string, substr=' ')
```

The function can be called with fewer arguments than there are parameters

Parameters with default values must come last

```
>>> def printName(last, first, mi=""):  
        print("%s, %s %s" % (last,  
first, mi))
```

```
>>> printName("Smith", "John")
```

```
Smith, John
```

```
>>> printName("Smith", "John", "Q")
```

```
Smith, John Q
```

# Keyword Arguments

Functions can be invoked using the name of the parameter and a value

```
func(param=value, ...)
```

- The order of values passed by keyword does not matter

```
def fun(key1="X", key2="X", key3="X",  
        key4="X") :  
    '''function with keywords and default  
    values'''
```

```
    print(key1, key2, key3, key4)
```

```
>>> fun(key3="O", key2="O")
```

```
X O O X
```

```
>>> fun(key4='Z')
```

```
X X X Z
```











# Functions at Values

- Functions can be used just like any other data type
- Functions can be assigned to variables

```
def sub(a, b):  
    return a-b
```

```
>>> op = sub  
>>> print op(3, 5)  
-2  
>>> type(op)  
<type 'function'>
```



# Functions as Parameters

Functions can be passed to other functions

```
def convert(data, convertFunc):  
    for i in range(len(data)):  
        data[i] = convertFunc(data[i])  
    return data
```

```
>>> convert(['1', '5', '10', '53'], int)  
[1, 5, 10, 53]
```

```
>>> convert(['1', 'nerd', '10', 'hi!'], len)  
[1.0, 5.0, 10.0, 53.0]
```









```
>>> convert(['1', '5', '10', '53'], complex)  
[(1+0j), (5+0j), (10+0j), (53+0j)]
```



# Functions can return multiple values

Return a tuple of values.

```
def separate(text, size=3):  
    head = text[:size]  
    tail = text[size:]  
    return (head,tail)  
  
    # ok to omit parens: start,last =  
separate(...)  
(start,last) = separate('GOODBYE', 4)  
start  
GOOD  
last  
BYE
```



# Modules

Modules can be “imported”

Module file name must end in .py

Used to divide code between files

```
import math
import string
...
```



# import Statement

```
import <module name>
```

`module name` is the file name without `.py` extension

You must use the module name to call functions

```
>>> import math
>>> dir(math)
['__doc__', '__name__', 'acos', 'asin',
'atan', 'atan2', 'ceil', 'cos', 'cosh', 'e',
'exp', 'fabs', 'floor', 'fmod', 'frexp',
...]
```

```
>>> math.e
2.71828182846
>>> math.sqrt(2.3)
1.51657508881
```

# import specific names

```
from <module> import <name>
```

Import a specific name from a module into global namespace

Module name is not required to access imported name(s)

```
>>> from math import sqrt
```

```
>>> sqrt(16)
```



```
4
```

```
>>> dir(math)
```

**Traceback (most recent call last):**

**File "<stdin>", line 1, in <module>**

**NameError: name 'math' is not defined**







# `import` all names from module

## `from <module> import *`

Import everything into global namespace

```
>>> dir()
```

```
['__builtins__', '__doc__', '__name__']
```

```
>>> from time import *
```

```
>>> dir()
```

```
['__builtins__', '__doc__', '__name__',  
'accept2dyear', 'altzone', 'asctime', 'clock',  
'ctime', 'daylight', 'gmtime', 'localtime',  
'mktime', 'sleep', 'strftime', 'time', ... ]
```

```
>>> time()
```

```
1054004638.75
```

# Python Standard Libraries

**sys**

System-specific parameters and functions

**time**

Time access and conversions

**thread**

Multiple threads of control

**re**

Regular expression operations

**email**

Email and MIME handling



**httplib**

HTTP protocol client

**tkinter**

GUI package based on TCL/Tk (in Python 2.x this is named Tkinter)

<http://docs.python.org/library/index.html>





# The `os` Module

Operating System related functions

```
import os
```

```
os.getcwd( )
```

Get current working directory

```
os.chdir("/temp/somedir")
```

Change dir. Use forward slash on MS Windows.

```
os.getenv('JAVA_HOME')
```

Get environment variable.

```
os.unlink('filename')
```



Remove regular file

```
os.removedirs('dirname')
```

Remove directory(s)

```
stats = os.stat('file')
```

Get file metadata: ctime, mtime, atime, uid, gid



# os.path

Module for manipulating paths

```
> (dir, file) = os.path.split("/some/path/test.py")
> dir
'/some/path'
> file
'test.py'
> (name, ext) = os.path.splitext(file)
> ext
'.py'
# Test absolute path to file
> os.chdir('/Temp/examples')
> os.path.realpath('readme.txt')
C:\\Temp\\examples\\readme.txt
```



# File Objects - open a file

`open(filename, mode)`

**mode** is one of:

'r' : Read

'w' : Write

'a' : Append



■ If a file opened for 'w' does not exist it will be created

Example

```
>>> inFile = open('input.txt', 'r')
```

```
>>> type(infile)
```

```
<type 'file'>
```



# File Methods









`read([size])`

Read at most `size` bytes and return as a string

`readlines([size])`

Read the lines of the file into a list of strings.

Use `size` as an approximate bound on the number of bytes returned



# File Methods for output








`write(text)`

Write `text` to the file

`writelines(string_sequence)`

Write each string in the sequence to the file

New lines are not added to the end of the strings







**with** to define a block for open

if an exception occurs.

```
with open("students.csv", 'r') as student_file:  
    # read each line of file  
    for line in student_file:  
        (id,name,email) = split(',', 3)  
        print("%s has id %s" % (name,id))
```

# Exceptions

Example: division by zero

```
>>> 1 / 0
```

Traceback (most recent call last):

File "<pyshell#0>", line 1, in ?

```
1 / 0
```

ZeroDivisionError: integer division or modulo by zero



# Exceptions

## Motivation

- Move error handling code away from main code
- Deal with “exceptional” cases separately

## How it works

- Exceptions are *thrown* (or raised) and *caught*
- An exception is caught by a catch code block
- When exception occurs, control jumps to a surrounding "catch" block. May *propagate* from function to caller.





# Throwing Exceptions








List index out of bounds

Invalid type conversions

Invalid arithmetic operation, e.g. `math.sqrt(-1)`

Exceptions can be thrown manually using the `raise` keyword

```
>>> raise ValueError, "Bad Value"
```



# Catching an Exception

```
<code block>  
except <Exception List1>:  
    <exception handling code block>  
except <Exception List2>:  
    <exception handling code block>  
except:  
    <exception handler for all other exceptions>  
else:  
    <code to execute if no exception occurs>
```

# Exception Example

```
try:  
    x = 1 / 0  
except ZeroDivisionError:  
    print('Division by zero')  
else:  
    print("x =", x)
```





# First matching except block is used

```
try:
```

```
    x = 1 / 0
```

```
except IOError:
```

```
    print 'Input/Output error'
```

```
except:
```

```
    print 'Unknown error'
```

Unknown error

# Types of Exceptions

a hierarchy of exceptions

All built-in exceptions are subclasses of `Exception`

An exception can be caught by any type higher up in the hierarchy

Exception

StandardError

ArithmeticError

ZeroDivisionError

SystemExit

ValueError



OverflowError

StopIteration

LookupError

IndexError

KeyError



# Example of Hierarchical Exception

```
try:
```

```
    x = 1 / 0
```

```
except ArithmeticError:
```

```
    print 'ArithmeticError caught'
```

ArithmeticException caught



# Propagation of Exceptions

Uncaught exceptions propagate up to the calling function

```
def func1():  
    try:  
        a = 1 / 0  
    except ValueError:  
        print 'caught by func1'
```

```
def func2():  
    try:  
        func1()  
    except:  
        print 'caught by func2'
```

```
>>> func2()  
caught by func2
```

# List Comprehensions

*expression for var in list ]*

Apply an expression to every element of a list

- Can simultaneously **map** and **filter**

```
>>> import math
```

```
>>> [math.pow(2,x) for x in range(1,7)]
```

```
[2.0, 4.0, 8.0, 16.0, 32.0, 64.0]
```

# List Comprehension with filter

```
result = [ expr for var in list if expr2 ]
```

apply to elements of *list* where *expr2* is true

Example: Remove smallest element from list

```
>>> lst1 = [5, 10, 3, 9]
```

```
>>> [x for x in lst1 if x != min(lst1)]
```

```
[5, 10, 9]
```

Example: Sum all lists of size greater than 2

```
>>> lst1 = [[1, 2, 4], [3, 1], [5, 9, 10, 11]]
```

```
>>> [reduce(operator.add, x) for x in lst1 if len(x) > 2]
```

```
[7, 35]
```



# List Comprehension with nested for

```
[expr for x in list1 for y in list2]
```

The loops will be nested

```
>>> vowels = ['a','e','i','o','u']  
>>> const = ['b','s']  
>>> [c+v for c in const for v in vowels]  
['ba', 'be', 'bi', 'bo', 'bu', 'sa', 'se', 'si',  
'so', 'su']
```

# List Comprehension for files

- Find all files in directory larger than 1MB
- Return the real path to file

```
import os, glob
```

```
[os.path.realpath(f) for f in glob.glob('*.*')  
    if os.stat(f).st_size >= 1000000]
```

# Dictionary Comprehensions

```
dict = {expr for var in list if expr2}
```

Like list comprehension but generates a dictionary.

- *expr* must be key:value pair (of course)

```
# Create dictionary of .exe filenames and sizes.
```

```
import os, glob
```

```
os.chdir('/windows/system32')
```

```
files = {fname:os.stat(fname).st_size  
         for fname in glob.glob('*.exe') }
```







```
# print them
```

```
for (key,val) in files.items():
```

```
    print("%-20s  %8d" % (key,val))
```



# Functional Programming



# Functional Approaches

- In Function Programming, functions can be used in the same way as other data types.

- Python borrows from functional languages:

Lisp/Scheme

Haskell



- Python built-in functions for functional style:

`map()`

`filter()`

`reduce()`

`zip()`



# map: "Apply to all" operation

```
result = map(func, list)
```

func is applied to each element of the list

result is a new list, same length as original list

the original list is not altered

```
>>> list = [2, 3, 4, 5]
>>> roots = map( math.sqrt, list )
>>> for x in roots:
    print(x)
1.41421356237
1.73205080757
2.0
2.2360679775
```

Function as  
argument.



# map in Action

$y_1$

$y_2$

$y_3$

$y_4$

$y_5$



$y_6$

$y_7$

$y_8$

func

$\hat{y}_1$



# map in Action

$y_1$

$y_2$

$y_3$

$y_4$

$y_5$

$y_6$



$y_7$

$y_8$

func

$\hat{y}_1$

$\hat{y}_2$



# map in Action

$y_1$

$y_2$

$y_3$

$y_4$

$y_5$

$y_6$

$y_7$



$y_8$

func

$\hat{y}_1$

$\hat{y}_2$

$\hat{y}_3$





# map in Action

$y_1$

$y_2$

$y_3$

$y_4$

$y_5$

$y_6$

$y_7$

$y_8$



func

$\hat{y}_1$

$\hat{y}_2$

$\hat{y}_3$

$\hat{y}_4$



# map in Action

$y_1$

$y_2$

$y_3$

$y_4$

$y_5$

$y_6$

$y_7$

$y_8$

func

$\hat{y}_1$

$\hat{y}_2$

$\hat{y}_3$



$\hat{y}_4$

$\hat{y}_5$

$\hat{y}_6$

$\hat{y}_7$

$\hat{y}_8$



# map with multiple lists

What if the function requires more than one argument?

```
result = map(func, list1, ..., listn)
```

- All lists must be of same length (*not really*)
- Number of lists (*n*) must match #args needed by func

# powers of 2

```
pows = map( math.pow, [2]*5, [1,2,3,4,5] )
```

# same thing, using a range

```
pows = map( math.pow, [2]*5, range(1,6) )
```



# Use map to reduce coding

```
lst1 = [0, 1, 2, 3]
```

```
lst2 = [4, 5, 6, 7]
```

```
lst3 = []
```



```
for k in range(len(lst1)):
```

```
    lst3.append( add2(lst1[k], lst2[k]) )
```

```
lst1 = [0, 1, 2, 3]
```

```
lst2 = [4, 5, 6, 7]
```

```
lst3 = map(add2, lst1, lst2)
```



# Benefits

The `map` function can be used like an expression

Can be used as a parameter to a function

```
>>> lst1 = [1, 2, 3, 4]
```

```
>>> string.join(lst1) # Error: lst1 contains ints
```

```
...
```

```
TypeError: sequence item 0: expected string, int  
found
```

```
>>> string.join( map(str, lst1) ) # Correct
```

```
'1 2 3 4'
```

# `filter` elements of a list

```
sublist = filter(func, list)
```

- return a sublist from `list` containing only elements that "pass" `func` (`func` returns `True` or non-zero for element)
- the result has length less than or equal to the `list`
- `list` is not altered

```
def isEven(x):  
    return x%2 == 0
```

```
lst = [2, 7, 9, 8, -12, 11]
```

```
even = filter(isEven, lst) # even = [2, 8, -12]
```





# reduce accumulate a result

```
result = reduce(func, list)
```

- Apply `func` cumulatively to a sequence
- `func` must take 2 parameters
- For each element in list, previous `func` result is used as 1st arg.

```
def multiply(x, y):  
    return x*y
```

```
lst = [1,2,3,4,5]
```

```
result = reduce(multiply, lst) # result = 1*2*3*4*5
```

# reduce with initial value

```
reduce(func, initial_value, list)
```

Use `initial_value` as parameter in first call to func

```
lst = [2,3,4,5]
```








```
result = reduce(multiply, 10, lst)
```

```
# result = 10 * 2 * 3 * 4 * 5
```

# Code Comparison

```
lst1 = [ [2, 4], [5, 9], [1, 7] ]  
result = operator.add([100], lst1[0])  
for element in lst1[1:]:  
    result = operator.add(sum, element)
```

```
lst1 = [ [2, 4], [5, 9], [1, 7] ]  
result = reduce(operator.add, lst1, [100])
```





# Join lists element-by-element

```
zip(list1, ..., listn)
```

Example: Combine two lists

```
>>> lst1 = [1, 2, 3, 4]
```

```
>>> lst2 = ['a', 'b', 'c', 'd', 'e']
```



```
>>> result = zip(lst1, lst2)
```

```
>>> result
```

```
[(1, 'a'), (2, 'b'), (3, 'c'), (4, 'd')]
```

The 'e' element was truncated since `lst1` only has 4 elements

The result is a list of tuples



# Uses for zip

Create a dictionary using `zip()` and `dict()`

```
>>> produce = ['apples', 'oranges', 'pears']  
>>> prices = [0.50, 0.45, 0.55]  
>>> priceDict = dict(zip(produce, prices))  
>>> print priceDict  
{'pears': 0.55, 'apples': 0.5, 'oranges': 0.45}
```

# Lambda Functions

Anonymous functions. Can be used assigned to variable.

Syntax: `lambda p1[,...,pn]: expression`

*expression* should not use `return`

Example: create a square function

```
>>> sqr = lambda x: x*x
```

```
>>> print sqr(5)
```



25

Example: average of 2 values

```
>>> avg = lambda x,y: (x+y)/2
```

```
>>> avg(2,7)
```

4.5





# Function can return a Lambda

```
# define a power function: only x is "bound" to the lambda
define power(n) :
    return lambda x: math.pow(x, n)

cube = power(3)
cube(10)
1000.0

list( map( cube, range(1,10) ) )
[1.0, 8.0, 27.0, ..., 729.0]
```

# References

## Python Documentation

<http://docs.python.org>



## Videos

*Python for Programmers* by Alex Martelli

<http://video.google.com/videoplay?docid=1135114630744003385>

*Advanced Python (Understanding Python)* by  
Thomas Wouters

<http://video.google.com/videoplay?docid=7760178035196894549>



# References

## Books

*Practical Programming: an Introduction ...*  
by Jennifer Campbell, et al. (Pragmatic  
Programmers, 2009)

Good book for novice programmer.

*Python Essential Reference, 4E.* (Addison  
Wesley)

Recommended by CPE/SKE students. Has tutorial and language  
description. More than just a reference.

