Computational Fluid Dynamics
HW1

Almog Dobrescu

ID 214254252

January 12, 2025

Contents

List of Figures

1 Inviscid Burgers Equation

The Inviscid Burgers equation, in conservation law form, is given by:

$$\frac{\partial u}{\partial t} + \frac{\partial F}{\partial x} = 0 \quad F = F_{(u)} = \frac{u^2}{2} \tag{1}$$

In non-conservation law form, is given by:

$$\frac{\partial u}{\partial t} + A\frac{\partial u}{\partial x} = 0 \quad A = \frac{\partial F}{\partial u} = u \tag{2}$$

The equation is obtained by neglecting the viscous term from the viscous Burger equation.

1.1 Boundary and Initial Conditions

$$\begin{aligned} u_{(x=0,t)} &= 1.0 \\ u_{(x=1,t)} &= u_1 \\ u_{(x,t=0)} &= 1 - (1 - u_1) \cdot x \end{aligned} \tag{3}$$

1.2 Finite Volume Formulation

$$u_i^{n+1} = u_i^n - \frac{\Delta t}{\Delta x}\left(f_{i+\frac{1}{2}}^n - f_{i-\frac{1}{2}}^n\right) \tag{4}$$

- For first-order schemes, there is no variation within a cell, and the value there is constant.
- For second-order schemes, the variation within the cell is linear.

1.3 CFL number

For the Roe method, the CFL number is defined as:

$$\text{CFL} = \frac{u\Delta t}{\Delta x} \tag{5}$$

We will want to set the maximal value of the *CFL* number. We will find the Δt at each cell and (Δt_i) and set the Δt of the current step as:

$$\Delta t = \min\left(\Delta t_i\right) \ \forall i \tag{6}$$

1.4 First Order Roe Method $(u_1 = 0.0)$

Roe scheme is based on the solution of the linear problem:

$$\frac{\partial u}{\partial t} + \bar{A}\frac{\partial u}{\partial x} = 0 \tag{7}$$

Where $\bar{A}$ is a constant matrix that is dependent on local conditions. The matrix is constructed in a way that guarantees uniform validity across discontinuities:

1. For any u_i, u_{i+1}:
$$F_{i+1} - F_i = \bar{A} \cdot (u_{i+1} - u_i)$$
2. When $u = u_i = u_{i+1}$ then:
$$\bar{A}(u_i, ui+1) = \bar{A}_{(u,u)} = \frac{\partial F}{\partial u} = u$$

In the case of the Burgers equation, the matrix $\bar{A}$ is a scalar, namely, $\bar{A} = \bar{u}$. The equation becomes:

$$\frac{\partial u}{\partial t} + \bar{u}\frac{\partial u}{\partial x} = 0 \tag{8}$$

The value of $\bar{u}$ for the cell face between i and $i+1$ is determined from the first conditions:

$$\bar{u} = \bar{u}i + \frac{1}{2} = \frac{Fi + 1 - F_i}{u_{i+1} - u_i} = \frac{\frac{1}{2}u_{i+1}^2 - \frac{1}{2}u_i^2}{u_{i+1} - u_i} = \begin{cases} \dfrac{u_i + u_{i+1}}{2} & u_i \neq u_{i+1} \\ u_i & u_i = u_{i+1} \end{cases} \tag{9}$$

The single wave that emanates from the cell interface travels either in the positive or negative direction, depending upon the sign of $\bar{u}_{i+\frac{1}{2}}$. Define:

$$\begin{cases} \bar{u}i + \frac{1}{2}^{+} \triangleq \dfrac{1}{2}\left(\bar{u}i + \dfrac{1}{2} + \left|\bar{u}_{i+\frac{1}{2}}\right|\right) \geq 0 \\ \\ \bar{u}i + \frac{1}{2}^{-} \triangleq \dfrac{1}{2}\left(\bar{u}i + \dfrac{1}{2} - \left|\bar{u}_{i+\frac{1}{2}}\right|\right) \leq 0 \end{cases} \quad \bar{u}i + \tfrac{1}{2} = \bar{u}i + \tfrac{1}{2}^{+} + \bar{u}_{i+\frac{1}{2}}^{-} \tag{10}$$

Using the jump relation, the numerical flux at the cell interface can be evaluated by one of the following:

$$\begin{cases} f_{i+\frac{1}{2}} - F_i = \bar{u}i + \frac{1}{2}^{-} \cdot (ui + 1 - u_i) \\ \\ F_{i+1} - f_{i+\frac{1}{2}} = \bar{u}i + \frac{1}{2}^{+} \cdot (ui + 1 - u_i) \end{cases} \tag{11}$$

The numerical flux may then be written in the following symmetric form:

$$\begin{aligned} f_{i+\frac{1}{2}} &= \frac{F_i + F_{i+1}}{2} - \frac{1}{2}\left(\bar{u}i + \frac{1}{2}^{+} - \bar{u}i + \frac{1}{2}^{-}\right)(u_{i+1} - u_i) \\ \text{OR}: \\ f_{i+\frac{1}{2}} &= \frac{F_i + F_{i+1}}{2} - \frac{1}{2}\left|\bar{u}i + \frac{1}{2}\right|(ui + 1 - u_i) \end{aligned} \tag{12}$$

1.5 Second Order Roe ($u_1 = 0.5$)

The first-order accurate Roe method interface flux function will be denoted like this:

$$f_{i+\frac{1}{2}}^{\text{Roe},1} = f_{(u_i, u_{i+1})}$$

The second order accurate Roe takes the form:

$$f_{i+\frac{1}{2}}^{\text{Roe},2} = f_{\left(u_{i+1}^{l}, u_{i+1}^{r}\right)}$$

Hence:

$$\begin{aligned} f_{i+\frac{1}{2}}^{\text{Roe},2} &= \frac{1}{2}\left(F_{\left(u_{1+\frac{1}{2}}^{l}\right)} + F_{\left(u_{1+\frac{1}{2}}^{r}\right)} - \left|\bar{u}i + \frac{1}{2}\right|\left(u1 + \frac{1}{2}^{r} - u_{1+\frac{1}{2}}^{l}\right)\right) \\ \bar{u}1 + \frac{1}{2} &= \frac{F\left(u_{1+\frac{1}{2}}^{r}\right) - F_{\left(u_{1+\frac{1}{2}}^{l}\right)}}{u_{1+\frac{1}{2}}^{r} - u_{1+\frac{1}{2}}^{l}} = \frac{u_{i+\frac{1}{2}}^{l} + u_{i+\frac{1}{2}}^{r}}{2} \end{aligned} \tag{13}$$

1.5.1 Without Limiters

The interface values without limiters are evaluated as:

$$\begin{cases} u^l_{i+\frac{1}{2}} & = & u_i + \frac{1-k}{4}\delta u_{i-\frac{1}{2}} + \frac{1+k}{4}\delta u_{i+\frac{1}{2}} \\ u^r_{i+\frac{1}{2}} & = & u_{i+1} - \frac{1+k}{4}\delta u_{i+\frac{1}{2}} - \frac{1-k}{4}\delta u_{i+\frac{3}{2}} \end{cases} \qquad \delta u_i \triangleq u_{i+\frac{1}{2}} - u_{i-\frac{1}{2}} \tag{14}$$

The parameter k determines the scheme:

$$k = \begin{cases} -1 & \text{upwind} \\ 1 & \text{central} \end{cases}$$

1.5.2 With Limiters

The interface values with limiters are evaluated as:

$$\begin{cases} u^l_{i+\frac{1}{2}} & = & u_i + \frac{1-k}{4}\overline{\delta^+}u_{i-\frac{1}{2}} + \frac{1+k}{4}\overline{\delta^-}u_{i+\frac{1}{2}} \\ u^r_{i+\frac{1}{2}} & = & u_{i+1} - \frac{1+k}{4}\overline{\delta^+}u_{i+\frac{1}{2}} - \frac{1-k}{4}\overline{\delta^-}u_{i+\frac{3}{2}} \end{cases} \qquad \overline{\delta^\pm}u \text{ are limited slopes} \tag{15}$$

$\overline{\delta}$ is an operator such that $\overline{\delta}u_i = \psi\delta u_i$, where $\psi(r)$ is a limiter function and:

$$r^\pm = \begin{cases} r^+_{1+\frac{1}{2}} & \triangleq & \dfrac{u_{i+2} - u_{i+1}}{u_{i+1} - u_i} = \dfrac{\Delta u_{i+1}}{\Delta u_i} \\ r^-_{1+\frac{1}{2}} & \triangleq & \dfrac{u_i - u_{i-1}}{u_{i+1} - u_i} = \dfrac{\nabla u_i}{\nabla u_{i+1}} \end{cases} \tag{16}$$

There are many types of limiters. For example, the van Albada limiter:

$$\psi(r) = \frac{r + r^2}{1 + r^2} \tag{17}$$

2 Generalized Burgers Equation

The generalized Burgers equation is given by:

$$\frac{\partial u}{\partial t} + (c + bu)\frac{\partial u}{\partial x} = \mu\frac{\partial^2 u}{\partial x^2} \tag{18}$$

Where:

$$c = \tfrac{1}{2} \qquad b = -1 \qquad \mu = [0.001, 0.25]$$

The equation can also be presented as:

$$\frac{\partial u}{\partial t} + \frac{\partial \bar{F}}{\partial x} = 0 \qquad \bar{F} = \underbrace{cu + \frac{bu^2}{2}}\,F - \mu\underbrace{\frac{\partial u}{\partial x}}\,F_\nu \tag{19}$$

In non-conservation law form, is given by:

$$\frac{\partial u}{\partial t} + A\frac{\partial u}{\partial x} = 0 \qquad A = \frac{\partial \bar{F}}{\partial u} = c + bu - \mu\frac{\partial}{\partial u}\left(\frac{\partial u}{\partial x}\right) \tag{20}$$

The generalized Burgers equation has a stationary solution:

$$u = -\frac{c}{b}\left(1 + \tanh\left(\frac{c\,(x - x_0)}{2\mu}\right)\right) \tag{21}$$

2.1 Domain and Computational Mesh

Using 41 grid points with $\Delta x = 1$ and computing until $t = 18.0$. $\Delta t = [0.5, 1.0]$.

2.2 Boundary and Initial Conditions

2.2.1 Initial Conditions

$$u_{(x,t=0)} = \frac{1}{2}\left(1 + \tanh\left(250\,(x - 20)\right)\right) \tag{22}$$

2.2.2 Boundary Conditions

Using Dirichlet boundary conditions:

$$u_{(x=0,t)} = 0 \qquad u_{(x=40,t)} = 1 \tag{23}$$

2.3 First Order Roe Method (explicit)

As written above for the inviscid Burgers equation (1.4), Roes scheme is based on the solution of the linear problem:

$$\frac{\partial u}{\partial t} + \bar{A}\frac{\partial u}{\partial x} = \mu\frac{\partial^2 u}{\partial x^2} \qquad \bar{A} = \frac{\partial F}{\partial u} = cu + \frac{bu^2}{2} \tag{24}$$

The value of $\bar{A}$ for the cell face between i and i+1 is determined from the first conditions:

$$\bar{A} = \bar{A}i + \frac{1}{2} = \frac{Fi + 1 - F_i}{u_{i+1} - u_i} = \frac{c\,(u_{i+1} - u_i) + \frac{b}{2}\left(u_{i+1}^2 - u_i^2\right)}{u_{i+1} - u_i} \tag{25}$$

The numerical flux at the cell interface:

$$\bar{f}i + \frac{1}{2} = \frac{\bar{F}_i + \bar{F}i + 1}{2} - \frac{1}{2}\left(\bar{A}i + \frac{1}{2}^+ - \bar{A}i + \frac{1}{2}^-\right)(u_{i+1} - u_i) \tag{26}$$

Where:

$$\begin{cases} \bar{A}i + \frac{1}{2}^+ \triangleq \dfrac{1}{2}\left(\bar{A}i + \dfrac{1}{2} + \left|\bar{A}_{i+\frac{1}{2}}\right|\right) \geq 0 \\ \bar{A}i + \frac{1}{2}^- \triangleq \dfrac{1}{2}\left(\bar{A}i + \dfrac{1}{2} - \left|\bar{A}_{i+\frac{1}{2}}\right|\right) \leq 0 \end{cases} \quad \bar{A}i + \tfrac{1}{2} = \bar{A}i + \tfrac{1}{2}^+ + \bar{A}^-_{i+\frac{1}{2}} \tag{27}$$

And finally:

$$u_i^{n+1} = u_i^n - \frac{\Delta t}{\Delta x}\left(\bar{f}i + \frac{1}{2}^n - \bar{f}i - \frac{1}{2}^n\right) \tag{28}$$

2.4 MacCormack Method

The original MacCormack method applied to Burgers equaiton results in:

$$\begin{aligned} &\text{Predictor :} \quad && u_i^{\overline{n+1}} = u_i^n - \Delta t \tfrac{\Delta F_i^n}{\Delta x} + r\delta^2 u_i^n \\ &\text{Corrector :} \quad && \tfrac{1}{2}\left(u_i^n + u_i^{\overline{n+1}} - \Delta t \tfrac{\nabla F_i^{\overline{n+1}}}{\Delta x}\right) + r\delta^2 u_i^{\overline{n+1}} \end{aligned} \tag{29}$$

2.5 First Order Beam and Warming

2.6 Second Order Beam and Warming