



JavaServer Pages™ Standard Tag Library

Version 1.2

Pierre Delisle, editor

Please send comments to jsr-52-comments@jcp.org

Sun Microsystems, Inc.
4150 Network Circle
Santa Clara, CA 95054
U.S.A.

8 May 2006

Sun Microsystems, Inc.
4150 Network Circle
Santa Clara, CA 95054
U.S.A.

Specification: JSR-000052 A Standard Tag Library for JavaServer Pages(tm) ("Specification")

Version: 1.2

Status: Maintenance Release

Release: 8 May 2006

Copyright 2006 SUN MICROSYSTEMS, INC.

4150 Network Circle, Santa Clara, California 95054, U.S.A

All rights reserved.

LIMITED LICENSE GRANTS

1. License for Evaluation Purposes. Sun hereby grants you a fully-paid, non-exclusive, non-transferable, worldwide, limited license (without the right to sublicense), under Sun's applicable intellectual property rights to view, download, use and reproduce the Specification only for the purpose of internal evaluation. This includes (i) developing applications intended to run on an implementation of the Specification, provided that such applications do not themselves implement any portion(s) of the Specification, and (ii) discussing the Specification with any third party; and (iii) excerpting brief portions of the Specification in oral or written communications which discuss the Specification provided that such excerpts do not in the aggregate constitute a significant portion of the Specification.

2. License for the Distribution of Compliant Implementations. Sun also grants you a perpetual, non-exclusive, non-transferable, worldwide, fully paid-up, royalty free, limited license (without the right to sublicense) under any applicable copyrights or, subject to the provisions of subsection 4 below, patent rights it may have covering the Specification to create and/or distribute an Independent Implementation of the Specification that: (a) fully implements the Specification including all its required interfaces and functionality; (b) does not modify, subset, superset or otherwise extend the Licensor Name Space, or include any public or protected packages, classes, Java interfaces, fields or methods within the Licensor Name Space other than those required/authorized by the Specification or Specifications being implemented; and (c) passes the Technology Compatibility Kit (including satisfying the requirements of the applicable TCK Users Guide) for such Specification ("Compliant Implementation"). In addition, the foregoing license is expressly conditioned on your not acting outside its scope. No license is granted hereunder for any other purpose (including, for example, modifying the Specification, other than to the extent of your fair use rights, or distributing the Specification to third parties). Also, no right, title, or interest in or to any trademarks, service marks, or trade names of Sun or Sun's licensors is granted hereunder. Java, and Java-related logos, marks and names are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries.

3. Pass-through Conditions. You need not include limitations (a)-(c) from the previous paragraph or any other particular "pass through" requirements in any license You grant concerning the use of your Independent Implementation or products derived from it. However, except with respect to Independent Implementations (and products derived from them) that satisfy limitations (a)-(c) from the previous paragraph, You may neither: (a) grant or otherwise pass through to your licensees any licenses under Sun's applicable intellectual property rights; nor (b) authorize your licensees to make any claims concerning their implementation's compliance with the Specification in question.

4. Reciprocity Concerning Patent Licenses.

a. With respect to any patent claims covered by the license granted under subparagraph 2 above that would be infringed by all technically feasible implementations of the Specification, such license is conditioned upon your offering on fair, reasonable and non-discriminatory terms, to any party seeking it from You, a perpetual, non-exclusive, non-transferable, worldwide license under Your patent rights which are or would be infringed by all technically feasible implementations of the Specification to develop, distribute and use a Compliant Implementation.

b With respect to any patent claims owned by Sun and covered by the license granted under subparagraph 2, whether or not their infringement can be avoided in a technically feasible manner when implementing the Specification, such license shall terminate with respect to such claims if You initiate a claim against Sun that it has, in the course of performing its responsibilities as the Specification Lead, induced any other entity to infringe Your patent rights.

c Also with respect to any patent claims owned by Sun and covered by the license granted under subparagraph 2 above, where the infringement of such claims can be avoided in a technically feasible manner when implementing the Specification such license, with respect to such claims, shall terminate if You initiate a claim against Sun that its making, having made, using, offering to sell, selling or importing a Compliant Implementation infringes Your patent rights.

5. Definitions . For the purposes of this Agreement: "Independent Implementation" shall mean an implementation of the Specification that neither derives from any of Sun's source code or binary code materials nor, except with an appropriate and separate license from Sun, includes any of Sun's source code or binary code materials; "Licensor Name Space" shall mean the public class or interface declarations whose names begin with "java", "javax", "com.sun" or their equivalents in any subsequent naming convention adopted by Sun through the Java Community Process, or any recognized successors or replacements thereof; and "Technology Compatibility Kit" or "TCK" shall mean the test suite and accompanying TCK User's Guide provided by Sun which corresponds to the Specification and that was available either (i) from Sun's 120 days before the first release of Your Independent Implementation that allows its use for commercial purposes, or (ii) more recently than 120 days from such release but against which You elect to test Your implementation of the Specification.

This Agreement will terminate immediately without notice from Sun if you breach the Agreement or act outside the scope of the licenses granted above.

DISCLAIMER OF WARRANTIES

THE SPECIFICATION IS PROVIDED "AS IS". SUN MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT (INCLUDING AS A CONSEQUENCE OF ANY PRACTICE OR IMPLEMENTATION OF THE SPECIFICATION), OR THAT THE CONTENTS OF THE SPECIFICATION ARE SUITABLE FOR ANY PURPOSE. This document does not represent any commitment to release or implement any portion of the Specification in any product. In addition, the Specification could include technical inaccuracies or typographical errors.

LIMITATION OF LIABILITY

TO THE EXTENT NOT PROHIBITED BY LAW, IN NO EVENT WILL SUN OR ITS LICENSORS BE LIABLE FOR ANY DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUE, PROFITS OR DATA, OR FOR SPECIAL, INDIRECT, CONSEQUENTIAL, INCIDENTAL OR PUNITIVE DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, ARISING OUT OF OR RELATED IN ANY WAY TO YOUR HAVING, IMPLEMENTING OR OTHERWISE USING THE SPECIFICATION, EVEN IF SUN AND/OR ITS LICENSORS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

You will indemnify, hold harmless, and defend Sun and its licensors from any claims arising or resulting from: (i) your use of the Specification; (ii) the use or distribution of your Java application, applet and/or implementation; and/or (iii) any claims that later versions or releases of any Specification furnished to you are incompatible with the Specification provided to you under this license.

RESTRICTED RIGHTS LEGEND

U.S. Government: If this Specification is being acquired by or on behalf of the U.S. Government or by a U.S. Government prime contractor or subcontractor (at any tier), then the Government's rights in the Software and accompanying documentation shall be only as set forth in this license; this is in accordance with 48 C.F.R. 227.7201 through 227.7202-4 (for Department of Defense (DoD) acquisitions) and with 48 C.F.R. 2.101 and 12.212 (for non-DoD acquisitions).

REPORT

If you provide Sun with any comments or suggestions concerning the Specification ("Feedback"), you hereby: (i) agree that such Feedback is provided on a non-proprietary and non-confidential basis, and (ii) grant Sun a perpetual, non-exclusive, worldwide, fully paid-up, irrevocable license, with the right to sublicense through multiple levels of sublicensees, to incorporate, disclose, and use without limitation the Feedback for any purpose.

GENERAL TERMS

Any action related to this Agreement will be governed by California law and controlling U.S. federal law. The U.N. Convention for the International Sale of Goods and the choice of law rules of any jurisdiction will not apply.

The Specification is subject to U.S. export control laws and may be subject to export or import regulations in other countries. Licensee

agrees to comply strictly with all such laws and regulations and acknowledges that it has the responsibility to obtain such licenses to export, re-export or import as may be required after delivery to Licensee.

This Agreement is the parties' entire agreement relating to its subject matter. It supersedes all prior or contemporaneous oral or written communications, proposals, conditions, representations and warranties and prevails over any conflicting or additional terms of any quote, order, acknowledgment, or other communication between the parties relating to its subject matter during the term of this Agreement. No modification to this Agreement will be binding, unless in writing and signed by an authorized representative of each party.

Contents

Preface xiv

1. Introduction 1

- 1.1 Goals 1
- 1.2 Multiple Tag Libraries 2
- 1.3 Container Requirement 2

2. Conventions 3

- 2.1 How Actions are Documented 3
 - 2.1.1 Attributes 4
 - 2.1.2 Syntax Notation 5
- 2.2 Scoped Variables 5
 - 2.2.1 var and scope 6
 - 2.2.2 Visibility 6
- 2.3 Static vs Dynamic Attribute Values 7
- 2.4 White Spaces 7
- 2.5 Body Content 7
- 2.6 Naming 8
- 2.7 Errors and Exceptions 8
- 2.8 Configuration Data 10
- 2.9 Default Values 11

3. Expression Language Overview	13
3.1 Expressions and Attribute Values	13
3.2 Accessing Application Data	14
3.3 Nested Properties and Accessing Collections	15
3.4 Operators	16
3.5 Automatic Type Conversion	16
3.6 Default Values	17
4. General-Purpose Actions	19
4.1 Overview	19
4.2 <code><c:out></code>	22
4.3 <code><c:set></code>	24
4.4 <code><c:remove></code>	27
4.5 <code><c:catch></code>	28
5. Conditional Actions	29
5.1 Overview	29
5.2 Custom Logic Actions	31
5.3 <code><c:if></code>	32
5.4 <code><c:choose></code>	33
5.5 <code><c:when></code>	34
5.6 <code><c:otherwise></code>	35
6. Iterator Actions	37
6.1 Overview	37
6.1.1 Collections of Objects to Iterate Over	38
6.1.2 Map	39
6.1.3 Iteration Status	39
6.1.4 Range Attributes	40
6.1.5 Tag Collaboration	40
6.1.6 Deferred Values	41

6.2	<c:forEach>	42
6.3	<c:forTokens>	46
7.	URL Related Actions	49
7.1	Hypertext Links	49
7.2	Importing Resources	50
7.2.1	URL	51
7.2.2	Exporting an object: String or Reader	51
7.2.3	URL Encoding	52
7.2.4	Networking Properties	52
7.3	HTTP Redirect	53
7.4	<c:import>	54
7.5	<c:url>	59
7.6	<c:redirect>	61
7.7	<c:param>	63
8.	Internationalization (i18n) Actions	65
8.1	Overview	66
8.1.1	<fmt:message>	67
8.2	I18n Localization Context	67
8.2.1	Preferred Locales	68
8.3	Determinining the Resource Bundle for an i18n Localization Context	70
8.3.1	Resource Bundle Lookup	70
8.3.2	Resource Bundle Determination Algorithm	71
8.3.3	Examples	72
8.4	Response Encoding	74
8.5	<fmt:setLocale>	76
8.6	<fmt:bundle>	78
8.7	<fmt:setBundle>	80
8.8	<fmt:message>	82
8.9	<fmt:param>	85

- 8.10 <fmt:requestEncoding> 87
- 8.11 Configuration Settings 89
 - 8.11.1 Locale 89
 - 8.11.2 Fallback Locale 89
 - 8.11.3 I18n Localization Context 90

9. Formatting Actions 91

- 9.1 Overview 91
 - 9.1.1 Formatting Numbers, Currencies, and Percentages 91
 - 9.1.2 Formatting Dates and Times 92
- 9.2 Formatting Locale 93
- 9.3 Establishing a Formatting Locale 95
 - 9.3.1 Locales Available for Formatting Actions 95
 - 9.3.2 Locale Lookup 95
 - 9.3.3 Formatting Locale Lookup Algorithm 95
- 9.4 Time Zone 96
- 9.5 <fmt:timeZone> 97
- 9.6 <fmt:setTimeZone> 98
- 9.7 <fmt:formatNumber> 100
- 9.8 <fmt:parseNumber> 104
- 9.9 <fmt:formatDate> 107
- 9.10 <fmt:parseDate> 110
- 9.11 Configuration Settings 113
 - 9.11.1 TimeZone 113

10. SQL Actions 115

- 10.1 Overview 115
 - 10.1.1 Data Source 115
 - 10.1.2 Querying a Database 116
 - 10.1.3 Updating a Database 118
 - 10.1.4 SQL Statement Parameters 118

10.2	Database Access	120
10.3	<sql:query>	121
10.4	<sql:update>	124
10.5	<sql:transaction>	127
10.6	<sql:setDataSource>	130
10.7	<sql:param>	132
10.8	<sql:dateParam>	134
10.9	Configuration Settings	136
10.9.1	DataSource	136
10.9.2	MaxRows	136
11.	XML Core Actions	137
11.1	Overview	137
11.1.1	XPath Context	137
11.1.2	XPath Variable Bindings	138
11.1.3	Java to XPath Type Mappings	139
11.1.4	XPath to Java Type Mappings	140
11.1.5	The <code>select</code> Attribute	140
11.1.6	Default Context Node	140
11.1.7	Resources Access	141
11.1.8	Core Actions	141
11.2	<x:parse>	143
11.3	<x:out>	146
11.4	<x:set>	148
12.	XML Flow Control Actions	149
12.1	Overview	149
12.2	<x:if>	151
12.3	<x:choose>	153
12.4	<x:when>	154
12.5	<x:otherwise>	155

12.6 `<x:forEach>` 156

13. XML Transform Actions 159

13.1 Overview 159

13.2 `<x:transform>` 161

13.3 `<x:param>` 164

14. Tag Library Validators 165

14.1 Overview 165

15. Functions 169

15.1 Overview 169

15.1.1 The `length` Function 169

15.1.2 String Manipulation Functions 170

15.2 `fn:contains` 173

15.3 `fn:containsIgnoreCase` 174

15.4 `fn:endsWith` 175

15.5 `fn:escapeXml` 176

15.6 `fn:indexOf` 177

15.7 `fn:join` 178

15.8 `fn:length` 179

15.9 `fn:replace` 180

15.10 `fn:split` 181

15.11 `fn:startsWith` 182

15.12 `fn:substring` 183

15.13 `fn:substringAfter` 184

15.14 `fn:substringBefore` 185

15.15 `fn:toLowerCase` 186

15.16 `fn:toUpperCase` 187

15.17 `fn:trim` 188

16. Java APIs	189
javax.servlet.jsp.jstl.core	191
ConditionalTagSupport	192
Config	195
IndexedValueExpression	201
IteratedExpression	204
IteratedValueExpression	206
LoopTag	209
LoopTagStatus	211
LoopTagSupport	213
StringTokenValueExpression	220
javax.servlet.jsp.jstl.fmt	223
LocaleSupport	224
LocalizationContext	227
javax.servlet.jsp.jstl.sql	229
Result	230
ResultSupport	232
SQLExecutionTag	234
javax.servlet.jsp.jstl.tlv	235
PermittedTaglibsTLV	236
ScriptFreeTLV	238
A. Compatibility & Migration	241
B. Changes	245

Preface

This is the JavaServer Pages™ Standard Tag Library 1.2 (JSTL 1.2) specification, developed by the JSR-52 expert group under the Java Community Process. See <http://www.jcp.org>.

Related Documentation

Implementors of JSTL and authors of JSP pages may find the following documents worth consulting for additional information:.

JavaServer Pages (JSP)	http://java.sun.com/jsp
Java Servlet Technology	http://java.sun.com/servlet
Java 2 Platform, Standard Edition	http://java.sun.com/j2se
Java 2 Platform, Enterprise Edition	http://java.sun.com/j2ee
JavaBeans	http://java.sun.com/beans
JDBC	http://java.sun.com/jdbc
Java Technology and XML	http://java.sun.com/xml
XPath specification	http://www.w3.org/TR/xpath
XML home page at W3C	http://www.w3.org/XML
HTML home page at W3C	http://www.w3.org/MarkUp
XML.org home page	http://www.xml.org

Typographical Conventions

Font Style	Uses
<i>Italic</i>	Emphasis, definition of term.
Monospace	Syntax, code examples, attribute names, Java language types, API, enumerated attribute values.

Acknowledgments

The JavaServer Pages™ Standard Tag Library (JSTL) specification is the result of collaborative work involving many individuals, all driven by a common goal of designing the best libraries possible for the JSP page author community.

We would like to thank all members of the JSR-52 expert group: Nathan Abramson, Shawn Bayern, Hans Bergsten, Paul Bonfanti, Vince Bonfanti, David Brown, Larry Cable, Tim Dawson, Morgan Delagrang, Bob Foster, David Geary, Scott Hasse, Hal Hildebrand, Jason Hunter, Serge Knystautas, Mark Kolb, Wellington Lacerda, Jan Luehe, Geir Magnusson Jr., Dan Malks, Craig McClanahan, Richard Morgan, Glenn Nielsen, Rickard Oberg, Joseph B. Ottinger, Eduardo Pelegri-Llopart, Sam Pullara, Tom Reilly, Brian Robinson, Russ Ryan, Pasi Salminen, Steven Sargent, Allan Scott, Virgil Sealy, Magnus Stenman, Gael Stevens, James Strachan, Christine Tomlinson, Norbert von Truchsess, Keyton Weissinger, Clement Wong, Alex Yiu.

This specification was first initiated by Eduardo Pelegri-Llopart. Eduardo's leadership in making the Java platform the best technology available for the web layer has been key in shaping the vision behind the standard tag library.

Shawn Bayern and Hans Bergsten deserve special credit for being actively involved in all design issues of this specification. Their vast expertise and commitment to excellence has had a profound impact in every single aspect of this specification. *Mille mercis Shawn et Hans!* Don't know how we would have done it without you two.

Many thanks to Jan Luehe for taking ownership of the internationalization and formatting chapters of this specification on short notice, and doing an incredible job.

Special mention to Nathan Abramson for being a driving force behind the expression language introduced in JSTL, to James Strachan for leading the group in our understanding of XML for page authors, and to Craig McClanahan for his help on servlet and J2EE platform related issues.

This specification has drawn a lot of its design ideas from pioneers in the field of tag libraries. We are grateful to the Jakarta project at Apache, as well as other efforts in the industry, where projects led by Craig McClanahan (Struts), James Strachan (XTags), Morgan Delagrang (DBTags), Tim Dawson (I18N), Glenn Nielsen (many utility taglibs), Scott Hasse (JPath), Dmitri Plotnikov (XPath), Pasi Salminen (O&D Struts), have greatly influenced the design of the JSTL libraries.

The RI team composed of Shawn Bayern (lead), Nathan Abramson, Justyna Horwat, and Jan Luehe has done a wonderful job at turning code faster than the specification could be written.

Quality has been in the capable hands of Ryan Lubke, lead of the TCK team that also includes Lance Andersen. David Geary's help in doing thorough reviews of the specification was also greatly appreciated.

We are also grateful to the product team at Sun Microsystems who helped us sail efficiently through this specification: Jim Driscoll, Karen Schaffer, George Grigoryev, Stephanie Bodoff, Vanitha Venkatraman, Prasad Subramanian, and Xiaotan He.

Finally, we'd like to thank the community at large for their ever increasing interest in this technology. We sure hope you'll enjoy the JSP Standard Tag Library.

Comments

We are interested in improving this specification and welcome your comments and suggestions. You can email your comments to us at:

`jsr-52-comments@jcp.org`

Introduction

This is the JavaServer Pages™ Standard Tag Library 1.2 (JSTL 1.2) specification, developed by the JSR-52 expert group under the Java Community Process (<http://www.jcp.org>).

1.1 Goals

The ultimate goal of JSTL is to help simplify JavaServer™ Pages (JSP™) page authors' lives.

A page author is someone who is responsible for the design of a web application's presentation layer using JSP pages. Many page authors are not fluent in any programming language.

One of the main difficulties a page author is faced with is the need to use a scripting language (the default being the Java programming language) to manipulate the dynamic data within a JSP page. Unfortunately, page authors often see scripting languages as complex and not very well adapted to their needs.

JSTL offers the following capabilities:

- General-purpose actions
These actions complement the expression language by allowing a page author to easily display expressions in the expression language, set and remove the value of JSP scoped attributes, as well as catch exceptions.
- Control flow actions
Tag-based control flow structures (conditionals, iterators), which are more natural to page authors.
- Tag library validators (TLVs)
TLVs allow projects to only allow specific tag libraries, as well as enforce JSP coding styles that are free of scripting elements.

The other key aspect of JSTL is that it provides standard actions and standard EL functions for functionality most often needed by page authors. These cover the following topics:

- Accessing URL-based resources
- Internationalization (i18n) and text formatting
- Relational database access (SQL)
- XML processing
- String manipulation

1.2 Multiple Tag Libraries

A tag library is a collection of actions that encapsulates functionality to be used from within a JSP page. JSTL includes a wide variety of actions that naturally fit into discrete functional areas. This is why JSTL, although referred to as the standard tag library (singular), is exposed via multiple tag libraries to clearly identify the functional areas it covers, as well as to give each area its own namespace. The tables below lists these functional areas along with the URIs used to reference the libraries. The tables also show the prefixes used in this specification (although page authors are free to use any prefix they want).

JSTL Tag Libraries

Functional Area	URI	Prefix
core	http://java.sun.com/jsp/jstl/core	c
XML processing	http://java.sun.com/jsp/jstl/xml	x
I18N capable formatting	http://java.sun.com/jsp/jstl/fmt	fmt
relational db access (SQL)	http://java.sun.com/jsp/jstl/sql	sql
Functions	http://java.sun.com/jsp/jstl/functions	fn

1.3 Container Requirement

JSTL 1.2 requires a JSP 2.1 web container. Please note that the expression language is part of the JSP specification starting with JSP 2.0.

Conventions

This chapter describes the conventions used in this specification.

2.1 How Actions are Documented

JSTL actions are grouped according to their functionality. These functional groups of actions are documented in their own chapter using the following structure:

- Motivation

Describes the motivation for standardizing the actions.

- Overview

Provides an overview of the capabilities provided by the actions. Sample code featuring these actions in their most common use cases is also provided.

- One section per action, with the following structure:

- Name

Tag library prefixes are used in this specification for all references to JSTL actions (e.g.: `<c:if>` instead of `<if>`).

- Short Description

- Syntax

The syntax notation is described in Section 2.1.2.

- Body Content

This section specifies which type of body content is supported by the action. As defined by the JSP specification, the body content type can be one of `empty`, `JSP`, or `tagdependent`. The section also specifies if the body content is processed by the action or is simply ignored by the action and just written to the current `JspWriter`. If the body content is processed, information is given on whether or not the body content is trimmed before the action begins processing it.

- Attributes

Details in Section 2.1.1 below.

- Constraints

List of additional constraints enforced by the action.

- Null & Error Handling

Details on how null and empty values are processed, as well as on exceptions thrown by the action.

- Description

This section provides more details on the action.

- Other sections

Other sections related to the group of actions described in the chapter may exist. These include sections on interfaces and classes exposed by these actions.

2.1.1 Attributes

For each attribute, the following information is given: name, dynamic behavior, type, and description.

The `rtexprvalue` element defined in a TLD is covered in this specification with the column titled “Dynamic” that captures the dynamic behavior of an attribute. The value can be either true or false. A false value in the dynamic column means that only a static string value can be specified for the attribute. A true value means that a *request-time attribute value* can be specified. As defined in the JSP specification, a “request-time attribute value” can be either a Java expression, an EL expression, or a value set by a `<jsp:attribute>`.

2.1.2 Syntax Notation

[...]	What is inside the square brackets is optional
{ <i>option1</i> <i>option2</i> <i>option3</i> ...}	Only one of the given options can be selected
<u><i>value</i></u>	The default value

For example, in the syntax below:

```
<c:set var="varName" [scope="{page|request|session|application}"]  
      value="value"/>
```

the attribute `scope` is optional. If it is specified, its value must be one of `page`, `request`, `session`, or `application`. The default value is `page`.

2.2 Scoped Variables

Actions usually collaborate with their environment in implicit or explicit ways, or both.

Implicit collaboration is often done via a well defined interface that allows nested tags to work seamlessly with the ancestor tag exposing that interface. The JSTL iterator tags support this mode of collaboration.

Explicit collaboration happens when a tag explicitly exposes information to its environment. Traditionally, this has been done by exposing a scripting variable with a value assigned from a JSP scoped attribute (which was saved by the tag handler). Because of the expression language, the need for scripting variables is significantly reduced. This is why all the JSTL tags expose information only as JSP scoped attributes (no scripting variable exposed). These exported JSP scoped attributes are referred to as *scoped variables* in this specification; this helps in preventing too much overloading of the term "attribute".

2.2.1 var and scope

The convention is to use the name `var` for attributes that export information. For example, the `<c:forEach>` action exposes the current item of the customer collection it is iterating over in the following way:

```
<c:forEach var="customer" items="${customers}">
  Current customer is <c:out value="${customer}" />
</c:forEach>
```

It is important to note that a name different than `id` was selected to stress the fact that only a scoped variable (JSP scoped attribute) is exposed, without any scripting variable.

If the scoped variable has at-end visibility (see Section 2.2.2), the convention also establishes the attribute `scope` to set the scope of the scoped variable.

The `scope` attribute has the semantics defined in the JSP specification, and takes the same values as the ones allowed in the `<jsp:useBean>` action; i.e. `page`, `request`, `session`, `application`. If no value is specified for `scope`, `page` scope is the default unless otherwise specified.

It is also important to note, as per the JSP specification, that specifying "session" scope is only allowed if the page has sessions enabled.

If an action exposes more than one scoped variable, the main one uses attribute names `var` and `scope`, while secondary ones have a suffix added for unique identification. For example, in the `<c:forEach>` action, the `var` attribute exposes the current item of the iteration (main variable exposed by the action), while the `varStatus` attribute exposes the current status of the iteration (secondary variable).

2.2.2 Visibility

Scoped variables exported by JSTL actions are categorized as either nested or at-end.

Nested scoped variables are only visible within the body of the action and are stored in "page" scope¹. The action must create the variable according to the semantics of `PageContext.setAttribute(varName, PAGE_SCOPE)`, and it must remove it at the end of the action according to the semantics of `PageContext.removeAttribute(varName, PAGE_SCOPE)`.²

At-end scoped variables are only visible at the end of the action. Their lifecycle is the one associated with their associated scope.

1. Since nested scoped variables are always saved in page scope, no `scope` attribute is associated with them.

In this specification, scoped variables exposed by actions are considered at-end by default. If a scoped variable is nested, it will be explicitly stated.

2.3 Static vs Dynamic Attribute Values

Except for the two exceptions described below, attribute values of JSTL actions can always be specified dynamically (see Section 2.1.1).

The first exception to this convention is for the `select` attribute of XML actions. This attribute is reserved in JSTL to specify a `String` literal that represents an expression in the XPath language.

The second exception is for attributes that define the name and scope of scoped variables (as introduced in Section 2.1.1) exported by JSTL actions.

Restricting these attributes to static values should benefit development tools, without any impediment to page authors.

2.4 White Spaces

Following the JSP specification (as well as the XML and XSLT specifications), whitespace characters are `#x20`, `#x9`, `#xD`, or `#xA`.

2.5 Body Content

If an action accepts a body content, an empty body is always valid, unless explicitly stated otherwise.

If the body content is used to set the value of an attribute, then an empty body content sets the attribute value to an empty string.

2. It is important to note that the JSP specification says that "A name should refer to a unique object at all points in the execution, that is all the different scopes really should behave as a single name space." The JSP specification also says that "A JSP container implementation may or may not enforce this rule explicitly due to performance reasons". Because of this, if a scoped variable with the same name as a nested variable already exists in a scope other than 'page', exactly what happens to that scoped variable depends on how the JSP container has been implemented. To comply with the JSP specification, and to avoid non-portable behavior, page authors should therefore avoid using the same name in different scopes.

If a body content is trimmed prior to being processed by the action, it is trimmed as defined in method `trim()` of the class `java.lang.String`.

2.6 Naming

JSTL adopts capitalization conventions of Java variables for compound words in action and attribute names. Recommended tag prefixes are kept lowercase. Thus, we have `<sql:transaction>` and `<c:forEach>`, as well as attributes such as `docSystemId` and `varDom`.

In some cases, attribute names for JSTL actions carry conventional meanings. For instance, Section 2.2.1 discussed the `var` and `scope` attributes. Section 11.1.5 discusses the `select` attribute used in JSTL's XML-processing tag library.

2.7 Errors and Exceptions

All syntax errors (as defined in the syntax section of each action, as well as the syntax of EL expressions as defined in Appendix A) must be reported at translation time.

Constraints, as defined in the constraints section of each action, must also be reported at translation time unless they operate on a dynamic attribute value, in which case errors are reported at runtime.

The conversion from a `String` value to the expected type of an attribute is handled according to the rules defined in the JSP specification.

Since it is hard for a page author to deal with exceptions, JSTL tries to avoid as many exception cases as possible, without causing other problems.

For instance, if `<c:forEach>` were to throw an exception when given a null value for the attribute `items`, it would be impossible to easily loop over a possibly missing string array that represents check-box selection in an HTML form (retrieved with an EL expression like `${paramValues.selections}`). A better choice is to do nothing in this case.

The conventions used in JSTL with respect to errors and exceptions are as follows:

- `scope`
 - Invalid value – translation time validation error
- `var`

- Empty – translation time validation error
- Dynamic attributes *with* a fixed set of valid String values:
 - null – use the default value
A null value can therefore be used to dynamically (e.g. by request parameter), turn on or off special features without too much work.
 - Invalid value – throw an exception
If a value is provided but is not valid, it's likely a typo or another mistake.
- Dynamic attributes *without* a fixed set of valid values:

The rules below assume that if the type of the value does not match the expected type, the EL will have applied coercion rules to try to accommodate the input value. Moreover, if the expected type is one of the types handled by the EL coercion rules, the EL will in most cases coerce null to an appropriate value. For instance, if the expected type is a Number, the EL will coerce a null value to 0, if it's Boolean it will be coerced to false.

 - null – behavior specific to the action
If this rule is applied, it's because the EL could not coerce the null into an appropriate default value. It is therefore up to the action to deal with the null value and is documented in the “Null & Error Handling” section of the action.
 - Invalid type – throw an exception
 - Invalid value – throw an exception
- Exceptions caused by the body content:
Always propagate, possibly after handling them (e.g. <sql:transaction>).
- Exceptions caused by the action itself:
Always propagate, possibly after handling them.
- Exceptions caused by the EL:
Always propagate.
- Exceptions caused by XPath:
Always propagate.

Page authors may catch an exception using <c:catch>, which exposes the exception through its var attribute. var is removed if no exception has occurred.

When this specification requires an action to throw an exception, this exception must be an instance of `javax.servlet.jsp.JspException` or a subclass. If an action catches any exceptions that occur in its body, its tag handler must provide the caught exception as the root cause of the `JspException` it re-throws.

Also, by default, JSTL actions do not catch or otherwise handle exceptions that occur during evaluation of their body content. If they do, it is documented in their “Null & Error Handling” or “Description” section.

2.8 Configuration Data

Context initialization parameters (see Servlet specification) are useful to configure the behavior of actions. For example, it is possible in JSTL to define the resource bundle used by I18N actions via the deployment descriptor (web.xml) as follows:

```
<web-app>
...
<context-param>
  <param-name>javax.servlet.jsp.jstl.fmt.localizationContext</
param-name>
  <param-value>com.acme.MyResources</param-value>
</context-param>
...
</web-app>
```

In many cases, it is also useful to allow configuration data to be overridden dynamically for a particular JSP scope (page, request, session, application) via a scoped variable. JSTL refers to scoped variables used for that purpose as *configuration variables*.

According to the JSP specification (JSP.2.8.2), a scoped variable name should refer to a unique object at all points in the execution. This means that all the different scopes (page, request, session, and application) that exist within a `PageContext` really should behave as a single name space; setting a scoped variable in any one scope overrides it in any of the other scopes.

Given this constraint imposed by the JSP specification, and in order to allow a configuration variable to be set for a particular scope without affecting its settings in any of the other scopes, JSTL provides the `Config` class (see Chapter 16 “Java APIs”). The `Config` class transparently manipulates the name of configuration variables so they behave as if scopes had their own private name space. Details on the name manipulations involved are voluntarily left unspecified and are handled transparently by the `Config` class. This ensures flexibility should the “scope name space” issue be addressed in the future by the JSP specification.

When setting configuration data via the deployment descriptor, the name associated with the context initialization parameter (e.g.

`javax.servlet.jsp.jstl.fmt.localizationContext`) must be used and only String values may be specified. Configuration data that can be set both through a context initialization parameter and configuration variables is referred to as a *configuration setting* in this specification.

As mentioned above, application developers may access configuration data through class `Config` (see Chapter 16 “Java APIs”). As a convenience, constant `String` values have been defined in the `Config` class for each configuration setting supported by JSTL. The values of these constants are the names of the context initialization parameters.

Each configuration variable clearly specifies the Java data type(s) it supports. If the type of the object used as the value of a configuration variable does not match one of those supported by the configuration variable, conversion is performed according to the conversion rules defined in the expression language. Setting a configuration variable is therefore exactly the same as setting an attribute value of an action using the EL. A failure of these conversion rules to determine an appropriate type coercion leads to a `JspException` at runtime.

2.9 Default Values

It is often desirable to display a default value if the output of an action yields a null value. This can be done in a generic way in JSTL by exporting the output of an action via attribute `var`, and then displaying the value of that scoped variable with action `<c:out>`.

For example:

```
<fmt:formatDate var="formattedDate" value="{reservationDate}"/>
Date: <c:out value="{formattedDate}" default="not specified"/>
```


Expression Language Overview

JSTL 1.0 introduced the notion of an expression language (EL) to make it easy for page authors to access and manipulate application data without having to master the complexity associated with programming languages such as Java and JavaScript.

Starting with JSP 2.0 / JSTL 1.1, the EL has become the responsibility of the JSP specification and is now formally defined there.

This chapter provides a simple overview of the key features of the expression language, it is therefore non-normative. Please refer to the JSP specification for the formal definition of the EL.

3.1 Expressions and Attribute Values

The EL is invoked exclusively via the construct `${expr}`. In the sample code below, an EL expression is used to set the value of attribute `test`, while a second one is used to display the title of a book.

```
<c:if test="${book.price <= user.preferences.spendingLimit}">
  The book ${book.title} fits your budget!
</c:if>
```

It is also possible for an attribute to contain more than one EL expression, mixed with static text. For example, the following would display “Price of *productName* is *productPrice*” for a list of products.

```
<c:forEach var="product" items="${products}">
  <c:out value="Price of ${product.name} is ${product.price}"/>
</c:forEach>
```

3.2 Accessing Application Data

An identifier in the EL refers to the JSP scoped variable returned by a call to `PageContext.findAttribute(identifier)`. This variable can therefore reside in any of the four JSP scopes: page, request, session, or application. A null value is returned if the variable does not exist in any of the scopes.

The EL also defines implicit objects to support easy access to application data that is of interest to a page author. `Implicit objects pageScope, requestScope, sessionScope, and applicationScope` provide access to the scoped variables in each one of these JSP scopes. It is also possible to access HTTP request parameters via the implicit objects `param` and `paramValues`. `param` is a Map object where `param["foo"]` returns the first string value associated with request parameter `foo`, while `paramValues["foo"]` returns an array of all string values associated with that request parameter.

The code below displays all request parameters along with all their associated values.

```
<c:forEach var="aParam" items="${paramValues}">
  param: ${aParam.key}
  values:
    <c:forEach var="aValue" items="${aParam.value}">
      ${aValue}
    </c:forEach>
  <br>
</c:forEach>
```

Request headers are also accessible in a similar fashion via implicit objects `header` and `headerValues`. `initParam` gives access to context initialization parameters, while `cookie` exposes cookies received in the request.

Implicit object `pageContext` is also provided for advanced usage, giving access to all properties associated with the `PageContext` of a JSP page such as the `HttpServletRequest`, `ServletContext`, and `HttpSession` objects and their properties.

3.3 Nested Properties and Accessing Collections

The application data that a page author manipulates in a JSP page usually consists of objects that comply with the JavaBeans specification, or that represent collections such as lists, maps, or arrays.

The EL recognizes the importance of these data structures and provides two operators, `"."` and `"["`, to make it easy to access the data encapsulated in these objects.

The `"."` operator can be used as a convenient shorthand for property access when the property name follows the conventions of Java identifiers. For example:

```
Dear ${user.firstName}
from ${user.address.city},
thanks for visiting our website!
```

The `"["` operator allows for more generalized access, as shown below:

```
<!-- "productDir" is a Map object containing the description of
      products, "preferences" is a Map object containing the
      preferences of a user --%>
product:
${productDir[product.custId]}
shipping preference:
${user.preferences["shipping"]}
```

3.4 Operators

The operators supported in the EL handle the most common data manipulations. The standard relational, arithmetic, and logical operators are provided in the EL. A very useful “empty” operator is also provided.

The six standard relational operators are supported: == (or eq), != (or ne), < (or lt), > (or gt), <= (or le), >= (or ge). The second versions of the last 4 operators are made available to avoid having to use entity references in XML syntax.

Arithmetic operators consist of addition (+), subtraction (-), multiplication (*), division (/ or div), and remainder/modulo (% or mod).

Logical operators consist of && (or and), || (or or), and ! (or not).

The empty operator is a prefix operator that can be used to determine if a value is null or empty. For example:

```
<c:if test="${empty param.name}">
  Please specify your name.
</c:if>
```

3.5 Automatic Type Conversion

The application data a page author has access to may not always exactly match the type expected by the attribute of an action or the type expected for an EL operator. The EL supports an exhaustive set of rules to coerce the type of the resulting value to the expected type.

For example, if request attributes beginValue and endValue are Integer objects, they will automatically be coerced to ints when used with the <c:forEach> action.

```
<c:forEach begin="${requestScope.beginValue}"
           end="${requestScope.endValue}">
  ...
</c:forEach>
```

In the example below, the parameter String value `param.start` is coerced to a number and is then added to 10 to yield an int value for attribute `begin`.

```
<c:forEach items="${products}" begin="${param.start + 10}">
    ...
</c:forEach>
```

3.6 Default Values

JSP pages are mostly used in presentation. Experience suggests that it is important to be able to provide as good a presentation as possible, even when simple errors occur in the page. To satisfy this requirement, the EL provides default values rather than errors when failure to evaluate an expression is deemed “recoverable”. Default values are type-correct values that allow a page to easily recover from these error conditions.

In the following example, the expression “`${user.address.city}`” evaluates to null rather than throwing a `NullPointerException` if there is no address associated with the `user` object. This way, a sensible default value can be displayed without having to worry about exceptions being thrown by the JSP page.

```
City: <c:out value="${user.address.city}" default="N/A"/>
```

In the following example, the addition operator considers the value of `param.start` to be 0 if it is not defined, therefore evaluating the expression to 10.

```
<c:forEach items="${products}" begin="${param.start + 10}">
    ...
</c:forEach>
```


General-Purpose Actions

core tag library

This chapter introduces general purpose actions to support the manipulation of scoped variables as well as to handle error conditions.

4.1 Overview

The `<c:out>` action provides a capability similar to JSP expressions such as `<%= scripting-language-expression %>` or `${el-expression}`. For example:

```
You have <c:out value="${sessionScope.user.itemCount}"/> items.
```

By default, `<c:out>` converts the characters `<`, `>`, `'`, `"`, and `&` to their corresponding character entity codes (e.g. `<` is converted to `<`). If these characters are not converted, the page may not be rendered properly by the browser, and it could also open the door for cross-site scripting attacks (e.g. someone could post JavaScript code for closing the window to an online discussion forum). The conversion may be bypassed by specifying `false` to the `escapeXml` attribute.

The `<c:out>` action also supports the notion of default values for cases where the value of an EL expression is null. In the example below, the value “unknown” will be displayed if the property `city` is not accessible.

```
<c:out value="${customer.address.city}" default="unknown"/>
```

The action `<c:set>` is used to set the value of a JSP scoped attribute as follows:

```
<c:set var="foo" value="value" />
```

It is also possible to set the value of a scoped variable (JSP scoped attribute) from the body of the `<c:set>` action. This solves the problem associated with not being able to set an attribute value from another action. In the past, a tag developer would often implement extra "attributes as tags" so the value of these attributes could be set from other actions.

For example, the action `<acme:att1>` was created only to support setting the value of `att1` of the parent tag `<acme:atag>` from other actions .

```
<acme:atag>
  <acme:att1>
    <acme:foo>mumbojumbo</acme:foo>
  </acme:att1>
</acme:atag>
```

With the `<c:set>` tag, this can be handled without requiring the extra `<acme:att1>` tag.

```
<c:set var="att1">
  <acme:foo>mumbojumbo</acme:foo>
</c:set>
<acme:atag att1="${att1}" />
```

In the preceding example, the `<c:set>` action sets the value of the `att1` scoped variable to the output of the `<acme:foo>` action. `<c:set>` – like all JSTL actions that create scoped attributes – creates scoped attributes in “page” scope by default.

`<c:set>` may also be used to set the property of a JavaBeans object, or add or set a specific element in a `java.util.Map` object. For example:.

```
<!-- set property in JavaBeans object -->
<c:set target="${cust.address}" property="city" value="${city}" />

<!-- set/add element in Map object -->
<c:set target="${preferences}" property="color"
  value="${param.color}" />
```

Finally, `<c:set>` may also be used to set a deferred-value that can later be evaluated by a tag handler. In this case, no scope can be specified. For example:

```
<!-- set deferred value -->
<c:set var="d" value="{handler.everythingDisabled}"/>
...
<h:inputText id="i1" disabled="{d}"/>
<h:inputText id="i2" disabled="{d}"/>
```

Action `<c:remove>` is the natural companion to `<c:set>`, allowing the explicit removal of scoped variables. For example:

```
<c:remove var="cachedResult" scope="application"/>
```

Finally, the `<c:catch>` action provides a complement to the JSP error page mechanism. It is meant to allow page authors to recover gracefully from error conditions that they can control. For example:

```
<c:catch var="exception">
  <!-- Execution we can recover from if exception occurs -->
  ...
</c:catch>
<c:if test="{exception != null}">
  Sorry. Processing could not be performed because...
</c:if>
```

4.2 <c:out>

Evaluates an expression and outputs the result of the evaluation to the current `JspWriter` object.

Syntax

Without a body

```
<c:out value="value" [escapeXml="{true|false}"]  
      [default="defaultValue"] />
```

With a body

```
<c:out value="value" [escapeXml="{true|false}"]>  
    default value  
</c:out>
```

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

Attributes

Name	Dyn	Type	Description
value	true	Object	Expression to be evaluated.
escapeXml	true	boolean	Determines whether characters <,>,&,' in the resulting string should be converted to their corresponding character entity codes. Default value is true.
default	true	Object	Default value if the resulting value is null.

Null & Error Handling

- If `value` is null, the default value takes over. If no default value is specified, it itself defaults to an empty string.

Description

The expression to be evaluated is specified via the `value` attribute.

If the result of the evaluation is not a `java.io.Reader` object, then it is coerced to a `String` and is subsequently emitted into the current `JspWriter` object.

If the result of the evaluation is a `java.io.Reader` object, data is first read from the `Reader` object and then written into the current `JspWriter` object. This special processing associated with `Reader` objects should help improve performance when large amount of data must be read and then displayed to the page.

If `escapeXml` is true, the following character conversions are applied:

Character	Character Entity Code
<	<
>	>
&	&
'	'
''	"

The default value can be specified either via the `default` attribute (using the syntax without a body), or within the body of the tag (using the syntax with a body). It defaults to an empty string.

4.3

<c:set>

Sets the value of a scoped variable or a property of a target object.

Syntax

Syntax 1: Set the value of a scoped variable using attribute value

```
<c:set value="value"
      var="varName" [scope="{page|request|session|application}"] />
```

Syntax 2: Set the value of a scoped variable using body content

```
<c:set var="varName" [scope="{page|request|session|application}"]>
  body content
</c:set>
```

Syntax 3: Set a property of a target object using attribute value

```
<c:set value="value"
      target="target" property="propertyName" />
```

Syntax 4: Set a property of a target object using body content

```
<c:set target="target" property="propertyName">
  body content
</c:set>
```

Syntax 5: Set a deferred value

```
<c:set var="varName" value="deferred-value" />
```

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

Attributes

Name	Dyn	Type	Description
value	true	Object	Expression to be evaluated.
var	false	String	Name of the exported scoped variable to hold the value specified in the action. The type of the scoped variable is whatever type the value expression evaluates to.

Name	Dyn	Type	Description
scope	false	String	Scope for var.
target	true	Object	Target object whose property will be set. Must evaluate to a JavaBeans object with setter property <code>property</code> , or to a <code>java.util.Map</code> object.
property	true	String	Name of the property to be set in the target object.

Null & Error Handling

- Syntax 3 and 4: Throw an exception under any of the following conditions:
 - `target` evaluates to null
 - `target` is not a `java.util.Map` object and is not a JavaBeans object that supports setting property `property`.
- If value is null
 - Syntax 1: the scoped variable defined by `var` and `scope` is removed.
 - If attribute `scope` is specified, the scoped variable is removed according to the semantics of `PageContext.removeAttribute(varName, scope)`.
 - Otherwise, there is no way to differentiate between syntax 1 and syntax 5. The scoped variable is removed according to the semantics of `PageContext.removeAttribute(varName)`, and the variable is removed from the `VariableMapper` as well.
 - Syntax 3:
 - if `target` is a `Map`, remove the entry with the key identified by `property`.
 - if `target` is a `JavaBean` component, set the property to null.
 - Syntax 5:
 - There is no way to differentiate between syntax 1 (where `scope` is not specified) and syntax 5. The scoped variable is removed according to the semantics of `PageContext.removeAttribute(varName)`, and the variable is removed from the `VariableMapper` as well.

Description

Syntax 1 and 2 set the value of a the scoped variable identified by `var` and `scope`.

Syntax 3 and 4:

- If the target expression evaluates to a `java.util.Map` object, set the value of the element associated with the key identified by `property`. If the element does not exist, add it to the `Map` object.
- Otherwise, set the value of the property `property` of the JavaBeans object `target`. If the type of the value to be set does not match the type of the bean `property`, conversion is performed according to the conversion rules defined in the expression language (see Section A.7). With the exception of a null value,

setting a bean property with `<c:set>` is therefore exactly the same as setting an attribute value of an action using the EL. A failure of these conversion rules to determine an appropriate type coercion leads to a `JspException` at runtime.

Syntax 5:

- Map the deferred-value specified to the "var" attribute into the EL `VariableMapper`.
- Some implementation notes illustrating how the `<c:set>` tag handler may process a deferred-value specified for the "value" attribute.

```
doStartTag()  
...  
// 'value' is a deferred-value  
// Get the current EL VariableMapper  
VariableMapper vm =  
    jspContext.getELContext().getVariableMapper();  
// Assign the expression to the variable specified  
// in the 'var' attribute, so any reference to that  
// variable will be replaced by the expression is  
// subsequent EL evaluations.  
vm.setVariable(getVar(), (ValueExpression)getValue());  
...
```

4.4 <c:remove>

Removes a scoped variable.

Syntax

```
<c:remove var="varName"  
[scope="{page|request|session|application}"]/>
```

Attributes

Name	Dynamic	Type	Description
var	false	String	Name of the scoped variable to be removed.
scope	false	String	Scope for var.

Description

The <c:remove> action removes a scoped variable.

If attribute `scope` is not specified, the scoped variable is removed according to the semantics of `PageContext.removeAttribute(varName)`. If attribute `scope` is specified, the scoped variable is removed according to the semantics of `PageContext.removeAttribute(varName, scope)`.

4.5 <c:catch>

Catches a `java.lang.Throwable` thrown by any of its nested actions.

Syntax

```
<c:catch [var="varName"]>  
    nested actions  
</c:catch>
```

Body Content

JSP. The body content is processed by the JSP container and the result is written to the current `JspWriter`.

Attributes

Name	Dynamic	Type	Description
var	false	String	Name of the exported scoped variable for the exception thrown from a nested action. The type of the scoped variable is the type of the exception thrown.

Description

The `<c:catch>` action allows page authors to handle errors from any action in a uniform fashion, and allows for error handling for multiple actions at once.

`<c:catch>` provides page authors with granular error handling: Actions that are of central importance to a page should not be encapsulated in a `<c:catch>`, so their exceptions will propagate to an error page, whereas actions with secondary importance to the page should be wrapped in a `<c:catch>`, so they never cause the error page mechanism to be invoked.

The exception thrown is stored in the scoped variable identified by `var`, which always has page scope. If no exception occurred, the scoped variable identified by `var` is removed if it existed.

If `var` is missing, the exception is simply caught and not saved.

Conditional Actions

core tag library

The output of a JSP page is often conditional on the value of dynamic application data. A simple scriptlet with an `if` statement can be used in such situations, but this forces a page author to use a scripting language whose syntax may be troublesome (e.g. one may forget the curly braces).

The JSTL conditional actions make it easy to do conditional processing in a JSP page.

5.1 Overview

The JSTL conditional actions are designed to support the two most common usage patterns associated with conditional processing: simple conditional execution and mutually exclusive conditional execution.

A *simple* conditional execution action evaluates its body content only if the test condition associated with it is true. In the following example, a special greeting is displayed only if this is a user's first visit to the site:

```
<c:if test="${user.visitCount == 1}">
    This is your first visit. Welcome to the site!
</c:if>
```

With *mutually exclusive* conditional execution, only one among a number of possible alternative actions gets its body content evaluated.

For example, the following sample code shows how the text rendered depends on a user's membership category.

```
<c:choose>
  <c:when test="${user.category == 'trial'}">
    ...
  </c:when>
  <c:when test="${user.category == 'member'}">
    ...
  </c:when>
  <c:when test="${user.category == 'vip'}">
    ...
  </c:when>
  <c:otherwise>
    ...
  </c:otherwise>
</c:choose>
```

An if/then/else statement can be easily achieved as follows:

```
<c:choose>
  <c:when test="${count == 0}">
    No records matched your selection.
  </c:when>
  <c:otherwise>
    ${count} records matched your selection.
  </c:otherwise>
</c:choose>
```

5.2 Custom Logic Actions

It is important to note that the `<c:if>` and `<c:when>` actions have different semantics. A `<c:if>` action will always process its body content if its test condition evaluates to true. A `<c:when>` action will process its body content if it is the *first* one in a series of `<c:when>` actions whose test condition evaluates to true.

These semantic differences are enforced by the fact that only `<c:when>` actions can be used within the context of a mutually exclusive conditional execution (`<c:choose>` action). This clean separation of behavior also impacts the way custom logic actions (i.e. actions who render their bodies depending on the result of a test condition) should be designed. Ideally, the result associated with the evaluation of a custom logic action should be usable both in the context of a simple conditional execution, as well as in a mutually exclusive conditional execution.

The proper way to enable this is by simply having the custom logic action export the result of the test condition as a scoped variable. This boolean result can then be used as the test condition of a `<c:when>` action.

In the example below, the fictitious custom action `<acme:fullMoon>` tells whether or not a page is accessed during a full moon. The behavior of an `if/then/else` statement is made possible by having the result of the `<acme:fullMoon>` action exposed as a boolean scoped variable that is then used as the test condition in the `<c:when>` action.

```
<acme:fullMoon var="isFullMoon"/>
<c:choose>
  <c:when test="${isFullMoon}">
    ...
  </c:when>
  <c:otherwise>
    ...
  </c:otherwise>
</c:choose>
```

To facilitate the implementation of conditional actions where the boolean result is exposed as a JSP scoped variable, class `ConditionalTagSupport` (see Chapter 16 “Java APIs”) has been defined in this specification.

5.3 <c:if>

Evaluates its body content if the expression specified with the `test` attribute is true.

Syntax

Syntax 1: Without body content

```
<c:if test="testCondition"
      var="varName" [scope="{page|request|session|application}"]/>
```

Syntax 2: With body content

```
<c:if test="testCondition"
      [var="varName"] [scope="{page|request|session|application}"]>
  body content
</c:if>
```

Body Content

JSP. If the test condition evaluates to true, the JSP container processes the body content and then writes it to the current `JspWriter`.

Attributes

Name	Dyn	Type	Description
test	true	boolean	The test condition that determines whether or not the body content should be processed.
var	false	String	Name of the exported scoped variable for the resulting value of the test condition. The type of the scoped variable is <code>Boolean</code> .
scope	false	String	Scope for <code>var</code> .

Constraints

- If `scope` is specified, `var` must also be specified.

Description

If the test condition evaluates to true, the body content is evaluated by the JSP container and the result is output to the current `JspWriter`.

5.4 <c:choose>

Provides the context for mutually exclusive conditional execution.

Syntax

```
<c:choose>
  body content (<when> and <otherwise> subtags)
</c:choose>
```

Body Content

JSP. The body content is processed by the JSP container (at most one of the nested actions will be processed) and written to the current `JspWriter`.

Attributes

None.

Constraints

- The body of the <c:choose> action can only contain:
 - White spaces
May appear anywhere around the <c:when> and <c:otherwise> subtags.
 - 1 or more <c:when> actions
Must all appear before <c:otherwise>
 - 0 or 1 <c:otherwise> action
Must be the last action nested within <c:choose>

Description

The <c:choose> action processes the body of the first <c:when> action whose test condition evaluates to true. If none of the test conditions of nested <c:when> actions evaluates to true, then the body of an <c:otherwise> action is processed, if present.

5.5 <c:when>

Represents an alternative within a <c:choose> action.

Syntax

```
<c:when test="testCondition">
    body content
</c:when>
```

Body Content

JSP. If this is the first <c:when> action to evaluate to true within <c:choose>, the JSP container processes the body content and then writes it to the current `JspWriter`.

Attributes

Name	Dynamic	Type	Description
test	true	boolean	The test condition that determines whether or not the body content should be processed.

Constraints

- Must have <c:choose> as an immediate parent.
- Must appear before an <c:otherwise> action that has the same parent.

Description

Within a <c:choose> action, the body content of the first <c:when> action whose test condition evaluates to true is evaluated by the JSP container, and the result is output to the current `JspWriter`.

5.6 <c:otherwise>

Represents the last alternative within a <c:choose> action.

Syntax

```
<c:otherwise>
    conditional block
</c:otherwise>
```

Body Content

JSP. If no <c:when> action nested within <c:choose> evaluates to true, the JSP container processes the body content and then writes it to the current `JspWriter`.

Attributes

None.

Constraints

- Must have <c:choose> as an immediate parent.
- Must be the last nested action within <c:choose>.

Description

Within a <c:choose> action, if none of the nested <c:when> test conditions evaluates to true, then the body content of the <c:otherwise> action is evaluated by the JSP container, and the result is output to the current `JspWriter`.

Iterator Actions

core tag library

Iterating over a collection of objects is a common occurrence in a JSP page. Just as with conditional processing, a simple scriptlet can be used in such situations. However, this once again forces a page author to be knowledgeable in many aspects of the Java programming language (how to iterate on various collection types, having to cast the returned object into the proper type, proper use of the curly braces, etc.).

The JSTL iterator actions simplify iterating over a wide variety of collections of objects.

6.1 Overview

The `<c:forEach>` action repeats its nested body content over the collection of objects specified by the `items` attribute. For example, the JSP code below creates an HTML table with one column that shows the default display value of each item in the collection.

```
<table>
  <c:forEach var="customer" items="${customers}">
    <tr><td>${customer}</td></tr>
  </c:forEach>
</table>
```

The `<c:forEach>` action has the following features:

- Supports all standard J2SE™ platform collection types.

A page author therefore does not have to worry about the specific type of the collection of objects to iterate over (see Section 6.1.1).

- Exports an object that holds the current item of the iteration.
Normally, each object exposed by `<c:forEach>` is an item of the underlying collection being iterated over. There are two exceptions to this to facilitate access to the information contained in arrays of primitive types, as well as in Map objects (see Section 6.1.2).
- Exports an object that holds information about the status of the iteration (see Section 6.1.3).
- Supports range attributes to iterate over a subset of the original collection (see Section 6.1.4).
- Exposes an interface as well as a base implementation class.
Developers can easily implement collaborating subtags as well as their own iteration tags (see Section 6.1.5).

`<c:forEach>` is the base iteration action in JSTL. It handles the most common iteration cases conveniently. Other iteration actions are also provided in the tag library to support specific, specialized functionality not handled by `<c:forEach>` (e.g. `<c:forEachTokens>` (Section 6.3) and `<x:forEach>` (Section 12.6)). Developers can also easily extend the behavior of this base iteration action to customize it according to an application's specific needs.

6.1.1 Collections of Objects to Iterate Over

A large number of *collection* types are supported by `<c:forEach>`, including all implementations of `java.util.Collection` (includes `List`, `LinkedList`, `ArrayList`, `Vector`, `Stack`, `Set`), and `java.util.Map` (includes `HashMap`, `Hashtable`, `Properties`, `Provider`, `Attributes`).

Arrays of objects as well as arrays of primitive types (e.g. `int`) are also supported. For arrays of primitive types, the current item for the iteration is automatically wrapped with its standard wrapper class (e.g. `Integer` for `int`, `Float` for `float`, etc.).

Implementations of `java.util.Iterator` and `java.util.Enumeration` are supported as well but these must be used with caution. `Iterator` and `Enumeration` objects are not resettable so they should not be used within more than one iteration tag.

Deprecated: Finally, `java.lang.String` objects can be iterated over if the string represents a list of comma separated values (e.g. `"Monday,Tuesday,Wednesday,Thursday,Friday"`).¹

Absent from the list of supported types is `java.sql.ResultSet` (which includes `javax.sql.RowSet`). The reason for this is that the SQL actions described in Section 10.1 use the `javax.servlet.jsp.jstl.sql.Result` interface to access

1. The proper way to process strings of tokens is via `<c:forEachTokens>` or via functions `split` and `join`.

the data returned from an SQL query. Class `javax.servlet.jsp.jstl.sql.ResultSupport` (see Chapter 16 “Java APIs”) allows business logic developers to easily convert a `ResultSet` object into a `javax.servlet.jsp.jstl.sql.Result` object, making life much easier for a page author that needs to manipulate the data returned from a SQL query.

6.1.2 Map

If the `items` attribute is of type `java.util.Map`, then the current item will be of type `java.util.Map.Entry`, which has the following two properties:

- **key** - the key under which this item is stored in the underlying `Map`
- **value** - the value that corresponds to this key

The following example uses `<c:forEach>` to iterate over the values of a `Hashtable`:

```
<c:forEach var="entry" items="${myHashtable}">
  Next element is ${entry.value}/>
</c:forEach>
```

6.1.3 Iteration Status

`<c:forEach>` also exposes information relative to the iteration taking place. The example below creates an HTML table with the first column containing the position of the item in the collection, and the second containing the name of the product.

```
<table>
  <c:forEach var="product" items="${products}"
    varStatus="status">
    <tr>
      <td>${status.count}</td>
      <td>${product.name}</td>
    </tr>
  </c:forEach>
</table>
```

See Chapter 16 “Java APIs” for details on the `LoopTagStatus` interface exposed by the `varStatus` attribute.

6.1.4 Range Attributes

A set of range attributes is available to iterate over a subset of the collection of items. The `begin` and `end` indices can be specified, along with a `step`. If the `items` attribute is not specified, then the value of the current item is set to the integer value of the current index. In this example, `i` would take values from 100 to 110 (inclusive).

```
<c:forEach var="i" begin="100" end="110">
    ${i}
</c:forEach>
```

6.1.5 Tag Collaboration

Custom actions give developers the power to provide added functionality to a JSP application without requiring the page author to use Java code. In this example, an item of the iteration is processed differently depending upon whether it is an odd or even element.

```
<c:forEach var="product" items="${products}" varStatus="status">
    <c:choose>
        <c:when test="${status.count % 2 == 0}">
            even item
        </c:when>
        <c:otherwise>
            odd item
        </c:otherwise>
    </c:choose>
</c:forEach>
```

If this type of processing is common, it could be worth providing custom actions that yield simpler code, as shown below.

```
<c:forEach var="product" items="${products}">
    <acme:even>
        even item
    </acme:even>
    <acme:odd>
        odd item
    </acme:odd>
</c:forEach>
```

In order to make this possible, custom actions like `<acme:odd>` and `<acme:even>` leverage the fact that `<c:forEach>` supports implicit collaboration via the interface `LoopTag` (see Chapter 16 “Java APIs”).

The fact that `<c:forEach>` exposes an interface also means that other actions with iterative behavior can be developed using the same interface and will collaborate in the same manner with nested tags. Class `LoopTagSupport` (see Chapter 16 “Java APIs”) provides a solid base for doing this.

6.1.6 Deferred Values

As of JSP 2.1, the new unified Expression Language supports the concept of deferred expressions (using the `#{}` syntax), i.e. expressions whose evaluation is deferred to application code (as opposed to immediate evaluation (using the `${}` syntax) where the expression is evaluated immediately by the container). Deferred expressions are used mostly with JavaServer Faces, a component-based UI framework for the webtier.

In order for JSTL iteration tags to support nested actions that access the iteration variable as a deferred-value, the `items` attribute must be specified as a deferred-value as well.

For example:

```
<c:forEach var="child" items="#{customer.children}">
  <h:inputText value="#{child.name}" />
</c:forEach>
```

Because a deferred-value is specified for `items`, the iteration tag has access to the original expression and can make the iteration variable available as a deferred-value with the proper index into the `items` collection. This deferred value can then be evaluated properly by the code associated with the `<h:inputText>` component.

6.2 <c:forEach>

Repeats its nested body content over a collection of objects, or repeats it a fixed number of times.

Syntax

Syntax 1: Iterate over a collection of objects

```
<c:forEach [var="varName"] items="collection"
           [varStatus="varStatusName"]
           [begin="begin"] [end="end"] [step="step"]>
```

body content

```
</c:forEach>
```

Syntax 2: Iterate a fixed number of times

```
<c:forEach [var="varName"]
           [varStatus="varStatusName"]
           begin="begin" end="end" [step="step"]>
```

body content

```
</c:forEach>
```

Body Content

JSP. As long as there are items to iterate over, the body content is processed by the JSP container and written to the current `JspWriter`.

Attributes

Name	Dyn	Type	Description
var	false	String	Name of the exported scoped variable for the current item of the iteration. This scoped variable has nested visibility. Its type depends on the object of the underlying collection.
items	true	Any of the supported types described in Section "Description" below.	Collection of items to iterate over.
varStatus	false	String	Name of the exported scoped variable for the status of the iteration. Object exported is of type <code>javax.servlet.jsp.jstl.core.LoopTagStatus</code> . This scoped variable has nested visibility.
begin	true	int	<u>If items specified:</u> Iteration begins at the item located at the specified index. First item of the collection has index 0. <u>If items not specified:</u> Iteration begins with index set at the value specified.
end	true	int	<u>If items specified:</u> Iteration ends at the item located at the specified index (inclusive). <u>If items not specified:</u> Iteration ends when index reaches the value specified.
step	true	int	Iteration will only process every step items of the collection, starting with the first one.

Constraints

- If specified, begin must be ≥ 0 .
- If end is specified and it is less than begin, the loop is simply not executed.
- If specified, step must be ≥ 1

Null & Error Handling

- If items is null, it is treated as an empty collection, i.e., no iteration is performed.

Description

If `begin` is greater than or equal to the size of `items`, no iteration is performed.

Collections Supported & Current Item

The data types listed below must be supported for `items`. With syntax 1, each object exposed via the `var` attribute is of the type of the object in the underlying collection, except for arrays of primitive types and maps (see below). With syntax 2, the object exported is of type `Integer`.

- Arrays

This includes arrays of objects as well as arrays of primitive types. For arrays of primitive types, the current item for the iteration is automatically wrapped with its standard wrapper class (e.g. `Integer` for `int`, `Float` for `float`, etc.)

Elements are processed in their indexing order.

- Implementation of `java.util.Collection`.

An `Iterator` object is obtained from the collection via the `iterator()` method, and the items of the collection are processed in the order returned by that `Iterator` object.

- Implementation of `java.util.Iterator`.

Items of the collection are processed in the order returned by the `Iterator` object.

- Implementation of `java.util.Enumeration`.

Items of the collection are processed in the order returned by the `Enumeration` object.

- Implementation of `java.util.Map`

The object exposed via the `var` attribute is of type `Map.Entry`.

A `Set` view of the mappings is obtained from the `Map` via the `entrySet()` method, from which an `Iterator` object is obtained via the `iterator()` method. The items of the collection are processed in the order returned by that `Iterator` object.

- String

The string represents a list of comma separated values, where the comma character is the token delimiter. Tokens are processed in their sequential order in the string.

Deferred Values

When a deferred-value is specified for the `items` attribute, the tag handler now adds at each iteration a mapping for the `var` attribute into the EL `VariableMapper`.

Below are some implementation notes illustrating how an iteration tag handler may process a deferred-value specified for the `items` attribute.

```
doStartTag()
...
// 'items' is a deferred-value
// Get the current EL VariableMapper
VariableMapper vm =
    jspContext.getELContext().getVariableMapper();
// Create an expression to be assigned to the variable
// specified in the 'var' attribute.
// 'index' is an iteration counter kept by the tag handler.
myimpl.IndexedExpression expr =
    new myimpl.IndexExpression(getItems(), index);
// Assign the expression to the variable specified in
// the 'var' attribute, so any reference to that variable
// will be replaced by the expression in subsequent EL
// evaluations.
oldMapping = vm.setVariable(getVar(), expr);
...

doEndTag()
...
// restore the original state of the VariableMapper
jspContext.getELContext().getVariableMapper().setVariable(
    getVar(), oldMapping);
...
```

The number of items referred to by the `items` attribute must be the same when Faces creates the component tree and when JSP executes the iteration tag. Undefined behavior will result if this is not the case.

6.3 <c:forTokens>

Iterates over tokens, separated by the supplied delimiters.

Syntax

```
<c:forTokens items="stringOfTokens" delims="delimiters"
    [var="varName"]
    [varStatus="varStatusName"]
    [begin="begin"] [end="end"] [step="step"]>
    body content
</c:forTokens>
```

Body Content

JSP. As long as there are items to iterate over, the body content is processed by the JSP container and written to the current `JspWriter`.

Attributes

Name	Dynamic	Type	Description
var	false	String	Name of the exported scoped variable for the current item of the iteration. This scoped variable has nested visibility.
items	true	String	String of tokens to iterate over.
delims	true	String	The set of delimiters (the characters that separate the tokens in the string).
varStatus	false	String	Name of the exported scoped variable for the status of the iteration. Object exported is of type <code>javax.servlet.jsp.jstl.core.LoopTagStatus</code> . This scoped variable has nested visibility.
begin	true	int	Iteration begins at the token located at the specified index. First token has index 0.
end	true	int	Iteration ends at the token located at the specified index (inclusive).
step	true	int	Iteration will only process every <code>step</code> tokens of the string, starting with the first one.

Constraints

- If specified, `begin` must be ≥ 0 .
- If `end` is specified and it is less than `begin`, the loop is simply not executed.
- If specified, `step` must be ≥ 1

Null & Error Handling

- If `items` is null, it is treated as an empty collection, i.e., no iteration is performed.
- If `delims` is null, `items` is treated as a single monolithic token. Thus, when `delims` is null, `<c:forTokens>` iterates exactly zero (if `items` is also null) or one time.

Description

The tokens of the string are retrieved using an instance of `java.util.StringTokenizer` with arguments `items` (the string to be tokenized) and `delims` (the delimiters).

Delimiter characters separate tokens. A token is a maximal sequence of consecutive characters that are not delimiters.

Deferred Values

See Section "Deferred Values" for `<c:forEach>`. Same comments apply here.

URL Related Actions

core tag library

Linking, importing, and redirecting to URL resources are features often needed in JSP pages. Since dealing with URLs can often be tricky, JSTL offers a comprehensive suite of URL-related actions to simplify these tasks.

7.1 Hypertext Links

By using the HTML <A> element, a page author can set a hypertext link as follows:

```
<a href="/register.jsp">Register</a>
```

If the link refers to a local resource and session tracking is enabled, it is necessary to *rewrite* the URL so session tracking can be used as a fallback, should cookies be disabled at the client.

Moreover, if query string parameters are added to the URL, it is important that they be properly URL encoded. *URL encoding* refers to the process of encoding special characters in a string, according to the rules defined in RFC 2396. For example, a space must be encoded in a URL string as a '+':

```
http://acme.com/app/choose?country=Dominican+Republic
```

As shown in the following example, the combination of the `<c:url>` and `<c:param>` actions takes care of all issues related to URL rewriting and encoding: `<c:url>` rewrites a URL if necessary, and `<c:param>` transparently encodes query string parameters (both name and value).

```
<c:url value="http://acme.com/exec/register" var="myUrl">
  <c:param name="name" value="{param.name}" />
  <c:param name="country" value="{param.country}" />
</c:url>
<a href='{<c:out value="{myUrl}" />'}>Register</a>
```

Another important feature of `<c:url>` is that it transparently prepends the context path to context-relative URLs. Assuming a context path of `/foo`, the following example

```
<c:url value="/ads/logo.html" />
```

yields the URL `/foo/ads/logo.html`.

7.2 Importing Resources

There is a wide variety of resources that a page author might be interested in including and/or processing within a JSP page. For instance, the example below shows how the content of the README file at the FTP site of acme.com could be included within the page.

```
<c:import url="ftp://ftp.acme.com/README" />
```

In the JSP specification, a `<jsp:include>` action provides for the inclusion of static and dynamic resources located in the same context as the current page. This is a very convenient feature that is widely used by page authors.

However, `<jsp:include>` falls short in flexibility when page authors need to get access to resources that reside outside of the web application. In many situations, page authors have the need to import the content of Internet resources specified via an absolute URL. Moreover, as sites grow in size, they may have to be implemented as a set of web applications where importing resources across web applications is a requirement.

`<jsp:include>` also falls short in efficiency when the content of the imported resource is used as the source for a companion process/transformation action, because unnecessary buffering occurs. In the example below, the `<acme:transform>` action uses the content of the included resource as the input of its transformation. `<jsp:include>` reads the content of the response, writes it to the body content of the enclosing `<acme:transform>`, which then re-reads the exact same content. It would be more efficient if `<acme:transform>` could access the input source directly and avoid the buffering involved in the body content of `<acme:transform>`.

```
<acme:transform>
  <jsp:include page="/exec/employeesList"/>
</acme:transform>
```

The main motivation behind `<c:import>` is to address these shortcomings by providing a simple, straightforward mechanism to access resources that can be specified via a URL. If accessing a resource requires specifying more arguments, then a protocol specific action (e.g. an `<http>` action) should be used for that purpose. JSTL does not currently address these protocol-specific elements but may do so in future releases.

7.2.1 URL

The `url` attribute is used to specify the URL of the resource to import. It can either be an absolute URL (i.e. one that starts with a protocol followed by a colon), a relative URL used to access a resource within the same context, or a relative URL used to access a resource within a foreign context. The three different types of URL are shown in the sample code below.

```
<%-- import a resource with an absolute URL --%>
<c:import url="http://acme.com/exec/customers?country=Japan/">

<%-- import a resource with a relative URL - same context --%>
<c:import url="/copyright.html"/>

<%-- import a resource with a relative URL - foreign context --%>
<c:import url="/logo.html" context="/master"/>
```

7.2.2 Exporting an object: String or Reader

By default, the content of an imported resource is included inline into the JSP page.

It is also possible to make the content of the resource available in two different ways: as a `String` object (attribute `var`), or as a `Reader` object (attribute `varReader`). `Process` or `Transform` tags can then access the resource's content through that exported object as shown in the following example.

```
<%-- Export the content of the URL resource as a String --%>
<c:import url="http://acme.com/exec/customers?country=USA"
         var="customers"/>
<acme:notify in="${customers}"/>

<%-- Export the content of the URL resource as a Reader --%>
<c:import url="http://acme.com/exec/customers?country=USA"
         varReader="customers">
  <acme:notify in="${customers}"/>
</c:import>
```

Exporting the resource as a `String` object caches its content and makes it reusable.

If the imported content is large, some performance benefits may be achieved by exporting it as a `Reader` object since the content can be accessed directly without any buffering. However, the performance benefits are not guaranteed since the reader's support is implementation dependent. It is also important to note that the `varReader` scoped variable has nested visibility; it can only be accessed within the body content of `<c:import>`.

7.2.3 URL Encoding

Just as with `<c:url>`, `<c:param>` can be nested within `<c:import>` to encode query string parameters.

7.2.4 Networking Properties

If the web container executes behind a firewall, some absolute URL resources may be inaccessible when using `<c:import>`. To provide access to these resources, the JVM of the container should be started with the proper networking properties (e.g. `proxyHost`, `proxyPort`). More details can be found in the Java 2 SDK, Standard Edition Documentation (Networking Features — Networking Properties).

7.3 HTTP Redirect

`<c:redirect>` completes the arsenal of URL related actions to support an HTTP redirect to a specific URL. For example:

```
<c:redirect url="http://acme.com/register"/>
```

7.4 <c:import>

Imports the content of a URL-based resource.

Syntax

Syntax 1: Resource content inlined or exported as a String object

```
<c:import url="url" [context="context"]  
    [var="varName"] [scope="{page|request|session|application}"]  
    [charEncoding="charEncoding"]>  
    optional body content for <c:param> subtags  
</c:import>
```

Syntax 2: Resource content exported as a Reader object

```
<c:import url="url" [context="context"]  
    varReader="varReaderName"  
    [charEncoding="charEncoding"]>  
    body content where varReader is consumed by another action  
</c:import>
```

Body Content

JSP. The body content is processed by the JSP container and the result is written to the current `JspWriter`.

Attributes

Name	Dynamic	Type	Description
url	true	String	The URL of the resource to import.
context	true	String	Name of the context when accessing a relative URL resource that belongs to a foreign context.
var	false	String	Name of the exported scoped variable for the resource's content. The type of the scoped variable is <code>String</code> .

Name	Dynamic	Type	Description
scope	false	String	Scope for var.
charEncoding	true	String	Character encoding of the content at the input resource.
varReader	false	String	Name of the exported scoped variable for the resource's content. The type of the scoped variable is Reader.

Null & Error Handling

- If `url` is null, empty, or invalid, a `JspException` is thrown.
- If `charEncoding` is null or empty, it is considered missing.
- For internal resources:
 - a) If a `RequestDispatcher` cannot be found for the resource, throw a `JspException` with the resource path included in the message.
 - b) Otherwise, if the `RequestDispatcher.include()` method throws an `IOException` or `RuntimeException`, throw a `JspException` with the caught exception as the root cause.
 - c) Otherwise, if the `RequestDispatcher.include()` method throws a `ServletException`, look for a root cause.
 - If there's a root cause, throw a `JspException` with the root cause message included in the message and the original root cause as the `JspException` root cause.
 - Otherwise, same as b).
 - d) Otherwise, if the resource invoked through `RequestDispatcher.include()` method sets a response status code other than 2xx (i.e. 200-299, the range of success codes in the HTTP response codes), throw a `JspException` with the path and status code in the message.
- For external resources
 - If the `URLConnection` class throws an `IOException` or a `RuntimeException`, throw a `JspException` with the message from the original exception included in the message and the original exception as the root cause.
 - For an `HttpURLConnection`, if the response status code is other than 2xx (i.e. 200-299, the range of success codes in the HTTP response codes), throw a `JspException` with the path and status code in the message.

Description

Using syntax 1, the content of the resource is by default written to the current `JspWriter`. If `var` is specified, the content of the resource is instead exposed as a `String` object.

Using syntax 2, the content of the resource is exported as a `Reader` object. The use of the `varReader` attribute comes with some restrictions.

It is the responsibility of the `<c:import>` tag handler to ensure that if it exports a `Reader`, this `Reader` is properly closed by the time the end of the page is reached¹. Because of this requirement, JSTL defines the exported `Reader` as having nested visibility: it may not currently be accessed after the end-tag for the `<c:import>` action². Implementations that use JSP 1.2 tag-extension API will likely need to implement `TryCatchFinally` with their `<c:import>` tag handlers and close the exported `Reader` in `doFinally()`.

It is also illegal to use nested `<c:param>` tags with syntax 2. Since the exposed `Reader` must be immediately available to the action's body, the connection to the resource must be established within the start element of the action. It is therefore impossible for nested `<c:param>` actions to modify the URL of the resource to be accessed, thus their illegality with syntax 2. In such a situation, `<c:url>` may be used to build a URL with query string parameters³. `<c:import>` will remove any session id information if necessary (see Section 7.5).

Character Encoding

`<c:import>` exposes a `String` or `Reader` object, both of which are sequences of text characters. It is possible to specify the character encoding of the input resource via the `charEncoding` attribute. The values supported for `charEncoding` are the same as the ones supported by the constructor of the Java class `InputStreamReader`.

If the character encoding is not specified, the following rules apply:

- If `URLConnection.getContentType()` has a non-null result, the character set is retrieved from `URLConnection.getContentType()` by parsing this method's result according to RFC 2045 (section 5.1).
- If this method's result does not include a character set, or if the character set causes `InputStreamReader(InputStream in, String charsetName)` to throw an `UnsupportedEncodingException`, then use ISO-8859-1 (which is the default value of `charset` for the `contentType` attribute of the JSP page directive).

1. If the responsibility was left to the consumer tag, this could lead to resource leaks (e.g. connection left open, memory space for buffers) until garbage collection is activated. This is because a consumer tag might not close the `Reader`, or because the page author might remove the consumer tag while leaving inadvertently the `<c:import>` tag in the page.
2. This restriction could eventually be lifted when the JSP spec supports the notion of page events that actions could register to. On a `pageExit` event, an `<c:import>` tag would then simply release its resources if it had not already been done, removing the requirement for nested visibility.
3. It is however important to note that using the output of `<c:url>` as the `url` attribute value of `<c:import>` won't work for context relative URLs (URLs that start with a `'/'`). That's because in those cases `<c:url>` prepends the context path to the URL value.

Note that the `charEncoding` attribute should normally only be required when accessing absolute URL resources where the protocol is not HTTP, and where the encoding is not ISO-8859-1.

Also, when dealing with relative URLs and the HTTP protocol, if the target resource declares a content encoding but proceeds to write a character invalid in that encoding, the treatment of that character is undefined.

Relative and Absolute URLs

The exact semantics of the `<c:import>` tag depends on what type of URL is being accessed.

Relative URL – same context

This is processed in the exact same way as the include action of the JSP specification (`<jsp:include>`). The resource belongs to the same web application as the including page and it is specified as a relative URL.

As specified in the JSP specification, a relative URL may either be a context-relative path, or a page-relative path. A *context-relative path* is a path that starts with a `"/"`. It is to be interpreted as relative to the application to which the JSP page belongs. A *page-relative path* is a path that does not start with a `"/"`. It is to be interpreted as relative to the current JSP page, as defined by the rules of inclusion of the `<jsp:include>` action in the JSP specification.

The semantics of importing a resource specified with a relative URL in the same context are the same as an include performed by a `RequestDispatcher` as defined in the Servlet specification. This means that the whole environment of the importing page is available to the target resource (including request and session attributes, as well as request parameters of the importing page).

Relative URL – foreign context

The resource belongs to a foreign context (web application) hosted under the same container as the importing page. The context name for the resource is specified via attribute `context`.

The relative URL must be context-relative (i.e. must start with a `"/"`) since the including page does not belong to the same context. Similarly, the context name must also start with a `"/"`.

The semantics of importing a resource specified with a relative URL in a foreign context are the same as an include performed by a `RequestDispatcher` on a foreign context as defined in the Servlet specification. This means that only the request environment of the importing page is available to the target resource.

It is important to note that importing resources in foreign contexts may not work in all containers. A security conscious environment may not allow access to foreign contexts. As a workaround, a foreign context resource can also be accessed using an absolute URL. However, it is more efficient to use a relative URL because the resource is then accessed using `RequestDispatcher` defined by the Servlet API.

Relative URL – query parameter aggregation rules

The query parameter aggregation rules work the same way they do with `<jsp:include>`; the original parameters are augmented with the new parameters, with new values taking precedence over existing values when applicable. The scope of the new parameters is the import call; the new parameters (and values) will not apply after the import. The behavior is therefore the same as the one defined for the `include()` method of `RequestDispatcher` in the Servlet specification.

Absolute URL

Absolute URLs are retrieved as defined by the `java.net.URL` and `java.net.URLConnection` classes. The `<c:import>` action therefore supports at a minimum the protocols offered in the J2SE 1.2 platform for absolute URLs. More protocols can be available to a web application, but this will depend on the the class libraries made available to the web application by the platform the container runs on.

When using an absolute URL to import a resource, none of the current execution environment (e.g. request and session attributes) is made available to the target resource, even if that absolute URL resolves to the same host and context path. Therefore, the request parameters of the importing page are not propagated to the target absolute URL.

When importing an external resource using the HTTP protocol, `<c:import>` behaves according to the semantics of a GET request sent via the `java.net.HttpURLConnection` class, with `setFollowRedirects` set to true.

7.5 <c:url>

Builds a URL with the proper rewriting rules applied.

Syntax

Syntax 1: Without body content

```
<c:url value="value" [context="context"]  
      [var="varName"] [scope="{page|request|session|application}"]/>
```

Syntax 2: With body content to specify query string parameters

```
<c:url value="value" [context="context"]  
      [var="varName"] [scope="{page|request|session|application}"]>  
  <c:param> subtags  
</c:url>
```

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

Attributes

Name	Dynamic	Type	Description
value	true	String	URL to be processed.
context	true	String	Name of the context when specifying a relative URL resource that belongs to a foreign context.
var	false	String	Name of the exported scoped variable for the processed url. The type of the scoped variable is <code>String</code> .
scope	false	String	Scope for var.

Description

<c:url> processes a URL and rewrites it if necessary. Only relative URLs are rewritten. Absolute URLs are not rewritten to prevent situations where an external URL could be rewritten and expose the session ID. A consequence is that if a page author wants session tracking, only relative URLs must be used with <c:url> to link to local resources.

The rewriting must be performed by calling method `encodeURL()` of the Servlet API.

If the URL contains characters that should be encoded (e.g. space), it is the user's responsibility to encode them.

The URL must be either an absolute URL starting with a scheme (e.g. "http://server/context/page.jsp") or a relative URL as defined by JSP 1.2 in JSP.2.2.1 "Relative URL Specification". As a consequence, an implementation must prepend the context path to a URL that starts with a slash (e.g. "/page2.jsp") so that such URLs can be properly interpreted by a client browser.

Specifying a URL in a foreign context is possible through the `context` attribute. The URL specified must start with a `/` (since this is a context-relative URL). The context name must also start with a `/` (since this is a standard way to identify a context).

Because the URL built by this action may include session information as a path parameter, it may fail if used with `RequestDispatcher` of the Servlet API. The consumer of the rewritten URL should therefore remove the session ID information prior to calling `RequestDispatcher`. This situation is properly handled in `<c:import>`.

By default, the result of the URL processing is written to the current `JspWriter`. It is also possible to export the result as a JSP scoped variable defined via the `var` and `scope` attributes.

`<c:param>` subtags can also be specified within the body of `<c:url>` for adding to the URL query string parameters, which will be properly encoded if necessary.

7.6 <c:redirect>

Sends an HTTP redirect to the client.

Syntax

Syntax 1: Without body content

```
<c:redirect url="value" [context="context"]/>
```

Syntax 2: With body content to specify query string parameters

```
<c:redirect url="value" [context="context"]>
  <c:param> subtags
</c:redirect>
```

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

Attributes

Name	Dyn	Type	Description
url	true	String	The URL of the resource to redirect to.
context	true	String	Name of the context when redirecting to a relative URL resource that belongs to a foreign context.

Description

This action sends an HTTP redirect response to the client and aborts the processing of the page by returning `SKIP_PAGE` from `doEndTag()`.

The URL must be either an absolute URL starting with a scheme (e.g. "http://server/context/page.jsp") or a relative URL as defined by JSP 1.2 in JSP.2.2.1 "Relative URL Specification". As a consequence, an implementation must prepend the context path to a URL that starts with a slash (e.g. "/page2.jsp") if the behavior is implemented using the `HttpServletResponse.sendRedirect()` method.

Redirecting to a resource in a foreign context is possible through the `context` attribute. The URL specified must must start with a "/" (since this is a context-relative URL). The context name must also start with a "/" (since this is a standard way to identify a context).

<c:redirect> follows the same rewriting rules as defined for <c:url>.

7.7

<c:param>

Adds request parameters to a URL. Nested action of <c:import>, <c:url>, <c:redirect>.

Syntax

Syntax 1: Parameter value specified in attribute "value"

```
<c:param name="name" value="value"/>
```

Syntax 2: Parameter value specified in the body content

```
<c:param name="name">
```

```
    parameter value
```

```
</c:param>
```

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

Attributes

Name	Dynamic	Type	Description
name	true	String	Name of the query string parameter.
value	true	String	Value of the parameter.

Null & Error Handling

- If name is null or empty, no action is performed. It is not an error.
- If value is null, it is processed as an empty value.

Description

Nested action of <c:import>, <c:url>, <c:redirect> to add request parameters to a URL. <c:param> also URL encodes both name and value.

One might argue that this is redundant given that a URL can be constructed to directly specify the query string parameters. For example:

```
<c:import url="/exec/doIt">
  <c:param name="action" value="register"/>
</c:import>
```

is the same as:

```
<c:import url="/exec/doIt?action=register"/>
```

It is indeed redundant, but is consistent with `<jsp:include>`, which supports nested `<jsp:param>` sub-elements. Moreover, it has been designed such that the attributes `name` and `value` are automatically URL encoded.

Internationalization (i18n) Actions

I18n-capable formatting tag library

With the explosion of application development based on web technologies, and the deployment of such applications on the Internet, applications must be able to adapt to the languages and formatting conventions of their clients. This means that page authors must be able to tailor page content according to the client's language and cultural formatting conventions. For example, the number 345987.246 should be formatted as 345 987,246 for France, 345.987,246 for Germany, and 345,987.246 for the U.S.

The process of designing an application (or page content) so that it can be adapted to various languages and regions without requiring any engineering changes is known as *internationalization*, or i18n for short. Once a web application has been internationalized, it can be adapted for a number of regions or languages by adding locale-specific components and text. This process is known as *localization*.

There are two approaches to internationalizing a web application:

- Provide a version of the JSP pages in each of the target locales and have a controller servlet dispatch the request to the appropriate page (depending on the requested locale). This approach is useful if large amounts of data on a page or an entire web application need to be internationalized.
- Isolate any locale-sensitive data on a page (such as error messages, string literals, or button labels) into resource bundles, and access the data via i18n actions, so that the corresponding translated message is fetched automatically and inserted into the page.

The JSTL i18n-capable formatting actions support either approach: They assist page authors with creating internationalized page content that can be localized into any locale available in the JSP container (this addresses the second approach), and allow various data elements such as numbers, currencies, dates and times to be formatted and parsed in a locale-sensitive or customized manner (this may be used in either approach).

JSTL's i18n actions are covered in this chapter. The formatting actions are covered in Chapter 9.

8.1 Overview

There are three key concepts associated with internationalization: locale, resource bundle, and basename.

A *locale* represents a specific geographical, political, or cultural region. A locale is identified by a language code, along with an optional country code¹.

- Language code

The language code is the lower-case two-letter code as defined by ISO-639 (e.g. “ca” for Catalan, “zh” for Chinese). The full list of these codes can be found at a number of sites, such as:

<http://www.ics.uci.edu/pub/ietf/http/related/iso639.txt>

- Country code

The country code is the upper-case two-letter code as defined by ISO-3166 (e.g. “IT” for Italy, “CR” for Costa Rica). The full list of these codes can be found at a number of sites, such as:

http://www.chemie.fu-berlin.de/diverse/doc/ISO_3166.html.

Note that the semantics of locales in JSTL are the same as the ones defined by the class `java.util.Locale`. A consequence of this is that, as of J2SE 1.4, new language codes defined in ISO 639 (e.g. `he`, `yi`, `id`) will be returned as the old codes (e.g. `iw`, `ji`, `in`). See the documentation of the `java.util.Locale` class for more details.

A *resource bundle* contains locale-specific objects. Each message in a resource bundle is associated with a key. Since the set of messages contained in a resource bundle can be localized for many locales, the resource bundles that translate the same set of messages are identified by the same *basename*. A specific resource bundle is therefore uniquely identified by combining its basename with a locale.

For instance, a web application could define the registration resource bundles with basename `Registration` to contain the messages associated with the registration portion of the application. Assuming that French and English are the only languages supported by the application, there will be two resource bundles:

`Registration_fr` (French language) and `Registration_en` (English language). Depending on the locale associated with the client request, the key “greeting” could be mapped to the message “Bonjour” (French) or “Hello” (English).

1. A variant code may also be specified, although rarely used.

8.1.1 <fmt:message>

It is possible to internationalize the JSP pages of a web application simply by using the <fmt:message> action as shown below:

```
<fmt:message key="greeting"/>
```

In this case, <fmt:message> leverages the default i18n localization context, making it extremely simple for a page author to internationalize JSP pages.

<fmt:message> also supports compound messages, i.e. messages that contain one or more variables. Parameter values for these variables may be supplied via one or more <fmt:param> subtags (one for each parameter value). This procedure is referred to as *parametric replacement*.

```
<fmt:message key="athletesRegistered">
  <fmt:param>
    <fmt:formatNumber value="${athletesCount}"/>
  </fmt:param>
</fmt:message>
```

Depending on the locale, this example could print the following messages:

```
french: Il y a 10 582 athletes enregistres.
english: There are 10,582 athletes registered.
```

8.2 I18n Localization Context

I18n actions use an i18n localization context to localize their data. An i18n localization context contains two pieces of information: a resource bundle and the locale for which the resource bundle was found.

An i18n action determine its i18n localization context in one of several ways, which are described in order of precedence:

- <fmt:message> bundle attribute

If attribute bundle is specified in <fmt:message>, the i18n localization context associated with it is used for localization.

- <fmt:bundle> action

If `<fmt:message>` actions are nested inside a `<fmt:bundle>` action, the i18n localization context of the enclosing `<fmt:bundle>` action is used for localization. The `<fmt:bundle>` action determines the resource bundle of its i18n localization context according to the resource bundle determination algorithm in Section 8.3, using the `basename` attribute as the resource bundle `basename`.

- I18n default localization context

The i18n localization context whose resource bundle is to be used for localization is specified via the `javax.servlet.jsp.jstl.fmt.localizationContext` configuration setting (see Section 8.11.3). If the configuration setting is of type `LocalizationContext` (see Chapter 16 “Java APIs”) its resource bundle component is used for localization. Otherwise, the configuration setting is of type `String`, and the action establishes its own i18n localization context whose resource bundle component is determined according to the resource bundle determination algorithm in Section 8.3, using the configuration setting as the resource bundle `basename`.

The example below shows how the various localization contexts can be established to define the resource bundle used for localization.

```
<%-- Use configuration setting --%>
<fmt:message key="Welcome" />

<fmt:setBundle basename="Errors" var="errorBundle" />
<fmt:bundle basename="Greetings">
  <%-- Localization context established by
        parent <fmt:bundle> tag --%>
  <fmt:message key="Welcome" />
  <%-- Localization context established by attribute bundle --%>
  <fmt:message key="WrongPassword" bundle="{errorBundle}" />
</fmt:bundle>
```

8.2.1 Preferred Locales

If the resource bundle of an i18n localization context needs to be determined, it is retrieved from the web application’s resources according to the algorithm described in section Section 8.3. This algorithm requires two pieces of information: the `basename` of the resource bundle (as described in the previous section) and the preferred locales.

The method for setting the preferred locales is characterized as either application-based or browser-based.

Application-based locale setting has priority over browser-based locale setting. In this mode, the locale is set via the `javax.servlet.jsp.jstl.fmt.locale` configuration setting (see Section 8.11.1). Setting the locale this way is useful in situations where an application lets its users pick their preferred locale and then sets the scoped variable accordingly. This may also be useful in the case where a client's preferred locale is retrieved from a database and installed for the page using the `<fmt:setLocale>` action.

The `<fmt:setLocale>` action may be used to set the `javax.servlet.jsp.jstl.fmt.locale` configuration variable as follows:

```
<fmt:setLocale value="en_US" />
```

In the *browser-based* locale setting, the client determines via its browser settings which locale(s) should be used by the web application. The action retrieves the client's locale preferences by calling `ServletRequest.getLocales()` on the incoming request. This returns a list of the locales (in order of preference) that the client wants to use.

Whether application- or browser-based locale setting is used, an ordered list of preferred locales is fed into the algorithm described in section Section 8.3 to determine the resource bundle for an i18n localization context.

8.3 Determinining the Resource Bundle for an i18n Localization Context

Given a basename and an ordered set of preferred locales, the resource bundle for an i18n localization context is determined according to the algorithm described in this section.

This algorithm is also exposed as a general convenience method in the `LocaleSupport` class (see Chapter 16 “Java APIs”) so that it may be used by any tag handler implementation that needs to produce localized messages. For example, this is useful for exception messages that are intended directly for user consumption on an error page.

8.3.1 Resource Bundle Lookup

Localization in JSTL is based on the same mechanisms offered in the J2SE platform. Resource bundles contain locale-specific objects, and when an i18n action requires a locale-specific resource, it simply loads it from the appropriate resource bundle.

The algorithm of Section 8.3.2 describes how the proper resource bundle is determined. This algorithm calls for a resource bundle lookup, where an attempt is made at fetching a resource bundle associated with a specific basename and locale.

JSTL leverages the semantics of the `java.util.ResourceBundle` method

```
getBundle(String basename, java.util.Locale locale)
```

for resource bundle lookup, with one important modification.

As stated in the documentation for `ResourceBundle`, a resource bundle lookup searches for classes and properties files with various suffixes on the basis of:

1. The specified locale
2. The current default locale as returned by `Locale.getDefault()`
3. The root resource bundle (basename)

In JSTL, the search is limited to the first level; i.e. the specified locale. Steps 2 and 3 are removed so that other locales may be considered before applying the JSTL fallback mechanism described in Section 8.3.2. Only if no fallback mechanism exists, or the fallback mechanism fails to determine a resource bundle, is the root resource bundle considered.

Resource bundles are therefore searched in the following order:

basename + "_" + language + "_" + country + "_" + variant
basename + "_" + language + "_" + country
basename + "_" + language

8.3.2 Resource Bundle Determination Algorithm

Notes:

- When there are multiple preferred locales, they are processed in the order they were returned by `ServletRequest.getLocales()`.
- The algorithm stops as soon as a resource bundle has been selected for the localization context.

Step 1: Find a match within the ordered set of preferred locales

A resource bundle lookup (see Section 8.3.1) is performed for each one of the preferred locales until a match is found. If a match is found, the locale that led to the match and the matched resource bundle are stored in the i18n localization context.

Step 2: Find a match with the fallback locale

A resource bundle lookup (see Section 8.3.1) is performed for the fallback locale specified in the `javax.servlet.jsp.jstl.fmt.fallbackLocale` configuration setting. If a match is found, the fallback locale and the matched resource bundle are stored in the i18n localization context.

If no match is found following the above two steps, an attempt is made to load the root resource bundle with the given basename. If such a resource bundle exists, it is used as the resource bundle of an i18n localization context that does not have any locale. Otherwise, the established i18n localization context contains neither a resource bundle nor a locale. It is then up to the i18n action relying on this i18n localization context for the localization of its data to take a proper corrective action.

It is important to note that this algorithm gives higher priority to a *language* match over an *exact* match that would have occurred further down the list of preferred locales. For example, if the browser-based locale settings are "en" and "fr_CA", with resource bundles "Messages_en" and "Messages_fr_CA", the Messages_en bundle will be selected as the resource bundle for the localization context.

The definition of a fallback locale along with its associated resource bundles is the only portable way a web application can ensure the proper localization of all its internationalized pages. The algorithm of this section never considers the default locale associated with the Java runtime of the container because this would result in a non-portable behavior.

The behavior is implementation-specific if the set of available resource bundles changes during execution of the page. Implementations may thus cache whatever information they deem necessary to improve the performance of the algorithm presented in this section.

8.3.3 Examples

The following examples demonstrate how the resource bundle is determined for an i18n localization context.

Example 1

Settings

Basename: Resources
Ordered preferred locales: en_GB, fr_CA
Fallback locale: fr_CA
Resource bundles: Resources_en, Resources_fr_CA

Algorithm Trace

Step 1: Find a match within the ordered set of preferred locales
en_GB match with Resources_en

Result

Resource bundle selected: Resources_en
Locale: en_GB

Example 2

Settings

Basename: Resources
Ordered preferred locales: de, fr
Fallback locale: en
Resource bundles: Resources_en

Algorithm Trace

Step 1: Find a match within the ordered set of preferred locales
de no match
fr no match
Step 2: Find a match with the fallback locale
en exact match with Resources_en

Result

Resource bundle selected: Resources_en
Locale: en

Example 3

Settings

Basename: Resources

Ordered preferred locales: ja, en_GB, en_US, en_CA, fr

Fallback locale: en

Resource bundles: Resources_en, Resources_fr, Resources_en_US

Algorithm Trace

Step 1: Find a match within the ordered set of preferred locales

ja	no match
en_GB	match with Resources_en

Result

Resource bundle selected: Resources_en

Locale: en_GB

Example 4

Settings

Basename: Resources

Ordered preferred locales: fr, sv

Fallback locale: en

Resource bundles: Resources_fr_CA, Resources_sv, Resources_en

Algorithm Trace

Step 1: Find a match within the ordered set of preferred locales

fr	no match
sv	match with Resources_sv

Result

Resource bundle selected: Resources_sv

Locale: sv

This example shows that whenever possible, a resource bundle for a specific language and country (Resources_fr_CA) should be backed by a resource bundle covering just the language (Resources_fr). If the country-specific differences of a language are too significant for there to be a language-only resource bundle, it is expected that clients will specify both a language and a country as their preferred language, in which case an exact resource bundle match will be found.

8.4 Response Encoding

Any i18n action that establishes a localization context is responsible for setting the response's locale of its page, unless the localization context that was established does not have any locale. This is done by calling method `ServletResponse.setLocale()` with the locale of the localization context. Unless a response character encoding has been explicitly defined by other JSP elements (or by direct calls to the Servlet API), calling `setLocale()` also sets the character encoding for the response (see the JSP and Servlet specifications for details).

This assumes that the response is buffered with a big enough buffer size, since `ServletResponse.setLocale()` must be called before `ServletResponse.getWriter()` in order for the specified locale to affect the construction of the writer.

More specifically, the response's `setLocale()` method is always called by the `<fmt:setLocale>` action (see Section 8.5). In addition, it is called by the following actions:

- Any `<fmt:bundle>` (see Section 8.6) and `<fmt:setBundle>` (see Section 8.7) action.
- Any `<fmt:message>` action that establishes an i18n localization context
- Any formatting action that establishes a formatting locale on its own (see Section 9.3).

After an action has called `ServletResponse.setLocale()`, if a session exists and has not been invalidated, it must determine the character encoding associated with the response locale (by calling `ServletResponse.getCharacterEncoding()`) and store it in the scoped variable `javax.servlet.jsp.jstl.fmt.request.charset` in session scope. This attribute may be used by the `<fmt:requestEncoding>` action (see Section 8.10) in a page invoked by a form included in the response to set the request charset to the same as the response charset. This makes it possible for the container to decode the form parameter values properly, since browsers typically encode form field values using the response's charset.

The rules related to the setting of an HTTP response character encoding, Content-Language header, and Content-Type header are clearly defined in the Servlet specification. To avoid any ambiguity, the JSTL and JSP specifications define behavior related to a response's locale and character encoding exclusively in terms of Servlet API calls.

It is therefore important to note that, as defined in the Servlet spec, a call to `ServletResponse.setLocale()` modifies the character encoding of the response only if it has not already been set explicitly by calls to `ServletResponse.setContentType()` (with `CHARSET` specified) or `ServletResponse.setCharacterEncoding()`.

Page authors should consult the JSP specification to understand how page directives related to locale and character encoding setting translate into Servlet API calls, and how they impact the final response settings.

8.5 <fmt:setLocale>

Stores the specified locale in the `javax.servlet.jsp.jstl.fmt.locale` configuration variable.

Syntax

```
<fmt:setLocale value="locale"
               [variant="variant"]
               [scope="{page|request|session|application}"]/>
```

Body Content

Empty.

Attributes

Name	Dynamic	Type	Description
value	true	String or <code>java.util.Locale</code>	A String value is interpreted as the printable representation of a locale, which must contain a two-letter (lower-case) language code (as defined by ISO-639), and may contain a two-letter (upper-case) country code (as defined by ISO-3166). Language and country codes must be separated by hyphen ('-') or underscore ('_').
variant	true	String	Vendor- or browser-specific variant. See the <code>java.util.Locale</code> javadocs for more information on variants.
scope	false	String	Scope of the <i>locale</i> configuration variable.

Null & Error Handling

- If `value` is null or empty, use the runtime default locale.

Description

The `<fmt:setLocale>` action stores the locale specified by the `value` attribute in the `javax.servlet.jsp.jstl.fmt.locale` configuration variable in the scope given by the `scope` attribute. If `value` is of type `java.util.Locale`, `variant` is ignored.

As a result of using this action, browser-based locale setting capabilities are disabled. This means that if this action is used, it should be declared at the beginning of a page, before any other i18n-capable formatting actions.

8.6 <fmt:bundle>

Creates an i18n localization context to be used by its body content.

Syntax

```
<fmt:bundle basename="basename"
             [prefix="prefix"]>
    body content
</fmt:bundle>
```

Body Content

JSP. The JSP container processes the body content and then writes it to the current `JspWriter`. The action ignores the body content.

Attributes

Name	Dynamic	Type	Description
basename	true	String	Resource bundle base name. This is the bundle's fully-qualified resource name, which has the same form as a fully-qualified class name, that is, it uses "." as the package component separator and does not have any file type (such as ".class" or ".properties") suffix.
prefix	true	String	Prefix to be prepended to the value of the message key of any nested <fmt:message> action.

Null & Error Handling

- If `basename` is null or empty, or a resource bundle cannot be found, the null resource bundle is stored in the i18n localization context.

Description

The <fmt:bundle> action creates an i18n localization context and loads its resource bundle into that context. The name of the resource bundle is specified with the `basename` attribute.

The specific resource bundle that is loaded is determined according to the algorithm presented in Section 8.3.2.

The scope of the i18n localization context is limited to the action's body content.

The `prefix` attribute is provided as a convenience for very long message key names. Its value is prepended to the value of the message key of any nested `<fmt:message>` actions.

For example, using the `prefix` attribute, the key names in:

```
<fmt:bundle basename="Labels">
  <fmt:message key="com.acme.labels.firstName"/>
  <fmt:message key="com.acme.labels.lastName"/>
</fmt:bundle>
```

may be abbreviated to:

```
<fmt:bundle basename="Labels" prefix="com.acme.labels.">
  <fmt:message key="firstName"/>
  <fmt:message key="lastName"/>
</fmt:bundle>
```

8.7 <fmt:setBundle>

Creates an i18n localization context and stores it in the scoped variable or the `javax.servlet.jsp.jstl.fmt.localizationContext` configuration variable.

Syntax

```
<fmt:setBundle basename="basename"
               [var="varName" ]
               [scope="{page|request|session|application}"] />
```

Body Content

Empty.

Attributes

Name	Dynamic	Type	Description
basename	true	String	Resource bundle base name. This is the bundle's fully-qualified resource name, which has the same form as a fully-qualified class name, that is, it uses "." as the package component separator and does not have any file type (such as ".class" or ".properties") suffix.
var	false	String	Name of the exported scoped variable which stores the i18n localization context of type <code>javax.servlet.jsp.jstl.fmt.LocalizationContext</code> .
scope	false	String	Scope of <code>var</code> or the localization context configuration variable.

Null & Error Handling

- If `basename` is null or empty, or a resource bundle cannot be found, the null resource bundle is stored in the i18n localization context.

Description

The `<fmt:setBundle>` action creates an i18n localization context and loads its resource bundle into that context. The name of the resource bundle is specified with the `basename` attribute.

The specific resource bundle that is loaded is determined according to the algorithm presented in Section 8.3.2.

The i18n localization context is stored in the scoped variable whose name is given by `var`. If `var` is not specified, it is stored in the `javax.servlet.jsp.jstl.fmt.localizationContext` configuration variable, thereby making it the new default i18n localization context in the given scope.

8.8 <fmt:message>

Looks up a localized message in a resource bundle.

Syntax

Syntax 1: without body content

```
<fmt:message key="messageKey"
             [bundle="resourceBundle"]
             [var="varName"]
             [scope="{page|request|session|application}"]/>
```

Syntax 2: with a body to specify message parameters

```
<fmt:message key="messageKey"
             [bundle="resourceBundle"]
             [var="varName"]
             [scope="{page|request|session|application}"]>
    <fmt:param> subtags
</fmt:message>
```

Syntax 3: with a body to specify key and optional message parameters

```
<fmt:message [bundle="resourceBundle"]
             [var="varName"]
             [scope="{page|request|session|application}"]>
    key
    optional <fmt:param> subtags
</fmt:message>
```

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

Attributes

Name	Dyn	Type	Description
key	true	String	Message key to be looked up.
bundle	true	LocalizationContext	Localization context in whose resource bundle the message key is looked up.
var	false	String	Name of the exported scoped variable which stores the localized message.
scope	false	String	Scope of var.

Constraints

- If `scope` is specified, `var` must also be specified.

Null & Error Handling

- If `key` is null or empty, the message is processed as if undefined; that is, an error message of the form "?????" is produced.
- If the i18n localization context that this action determines does not have any resource bundle, an error message of the form "???<key>???" is produced

Description

The `<fmt:message>` action looks up the localized message corresponding to the given message key.

The message key may be specified via the `key` attribute or from the tag's body content. If this action is nested inside a `<fmt:bundle>` action, and the parent `<fmt:bundle>` action contains a `prefix` attribute, the specified prefix is prepended to the message key.

`<fmt:message>` uses the resource bundle of the i18n localization context determined according to Section 8.2.

If the given key is not found in the resource bundle, or the i18n localization context does not contain any resource bundle, the result of the lookup is an error message of the form "???<key>???" (where `<key>` is the name of the undefined message key).

If the message corresponding to the given key is *compound*, that is, contains one or more variables, it may be supplied with parameter values for these variables via one or more `<fmt:param>` subtags (one for each parameter value). This procedure is referred to as *parametric replacement*. Parametric replacement takes place in the order of the `<fmt:param>` subtags.

In the presence of one or more `<fmt:param>` subtags, the message is supplied to the `java.text.MessageFormat` method `applyPattern()`, and the values of the `<fmt:param>` tags are collected in an `Object[]` and supplied to the `java.text.MessageFormat` method `format()`. The locale of the `java.text.MessageFormat` is set to the appropriate localization context locale before `applyPattern()` is called. If the localization context does not have any locale, the locale of the `java.text.MessageFormat` is set to the locale returned by the formatting locale lookup algorithm of Section 9.3, except that the available formatting locales are given as the intersection of the number- and date- formatting locales. If this algorithm does not yield any locale, the locale of the `java.text.MessageFormat` is set to the runtime's default locale.

If the message is compound and no `<fmt:param>` subtags are specified, it is left unmodified (that is, `java.text.MessageFormat` is not used).

The `<fmt:message>` action outputs its result to the current `JspWriter` object, unless the `var` attribute is specified, in which case the result is stored in the named JSP attribute.

8.9 <fmt:param>

Supplies a single parameter for parametric replacement to a containing <fmt:message> (see Section 8.8) action.

Syntax

Syntax 1: value specified via attribute "value"

```
<fmt:param value="messageParameter" />
```

Syntax 2: value specified via body content

```
<fmt:param>
  body content
</fmt:param>
```

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

Attributes

Name	Dynamic	Type	Description
value	true	Object	Argument used for parametric replacement.

Constraints

- Must be nested inside a <fmt:message> action.

Description

The <fmt:param> action supplies a single parameter for parametric replacement to the compound message given by its parent <fmt:message> action.

Parametric replacement takes place in the order of the `<fmt:param>` tags. The semantics of the replacement are defined as in the class

`java.text.MessageFormat`:

the compound message given by the parent `<fmt:message>` action is used as the argument to the `applyPattern()` method of a `java.text.MessageFormat` instance, and the values of the `<fmt:param>` tags are collected in an `Object[]` and supplied to that instance's `format()` method.

The argument value may be specified via the `value` attribute or inline via the tag's body content.

8.10 <fmt:requestEncoding>

Sets the request's character encoding.

Syntax

```
<fmt:requestEncoding [value="charsetName"] />
```

Body Content

Empty.

Attributes

Name	Dynamic	Type	Description
value	true	String	Name of character encoding to be applied when decoding request parameters.

Description

The <fmt:requestEncoding> action may be used to set the request's character encoding, in order to be able to correctly decode request parameter values whose encoding is different from ISO-8859-1.

This action is needed because most browsers do not follow the HTTP specification and fail to include a `Content-Type` header in their requests.

More specifically, the purpose of the <fmt:requestEncoding> action is to set the request encoding to be the same as the encoding used for the response containing the form that invokes this page.

This action calls the `setCharacterEncoding()` method on the servlet request with the character encoding name specified in the `value` attribute. It must be used before any parameters are retrieved, either explicitly or through the use of an EL expression.

If the character encoding of the request parameters is not known in advance (since the locale and thus character encoding of the page that generated the form collecting the parameter values was determined dynamically), the `value` attribute must not be specified. In this case, the <fmt:requestEncoding> action first checks if there is a charset defined in the request `Content-Type` header. If not, it uses the character

encoding from the `javax.servlet.jsp.jstl.fmt.request.charset` scoped variable which is searched in session scope. If this scoped variable is not found, the default character encoding (ISO-8859-1) is used.

8.11 Configuration Settings

This section describes the i18n-related configuration settings. Refer to Section 2.8 for more information on how JSTL processes configuration data.

8.11.1 Locale

Variable name	<code>javax.servlet.jsp.jstl.fmt.locale</code>
Java Constant	<code>Config.FMT_LOCALE</code>
Type	String or <code>java.util.Locale</code>
Set by	<code><fmt:setLocale></code>
Used by	<code><fmt:bundle></code> , <code><fmt:setBundle></code> , <code><fmt:message></code> , <code><fmt:formatNumber></code> , <code><fmt:parseNumber></code> , <code><fmt:formatDate></code> , <code><fmt:parseDate></code>

Specifies the locale to be used by the i18n-capable formatting actions, thereby disabling browser-based locales. A String value is interpreted as defined in action `<fmt:setLocale>` (see Section 8.5).

8.11.2 Fallback Locale

Variable name	<code>javax.servlet.jsp.jstl.fmt.fallbackLocale</code>
Java Constant	<code>Config.FMT_FALLBACK_LOCALE</code>
Type	String or <code>java.util.Locale</code>
Set by	
Used by	<code><fmt:bundle></code> , <code><fmt:setBundle></code> , <code><fmt:message></code> , <code><fmt:formatNumber></code> , <code><fmt:parseNumber></code> , <code><fmt:formatDate></code> , <code><fmt:parseDate></code>

Specifies the fallback locale to be used by the i18n-capable formatting actions if none of the preferred match any of the available locales. A String value is interpreted as defined in action `<fmt:setLocale>` (see Section 8.5).

8.11.3 I18n Localization Context

Variable name	<code>javax.servlet.jsp.jstl.fmt.localizationContext</code>
Java Constant	<code>Config.FMT_LOCALIZATION_CONTEXT</code>
Type	String or <code>javax.servlet.jsp.jstl.fmt.LocalizationContext</code>
Set by	<code><fmt:setBundle></code>
Used by	<code><fmt:message></code> , <code><fmt:formatNumber></code> , <code><fmt:parseNumber></code> , <code><fmt:formatDate></code> , <code><fmt:parseDate></code>

Specifies the default i18n localization context to be used by the i18n-capable formatting actions. A String value is interpreted as a resource bundle basename.

Formatting Actions

l18n-capable formatting tag library

The JSTL formatting actions allow various data elements in a JSP page, such as numbers, dates and times, to be formatted and parsed in a locale-sensitive or customized manner.

9.1 Overview

9.1.1 Formatting Numbers, Currencies, and Percentages

The `<fmt:formatNumber>` action allows page authors to format numbers, currencies, and percentages according to the client's cultural formatting conventions.

For example, the output of:

```
<fmt:formatNumber value="9876543.21" type="currency" />
```

varies with the page's locale (given in parentheses), as follows:

```
SFr. 9'876'543.21 (fr_CH)  
$9,876,543.21 (en_US)
```

While the previous example uses the default formatting pattern (for currencies) of the page's locale, it is also possible to specify a customized formatting pattern. For example, a pattern of ".000" will cause any numeric value formatted with it to be represented with 3 fraction digits, adding trailing zeros if necessary, so that:

```
<fmt:formatNumber value="12.3" pattern=".000"/>
```

will output "12.300".

Likewise, a pattern of "#,##0.0#" specifies that any numeric value formatted with it will be represented with a minimum of 2 integer digits, 1 fraction digit, and a maximum of 2 fraction digits, with every 3 integer digits grouped. Applied to "123456.7891", as in:

```
<fmt:formatNumber value="123456.7891" pattern="#,##0.0#"/>
```

the formatted output will be "123,456.79" (note that rounding is handled automatically).

The following example formats a numeric value as a currency, stores it in a scoped variable, parses it back in, and outputs the parsed result (which is the same as the original numeric value):

```
<fmt:formatNumber value="123456789" type="currency" var="cur"/>
<fmt:parseNumber value="${cur}" type="currency"/>
```

A similar sequence of actions could have been used to retrieve a currency-formatted value from a database, parse its numeric value, perform an arithmetic operation on it, reformat it as a currency, and store it back to the database.

9.1.2 Formatting Dates and Times

The `<fmt:formatDate>` action allows page authors to format dates and times according to the client's cultural formatting conventions.

For example, assuming a current date of Oct 22, 2001 and a current time of 4:05:53PM, the following action:

```
<jsp:useBean id="now" class="java.util.Date" />
<fmt:formatDate value="${now}" timeStyle="long"
dateStyle="long"/>
```

will output

October 22, 2001 4:05:53 PM PDT

for the U.S. and

22 octobre 2001 16:05:53 GMT-07:0

for the French locale.

Page authors may also specify a customized formatting style for their dates and times. Assuming the same current date and time as in the above example, this action:

```
<fmt:formatDate value="${now}" pattern="dd.MM.yy" />
```

will output

22.10.01

for the U.S. locale.

Time information on a page may be tailored to the preferred time zone of a client. This is useful if the server hosting the page and its clients reside in different time zones. If time information is to be formatted or parsed in a time zone different from that of the JSP container, the `<fmt:formatDate>` and `<fmt:parseDate>` action may be nested inside a `<fmt:timeZone>` action or supplied with a `timeZone` attribute.

In the following example, the current date and time are formatted in the "GMT+1:00" time zone:

```
<fmt:timeZone value="GMT+1:00">
  <fmt:formatDate value="${now}" type="both" dateStyle="full"
    timeStyle="full" />
</fmt:timeZone>
```

9.2 Formatting Locale

A formatting action¹ may leverage an `i18n` localization context to determine its formatting locale or establish a formatting locale on its own, by following these steps:

1. Four formatting actions localize their data: `<fmt:formatNumber>`, `<fmt:parseNumber>`, `<fmt:formatDate>`, `<fmt:parseDate>`.

- `<fmt:bundle>` action

If a formatting action is nested inside a `<fmt:bundle>` action (see Section 8.6), the locale of the `i18n` localization context of the enclosing `<fmt:bundle>` action is used as the formatting locale. The `<fmt:bundle>` action determines the resource bundle of its `i18n` localization context according to the resource bundle determination algorithm in Section 8.3, using the `basename` attribute as the resource bundle `basename`. If the `i18n` localization context of the enclosing `<fmt:bundle>` action does not contain any locale, go to the next step.

- `I18n` default localization context

The default `i18n` localization context may be specified via the `javax.servlet.jsp.jstl.fmt.localizationContext` configuration setting. If such a configuration setting exists, and its value is of type `LocalizationContext`, its locale is used as the formatting locale. Otherwise, if the configuration setting is of type `String`, the formatting action establishes its own `i18n` localization context and uses its locale as the formatting locale (in this case, the resource bundle component of the `i18n` localization context is determined according to the resource bundle determination algorithm in Section 8.3, using the configuration setting as the resource bundle `basename`). If the `i18n` localization context determined in this step does not contain any locale, go to the next step.

- Formatting locale lookup

The formatting action establishes a locale according to the algorithm described in Section 9.3. This algorithm requires the preferred locales. The way the preferred locales are set is exactly the same as with `i18n` actions and is described in Section 8.2.1.

The following example shows how the various localization contexts can be established to define the formatting locale.

```
<jsp:useBean id="now" class="java.util.Date" />

<%-- Formatting locale lookup --%>
<fmt:formatDate value="${now}" />

<fmt:bundle basename="Greetings">
  <%-- I18n localization context from parent <fmt:bundle> tag --%>
  <fmt:message key="Welcome" />
  <fmt:formatDate value="${now}" />
</fmt:bundle>
```

9.3 Establishing a Formatting Locale

If a formatting action fails to leverage an i18n localization context for its formatting locale – either because the formatting action has no way of referring to an i18n localization context, or the i18n localization context does not have any locale – it must establish the formatting locale on its own, given an ordered set of preferred locales, according to the formatting locale lookup algorithm described in this section.

9.3.1 Locales Available for Formatting Actions

The algorithm described in Section 9.3.3 compares preferred locales against the set of locales that are available for a specific formatting action.

The locales available for actions `<fmt:formatNumber>` and `<fmt:parseNumber>` are determined by a call to `java.text.NumberFormat.getAvailableLocales()`.

The locales available for `<fmt:formatDate>` and `<fmt:parseDate>` are determined by a call to `java.text.DateFormat.getAvailableLocales()`.

9.3.2 Locale Lookup

The algorithm of Section 9.3.3 describes how the proper locale is determined. This algorithm calls for a locale lookup: it attempts to find among the available locales, a locale that matches the specified one.

The locale lookup is similar to the resource bundle lookup described in Section 8.3.1, except that instead of trying to match a resource bundle, the locale lookup tries to find a match in a list of available locales. A match of the specified locale against an available locale is therefore attempted in the following order:

- Language, country, and variant are the same
- Language and country are the same
- Language is the same and the available locale does not have a country

9.3.3 Formatting Locale Lookup Algorithm

Notes:

- When there are multiple preferred locales, they are processed in the order they were returned by a call to `ServletRequest.getLocales()`.

- The algorithm stops as soon as a locale has been selected for the localization context.

Step 1: Find a match within the ordered set of preferred locales

A locale lookup (see Section 9.3.2) is performed for each one of the preferred locales until a match is found. The first match is used as the formatting locale.

Step 2: Find a match with the fallback locale

A locale lookup (see Section 9.3.2) is performed for the fallback locale specified in the `javax.servlet.jsp.jstl.fmt.fallbackLocale` configuration setting. If a match exists, it is used as the formatting locale.

If no match is found after the above two steps, it is up to the formatting action to take a corrective action.

The result of the formatting locale lookup algorithm may be cached, so that subsequent formatting actions that need to establish the formatting locale on their own may leverage it.

9.4 Time Zone

Time information on a page may be tailored to the preferred time zone of a client. This is useful if the server hosting the page and its clients reside in different time zones (page authors could be advised to always use the "long" time format which includes the time zone, but that would still require clients to convert the formatted time into their own time zone).

When formatting time information using the `<fmt:formatDate>` action (see Section 9.8), or parsing time information that does not specify a time zone using the `<fmt:parseDate>` action (see Section 9.9), the time zone to use is determined as follows and in this order:

- Use the time zone from the action's `timeZone` attribute.
- If attribute `timeZone` is not specified and the action is nested inside an `<fmt:timeZone>` action, use the time zone from the enclosing `<fmt:timeZone>` action.
- Use the time zone given by the `javax.servlet.jsp.jstl.fmt.timeZone` configuration setting.
- Use the JSP container's time zone.

9.5 <fmt:timeZone>

Specifies the time zone in which time information is to be formatted or parsed in its body content.

Syntax

```
<fmt:timeZone value="timeZone">
    body content
</fmt:timeZone>
```

Body Content

JSP. The JSP container processes the body content and then writes it to the current `JspWriter`. The action ignores the body content.

Attributes

Name	Dyn	Type	Description
value	true	String or <code>java.util.TimeZone</code>	The time zone. A <code>String</code> value is interpreted as a time zone ID. This may be one of the time zone IDs supported by the Java platform (such as "America/Los_Angeles") or a custom time zone ID (such as "GMT-8"). See <code>java.util.TimeZone</code> for more information on supported time zone formats.

Null & Error Handling

- If `value` is null or empty, the GMT timezone is used.

Description

The `<fmt:timeZone>` action specifies the time zone in which to format or parse the time information of any nested time formatting (see Section 9.8) or parsing (see Section 9.9) actions.

If the time zone is given as a string, it is parsed using `java.util.TimeZone.getTimeZone()`.

9.6 <fmt:setTimeZone>

Stores the specified time zone in a scoped variable or the time zone configuration variable.

Syntax

```
<fmt:setTimeZone value="timeZone"  
                [var="varName"]  
                [scope="{page|request|session|application}"]/>
```

Body Content

Empty.

Attributes

Name	Dyn	Type	Description
value	true	String or java.util.TimeZone	The time zone. A String value is interpreted as a time zone ID. This may be one of the time zone IDs supported by the Java platform (such as "America/Los_Angeles") or a custom time zone ID (such as "GMT-8"). See java.util.TimeZone for more information on supported time zone formats.
var	false	String	Name of the exported scoped variable which stores the time zone of type java.util.TimeZone.
scope	false	String	Scope of var or the time zone configuration variable.

Null & Error Handling

- If value is null or empty, the GMT timezone is used.

Description

The `<fmt:setTimeZone>` action stores the given time zone in the scoped variable whose name is given by `var`. If `var` is not specified, the time zone is stored in the `javax.servlet.jsp.jstl.fmt.timeZone` configuration variable, thereby making it the new default time zone in the given scope. If the time zone is given as a string, it is parsed using `java.util.TimeZone.getTimeZone()`.

9.7 <fmt:formatNumber>

Formats a numeric value in a locale-sensitive or customized manner as a number, currency, or percentage.

Syntax

Syntax 1: without a body

```
<fmt:formatNumber value="numericValue"
    [type="{number|currency|percent}"]
    [pattern="customPattern"]
    [currencyCode="currencyCode"]
    [currencySymbol="currencySymbol"]
    [groupingUsed="{true|false}"]
    [maxIntegerDigits="maxIntegerDigits"]
    [minIntegerDigits="minIntegerDigits"]
    [maxFractionDigits="maxFractionDigits"]
    [minFractionDigits="minFractionDigits"]
    [var="varName"]
    [scope="{page|request|session|application}"]/>
```

Syntax 2: with a body to specify the numeric value to be formatted

```
<fmt:formatNumber [type="{number|currency|percent}"]
    [pattern="customPattern"]
    [currencyCode="currencyCode"]
    [currencySymbol="currencySymbol"]
    [groupingUsed="{true|false}"]
    [maxIntegerDigits="maxIntegerDigits"]
    [minIntegerDigits="minIntegerDigits"]
    [maxFractionDigits="maxFractionDigits"]
    [minFractionDigits="minFractionDigits"]
    [var="varName"]
    [scope="{page|request|session|application}"]>
    numeric value to be formatted
</fmt:formatNumber>
```

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

Attributes

Name	Dyn	Type	Description
value	true	String or Number	Numeric value to be formatted.
type	true	String	Specifies whether the value is to be formatted as number, currency, or percentage.
pattern	true	String	Custom formatting pattern.
currencyCode	true	String	ISO 4217 currency code. Applied only when formatting currencies (i.e. if type is equal to "currency"); ignored otherwise.
currencySymbol	true	String	Currency symbol. Applied only when formatting currencies (i.e. if type is equal to "currency"); ignored otherwise.
groupingUsed	true	boolean	Specifies whether the formatted output will contain any grouping separators.
maxIntegerDigits	true	int	Maximum number of digits in the integer portion of the formatted output.
minIntegerDigits	true	int	Minimum number of digits in the integer portion of the formatted output.
maxFractionDigits	true	int	Maximum number of digits in the fractional portion of the formatted output.
minFractionDigits	true	int	Minimum number of digits in the fractional portion of the formatted output.
var	false	String	Name of the exported scoped variable which stores the formatted result as a String.
scope	false	String	Scope of var.

Constraints

- If `scope` is specified, `var` must also be specified.
- The value of the `currencyCode` attribute must be a valid ISO 4217 currency code.

Null & Error Handling

- If `value` is null or empty, nothing is written to the current `JspWriter` object and the scoped variable is removed if it is specified (see attributes `var` and `scope`).

- If this action fails to determine a formatting locale, it uses `Number.toString()` as the output format.
- If the attribute `pattern` is null or empty, it is ignored.
- If an exception occurs during the parsing of a string value, it must be caught and rethrown as a `JspException`. The message of the rethrown `JspException` must include the string value, and the caught exception must be provided as the root cause.

Description

The numeric value to be formatted may be specified via the `value` attribute; if missing, it is read from the tag's body content.

The formatting pattern may be specified via the `pattern` attribute, or is looked up in a locale-dependent fashion.

A pattern string specified via the `pattern` attribute must follow the pattern syntax specified by the class `java.text.DecimalFormat`.

If looked up in a locale-dependent fashion, the formatting pattern is determined via a combination of the formatting locale, which is determined according to Section 9.2, and the `type` attribute. Depending on the value of the `type` attribute, the given numeric value is formatted as a number, currency, or percentage. The locale's default formatting pattern for numbers, currencies, or percentages is determined by calling the `java.text.NumberFormat` method `getNumberInstance`, `getCurrencyInstance`, or `getPercentInstance`, respectively, with the formatting locale.

The `pattern` attribute takes precedence over `type`. In either case, the formatting symbols (such as decimal separator and grouping separator) are given by the formatting locale.

The (specified or locale-dependent) formatting pattern may be further fine-tuned using the formatting options described below.

If the numeric value is given as a string literal, it is first parsed into a `java.lang.Number`. If the string does not contain any decimal point, it is parsed using `java.lang.Long.valueOf()`, or `java.lang.Double.valueOf()` otherwise.

The formatted result is output to the current `JspWriter` object, unless the `var` attribute is given, in which case it is stored in the named scoped variable.

Formatting Options

The `groupingUsed` attribute specifies whether the formatted output will contain any grouping separators. See the `java.text.NumberFormat` method `setGroupingUsed()` for more information.

The minimum and maximum number of digits in the integer and fractional portions of the formatted output may be given via the `minIntegerDigits`, `maxIntegerDigits`, `minFractionDigits`, and `maxFractionDigits` attributes, respectively. See the `java.text.NumberFormat` methods `setMinimumIntegerDigits()`, `setMaximumIntegerDigits()`, `setMinimumFractionDigits()`, and `setMaximumFractionDigits()` for more information.

Formatting Currencies

When formatting currencies using the specified or locale-dependent formatting pattern for currencies, the currency symbol of the formatting locale is used by default. It can be overridden by using the `currencySymbol` or `currencyCode` attributes, which specify the currency symbol or currency code, respectively, of the currency to use.

If both `currencyCode` and `currencySymbol` are present, `currencyCode` takes precedence over `currencySymbol` if the `java.util.Currency` class is defined in the container's runtime (that is, if the container's runtime is J2SE 1.4 or greater), and `currencySymbol` takes precedence otherwise. If only `currencyCode` is given, it is used as a currency symbol if `java.util.Currency` is not defined.

9.8 <fmt:parseNumber>

Parses the string representation of numbers, currencies, and percentages that were formatted in a locale-sensitive or customized manner.

Syntax

Syntax 1: without a body

```
<fmt:parseNumber    value="numericValue"
                    [type="{number|currency|percent}"]
                    [pattern="customPattern"]
                    [parseLocale="parseLocale"]
                    [integerOnly="{true|false}"]
                    [var="varName"]
                    [scope="{page|request|session|application}"]/>
```

Syntax 2: with a body to specify the numeric value to be parsed

```
<fmt:parseNumber    [type="{number|currency|percent}"]
                    [pattern="customPattern"]
                    [parseLocale="parseLocale"]
                    [integerOnly="{true|false}"]
                    [var="varName"]
                    [scope="{page|request|session|application}"]>
    numeric value to be parsed
</fmt:parseNumber>
```

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

Attributes

Name	Dyn	Type	Description
value	true	String	String to be parsed.
type	true	String	Specifies whether the string in the value attribute should be parsed as a number, currency, or percentage.
pattern	true	String	Custom formatting pattern that determines how the string in the value attribute is to be parsed.
parseLocale	true	String or <code>java.util.Locale</code>	Locale whose default formatting pattern (for numbers, currencies, or percentages, respectively) is to be used during the parse operation, or to which the pattern specified via the pattern attribute (if present) is applied.
integerOnly	true	boolean	Specifies whether just the integer portion of the given value should be parsed.
var	false	String	Name of the exported scoped variable which stores the parsed result (of type <code>java.lang.Number</code>).
scope	false	String	Scope of var.

Constraints

- If scope is specified, var must also be specified.

Null & Error Handling

- If the numeric string to be parsed is null or empty, the scoped variable defined by attributes var and scope is removed. This allows "empty" input to be distinguished from "invalid" input, which causes an exception.
- If parseLocale is null or empty, it is treated as if it was missing.
- If an exception occurs during the parsing of the value, it must be caught and rethrown as a `JspException`. The message of the rethrown `JspException` must include the value that was to be parsed, and the caught exception must be provided as the root cause.
- If this action fails to determine a formatting locale, it must throw a `JspException` whose message must include the value that was to be parsed.
- If the attribute pattern is null or empty, it is ignored.

Description

The numeric value to be parsed may be specified via the `value` attribute; if missing, it is read from the action's body content.

The parse pattern may be specified via the `pattern` attribute, or is looked up in a locale-dependent fashion.

A pattern string specified via the `pattern` attribute must follow the pattern syntax specified by `java.text.DecimalFormat`.

If looked up in a locale-dependent fashion, the parse pattern is determined via a combination of the `type` and `parseLocale` attributes. Depending on the value of the `type` attribute, the given numeric value is parsed as a number, currency, or percentage. The parse pattern for numbers, currencies, or percentages is determined by calling the `java.text.NumberFormat` method `getNumberInstance`, `getCurrencyInstance`, or `getPercentInstance`, respectively, with the locale specified via `parseLocale`. If `parseLocale` is missing, the formatting locale, which is obtained according to Section 9.2, is used as the parse locale.

The `pattern` attribute takes precedence over `type`. In either case, the formatting symbols in the pattern (such as decimal separator and grouping separator) are given by the parse locale.

The `integerOnly` attribute specifies whether just the integer portion of the given value should be parsed. See the `java.text.NumberFormat` method `setParseIntegerOnly()` for more information.

If the `var` attribute is given, the parse result (of type `java.lang.Number`) is stored in the named scoped variable. Otherwise, it is output to the current `JspWriter` object using `java.lang.Number.toString()`.

9.9 <fmt:formatDate>

Allows the formatting of dates and times in a locale-sensitive or customized manner.

Syntax

```
<fmt:formatDate value="date"
    [type="{time|date|both}"]
    [dateStyle="{default|short|medium|long|full}"]
    [timeStyle="{default|short|medium|long|full}"]
    [pattern="customPattern"]
    [timeZone="timeZone"]
    [var="varName"]
    [scope="{page|request|session|application}"] />
```

Body Content

Empty.

Attributes

Name	Dynamic	Type	Description
value	true	java.util.Date	Date and/or time to be formatted.
type	true	String	Specifies whether the time, the date, or both the time and date components of the given date are to be formatted.
dateStyle	true	String	Predefined formatting style for dates. Follows the semantics defined in class <code>java.text.DateFormat</code> . Applied only when formatting a date or both a date and time (i.e. if <code>type</code> is missing or is equal to "date" or "both"); ignored otherwise.
timeStyle	true	String	Predefined formatting style for times. Follows the semantics defined in class <code>java.text.DateFormat</code> . Applied only when formatting a time or both a date and time (i.e. if <code>type</code> is equal to "time" or "both"); ignored otherwise.
pattern	true	String	Custom formatting style for dates and times.

Name	Dynamic	Type	Description
timeZone	true	String or java.util.TimeZone	Time zone in which to represent the formatted time.
var	false	String	Name of the exported scoped variable which stores the formatted result as a String.
scope	false	String	Scope of var.

Constraints

- If `scope` is specified, `var` must also be specified.

Null & Error Handling

- If `value` is null or empty, nothing is written to the current `JspWriter` object and the scoped variable is removed if it is specified (see attributes `var` and `scope`).
- If `timeZone` is null or empty, it is handled as if it was missing.
- If this action fails to determine a formatting locale, it uses `java.util.Date.toString()` as the output format.

Description

Depending on the value of the `type` attribute, only the time, the date, or both the time and date components of the date specified via the `value` attribute or the body content are formatted, using one of the predefined formatting styles for dates (specified via the `dateStyle` attribute) and times (specified via the `timeStyle` attribute) of the formatting locale, which is determined according to Section 9.2.

`dateStyle` and `timeStyle` support the semantics defined in `java.text.DateFormat`.

Page authors may also apply a customized formatting style to their times and dates by specifying the `pattern` attribute, in which case the `type`, `dateStyle`, and `timeStyle` attributes are ignored. The specified formatting pattern must use the pattern syntax specified by `java.text.SimpleDateFormat`.

In order to format the current date and time, a `<jsp:useBean>` action may be used as follows:

```
<jsp:useBean id="now" class="java.util.Date" />
<fmt:formatDate value="${now}" />
```

If the string representation of a date or time needs to be formatted, the string must first be parsed into a `java.util.Date` using the `<fmt:parseDate>` action, whose parsing result may then be supplied to the `<fmt:formatDate>` action:

```
<fmt:parseDate value="4/13/02" pattern="M/d/yy" var="parsed"/>
<fmt:formatDate value="${parsed}" dateStyle="full"/>
```

The action's result is output to the current `JspWriter` object, unless the `var` attribute is specified, in which case it is stored in the named scoped variable.

9.10 <fmt:parseDate>

Parses the string representation of dates and times that were formatted in a locale-sensitive or customized manner.

Syntax

Syntax 1: without a body

```
<fmt:parseDate    value="dateString"
                  [type="{time|date|both}"]
                  [dateStyle="{default|short|medium|long|full}"]
                  [timeStyle="{default|short|medium|long|full}"]
                  [pattern="customPattern"]
                  [timeZone="timeZone"]
                  [parseLocale="parseLocale"]
                  [var="varName"]
                  [scope="{page|request|session|application}"] />
```

Syntax 2: with a body to specify the date value to be parsed

```
<fmt:parseDate    [type="{time|date|both}"]
                  [dateStyle="{default|short|medium|long|full}"]
                  [timeStyle="{default|short|medium|long|full}"]
                  [pattern="customPattern"]
                  [timeZone="timeZone"]
                  [parseLocale="parseLocale"]
                  [var="varName"]
                  [scope="{page|request|session|application}"]>
    date value to be parsed
</fmt:parseDate>
```

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

Attributes

Name	Dyn	Type	Description
value	true	String	Date string to be parsed.
type	true	String	Specifies whether the date string in the value attribute is supposed to contain a time, a date, or both.
dateStyle	true	String	Predefined formatting style for days which determines how the date component of the date string is to be parsed. Applied only when formatting a date or both a date and time (i.e. if type is missing or is equal to "date" or "both"); ignored otherwise.
timeStyle	true	String	Predefined formatting styles for times which determines how the time component in the date string is to be parsed. Applied only when formatting a time or both a date and time (i.e. if type is equal to "time" or "both"); ignored otherwise.
pattern	true	String	Custom formatting pattern which determines how the date string is to be parsed.
timeZone	true	String or <code>java.util.TimeZone</code>	Time zone in which to interpret any time information in the date string.
parseLocale	true	String or <code>java.util.Locale</code>	Locale whose predefined formatting styles for dates and times are to be used during the parse operation, or to which the pattern specified via the pattern attribute (if present) is applied.
var	false	String	Name of the exported scoped variable in which the parsing result (of type <code>java.util.Date</code>) is stored.
scope	false	String	Scope of var.

Constraints

- If `scope` is specified, `var` must also be specified.

Null & Error Handling

- If the date string to be parsed is null or empty, the scoped variable defined by `var` and `scope` is removed. This allows "empty" input to be distinguished from "invalid" input, which causes an exception.
- If `timeZone` is null or empty, it is treated as if it was missing.
- If `parseLocale` is null or empty, it is treated as if it was missing.
- If an exception occurs during the parsing of the value, it must be caught and rethrown as a `JspException`. The message of the rethrown `JspException` must include the value that was to be parsed, and the caught exception must be provided as the root cause.
- If this action fails to determine a formatting locale, it must throw a `JspException` whose message must include the value that was to be parsed.

Description

The date string to be parsed may be specified via the `value` attribute or via the tag's body content.

Depending on the value of the `type` attribute, the given date string is supposed to contain only a time, only a date, or both. It is parsed according to one of the predefined formatting styles for dates (specified via the `dateStyle` attribute) and times (specified via the `timeStyle` attribute) of the locale specified by the `parseLocale` attribute. If the `parseLocale` attribute is missing, the formatting locale, which is determined according to Section 9.2, is used as the parse locale.

If the given date string uses a different format, the pattern required to parse it must be specified via the `pattern` attribute, which must use the pattern syntax specified by `java.text.SimpleDateFormat`. In this case, the `type`, `dateStyle`, and `timeStyle` attributes are ignored. Parsing is non-lenient, i.e. the given date string must strictly adhere to the parsing format.

If the given time information does not specify a time zone, it is interpreted in the time zone determined according to Section 9.4.

If the `var` attribute is given, the parsing result (of type `java.util.Date`) is stored in the named scoped variable. Otherwise, it is output to the current `JspWriter` using the `java.util.Date` method `toString()`.

9.11 Configuration Settings

This section describes the formatting-related configuration settings. Refer to Section 2.8 for more information on how JSTL processes configuration data.

9.11.1 TimeZone

Variable name	<code>javax.servlet.jsp.jstl.fmt.timeZone</code>
Java Constant	<code>Config.FMT_TIMEZONE</code>
Type	String or <code>java.util.TimeZone</code>
Set by	<code><fmt:setTimeZone></code>
Used by	<code><fmt:formatDate></code> , <code><fmt:parseDate></code>

Specifies the application's default time zone. A String value is interpreted as defined in action `<fmt:timeZone>` (see Section 9.5).

SQL Actions

sql tag library

Many web applications need to access relational databases as the source of dynamic data for their presentation layer. While it is generally preferred to have database operations handled within the business logic of a web application designed with an MVC architecture, there are situations where page authors require this capability within their JSP pages (e.g. prototyping/testing, small scale/simple applications, lack of developer resources).

The JSTL SQL actions provide the basic capabilities to easily interact with relational databases.

10.1 Overview

The JSTL SQL actions allow page authors to:

- Perform database queries (*select*)
- Easily access query results
- Perform database updates (*insert*, *update*, *delete*)
- Group several database operations into a transaction

10.1.1 Data Source

SQL actions operate on a data source, as defined by the Java class `javax.sql.DataSource`. A `DataSource` object provides connections to the physical data source it represents. Within the context of a `Connection` retrieved from the `DataSource`, SQL statements are executed and results are returned.

A data source can be specified explicitly via the `dataSource` attribute in SQL actions, or it can be totally transparent to a page author by taking advantage of the data source configuration setting (`javax.servlet.jsp.jstl.sql.dataSource`).

There are two ways a data source can be specified as a string.

The first way is through a JNDI relative path, assuming a container supporting JNDI. For example, with the absolute JNDI resource path `java:comp/env/jdbc/myDatabase`, the JNDI relative path to the data source resource would simply be `jdbc/myDatabase`, given that `java:comp/env` is the standard JNDI root for a J2EE application.

The second way is by specifying the parameters needed by the JDBC `DriverManager` class, using the following syntax (see Section 10.6 for details on the JDBC parameters)

```
url[, [driver][, [user][, password]]]
```

For example,

```
jdbc:mysql://localhost/,org.gjt.mm.mysql.Driver
```

where the database has been setup for access without any username or password. If the `'` character occurs in any of the JDBC parameters, it can be escaped by `'\'`. The character `'\'` itself can be escaped in the same way.

While the JDBC `DriverManager` class provides a low cost way to use SQL actions, it is not recommended to use it other than for prototyping purposes because it does not provide connection management features one can expect from a properly designed `DataSource` object.

10.1.2 Querying a Database

The most common use of the database actions is to query a database and display the results of the query.

The following sample code selects all customers from China from the customers table in the database, orders them by last name, and finally displays their last name, first name, and address in an HTML table.

```
<sql:query var="customers" dataSource="${dataSource}">
  SELECT * FROM customers
  WHERE country = 'China'
  ORDER BY lastname
</sql:query>

<table>
  <c:forEach var="row" items="${customers.rows}">
    <tr>
      <td><c:out value="${row.lastName}"/></td>
      <td><c:out value="${row.firstName}"/></td>
      <td><c:out value="${row.address}"/></td>
    </tr>
  </c:forEach>
</table>
```

This next example shows a generic way to display the results of a query with column names as headers:

```
<table>
  <!-- column headers -->
  <tr>
    <c:forEach var="columnName" items="${result.columnNames}">
      <th><c:out value="${columnName}"/></th>
    </c:forEach>
  </tr>
  <!-- column data -->
  <c:forEach var="row" items="${result.rowsByIndex}">
    <tr>
      <c:forEach var="column" items="${row}">
        <td><c:out value="${column}"/></td>
      </c:forEach>
    </tr>
  </c:forEach>
</table>
```

10.1.3 Updating a Database

The `<sql:update>` action updates a database. To ensure database integrity, several updates to a database may be grouped into a transaction by nesting the `<sql:update>` actions inside a `<sql:transaction>` action.

For example, the following code transfers money between two accounts in one transaction:

```
<sql:transaction dataSource="${dataSource}">
  <sql:update>
    UPDATE account
    SET Balance = Balance - ?
    WHERE accountNo = ?
    <sql:param value="${transferAmount}" />
    <sql:param value="${accountFrom}" />
  </sql:update>
  <sql:update>
    UPDATE account
    SET Balance = Balance + ?
    WHERE accountNo = ?
    <sql:param value="${transferAmount}" />
    <sql:param value="${accountTo}" />
  </sql:update>
</sql:transaction>
```

10.1.4 SQL Statement Parameters

The JSTL database actions support substituting parameter values for parameter markers ("?",) in SQL statements (as shown in the previous example). This form of parametric replacement is exposed by the `SQLExecutionTag` interface (see Chapter 16 "Java APIs").

The `SQLExecutionTag` interface is implemented by the tag handlers for `<sql:query>` and `<sql:update>`. It is exposed in order to support custom parameter actions. These custom actions may retrieve their parameters from any source and process them before substituting them for a parameter marker in the SQL statement of the enclosing `SQLExecutionTag` action.

For example, a GUI front end may have a user enter a date as three separate fields (year, month, and day), and use this information in a database query. If the database table being accessed provides only a single column for the complete date, action

`<acme:dateParam>` could assemble the three separate input parameters into one and pass it to the `addSqlParameter()` method of its enclosing `SQLExecutionTag` action:

```
<sql:update>
  UPDATE PersonalInfo
  SET BirthDate = ?
  WHERE clientId = ?
  <acme:dateParam year="${year}" month="${month}" day="${day}" />
  <sql:param value="${clientId}" />
</sql:update>
```

The JSTL formatting tags may be used to parse the string representation of dates and numbers into instances of `java.util.Date` and `java.lang.Number`, respectively, before supplying them to an enclosing `SQLExecutionTag` for parametric replacement:

```
<sql:update sql="${sqlUpdateStmt}" dataSource="${dataSource}">
  <fmt:parseDate var="myDate" value="${someDate}" />
  <sql:param value="${myDate}" />
</sql:update>
```

10.2 Database Access

This section describes the algorithm used by the SQL actions (`<sql:query>`, `<sql:update>`, `<sql:transaction>`) to access a database.

- Try to get a reference to a data source as follows:
 - If the attribute `dataSource` is specified, use the value specified for that attribute as the data source.
 - Otherwise, get the configuration setting associated with `javax.servlet.jsp.jstl.sql.dataSource` using `Config.find()` (see Section 2.8). Use the value found as the data source if it is not null.
- If a data source is obtained from the previous step:
 - If it is a `DataSource` object, this is the data source used by the action to access the database.
 - Otherwise, if it is a `String`:
 - Assume this is a JNDI relative path and retrieve the data source from the container's JNDI naming context by concatenating the specified relative path to the J2EE defined root (`java:comp/env/`).
 - If the previous step fails (data source not found), assume the string specifies JDBC parameters using the syntax described in Section 10.1.1 and do as follows:
 - If driver is specified, ensure it is loaded
 - Access the named URL through the `DriverManager` class, using an empty string for user or password if they are not specified.
 - If the previous step fails, throw an exception.
 - Otherwise, throw an exception.

An implementation need not create new objects each time a SQL action is called and the algorithm above does not yield a `DataSource` object directly; i.e when a JNDI path or parameters for the JDBC `DriverManager` class are used. It may reuse objects that it previously created for identical arguments.

It is important to note that actions that open a connection to a database must close the connection as well as release any other associated resources (for example, `Statement`, `PreparedStatement` and `ResultSet` objects) by the time the action completes. This ensures that no connections are left open and that leaks are avoided when these actions are used with pooling mechanisms.

10.3 <sql:query>

Queries a database.

Syntax

Syntax 1: Without body content

```
<sql:query sql="sqlQuery"
    var="varName" [scope="{page|request|session|application}"]
    [dataSource="dataSource"]
    [maxRows="maxRows"]
    [startRow="startRow"] />
```

Syntax 2: With a body to specify query arguments

```
<sql:query sql="sqlQuery"
    var="varName" [scope="{page|request|session|application}"]
    [dataSource="dataSource"]
    [maxRows="maxRows"]
    [startRow="startRow"]>
    <sql:param> actions
</sql:query>
```

Syntax 3: With a body to specify query and optional query parameters

```
<sql:query var="varName"
    [scope="{page|request|session|application}"]
    [dataSource="dataSource"]
    [maxRows="maxRows"]
    [startRow="startRow"]>
    query
    optional <sql:param> actions
</sql:query>
```

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

Attributes

Name	Dynamic	Type	Description
sql	true	String	SQL query statement.
dataSource	true	javax.sql.DataSource or String	Data source associated with the database to query. A String value represents a relative path to a JNDI resource or the parameters for the DriverManager class.
maxRows	true	int	The maximum number of rows to be included in the query result. If not specified, or set to -1, no limit on the maximum number of rows is enforced.
startRow	true	int	The returned Result object includes the rows starting at the specified index. The first row of the original query result set is at index 0. If not specified, rows are included starting from the first row at index 0.
var	false	String	Name of the exported scoped variable for the query result. The type of the scoped variable is javax.servlet.jsp.jstl.sql.Result (see Chapter 16 “Java APIs”).
scope	false	String	Scope of var.

Constraints

- If dataSource is specified, this action must not be nested inside a <sql:transaction>.¹
- maxRows must be >= -1

Null & Error Handling

- If dataSource is null, a JspException is thrown.
- If an exception occurs during the execution of this action, it must be caught and rethrown as a JspException. The message of the rethrown JspException must include the SQL statement, and the caught exception must be provided as the root cause.

Description

The <sql:query> action queries a database and returns a single result set containing rows of data that it stores in the scoped variable identified by the var and scope attributes.

1. <sql:transaction> is responsible for setting the data source in a transaction.

If the query produces no results, an empty `Result` object (of size zero) is returned.

The SQL query statement may be specified by the `sql` attribute or from the action's body content.

The query statement may contain parameter markers ("?",) identifying JDBC `PreparedStatement` parameters, whose values must be supplied by nested parameter actions (such as `<sql:param>`, see Section 10.7). The `<sql:query>` action implements the `SQLExecutionTag` interface (see Chapter 16 "Java APIs"), allowing parameter values to be supplied by custom parameter actions.

maxRows and startRow

The maximum number of rows to be included in the query result may be specified by the `maxRows` attribute (for a specific `<sql:query>` action) or by the configuration setting `javax.servlet.jsp.jstl.sql.maxRows` (see Section 2.8 and Section 10.9). Attribute `maxRows` has priority over the configuration setting. A value of -1 means that no limit is enforced on the maximum number of rows.

The `startRow` attribute may be used to specify the index of the first row to be included in the returned `Result` object. For example, if given a value of 10, the returned `Result` object will start with the row located at index 10 (i.e. rows 0 through 9 of the original query result set are skipped). All remaining rows of the original query result set are included.

If both `startRow` and `maxRows` are specified, a maximum of `startRow + maxRows` rows are retrieved from the database. All rows up to `startRow` are then discarded, and the remaining rows (from `startRow` through `startRow + maxRows`) are included in the result.

When using `startRow`, it is important to note that the order in which rows are returned is not guaranteed between RDBMS implementations unless an "order by" clause is specified in the query.

`maxRows` and `startRow` protect against so-called "runaway queries", allow efficient access to the top rows of large result sets, and also provide a "poor-man's way" of paging through a large query result by increasing `startRow` by `maxRows` over a previous page.

Obtaining and Releasing a Connection

If `<sql:query>` is nested inside an `<sql:transaction>` action, the `Connection` object is obtained from that parent `<sql:transaction>` which is responsible for managing access to the database.

Otherwise, access to the database is performed according to the algorithm described in Section 10.2. A `Connection` object is obtained and released before the action completes.

10.4 <sql:update>

Executes an SQL INSERT, UPDATE, or DELETE statement. In addition, SQL statements that return nothing, such as SQL DDL statements, can be executed.

Syntax

Syntax 1: Without body content

```
<sql:update sql="sqlUpdate"
  [dataSource="dataSource"]
  [var="varName"] [scope="{page|request|session|application}"] />
```

Syntax 2: With a body to specify update parameters

```
<sql:update sql="sqlUpdate"
  [dataSource="dataSource"]
  [var="varName"] [scope="{page|request|session|application}"]>
  <sql:param> actions
</sql:update>
```

Syntax 3: With a body to specify update statement and optional update parameters

```
<sql:update [dataSource="dataSource"]
  [var="varName"] [scope="{page|request|session|application}"]>
  update statement
  optional <sql:param> actions
</sql:update>
```

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

Attributes

Name	Dyn	Type	Description
sql	true	String	SQL update statement.
dataSource	true	javax.sql.DataSource or String	Data source associated with the database to update. A String value represents a relative path to a JNDI resource or the parameters for the JDBC DriverManager class.
var	false	String	Name of the exported scoped variable for the result of the database update. The type of the scoped variable is <code>java.lang.Integer</code> .
scope	false	String	Scope of <code>var</code> .

Constraints

- If `scope` is specified, `var` must also be specified.
- If `dataSource` is specified, this action must not be nested inside a `<sql:transaction>`.

Null & Error Handling

- If `dataSource` is null, a `JspException` is thrown.
- If an exception occurs during the execution of this action, it must be caught and rethrown as a `JspException`. The message of the rethrown `JspException` must include the SQL statement, and the caught exception must be provided as the root cause.

Description

The SQL update statement may be specified by the `sql` attribute or from the action's body content.

The update statement may contain parameter markers ("?) identifying JDBC `PreparedStatement` parameters, whose values must be supplied by nested parameter actions (such as `<sql:param>`, see Section 10.7). The `<sql:update>` action implements the `SQLExecutionTag` interface (see Chapter 16 "Java APIs"), allowing the parameter values to be supplied by custom parameter tags.

The connection to the database is obtained in the same manner as described for `<sql:query>` (see Section 10.3).

The result of an `<sql:update>` action is stored in a scoped variable named by the `var` attribute, if that attribute was specified. That result represents the number of rows that were affected by the update. Zero is returned if no rows were affected by

INSERT, DELETE, or UPDATE, and for any SQL statement that returns nothing (such as SQL DDL statements). This is consistent with method `executeUpdate()` of the JDBC class `Statement`.

10.5 <sql:transaction>

Establishes a transaction context for <sql:query> and <sql:update> subtags.

Syntax

```
<sql:transaction [dataSource="dataSource"]
    [isolation=isolationLevel]>
    <sql:query> and <sql:update> statements
</sql:transaction>
```

```
isolationLevel ::= "read_committed"
                  | "read_uncommitted"
                  | "repeatable_read"
                  | "serializable"
```

Body Content

JSP. The JSP container processes the body content and then writes the result to the current `JspWriter`. The action ignores the body content.

Attributes

Name	Dyn	Type	Description
dataSource	true	javax.sql.DataSource or String	DataSource associated with the database to access. A String value represents a relative path to a JNDI resource or the parameters for the JDBC DriverManager facility.
isolation	true	String	Transaction isolation level. If not specified, it is the isolation level the DataSource has been configured with.

Constraints

- Any nested <sql:query> and <sql:update> actions must not specify a dataSource attribute.

Null & Error Handling

- If dataSource is null, a `JspException` is thrown.

- Any exception occurring during the execution of this action must be caught and rethrown after the transaction has been rolled back (see description below for details).

Description

The `<sql:transaction>` action groups nested `<sql:query>` and `<sql:update>` actions into a transaction.

The transaction isolation levels are defined by `java.sql.Connection`.

The tag handler of the `<sql:transaction>` action must perform the following steps in its lifecycle methods:

- `doStartTag()`:
 - Determines the transaction isolation level the DBMS is set to (using the `Connection` method `getTransactionIsolation()`).
If transactions are not supported (that is, the transaction isolation level is equal to `TRANSACTION_NONE`), an exception is raised, causing the transaction to fail.
For any other transaction isolation level, the auto-commit mode is saved (so it can later be restored), and then disabled by calling `setAutoCommit(false)` on the `Connection`.
 - If the `isolation` attribute is specified and differs from the connection's current isolation level, the current transaction isolation level is saved (so it can later be restored) and set to the specified level (using the `Connection` method `setTransactionIsolation()`).
- `doEndTag()`: Calls the `Connection` method `commit()`.
- `doCatch()`: Calls the `Connection` method `rollback()`.
- `doFinally()`:
 - If a transaction isolation level has been saved, it is restored using the `Connection` method `setTransactionIsolation()`.
 - Restore auto-commit mode to its saved value by calling `setAutoCommit()` on the `Connection`.
 - Closes the connection.

The `Connection` object is obtained and managed in the same manner as described for `<sql:query>` (see Section 10.3), except that it is never obtained from a parent tag (`<sql:transaction>` tags can not be nested as a means to propagate a `Connection`).

Note that the `<sql:transaction>` tag handler commits or rollbacks the transaction (if it catches an exception) by calling the JDBC `Connection` `commit()` and `rollback()` methods respectively. Executing the corresponding SQL statements using `<sql:update>`, e.g. `<sql:update sql="rollback" />`, within the `<sql:transaction>` element body is not supported and the result of doing so is unpredictable.

Finally, the behavior of the `<sql:transaction>` action is undefined if it executes in the context of a larger JTA user transaction.

10.6 <sql:setDataSource>

Exports a data source either as a scoped variable or as the data source configuration variable (`javax.servlet.jsp.jstl.sql.dataSource`).

Syntax

```
<sql:setDataSource
    {dataSource="dataSource" |
      url="jdbcUrl"
      [driver="driverClassName"]
      [user="userName"]
      [password="password"]}
    [var="varName"]
    [scope="{page|request|session|application}"] />
```

Body Content

Empty.

Attributes

Name	Dyn	Type	Description
dataSource	true	String or <code>javax.sql.DataSource</code>	Data source. If specified as a string, it can either be a relative path to a JNDI resource, or a JDBC parameters string as defined in Section 10.1.1.
driver	true	String	JDBC parameter: driver class name.
url	true	String	JDBC parameter: URL associated with the database.
user	true	String	JDBC parameter: database user on whose behalf the connection to the database is being made.
password	true	String	JDBC parameter: user password
var	false	String	Name of the exported scoped variable for the data source specified. Type can be String or DataSource.
scope	false	String	If var is specified, scope of the exported variable. Otherwise, scope of the data source configuration variable.

Null & Error Handling

- If `dataSource` is null, a `JspException` is thrown.

Description

If the `var` attribute is specified, the `<sql:setDataSource>` action exports the data source specified (either as a `DataSource` object or as a `String`) as a scoped variable. Otherwise, the data source is exported in the `javax.servlet.jsp.jstl.sql.dataSource` configuration variable.

The data source may be specified either via the `dataSource` attribute (as a `DataSource` object, JNDI relative path, or JDBC parameters string), or via the four JDBC parameters attributes. These four attributes are provided as a simpler alternative to the JDBC parameters string syntax defined in Section 10.1.1 that would have to be used with the `dataSource` attribute.

As mentioned in Section 10.1.1, using JDBC's `DriverManager` class to access a database is intended for prototyping purposes only because it does not provide connection management features one can expect from a properly designed `DataSource` object.

10.7 <sql:param>

Sets the values of parameter markers ("?",) in a SQL statement. Subtag of `SQLExecutionTag` actions such as `<sql:query>` and `<sql:update>`.

Syntax

Syntax 1: Parameter value specified in attribute "value"

```
<sql:param value="value"/>
```

Syntax 2: Parameter value specified in the body content

```
<sql:param>
    parameter value
</sql:param>
```

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

Attributes

Name	Dyn	Type	Description
value	true	Object	Parameter value.

Constraints

- Must be nested inside an action whose tag handler is an instance of `SQLExecutionTag` (see Chapter 16 "Java APIs").

Null & Error Handling

- If `value` is null, the parameter is set to the SQL value NULL.

Description

The `<sql:param>` action substitutes the given parameter value for a parameter marker("?",) in the SQL statement of its enclosing `SQLExecutionTag` action.

Parameters are substituted in the order in which they are specified.

The `<sql:param>` action locates its nearest ancestor that is an instance of `SQLExecutionTag` and calls its `addSQLParameter()` method, supplying it with the given parameter value.

It is important to note that the semantics of `SQLExecutionTag.addSQLParameter()` are such that supplying a parameter with a `String` value (e.g. when using syntax 2) only works for columns of text type (`CHAR`, `VARCHAR` or `LONGVARCHAR`).

10.8 <sql:dateParam>

Sets the values of parameter markers ("?",) in a SQL statement for values of type `java.util.Date`. Subtag of `SQLExecutionTag` actions, such as `<sql:query>` and `<sql:update>`.

Syntax

```
<sql:dateParam value="value" [type="{timestamp|time|date}"]/>
```

Body Content

Empty.

Attributes

Name	Dyn	Type	Description
value	true	<code>java.util.Date</code>	Parameter value for DATE, TIME, or TIMESTAMP column in a database table.
type	true	String	One of "date", "time" or "timestamp".

Constraints

- Must be nested inside an action whose tag handler is an instance of `SQLExecutionTag` (see Chapter 16 "Java APIs").

Null & Error Handling

- If `value` is null, the parameter is set to the SQL value NULL.

Description

This action converts the provided `java.util.Date` instance to one of `java.sql.Date`, `java.sql.Time` or `java.sql.Timestamp` as defined by the `type` attribute as follows:

- If the `java.util.Date` object provided by the `value` attribute is an instance of `java.sql.Time`, `java.sql.Date`, or `java.sql.Timestamp`, and the `type` attribute matches this object's type, then it is passed as is to the database.

- Otherwise, the object is converted to the appropriate type by calling that type's constructor with a parameter of `date.getTime()`, where `date` is the value of the `value` attribute.

The `<sql:dateParam>` action substitutes the given parameter value for a parameter marker(`"?"`) in the SQL statement of its enclosing `SQLExecutionTag` action.

Parameters are substituted in the order in which they are specified.

The `<sql:dateParam>` action locates its nearest ancestor that is an instance of `SQLExecutionTag` and calls its `addSQLParameter()` method, supplying it with the given parameter value.

10.9 Configuration Settings

This section describes the configuration settings used by the SQL actions. Refer to Section 2.8 for more information on how JSTL processes configuration data.

10.9.1 DataSource

Variable name	<code>javax.servlet.jsp.jstl.sql.dataSource</code>
Java Constant	<code>Config.SQL_DATA_SOURCE</code>
Type	String or <code>javax.sql.DataSource</code>
Set by	<code><sql:setDataSource></code> , Deployment Descriptor, Config class
Used by	<code><sql:query></code> , <code><sql:update></code> , <code><sql:transaction></code>

The data source to be accessed by the SQL actions. It can be specified as a string representing either a JNDI relative path or a JDBC parameters string (as defined in Section 10.1.1), or as a `javax.sql.DataSource` object.

10.9.2 MaxRows

Variable name	<code>javax.servlet.jsp.jstl.sql.maxRows</code>
Java Constant	<code>Config.SQL_MAX_ROWS</code>
Type	Integer
Set by	Deployment Descriptor, Config class
Used by	<code><sql:query></code>

The maximum number of rows to be included in a query result. If the maximum number of rows is not specified, or is -1, it means that no limit is enforced on the maximum number of rows. Value must be ≥ -1 .

XML Core Actions

xml tag library

Enterprise data used in the web tier is increasingly XML these days — when companies cooperate over the web, XML is the data format of choice for exchanging information.

XML is therefore becoming more and more important in a page author's life. The set of XML actions specified in JSTL is meant to address the basic XML needs a page author is likely to encounter.

The XML actions are divided in three categories: XML core actions (this chapter), XML flow control actions (Chapter 12), and XML transform actions (Chapter 13).

11.1 Overview

A key aspect of dealing with XML documents is to be able to easily access their content. XPath, a W3C recommendation since 1999, provides a concise notation for specifying and selecting parts of an XML document. The XML set of actions in JSTL is therefore based on XPath.

The introduction of XPath for the XML tagset expands the notion of expression language. XPath is an expression language that is used locally for the XML actions. Below are the rules of integration that XPath follows as a *local* expression language. These rules ensure that XPath integrates nicely within the JSTL environment.

11.1.1 XPath Context

In XPath, the context for evaluating an expression consists of:

- A node or nodeset

- Variable bindings (see below)
- Function library

The default function library comes with the XPath engine. Some engines provide extension functions or allow customization to add new functions. The XPath function library in JSTL is limited to the core function library of the XPath specification.
- Namespace prefix definitions which allow namespace prefixes to be used within an XPath expression.

11.1.2 XPath Variable Bindings

The XPath engine supports the following scopes to easily access web application data within an XPath expression. These scopes are defined in exactly the same way as their implicit object counterparts in the JSTL expression language (see Section A.6).

Expression	Mapping
<code>\$foo</code>	<code>pageContext.findAttribute("foo")</code>
<code>\$param:foo</code>	<code>request.getParameter("foo")</code>
<code>\$header:foo</code>	<code>request.getHeader("foo")</code>
<code>\$cookie:foo</code>	maps to the cookie's value for name foo
<code>\$initParam:foo</code>	<code>application.getInitParameter("foo")</code>
<code>\$pageScope:foo</code>	<code>pageContext.getAttribute("foo", PageContext.PAGE_SCOPE)</code>
<code>\$requestScope:foo</code>	<code>pageContext.getAttribute("foo", PageContext.REQUEST_SCOPE)</code>
<code>\$sessionScope:foo</code>	<code>pageContext.getAttribute("foo", PageContext.SESSION_SCOPE)</code>
<code>\$applicationScope:foo</code>	<code>pageContext.getAttribute("foo", PageContext.APPLICATION_SCOPE)</code>

Through these mappings, JSP scoped variables, request parameters, headers, and cookies, as well as context init parameters can all be used inside XPath expressions easily. For example:

```
/foo/bar[@x=$param:name]
```

would find the "bar" element with an attribute "x" equal to the value of the http request parameter "name".

11.1.3 Java to XPath Type Mappings

An XPath variable must reference a `java.lang.Object` instance in one of the supported scopes, identified by namespace prefix. The following mappings must be supported:

Java Type	XPath Type
<code>java.lang.Boolean</code>	boolean
<code>java.lang.Number</code>	number
<code>java.lang.String</code>	string
Object exported by <code><x:parse></code>	node-set

A compliant implementation must allow an XPath variable to address objects exposed by that implementation's handlers for `<x:set>` and `<x:forEach>`. For example, while an implementation of `<x:set>` may expose, for a node-set *S*, an object of any valid Java type, subsequent XPath evaluations must interpret this object as the node-set *S*.

An XPath expression must also treat variables that resolve to implementations of standard DOM interfaces as representing nodes of the type bound to that interface by the DOM specification.

XPath variable references that address objects of other types result in implementation-defined behavior. (An implementation may throw an exception if it encounters an unrecognized type.) Following the XPath specification (section 3.1), a variable name that is not bound to any value results in an exception.

11.1.4 XPath to Java Type Mappings

Evaluation of XPath expressions evaluate to XPath types. Their mapping to Java objects is defined as follows:

XPath Type	Java Type
boolean true or false	<code>java.lang.Boolean</code>
number a floating-point number	<code>java.lang.Number</code>
string a sequence of UCS characters	<code>java.lang.String</code>
node-set an unordered collection of nodes without duplicates	Type usable by JSTL XML-manipulation tags in the same JSTL implementation. The specific Java type representing node-sets may thus vary by implementation.

11.1.5 The select Attribute

In all the XML actions of JSTL, XPath expressions are always specified using the `select` attribute. `select` is therefore always specified as a string literal that is evaluated by the XPath engine.

This clear separation, where only the `select` attribute of XML actions evaluates XPath expressions, helps avoid confusion between XPath (expression language that is local to the XML actions) and the JSTL expression language (global to all actions with dynamic attributes in the EL version of the tag library).

11.1.6 Default Context Node

The context node for every XPath expression evaluation in JSTL that does not appear in the body of an `<x:forEach>` tag is the root of an empty document. Page authors wishing to work with documents must therefore supply their own node(s) using an XPath variable (see Section 11.1.2).

Action `<x:forEach>` establishes for its nested actions a specific context for XPath expressions evaluation. See Section 12.6 for details.

11.1.7 Resources Access

XML actions such as `<x:parse>` and `<x:transform>` allow the specification of XML and/or XSLT documents as `String` or `Reader` objects. Accessing a resource through a URL is therefore handled through the `<c:import>` action that works seamlessly with the XML tags as shown below:

```
<c:import url="http://acme.com/productInfo" var="doc">
  <c:param name="productName" value="{product.name}" />
</c:import>
<x:parse doc="{doc}" var="parsedDoc" />
```

To resolve references to external entities, the `systemId` (`<x:parse>`) and `docSystemId/xsltSystemId` (`<x:transform>`) attributes can be used. For these attributes:

- Absolute URLs are passed to the parser directly
- Relative URLs are treated as references to resources (e.g., loaded via `ServletContext.getResource()`) and loaded using an `EntityResolver` and `URIResolver` as necessary

11.1.8 Core Actions

The XML core actions provide “expression language support” for XPath. These actions are therefore similar to the EL support actions `<c:out>` and `<c:set>` covered in Chapter 4, except that they apply to XPath expressions.

The core XML actions feature one additional action, `<x:parse>`, to parse an XML document into a data structure that can then be processed by the XPath engine. For example:

```
<!-- parse an XML document -->
<c:import url="http://acme.com/customer?id=76567" var="doc" />
<x:parse doc="{doc}" var="parsedDoc" />

<!-- access XML data via XPath expressions -->
<x:out select="$parsedDoc/name" />
<x:out select="$parsedDoc/address" />

<!-- set a scoped variable -->
<x:set var="custName" scope="request" select="$parsedDoc/name" />
```

The context for the evaluation of an XPath Expression can be set either directly within the XPath expression (as shown in the example above), or via an ancestor tag that sets a context that can be used by nested tags. An example of this is with action `<x:forEach>` (see Section 12.6).

```
<!-- context set by ancestor tag <x:forEach> -->
<x:forEach select="$parsedDoc//customer">
  <x:out select="name" />
</x:forEach>
```


11.2 <x:parse>

Parses an XML document.

Syntax

Syntax 1: XML document specified via a String or Reader object

```
<x:parse {doc="XMLDocument" | xml1="XMLDocument"}
    {var="var" [scope="scope"] | varDom="var" [scopeDom="scope"]}
    [systemId="systemId"]
    [filter="filter"] />
```

Syntax 2: XML document specified via the body content

```
<x:parse
    {var="var" [scope="scope"] | varDom="var" [scopeDom="scope"]}
    [systemId="systemId"]
    [filter="filter"]>
    XML Document to parse
</x:parse>
```

where *scope* is {page|request|session|application}

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

Attributes

Name	Dyn	Type	Description
doc	true	String, Reader	Source XML document to be parsed.
xml	true	String, Reader	<i>Deprecated</i> ¹ . Use attribute <code>doc</code> instead.
systemId	true	String	The system identifier (URI) for parsing the XML document.
filter	true	org.xml.sax. XMLFilter	Filter to be applied to the source document.

1. Deprecated.

Name	Dyn	Type	Description
var	false	String	Name of the exported scoped variable for the parsed XML document. The type of the scoped variable is implementation dependent.
scope	false	String	Scope for var.
varDom	false	String	Name of the exported scoped variable for the parsed XML document. The type of the scoped variable is <code>org.w3c.dom.Document</code> .
scopeDom	false	String	Scope for varDom.

1. Names beginning with the string "xml" are reserved by the XML specification.

Null & Error Handling

- If the source XML document is null or empty, a `JspException` is thrown.
- If `filter` is null, filtering is not performed.

Description

The `<x:parse>` action parses an XML document and saves the resulting object in the scoped variable specified by attribute `var` or `varDom`. It does not perform any validation against DTDs or Schemas.

The XML document can be specified either with the `doc` attribute, or inline via the action's body content.

`var` **and** `varDom`

If `var` is used, the type of the resulting object is not defined by this specification. This allows implementations to use whatever they deem best for an efficient implementation of the XML tagset. `varDom` exposes a DOM document, allowing collaboration with custom actions. Objects exposed by `var` and `varDom` can both be used to set the context of an XPath expression.

Filtering for Performance Benefits

If an implementation of the XML tagset is based on DOM-like structures, there will be a significant performance impact when dealing with large XML documents. To help with this, attribute `filter` can be used to allow filtering of the input data prior to having it parsed by the implementation into a DOM-like structure.

For example, if one is interested in processing only the "European" customers which represent only 10% of the original XML document received as input, it will greatly reduce the size and complexity of the resulting DOM structure if all non-European customers are pruned from the XML document prior to parsing.

```
<c:import url="http://acme.com/customers" var="doc"/>
<x:parse doc="${doc}" filter="${filterEuropeanCust}"
        var="parsedDoc"/>
```

The `filter` attribute accepts an object of type `org.xml.sax.XMLFilter`.

If configuration of the filter is desirable, it is suggested that the developer of the filter provides a custom tag for easy configuration by a page author.

11.3 <x:out>

Evaluates an XPath expression and outputs the result of the evaluation to the current `JspWriter` object.

Syntax

```
<x:out select="XPathExpression" [escapeXml="{true|false}"] />
```

Body Content

Empty.

Attributes

Name	Dynamic	Type	Description
select	false	String	XPath expression to be evaluated.
escapeXml	true	boolean	Determines whether characters <code><</code> , <code>></code> , <code>&</code> , <code>'</code> , <code>"</code> in the resulting string should be converted to their corresponding character entity codes. Default value is true.

Description

The expression to be evaluated is specified via attribute `select` and must be in XPath syntax. The result of the evaluation is converted to a `String` as if the `XPath.string()` function were applied, and is subsequently written to the current `JspWriter` object.

This action is the equivalent of `<%= . . . %>` (display the result of an expression in the JSP syntax) and `<c:out>` (display the result of an expression in the expression language syntax).

If `escapeXml` is true, the following character conversions are applied:

Character	Character Entity Code
<	<
>	>
&	&
'	'
“	"

11.4 <x:set>

Evaluates an XPath expression and stores the result into a scoped variable.

Syntax

```
<x:set select="XPathExpression"
      var="varName" [scope="{page|request|session|application}"]/>
```

Body Content

Empty.

Attributes

Name	Dynamic	Type	Description
select	false	String	XPath expression to be evaluated.
var	false	String	Name of the exported scoped variable to hold the <i>value</i> specified in the action. The type of the scoped variable is whatever type the <i>select</i> expression evaluates to.
scope	false	String	Scope for var.

Description

Evaluates an XPath expression (specified via attribute *select*) and stores the result into a scoped variable (specified via attributes *var* and *scope*).

The mapping of XPath types to Java types is described in Section 11.1.4.

XML Flow Control Actions

xml tag library

The core set of XML actions provides the basic functionality to easily parse and access XML data. Another important piece of functionality is the ability to iterate over elements in an XML document, as well as conditionally process JSP code fragments depending on the result of an XPath expression. The XML flow control actions provide these capabilities.

12.1 Overview

The XML flow control actions provide flow control based on the value of XPath expressions. These actions are therefore similar to the EL flow control actions (`<c:if>`, `<c:choose>`, and `<c:forEach>`), except that they apply to XPath expressions.

The `<x:if>` action has a `select` attribute that specifies an XPath expression. The expression is evaluated and the resulting object is converted to a `boolean` according to the semantics of the XPath `boolean()` function:

- A number is true if and only if it is neither positive or negative zero nor NaN
- A node-set is true if and only if it is non-empty
- A string is true if and only if its length is non-zero

`<x:if>` renders its body if the result is true. For example:

```
<x:if select="$customer/[location='UK']">
    UK based customer
</x:if>
```

The `<x:choose>` action selects one among a number of possible alternatives. It consists of a sequence of `<x:when>` elements followed by an optional `<x:otherwise>`. Each `<x:when>` element has a single attribute, `select`, which specifies an XPath expression. When a `<x:choose>` element is processed, each of the `<x:when>` elements has its expression evaluated in turn, and the resulting object is converted to a boolean according to the semantics of the XPath boolean function. The body of the first, and only the first, `<x:when>` whose result is true is rendered.

If none of the test conditions of nested `<x:when>` tags evaluates to true, then the body of an `<x:otherwise>` tag is evaluated, if present.

```
<x:choose>
  <x:when select="$customer/firstName">
    Hello <x:out select="$customer/firstName" />
  </x:when>
  <x:otherwise>
    Hello my friend
  </x:otherwise>
</x:choose>
```

The `<x:forEach>` action evaluates the given XPath expression and iterates over the result, setting the context node to each element in the iteration. For example:

```
<x:forEach select="$doc//author">
  <x:out select="@name" />
</x:forEach>
```

12.2 <x:if>

Evaluates the XPath expression specified in the `select` attribute and renders its body content if the expression evaluates to true.

Syntax

Syntax 1: Without body content

```
<x:if select="XPathExpression"
      var="varName" [scope="{page|request|session|application}"] />
```

Syntax 2: With body content

```
<x:if select="XPathExpression"
      [var="varName" [scope="{page|request|session|application}"]]>
    body content
</x:if>
```

Body Content

JSP. If the test condition evaluates to true, the JSP container processes the body content and then writes it to the current `JspWriter`.

Attributes

Name	Dynamic	Type	Description
<code>select</code>	false	String	The test condition that tells whether or not the body content should be processed.
<code>var</code>	false	String	Name of the exported scoped variable for the resulting value of the test condition. The type of the scoped variable is <code>Boolean</code> .
<code>scope</code>	false	String	Scope for <code>var</code> .

Constraints

- If `scope` is specified, `var` must also be specified.

Description

The XPath expression specified via attribute `select` is evaluated, and the resulting object is converted to a `boolean` according to the semantics of the XPath `boolean()` function. If true, the body content is evaluated by the JSP container and the result is written to the current `JspWriter`.

12.3 <x:choose>

Provides the context for mutually exclusive conditional execution.

Syntax

```
<x:choose>
  body content (<x:when> and <x:otherwise> subtags)
</x:choose>
```

Body Content

JSP. The body content is processed by the JSP container (at most one of the nested elements will be processed) and written to the current `JspWriter`.

Constraints

- The body of the <x:choose> action can only contain:
 - White spaces
May appear anywhere around the <x:when> and <x:otherwise> subtags.
 - 1 or more <x:when> actions
Must all appear before <x:otherwise>
 - 0 or 1 <x:otherwise> action
Must be the last action nested within <x:choose>

Description

The <x:choose> action processes the body of the first <x:when> action whose test condition evaluates to true. If none of the test conditions of nested <x:when> actions evaluates to true, then the body of an <x:otherwise> action is processed, if present.

12.4 <x:when>

Represents an alternative within an <x:choose> action.

Syntax

```
<x:when select="XPathExpression">
    body content
</x:when>
```

Body Content

JSP. If this is the first <x:when> action to evaluate to true within <x:choose>, the JSP container processes the body content and then writes it to the current `JspWriter`.

Attributes

Name	Dynamic	Type	Description
select	false	String	The test condition that tells whether or not the body content should be processed

Constraints

- Must have <x:choose> as an immediate parent.
- Must appear before an <x:otherwise> action that has the same parent.

Description

The XPath expression specified via attribute `select` is evaluated, and the resulting object is converted to a `boolean` according to the semantics of the XPath `boolean()` function. If this is the first <x:when> action to evaluate to true within <x:choose>, the JSP container processes the body content and then writes it to the current `JspWriter`.

12.5 <x:otherwise>

Represents the last alternative within a <x:choose> action.

Syntax

```
<x:otherwise>
    conditional block
</x:otherwise>
```

Body Content

JSP. If no <x:when> action nested within <x:choose> evaluates to true, the JSP container processes the body content and then writes it to the current `JspWriter`.

Attributes

None.

Constraints

- Must have <x:choose> as an immediate parent.
- Must be the last nested action within <x:choose>.

Description

Within a <x:choose> action, if none of the nested <x:when> test conditions evaluates to true, then the body content of the <x:otherwise> action is evaluated by the JSP container, and the result is written to the current `JspWriter`.

12.6 <x:forEach>

Evaluates the given XPath expression and repeats its nested body content over the result, setting the context node to each element in the iteration.

Syntax

```
<x:forEach [var="varName" ] select="XPathExpression">
    [varStatus="varStatusName" ]
    [begin="begin" ] [end="end" ] [step="step"]>
    body content
</x:forEach>
```

Body Content

JSP. As long as there are items to iterate over, the body content is processed by the JSP container and written to the current `JspWriter`.

Attributes

Name	Dynamic	Type	Description
var	false	String	Name of the exported scoped variable for the current item of the iteration. This scoped variable has nested visibility. Its type depends on the result of the XPath expression in the <code>select</code> attribute.
select	false	String	XPath expression to be evaluated.
varStatus	false	String	Name of the exported scoped variable for the status of the iteration. Object exported is of type <code>javax.servlet.jsp.jstl.core.LoopTagStatus</code> . This scoped variable has nested visibility.
begin	true	int	Iteration begins at the item located at the specified index. First item of the collection has index 0.
end	true	int	Iteration ends at the item located at the specified index (inclusive).
step	true	int	Iteration will only process every <code>step</code> items of the collection, starting with the first one.

Constraints

- If specified, `begin` must be ≥ 0 .
- If `end` is specified and it is less than `begin`, the loop is simply not executed.
- If specified, `step` must be ≥ 1

Null & Error Handling

- If `select` is empty, a `JspException` is thrown.

Description

Inside the body of the `<x:forEach>` tag, the context for XPath expression evaluations is obtained as follows:

- variable, function, and namespace bindings operate as in the rest of JSTL
- the context node is the node whose representation would be exposed by 'var' (whether or not the 'var' attribute is specified)
- the context position is the iteration 'count' (with the same meaning as in `<c:forEach>`)
- the context size is equal to the number of nodes in the node-set over which `<x:forEach>` is iterating

XML Transform Actions

xml tag library

The transformation of XML documents using XSLT stylesheets is popular in many web applications. The XML transform actions provide this capability so XSLT transformations can be performed within JSP pages.

13.1 Overview

The XML transform actions support the transformation of XML documents with XSLT stylesheets.

In the example below, an external XML document (retrieved from an absolute URL) is transformed by a local XSLT stylesheet (context relative path). The result of the transformation is written to the page.

```
<c:import url="http://acme.com/customers" var="doc"/>
<c:import url="/WEB-INF/xslt/customerList.xsl" var="xslt"/>
<x:transform doc="${doc}" xslt="${xslt}"/>
```

It is possible to set transformation parameters via nested `<x:param>` actions. For example:

```
<x:transform doc="${doc}" xslt="${xslt}">
  <x:param name="foo" value="foo-value"/>
</x:transform>
```

It is sometimes the case that the same stylesheet transformation needs to be applied multiple times to different source XML documents. A more efficient approach is to process the transformation stylesheet once, and then save this "transformer" object for successive transformations. The specification allows implementations to support transparent caching of transformer objects to improve performance.

13.2 <x:transform>

Applies an XSLT stylesheet transformation to an XML document.

Syntax

Syntax 1: Without body content

```
<x:transform
    {doc="XMLDocument" | xml1="XMLDocument"} xslt="XSLTStylesheet"
    [{docSystemId="XMLSystemId" | xmlSystemId1="XMLSystemId"}]
    [xsltSystemId="XSLTSystemId"]
    [{var="varName" [scope="scopeName"] | result="resultObject"}]
```

Syntax 2: With a body to specify transformation parameters

```
<x:transform
    {doc="XMLDocument" | xml1="XMLDocument"} xslt="XSLTStylesheet"
    [{docSystemId="XMLSystemId" | xmlSystemId1="XMLSystemId"}]
    [xsltSystemId="XSLTSystemId"]
    [{var="varName" [scope="scopeName"] | result="resultObject"}]
    <x:param> actions
</x:transform>
```

Syntax 3: With a body to specify XML document and optional transformation parameters

```
<x:transform
    xslt="XSLTStylesheet"
    [{docSystemId="XMLSystemId" | xmlSystemId1="XMLSystemId"}]
    xsltSystemId="XSLTSystemId"
    [{var="varName" [scope="scopeName"] | result="resultObject"}]
    XML Document to parse
    optional <x:param> actions
</x:transform>
```

where scopeName is {page | request | session | application}

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

1. Deprecated.

Attributes

Name	Dyn	Type	Description
doc	true	String, Reader, javax.xml.transform.Source, org.w3c.dom.Document, or object exported by <x:parse>, <x:set>.	Source XML document to be transformed. (If exported by <x:set>, it must correspond to a well-formed XML document, not a partial document.)
xml	true	String, Reader, javax.xml.transform.Source, org.w3c.dom.Document, or object exported by <x:parse>, <x:set>.	<i>Deprecated</i> ¹ . Use attribute doc instead.
xslt	true	String, Reader or javax.xml.transform.Source	Transformation stylesheet as a String, Reader, or Source object.
docSystemId	true	String	The system identifier (URI) for parsing the XML document.
xmlSystemId	true	String	<i>Deprecated</i> ¹ . Use attribute docSystemId instead.
xsltSystemId	true	String	The system identifier (URI) for parsing the XSLT stylesheet.
var	false	String	Name of the exported scoped variable for the transformed XML document. The type of the scoped variable is org.w3c.dom.Document.
scope	false	String	Scope for var.
result	true	javax.xml.transform.Result	Object that captures or processes the transformation result.

1. Names beginning with the string "xml" are reserved by the XML specification.

Null & Error Handling

- If the source XML document is null or empty, a `JspException` is thrown.
- If the source XSLT document is null or empty, a `JspException` is thrown.

Description

The `<x:transform>` tag applies a transformation to an XML document (attribute `doc` or the action's body content), given a specific XSLT stylesheet (attribute `xslt`). It does not perform any validation against DTD's or Schemas.

Nothing prevents an implementation from caching `Transformer` objects across invocations of `<x:transform>`, though implementations should be careful they take into account both the `xslt` and `xsltSystemId` attributes when deciding whether to use a cached `Transformer` or produce a new one. An implementation may assume that any external entities that were referenced during parsing will not change values during the life of the application.

The result of the transformation is written to the page by default. It is also possible to capture the result of the transformation in two other ways:

- `javax.xml.transform.Result` object specified by the `result` attribute.
- `org.w3c.dom.Document` object saved in the scoped variable specified by the `var` and `scope` attributes.

13.3 <x:param>

Set transformation parameters. Nested action of <x:transform>.

Syntax

Syntax 1: Parameter value specified in attribute "value"

```
<x:param name="name" value="value" />
```

Syntax 2: Parameter value specified in the body content

```
<x:param name="name">  
    parameter value  
</x:param>
```

Body Content

JSP. The JSP container processes the body content, then the action trims it and processes it further.

Attributes

Name	Dynamic	Type	Description
name	true	String	Name of the transformation parameter.
value	true	Object	Value of the parameter.

Description

The <x:param> action must be nested within <x:transform> to set transformation parameters. The value of the parameter can be specified either via the `value` attribute, or via the action's body content.

Tag Library Validators

JSP 1.2 provides tag library validators (TLVs) as a mechanism for a tag library to enforce constraints on the JSP document (the "XML view") associated with any JSP page into which the tag library is imported. While the expectation is that TLVs used by a tag library will typically enforce multi-tag constraints related to usage of the library's tags themselves, a TLV is free to perform arbitrary validation of JSP documents. A TLV returns to the container information about which elements, if any, are in violation of its specific constraints, along with textual descriptions of the syntactic violation.

JSTL provides TLVs that perform "reusable" validation; i.e. generic validation that custom tag-library authors might wish to incorporate in their own tag libraries. These tag libraries do not necessarily need to be substantial collections of tags; a taglib may exist simply to provide site-specific validation logic. Just like tag libraries whose primary focus is to provide new tags, such "validation-centric" tag libraries may be configured and used by "back-end" developers in order to affect the "front-end" JSP page author's environment.

This chapter covers the JSTL tag library validators.

14.1 Overview

JSTL exposes via TLVs two simple types of validations. These TLV classes may be used in custom tag-library descriptors (TLDs) to restrict the page author's activities. The two types of validation provided in this fashion are:

- ScriptFree (see Chapter 16 "Java APIs")
Assurance of script-free pages
- PermittedTaglibs (see Chapter 16 "Java APIs")
Enumeration of permitted tag libraries (including JSTL) on a page

For example, to prevent a JSP page from using JSP scriptlets and JSP declarations, but still allow expressions, a developer could create the following TLD:

```
<?xml version="1.0" encoding="UTF-8" ?>

<taglib xmlns="http://java.sun.com/xml/ns/j2ee"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation=
    "http://java.sun.com/xml/ns/j2ee web jsptaglibrary_2_0.xsd"
  version="2.0">
  <description>
    Validates JSP pages to prohibit use of scripting elements.
  </description>
  <tlib-version>1.0</tlib-version>
  <jsp-version>2.0</jsp.version>
  <short-name>scriptfree</short-name>
  <uri>http://acme.com/scriptfree</uri>

  <validator>
    <validator-class>
      javax.servlet.jsp.jstl.tlv.ScriptFreeTLV
    </validator-class>
    <init-param>
      <param-name>allowDeclarations</param-name>
      <param-value>false</param-value>
    </init-param>
    <init-param>
      <param-name>allowScriptlets</param-name>
      <param-value>false</param-value>
    </init-param>
    <init-param>
      <param-name>allowExpressions</param-name>
      <param-value>true</param-value>
    </init-param>
    <init-param>
      <param-name>allowRTEExpressions</param-name>
      <param-value>true</param-value>
    </init-param>
  </validator>
</taglib>
```

Note that in JSP 2.0, scripting elements can also be disabled through the use of the `scripting-invalid` configuration element (see the JSP specification for details).

Similarly, to restrict a JSP page to a set of permitted tag-libraries (in the example below, the JSTL “EL” tag libraries), a developer could create the following TLD:

```
<?xml version="1.0" encoding="UTF-8" ?>

<taglib xmlns="http://java.sun.com/xml/ns/j2ee"
        xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
        xsi:schemaLocation=
            "http://java.sun.com/xml/ns/j2ee web jsptaglibrary_2_0.xsd"
        version="2.0">
    <description>
        Restricts JSP pages to the JSTL tag libraries
    </description>
    <tlib-version>1.0</tlib-version>
    <jsp-version>2.0</jsp.version>
    <short-name>jstl taglibs only</scriptfree>
    <uri>http://acme.com/jstlTaglibsOnly</uri>

    <validator>
        <validator-class>
            javax.servlet.jsp.jstl.tlv.PermittedTaglibsTLV
        </validator-class>
        <init-param>
            <param-name>permittedTaglibs</param-name>
            <param-value>
                http://java.sun.com/jstl/core
                http://java.sun.com/jstl/xml
                http://java.sun.com/jstl/fmt
                http://java.sun.com/jstl/sql
            </param-value>
        </init-param>
    </validator>
</taglib>
```


Functions

function tag library

Just like custom actions allow developers to extend the JSP syntax with their own customized behavior, the expression language defined in JSP 2.0 introduces the notion of *functions* to allow developers to extend the capabilities of the Expression Language.

JSTL is about the standardization, via these extension mechanisms, of behavior that is commonly needed by page authors. In addition to defining a standard set of actions, JSTL therefore also defines a standardized set of EL functions. These functions are described in this chapter.

15.1 Overview

The JSTL functions are all grouped within the *function* tag library. They cover various domains of functionality described below.

15.1.1 The length Function

A feature sorely missed in JSTL 1.0 was the ability to easily get the size of a collection. While the `java.util.Collection` interface defines a `size()` method, it unfortunately does not conform to the JavaBeans architecture design pattern for properties and cannot be accessed via the expression language.

The `length` function has been designed to be very similar to the use of "length" in EcmaScript. It can be applied to any object supported by the JSTL iteration action `<c:forEach>`¹ and returns the length of the collection. When applied to a `String`, it returns the number of characters in the string.

A sample use of `length` is shown in the example below where scoped variable `athletes` is a collection of `Athletes` objects.

There are `${fn:length(athletes)}` athletes representing `${country}`

15.1.2 String Manipulation Functions

String manipulation functions allow page authors to:

- Change the capitalization of a string (`toLowerCase`, `toUpperCase`)
- Get a subset of a string (`substring`, `substringAfter`, `substringBefore`)
- Trim a string (`trim`)
- Replace characters in a string (`replace`)
- Check if a string contains another string (`indexOf`, `startsWith`, `endsWith`, `contains`, `containsIgnoreCase`)
- split a string (`split`) into an array, and join an array into a string (`join`)
- Escape XML characters in the string (`escapeXml`)

1. Note that the support in `<c:forEach>` for strings representing lists of coma separated values has been deprecated. The proper way to process strings of tokens is via `<c:forTokens>` or via functions `split` and `join`.

The example below shows simple uses of these functions.

```
<%-- truncate name to 30 chars and display it in uppercase --%>
${fn:toUpperCase(fn:substring(name, 0, 30))}

<%-- Display the text value prior to the first '*' character --%>
${fn:substringBefore(text, '*')}

<%-- Scoped variable "custId" may contain whitespaces at the
beginning or end. Trim it first, otherwise we end up with +'s in
the URL --%>
<c:url var="myUrl" value="${base}/cust">
  <c:param name="custId" value="${fn:trim(custId)}"/>
</c:url>

<%-- Display the text in between brackets --%>
${fn:substring(text, fn:indexOf(text, '(')+1,
               fn:indexOf(text, ')'))}

<%-- Display the name if it contains the search string --%>
<c:if test="${fn:containsIgnoreCase(name, searchString)}">
  Found name: ${name}
</c:if>

<%-- Display the last 10 characters of the text value --%>
${fn:substring(text, fn:length(text)-10)}

<%-- Display text value with bullets instead of '-' --%>
${fn:replace(text, '-', '&#149;')}
```

While one can always use `<c:out>` to make sure that XML characters are properly escaped, the function `escapeXml` provides a syntax that is more concise as can be seen in the following example:

```
<%-- Escape XML characters when displaying the value of a
request parameter (avoid cross-site scripting) --%>

<input name="userName" value="${fn:escapeXml(param:userName)}">

<%-- Escape XML characters when passing an attribute value to
an action --%>

<%-- Using <c:out> with <c:set>--%>
<c:set var="nameEscaped">
  <c:out value="${name}"/>
</c:set>
<my:tag name="${nameEscaped}"/>

<%-- Using <c:out> with <jsp:attribute>--%>
<my:tag>
  <jsp:attribute name="name">
    <c:out value="${name}"/>
  </jsp:attribute>
</my:tag>

<%-- Using fn:escapeXml --%>
<my:tag title="${fn:escapeXml(name)}"/>
```

15.2 fn:contains

Tests if a string contains the specified substring.

Syntax

`fn:contains(string, substring)` → boolean

Arguments & Result

Argument	Type	Description
<code>string</code>	String	The input string on which the function is applied.
<code>substring</code>	String	The substring tested for.
Result	boolean	true if the character sequence represented by the <code>substring</code> argument exists in the character sequence represented by the <code>string</code> argument, false otherwise.

Null & Error Handling

- If `string` is null, it is processed as an empty string.
- If `substring` is null, it is processed as an empty string.

Description

Returns true if the character sequence represented by the `substring` argument exists in the character sequence represented by the `string` argument, false otherwise.

If `substring` is empty, this matches the beginning of the string and the value returned is true.

Essentially, `fn:contains` returns the value of:

```
fn:indexOf(string, substring) != -1.
```

15.3 fn:containsIgnoreCase

Tests if a string contains the specified substring in a case insensitive way.

Syntax

`fn:containsIgnoreCase(string, substring) → boolean`

Arguments & Result

Argument	Type	Description
<code>string</code>	<code>String</code>	The input string on which the function is applied.
<code>substring</code>	<code>String</code>	The substring tested for.
Result	<code>boolean</code>	true if the character sequence represented by the <code>substring</code> argument exists in the character sequence represented by the <code>string</code> argument ignoring case differences, false otherwise.

Null & Error Handling

- If `string` is null, it is processed as an empty string.
- If `substring` is null, it is processed as an empty string.

Description

The behavior is the same as `fn:contains`, except that the comparison is done in a case insensitive way, as in:

`fn:contains(fn:toUpperCase(string), fn:toUpperCase(substring)).`

15.4 fn:endsWith

Tests if a string ends with the specified suffix.

Syntax

`fn:endsWith(string, suffix) → boolean`

Arguments & Result

Argument	Type	Description
<code>string</code>	<code>String</code>	The input string on which the function is applied.
<code>suffix</code>	<code>String</code>	The suffix to be matched.
Result	<code>boolean</code>	<code>true</code> if the character sequence represented by the <code>suffix</code> argument is a suffix of the character sequence represented by the <code>string</code> argument, <code>false</code> otherwise.

Null & Error Handling

- If `string` is null, it is processed as an empty string.
- If `substring` is null, it is processed as an empty string.

Description

Behavior is similar to `fn:startsWith`, except that the substring must be at the end of the input string.

If `suffix` is empty, this matches the end of the string and the value returned is `true`.

15.5 fn:escapeXml

Escapes characters that could be interpreted as XML markup.

Syntax

`fn:escapeXml(string) → String`

Arguments & Result

Argument	Type	Description
<code>string</code>	<code>String</code>	The input string on which the conversion is applied.
Result	<code>String</code>	Converted string.

Null & Error Handling

- If `string` is null, it is processed as an empty string.

Description

Escapes characters that could be interpreted as XML markup. The conversions are the same as the ones applied by `<c:out>` when attribute `escapeXml` is set to true. See Section 4.2.

If `string` is an empty string, an empty string is returned.

15.6 fn:indexOf

Returns the index within a string of the first occurrence of a specified substring.

Syntax

`fn:indexOf(string, substring) → int`

Arguments & Result

Argument	Type	Description
string	String	The input string on which the function is applied.
substring	String	The substring to search for in the input string.
Result	int	If the substring argument is a substring of the input string, returns the index of the first character of the first such substring; if it does not occur as a substring, -1 is returned.

Null & Error Handling

- If `string` is null, it is processed as an empty string.
- If `substring` is null, it is processed as an empty string.

Description

Returns the index (0-based) within a string of the first occurrence of a specified substring according to the semantics of method `indexOf(substring)` of the Java class `java.lang.String`, with the exception of the "Null and Error Handling" processing described above.

If `substring` is empty, this matches the beginning of the string and the value returned is 0.

15.7 fn:join

Joins all elements of an array into a string.

Syntax

`fn:join(array, separator) → String`

Arguments & Result

Argument	Type	Description
array	String[]	Array of strings to be joined.
separator	String	String to separate each element of the array in the resulting string.
Result	String	All array elements joined into one string.

Null & Error Handling

- If `array` is null, an empty string is returned.
- If `separator` is null, it is processed as an empty string.

Description

Joins all elements of the string array into a string.

If `separator` is an empty string, then the elements are joined together without any separator.

15.8 fn:length

Returns the number of items in a collection, or the number of characters in a string.

Syntax

`fn:length(input) → integer`

Arguments & Result

Argument	Type	Description
<code>input</code>	Any of the types supported for the <code>items</code> attribute in the <code><c:forEach></code> action, or <code>String</code> .	The input collection or string on which the length is computed.
Result	<code>int</code>	Length of the collection or the string.

Null & Error Handling

- If `input` is null, it is treated as an empty collection and the value returned is 0.
- If `input` is an empty string, the value returned is 0.

15.9 fn:replace

Returns a string resulting from replacing in an input string all occurrences of a "before" substring into an "after" substring.

Syntax

```
fn:replace(inputString, beforeSubstring, afterSubstring) → String
```

Arguments & Result

Argument	Type	Description
<code>inputString</code>	String	The input string on which the replace function is applied.
<code>beforeSubstring</code>	String	The "before" substring to be replaced.
<code>afterSubstring</code>	String	The "after" substring that replaces the "before" substring.
Result	String	The string that results from replacing <code>beforeSubstring</code> with <code>afterSubstring</code> .

Null & Error Handling

-
- If `inputString` is null, it is processed as an empty string.
 - If `beforeSubstring` is null, it is processed as an empty string.
 - If `afterSubstring` is null, it is processed as an empty string.

Description

All occurrences of `beforeSubstring` are replaced by `afterSubstring`. The text replaced is not reprocessed for further replacements.

If `inputString` is an empty string, an empty string is returned.

If `beforeSubstring` is an empty string, the input string is returned.

If `afterSubstring` is an empty string, all occurrences of `beforeSubstring` are removed from `inputString`.

15.10 fn:split

Splits a string into an array of substrings.

Syntax

```
fn:split(string, delimiters) → String[]
```

Arguments & Result

Argument	Type	Description
<code>string</code>	String	The input string that gets split into an array of substrings.
<code>delimiters</code>	String	Delimiter characters used to split the string.
Result	String[]	Array of strings.

Null & Error Handling

- If `string` is null, it is processed as an empty string.
- If `delimiters` is null, it is processed as an empty string.

Description

Breaks a string into tokens according to the semantics of the Java class `java.util.StringTokenizer`, with the exception of the "Null and Error Handling" described above.

If the input string is empty, the array returned contains one element consisting of an empty string (no splitting occurred, original string is returned).

If `delimiters` is an empty string, the array returned contains one element consisting of the input string (no splitting occurred, original string is returned).

Delimiter characters themselves are not treated as tokens, and are not included in any token.

15.11 fn:startsWith

Tests if a string starts with the specified prefix.

Syntax

`fn:startsWith(string, prefix)` → boolean

Arguments & Result

Argument	Type	Description
<code>string</code>	String	The input string on which the function is applied.
<code>prefix</code>	String	The prefix to be matched.
Result	boolean	true if the character sequence represented by the <code>prefix</code> argument is a prefix of the character sequence represented by the <code>string</code> argument, false otherwise.

Null & Error Handling

- If `string` is null, it is processed as an empty string.
- If `prefix` is null, it is processed as an empty string.

Description

Tests if an input string starts with the specified prefix according to the semantics of method `startsWith(String prefix)` of the Java class `java.lang.String`, with the exception of the "Null and Error Handling" processing described above.

If `prefix` is empty, this matches the beginning of the string and the value returned is true.

15.12 fn:substring

Returns a subset of a string.

Syntax

`fn:substring(string, beginIndex, endIndex) → String`

Arguments & Result

Argument	Type	Description
<code>string</code>	<code>String</code>	The input string on which the substring function is applied.
<code>beginIndex</code>	<code>int</code>	The beginning index (0-based), inclusive.
<code>endIndex</code>	<code>int</code>	The ending index (0-based), exclusive .
Result	<code>String</code>	The substring of the input string.

Null & Error Handling

- If `string` is null, it is processed as an empty string.
- If `beginIndex` is greater than the last index of the input string, an empty string is returned.
- If `beginIndex` is less than 0, its value is adjusted to be 0.
- If `endIndex` is less than 0 or greater than the length of the input string, its value is adjusted to be the length of the input string (the substring therefore starts at `beginIndex` and extends to the end of the input string).
- If `endIndex` is less than `beginIndex`, an empty string is returned.

Description

Returns a substring of the input string according to the semantics of method `substring()` of the Java class `java.lang.String`, with the exception of the "Null and Error Handling" processing described above.

Using a 0-based indexing scheme, the substring begins at the specified `beginIndex` and extends to the character at index `endIndex-1`. The length of the substring is therefore `endIndex-beginIndex`.

It is suggested to use the value -1 for `endIndex` to extend the substring to the end of the input string.

15.13 fn:substringAfter

Returns a subset of a string following a specific substring.

Syntax

`fn:substringAfter(string, substring) → String`

Arguments & Result

Argument	Type	Description
<code>string</code>	String	The input string on which the substring function is applied.
<code>substring</code>	String	The substring that delimits the beginning of the subset of the input string to be returned.
Result	String	The substring of the input string.

Null & Error Handling

- If `string` is null, it is processed as an empty string.
- If `substring` is null, it is processed as an empty string.

Description

The substring returned starts at the first character after the substring matched in the input string, and extends up to the end of the input string.

If `string` is an empty string, an empty string is returned.

If `substring` is an empty string, it matches the beginning of the input string and the input string is returned. This is consistent with the behavior of function `indexOf`, where an empty substring returns index 0.

If `substring` does not occur in the input string, an empty string is returned.

15.14 fn:substringBefore

Returns a subset of a string before a specific substring.

Syntax

`fn:substringBefore(string, substring) → String`

Arguments & Result

Argument	Type	Description
<code>string</code>	String	The input string on which the substring function is applied.
<code>substring</code>	String	The substring that delimits the end of subset of the input string to be returned.
Result	String	The substring of the input string.

Null & Error Handling

- If `string` is null, it is processed as an empty string.
- If `substring` is null, it is processed as an empty string.

Description

The substring returned starts at the first character in the input string and extends up to the character just before the substring matched in the input string.

If `string` is an empty string, an empty string is returned.

If `substring` is an empty string, it matches the beginning of the input string and an empty string is returned. This is consistent with the behavior of function `indexOf`, where an empty substring returns index 0.

If `substring` does not occur in the input string, an empty string is returned.

15.15 fn:toLowerCase

Converts all of the characters of a string to lower case.

Syntax

`fn:toLowerCase(string) → String`

Arguments & Result

Argument	Type	Description
<code>string</code>	<code>String</code>	The input string on which the transformation to lower case is applied.
Result	<code>String</code>	The input string transformed to lower case.

Null & Error Handling

- If `string` is null, it is treated as an empty string and an empty string is returned.

Description

Converts all of the characters of the input string to lower case according to the semantics of method `toLowerCase()` of the Java class `java.lang.String`.

15.16 fn:toUpperCase

Converts all of the characters of a string to upper case.

Syntax

`fn:toUpperCase(string) → String`

Arguments & Result

Argument	Type	Description
<code>string</code>	<code>String</code>	The input string on which the transformation to upper case is applied.
Result	<code>String</code>	The input string transformed to upper case.

Null & Error Handling

- If `string` is null, it is treated as an empty string and an empty string is returned.

Description

Converts all of the characters of the input string to upper case according to the semantics of method `toUpperCase()` of the Java class `java.lang.String`.

15.17 fn:trim

Removes white space from both ends of a string.

Syntax

`fn:trim(string) → String`

Arguments & Result

Argument	Type	Description
<code>string</code>	<code>String</code>	The input string on which the trim is applied.
Result	<code>String</code>	The trimmed string.

Null & Error Handling

- If `string` is null, it is treated as an empty string and an empty string is returned.

Description

Removes white space from both ends of a string according to the semantics of method `trim()` of the Java class `java.lang.String`.

Java APIs

This chapter describes the Java APIs exposed by the JSTL specification. The content of this chapter is generated automatically from Javadoc annotations embedded into the actual Java classes and interfaces of the implementation. This ensures that both the specification and implementation are synchronized.

Package

javax.servlet.jsp.jstl.core

Description

Class Summary	
Interfaces	
LoopTag ₂₀₉	JSTL allows developers to write custom iteration tags by implementing the LoopTag interface.
LoopTagStatus ₂₁₁	Exposes the current status of an iteration.
Classes	
ConditionalTagSupport ₁₉₂	Abstract class that facilitates implementation of conditional actions where the boolean result is exposed as a JSP scoped variable.
Config ₁₉₅	Class supporting access to configuration settings.
IndexedValueExpression ₂₀₁	
IteratedExpression ₂₀₄	
IteratedValueExpression ₂₀₆	
LoopTagSupport ₂₁₃	Base support class to facilitate implementation of iteration tags.
StringTokenValueExpression ₂₂₀	

javax.servlet.jsp.jstl.core ConditionalTagSupport

Declaration

public abstract class **ConditionalTagSupport** extends javax.servlet.jsp.tagext.TagSupport

```
java.lang.Object
|
+--javax.servlet.jsp.tagext.TagSupport
|
+--javax.servlet.jsp.jstl.core.ConditionalTagSupport
```

All Implemented Interfaces: javax.servlet.jsp.tagext.IterationTag,
javax.servlet.jsp.tagext.JspTag, java.io.Serializable,
javax.servlet.jsp.tagext.Tag

Description

Abstract class that facilitates implementation of conditional actions where the boolean result is exposed as a JSP scoped variable. The boolean result may then be used as the test condition in a <c:when> action.

This base class provides support for:

- Conditional processing of the action's body based on the returned value of the abstract method `condition()`.
- Storing the result of `condition()` as a Boolean object into a JSP scoped variable identified by attributes `var` and `scope`.

Member Summary

Constructors

[ConditionalTagSupport\(\) ₁₉₃](#)

Methods

```
protected abstract boolean condition() 193
                        int doStartTag() 193
                        void release() 194
                        void setScope(java.lang.String scope) 194
                        void setVar(java.lang.String var) 194
```

Inherited Member Summary

Fields inherited from interface **IterationTag**

EVAL_BODY_AGAIN

Fields inherited from interface **Tag**

Inherited Member Summary

EVAL_BODY_INCLUDE, EVAL_PAGE, SKIP_BODY, SKIP_PAGE

Fields inherited from class **TagSupport**

id, pageContext

Methods inherited from class **Object**

clone(), equals(Object), finalize(), getClass(), hashCode(), notify(), notifyAll(), toString(), wait(), wait(long), wait(long, int)

Methods inherited from class **TagSupport**

doAfterBody(), doEndTag(), findAncestorWithClass(Tag, Class), getId(), getParent(), getValue(String), getValues(), removeValue(String), setId(String), setPageContext(PageContext), setParent(Tag), setValue(String, Object)

Constructors

ConditionalTagSupport()

```
public ConditionalTagSupport()
```

Base constructor to initialize local state. As with `TagSupport`, subclasses should not implement constructors with arguments, and no-argument constructors implemented by subclasses must call the superclass constructor.

Methods

condition()

```
protected abstract boolean condition()  
    throws JspTagException
```

Subclasses implement this method to compute the boolean result of the conditional action. This method is invoked once per tag invocation by `doStartTag()`.

Returns: a boolean representing the condition that a particular subclass uses to drive its conditional logic.

Throws:

```
javax.servlet.jsp.JspTagException
```

doStartTag()

```
public int doStartTag()  
    throws JspException
```

Includes its body if `condition()` evaluates to true.

Overrides: `doStartTag` in class `TagSupport`

Throws:

```
javax.servlet.jsp.JspException
```

release()

```
public void release()
```

Releases any resources this ConditionalTagSupport may have (or inherit).

Overrides: release in class TagSupport

setScope(String)

```
public void setScope(java.lang.String scope)
```

Sets the 'scope' attribute.

Parameters:

scope - Scope of the 'var' attribute

setVar(String)

```
public void setVar(java.lang.String var)
```

Sets the 'var' attribute.

Parameters:

var - Name of the exported scoped variable storing the result of `condition()`.

javax.servlet.jsp.jstl.core Config

Declaration

```
public class Config
```

```
java.lang.Object  
|  
+--javax.servlet.jsp.jstl.core.Config
```

Description

Class supporting access to configuration settings.

Member Summary

Fields

```
                static  FMT\_FALLBACK\_LOCALE196  
java.lang.String  
                static  FMT\_LOCALE196  
java.lang.String  
                static  FMT\_LOCALIZATION\_CONTEXT196  
java.lang.String  
                static  FMT\_TIME\_ZONE196  
java.lang.String  
                static  SQL\_DATA\_SOURCE196  
java.lang.String  
                static  SQL\_MAX\_ROWS196  
java.lang.String
```

Constructors

```
                Config\(\)197
```

Methods

```
                static  find(javax.servlet.jsp.PageContext pc, java.lang.String  
java.lang.Object      name\)197  
                static  get(javax.servlet.http.HttpSession session, java.lang.String  
java.lang.Object      name\)198  
                static  get(javax.servlet.jsp.PageContext pc, java.lang.String name,  
java.lang.Object      int scope\)197  
                static  get(javax.servlet.ServletContext context, java.lang.String  
java.lang.Object      name\)198  
                static  get(javax.servlet.HttpServletRequest request, java.lang.String  
java.lang.Object      name\)197  
                static void remove(javax.servlet.http.HttpSession session,  
                                java.lang.String name\)199  
                static void remove(javax.servlet.jsp.PageContext pc, java.lang.String  
                                name, int scope\)198  
                static void remove(javax.servlet.ServletContext context, java.lang.String  
                                name\)199  
                static void remove(javax.servlet.HttpServletRequest request, java.lang.String  
                                name\)199
```

Member Summary

static void	<code>set(javax.servlet.http.HttpSession session, java.lang.String name, java.lang.Object value)</code> ²⁰⁰
static void	<code>set(javax.servlet.jsp.PageContext pc, java.lang.String name, java.lang.Object value, int scope)</code> ¹⁹⁹
static void	<code>set(javax.servlet.ServletContext context, java.lang.String name, java.lang.Object value)</code> ²⁰⁰
static void	<code>set(javax.servlet.ServletRequest request, java.lang.String name, java.lang.Object value)</code> ²⁰⁰

Inherited Member Summary

Methods inherited from class `Object`

`clone()`, `equals(Object)`, `finalize()`, `getClass()`, `hashCode()`, `notify()`, `notifyAll()`, `toString()`, `wait()`, `wait(long)`, `wait(long, int)`

Fields

FMT_FALLBACK_LOCALE

```
public static final java.lang.String FMT_FALLBACK_LOCALE
```

Name of configuration setting for fallback locale

FMT_LOCALE

```
public static final java.lang.String FMT_LOCALE
```

Name of configuration setting for application- (as opposed to browser-) based preferred locale

FMT_LOCALIZATION_CONTEXT

```
public static final java.lang.String FMT_LOCALIZATION_CONTEXT
```

Name of configuration setting for i18n localization context

FMT_TIME_ZONE

```
public static final java.lang.String FMT_TIME_ZONE
```

Name of localization setting for time zone

SQL_DATA_SOURCE

```
public static final java.lang.String SQL_DATA_SOURCE
```

Name of configuration setting for SQL data source

SQL_MAX_ROWS

```
public static final java.lang.String SQL_MAX_ROWS
```

Name of configuration setting for maximum number of rows to be included in SQL query result

Constructors

Config()

```
public Config()
```

Methods

find(PageContext, String)

```
public static java.lang.Object find(javax.servlet.jsp.PageContext pc,  
    java.lang.String name)
```

Finds the value associated with a specific configuration setting identified by its context initialization parameter name.

For each of the JSP scopes (page, request, session, application), get the value of the configuration variable identified by name using method `get ()`. Return as soon as a non-null value is found. If no value is found, get the value of the context initialization parameter identified by name.

Parameters:

pc - Page context in which the configuration setting is to be searched

name - Context initialization parameter name of the configuration setting

Returns: The `java.lang.Object` associated with the configuration setting identified by name, or null if it is not defined.

get(PageContext, String, int)

```
public static java.lang.Object get(javax.servlet.jsp.PageContext pc,  
    java.lang.String name, int scope)
```

Looks up a configuration variable in the given scope.

The lookup of configuration variables is performed as if each scope had its own name space, that is, the same configuration variable name in one scope does not replace one stored in a different scope.

Parameters:

pc - Page context in which the configuration variable is to be looked up

name - Configuration variable name

scope - Scope in which the configuration variable is to be looked up

Returns: The `java.lang.Object` associated with the configuration variable, or null if it is not defined.

get(ServletRequest, String)

```
public static java.lang.Object get(javax.servlet.ServletRequest request,  
    java.lang.String name)
```

Looks up a configuration variable in the “request” scope.

The lookup of configuration variables is performed as if each scope had its own name space, that is, the same configuration variable name in one scope does not replace one stored in a different scope.

Parameters:

`request` - Request object in which the configuration variable is to be looked up
`name` - Configuration variable name

Returns: The `java.lang.Object` associated with the configuration variable, or null if it is not defined.

get(HttpSession, String)

```
public static java.lang.Object get(javax.servlet.http.HttpSession session,  
    java.lang.String name)
```

Looks up a configuration variable in the “session” scope.

The lookup of configuration variables is performed as if each scope had its own name space, that is, the same configuration variable name in one scope does not replace one stored in a different scope.

Parameters:

`session` - Session object in which the configuration variable is to be looked up
`name` - Configuration variable name

Returns: The `java.lang.Object` associated with the configuration variable, or null if it is not defined, if session is null, or if the session is invalidated.

get(ServletContext, String)

```
public static java.lang.Object get(javax.servlet.ServletContext context,  
    java.lang.String name)
```

Looks up a configuration variable in the “application” scope.

The lookup of configuration variables is performed as if each scope had its own name space, that is, the same configuration variable name in one scope does not replace one stored in a different scope.

Parameters:

`context` - Servlet context in which the configuration variable is to be looked up
`name` - Configuration variable name

Returns: The `java.lang.Object` associated with the configuration variable, or null if it is not defined.

remove(PageContext, String, int)

```
public static void remove(javax.servlet.jsp.PageContext pc, java.lang.String name,  
    int scope)
```

Removes a configuration variable from the given scope.

Removing a configuration variable is performed as if each scope had its own namespace, that is, the same configuration variable name in one scope does not impact one stored in a different scope.

Parameters:

`pc` - Page context from which the configuration variable is to be removed
`name` - Configuration variable name
`scope` - Scope from which the configuration variable is to be removed

remove(ServletRequest, String)

```
public static void remove(javax.servlet.ServletRequest request, java.lang.String name)
```

Removes a configuration variable from the “request” scope.

Removing a configuration variable is performed as if each scope had its own namespace, that is, the same configuration variable name in one scope does not impact one stored in a different scope.

Parameters:

request - Request object from which the configuration variable is to be removed

name - Configuration variable name

remove(HttpSession, String)

```
public static void remove(javax.servlet.http.HttpSession session, java.lang.String name)
```

Removes a configuration variable from the “session” scope.

Removing a configuration variable is performed as if each scope had its own namespace, that is, the same configuration variable name in one scope does not impact one stored in a different scope.

Parameters:

session - Session object from which the configuration variable is to be removed

name - Configuration variable name

remove(ServletContext, String)

```
public static void remove(javax.servlet.ServletContext context, java.lang.String name)
```

Removes a configuration variable from the “application” scope.

Removing a configuration variable is performed as if each scope had its own namespace, that is, the same configuration variable name in one scope does not impact one stored in a different scope.

Parameters:

context - Servlet context from which the configuration variable is to be removed

name - Configuration variable name

set(PageContext, String, Object, int)

```
public static void set(javax.servlet.jsp.PageContext pc, java.lang.String name,  
    java.lang.Object value, int scope)
```

Sets the value of a configuration variable in the given scope.

Setting the value of a configuration variable is performed as if each scope had its own namespace, that is, the same configuration variable name in one scope does not replace one stored in a different scope.

Parameters:

pc - Page context in which the configuration variable is to be set

name - Configuration variable name

value - Configuration variable value

scope - Scope in which the configuration variable is to be set

set(ServletRequest, String, Object)

```
public static void set(javax.servlet.ServletRequest request, java.lang.String name,  
    java.lang.Object value)
```

Sets the value of a configuration variable in the “request” scope.

Setting the value of a configuration variable is performed as if each scope had its own namespace, that is, the same configuration variable name in one scope does not replace one stored in a different scope.

Parameters:

`request` - Request object in which the configuration variable is to be set

`name` - Configuration variable name

`value` - Configuration variable value

set(HttpSession, String, Object)

```
public static void set(javax.servlet.http.HttpSession session, java.lang.String name,  
    java.lang.Object value)
```

Sets the value of a configuration variable in the “session” scope.

Setting the value of a configuration variable is performed as if each scope had its own namespace, that is, the same configuration variable name in one scope does not replace one stored in a different scope.

Parameters:

`session` - Session object in which the configuration variable is to be set

`name` - Configuration variable name

`value` - Configuration variable value

set(ServletContext, String, Object)

```
public static void set(javax.servlet.ServletContext context, java.lang.String name,  
    java.lang.Object value)
```

Sets the value of a configuration variable in the “application” scope.

Setting the value of a configuration variable is performed as if each scope had its own namespace, that is, the same configuration variable name in one scope does not replace one stored in a different scope.

Parameters:

`context` - Servlet context in which the configuration variable is to be set

`name` - Configuration variable name

`value` - Configuration variable value

javax.servlet.jsp.jstl.core IndexedValueExpression

Declaration

```
public final class IndexedValueExpression extends javax.el.ValueExpression
```

```
java.lang.Object
|
+--javax.el.Expression
|
+--javax.el.ValueExpression
|
+--javax.servlet.jsp.jstl.core.IndexedValueExpression
```

All Implemented Interfaces: java.io.Serializable

Member Summary

Fields

```
protected int i202
java.lang.Integer
protected int orig202
javax.el.ValueExpression
```

Constructors

```
IndexedValueExpression(javax.el.ValueExpression orig, int i)202
```

Methods

```
boolean equals(java.lang.Object obj)202
java.lang.Class getExpectedType()202
java.lang.String getExpressionString()202
java.lang.Class getType(javax.el.ELContext context)202
java.lang.Object getValue(javax.el.ELContext context)202
int hashCode()202
boolean isLiteralText()202
boolean isReadOnly(javax.el.ELContext context)203
void setValue(javax.el.ELContext context, java.lang.Object value)203
```

Inherited Member Summary

Methods inherited from class Object

```
clone(), finalize(), getClass(), notify(), notifyAll(), toString(), wait(),
wait(long), wait(long, int)
```

Fields

i

```
protected final java.lang.Integer i
```

orig

```
protected final javax.el.ValueExpression orig
```

Constructors

IndexedValueExpression(ValueExpression, int)

```
public IndexedValueExpression(javax.el.ValueExpression orig, int i)
```

Methods

equals(Object)

```
public boolean equals(java.lang.Object obj)
```

Overrides: equals in class Object

getExpectedType()

```
public java.lang.Class getExpectedType()
```

getExpressionString()

```
public java.lang.String getExpressionString()
```

getType(ELContext)

```
public java.lang.Class getType(javax.el.ELContext context)
```

getValue(ELContext)

```
public java.lang.Object getValue(javax.el.ELContext context)
```

hashCode()

```
public int hashCode()
```

Overrides: hashCode in class Object

isLiteralText()

```
public boolean isLiteralText()
```

isReadOnly(ELContext)

```
public boolean isReadOnly(javax.el.ELContext context)
```

setValue(ELContext, Object)

```
public void setValue(javax.el.ELContext context, java.lang.Object value)
```

javax.servlet.jsp.jstl.core IteratedExpression

Declaration

```
public final class IteratedExpression
```

```
java.lang.Object  
|  
+--javax.servlet.jsp.jstl.core.IteratedExpression
```

Member Summary

Fields

```
protected orig204  
javax.el.ValueExpression  
on
```

Constructors

```
IteratedExpression(javax.el.ValueExpression orig)204
```

Methods

```
java.lang.Object getItem(javax.el.ELContext context, int i)205  
getValueExpression()205  
javax.el.ValueExpression  
on
```

Inherited Member Summary

Methods inherited from class Object

```
clone(), equals(Object), finalize(), getClass(), hashCode(), notify(), notifyAll(),  
toString(), wait(), wait(long), wait(long, int)
```

Fields

orig

```
protected final javax.el.ValueExpression orig
```

Constructors

IteratedExpression(ValueExpression)

```
public IteratedExpression(javax.el.ValueExpression orig)
```

Methods

getItem(ELContext, int)

```
public java.lang.Object getItem(javax.el.ELContext context, int i)
```

Evaluates the stored ValueExpression and return the indexed item.

Parameters:

context - The ELContext used to evaluate the ValueExpression

i - The index of the item to be retrieved

getValueExpression()

```
public javax.el.ValueExpression getValueExpression()
```

javax.servlet.jsp.jstl.core IteratedValueExpression

Declaration

public final class **IteratedValueExpression** extends javax.el.ValueExpression

```
java.lang.Object
|
+--javax.el.Expression
|   |
|   +--javax.el.ValueExpression
|       |
|       +--javax.servlet.jsp.jstl.core.IteratedValueExpression
```

All Implemented Interfaces: java.io.Serializable

Member Summary

Fields

```
protected int    i207
protected        iteratedExpression207
IteratedExpression
```

Constructors

```
IteratedValueExpression(IteratedExpression iteratedExpr, int
i)207
```

Methods

```
boolean    equals(java.lang.Object obj)207
java.lang.Class    getExpectedType()207
java.lang.String    getExpressionString()207
java.lang.Class    getType(javax.el.ELContext context)207
java.lang.Object    getValue(javax.el.ELContext context)207
int            hashCode()207
boolean        isLiteralText()207
boolean        isReadOnly(javax.el.ELContext context)208
void           setValue(javax.el.ELContext context, java.lang.Object
value)208
```

Inherited Member Summary

Methods inherited from class Object

```
clone(), finalize(), getClass(), notify(), notifyAll(), toString(), wait(),
wait(long), wait(long, int)
```

Fields

i

protected final int **i**

iteratedExpression

protected final [javax.servlet.jsp.jstl.core.IteratedExpression₂₀₄](#) **iteratedExpression**

Constructors

IteratedValueExpression(IteratedExpression, int)

```
public IteratedValueExpression(javax.servlet.jsp.jstl.core.IteratedExpression204
    iteratedExpr, int i)
```

Methods

equals(Object)

```
public boolean equals(java.lang.Object obj)
```

Overrides: equals in class Object

getExpectedType()

```
public java.lang.Class getExpectedType()
```

getExpressionString()

```
public java.lang.String getExpressionString()
```

getType(ELContext)

```
public java.lang.Class getType(javax.el.ELContext context)
```

getValue(ELContext)

```
public java.lang.Object getValue(javax.el.ELContext context)
```

hashCode()

```
public int hashCode()
```

Overrides: hashCode in class Object

isLiteralText()

```
public boolean isLiteralText()
```

isReadOnly(ELContext)

```
public boolean isReadOnly(javax.el.ELContext context)
```

setValue(ELContext, Object)

```
public void setValue(javax.el.ELContext context, java.lang.Object value)
```

javax.servlet.jsp.jstl.core LoopTag

Declaration

```
public interface LoopTag extends javax.servlet.jsp.tagext.Tag
```

All Superinterfaces: javax.servlet.jsp.tagext.JspTag,
javax.servlet.jsp.tagext.Tag

All Known Implementing Classes: [LoopTagSupport](#)₂₁₃

Description

JSTL allows developers to write custom iteration tags by implementing the LoopTag interface. This is not to be confused with javax.servlet.jsp.tagext.IterationTag as defined in JSP 1.2. LoopTag establishes a mechanism for iteration tags to be recognized and for type-safe implicit collaboration with custom subtags.

In most cases, it will not be necessary to implement this interface manually, for a base support class (LoopTagSupport) is provided to facilitate implementation.

Member Summary

Methods

```
java.lang.Object  getCurrent\(\)209  
LoopTagStatus    getLoopStatus\(\)210
```

Inherited Member Summary

Fields inherited from interface Tag

```
EVAL_BODY_INCLUDE, EVAL_PAGE, SKIP_BODY, SKIP_PAGE
```

Methods inherited from interface Tag

```
doEndTag(), doStartTag(), getParent(), release(), setPageContext(PageContext),  
setParent(Tag)
```

Methods

getCurrent()

```
public java.lang.Object getCurrent()
```

Retrieves the current item in the iteration. Behaves idempotently; calling `getCurrent()` repeatedly should return the same Object until the iteration is advanced. (Specifically, calling `getCurrent()` does **not** advance the iteration.)

Returns: the current item as an object

getLoopStatus()

```
public javax.servlet.jsp.jstl.core.LoopTagStatus211 getLoopStatus()
```

Retrieves a 'status' object to provide information about the current round of the iteration.

Returns: The `LoopTagStatus` for the current `LoopTag`.

javax.servlet.jsp.jstl.core LoopTagStatus

Declaration

```
public interface LoopTagStatus
```

Description

Exposes the current status of an iteration. JSTL provides a mechanism for LoopTags to return information about the current index of the iteration and convenience methods to determine whether or not the current round is either the first or last in the iteration. It also lets authors use the status object to obtain information about the iteration range, step, and current object.

Environments that require more status can extend this interface.

Member Summary

Methods

java.lang.Integer	getBegin() <small>211</small>
int	getCount() <small>211</small>
java.lang.Object	getCurrent() <small>212</small>
java.lang.Integer	getEnd() <small>212</small>
int	getIndex() <small>212</small>
java.lang.Integer	getStep() <small>212</small>
boolean	isFirst() <small>212</small>
boolean	isLast() <small>212</small>

Methods

getBegin()

```
public java.lang.Integer getBegin()
```

Returns the value of the 'begin' attribute for the associated tag, or null if no 'begin' attribute was specified.

Returns: the 'begin' value for the associated tag, or null if no 'begin' attribute was specified

getCount()

```
public int getCount()
```

Retrieves the "count" of the current round of the iteration. The count is a relative, 1-based sequence number identifying the current "round" of iteration (in context with all rounds the current iteration will perform).

As an example, an iteration with begin = 5, end = 15, and step = 5 produces the counts 1, 2, and 3 in that order.

Returns: the 1-based count of the current round of the iteration

getCurrent()

```
public java.lang.Object getCurrent()
```

Retrieves the current item in the iteration. Behaves idempotently; calling `getCurrent()` repeatedly should return the same `Object` until the iteration is advanced. (Specifically, calling `getCurrent()` does **not** advance the iteration.)

Returns: the current item as an object

getEnd()

```
public java.lang.Integer getEnd()
```

Returns the value of the 'end' attribute for the associated tag, or null if no 'end' attribute was specified.

Returns: the 'end' value for the associated tag, or null if no 'end' attribute was specified

getIndex()

```
public int getIndex()
```

Retrieves the index of the current round of the iteration. If iteration is being performed over a subset of an underlying array, `java.lang.Collection`, or other type, the index returned is absolute with respect to the underlying collection. Indices are 0-based.

Returns: the 0-based index of the current round of the iteration

getStep()

```
public java.lang.Integer getStep()
```

Returns the value of the 'step' attribute for the associated tag, or null if no 'step' attribute was specified.

Returns: the 'step' value for the associated tag, or null if no 'step' attribute was specified

isFirst()

```
public boolean isFirst()
```

Returns information about whether the current round of the iteration is the first one. This current round may be the 'first' even when `getIndex() != 0`, for 'index' refers to the absolute index of the current 'item' in the context of its underlying collection. It is always the case that a true result from `isFirst()` implies `getCount() == 1`.

Returns: `true` if the current round is the first in the iteration, `false` otherwise.

isLast()

```
public boolean isLast()
```

Returns information about whether the current round of the iteration is the last one. As with `isFirst()`, subsetting is taken into account. `isLast()` doesn't necessarily refer to the status of the underlying `Iterator`; it refers to whether or not the current round will be the final round of iteration for the tag associated with this `LoopTagStatus`.

Returns: `true` if the current round is the last in the iteration, `false` otherwise.

javax.servlet.jsp.jstl.core LoopTagSupport

Declaration

```
public abstract class LoopTagSupport extends javax.servlet.jsp.tagext.TagSupport implements
    LoopTag209, javax.servlet.jsp.tagext.IterationTag,
    javax.servlet.jsp.tagext.TryCatchFinally
```

```
java.lang.Object
|
+--javax.servlet.jsp.tagext.TagSupport
|
+--javax.servlet.jsp.jstl.core.LoopTagSupport
```

All Implemented Interfaces: javax.servlet.jsp.tagext.IterationTag, javax.servlet.jsp.tagext.JspTag, [LoopTag209](#), java.io.Serializable, javax.servlet.jsp.tagext.Tag, javax.servlet.jsp.tagext.TryCatchFinally

Description

Base support class to facilitate implementation of iteration tags.

Since most iteration tags will behave identically with respect to actual iterative behavior, JSTL provides this base support class to facilitate implementation. Many iteration tags will extend this and merely implement the `hasNext()` and `next()` methods to provide contents for the handler to iterate over.

In particular, this base class provides support for:

- Iteration control, based on protected `prepare()`, `next()`, and `hasNext()` methods
- Subsetting (begin, end, step>functionality, including validation of subset parameters for sensibility)
- item retrieval (`getCurrent()`)
- status retrieval (`LoopTagStatus`)
- exposing attributes (set by `var` and `varStatus` attributes)

In providing support for these tasks, `LoopTagSupport` contains certain control variables that act to modify the iteration. Accessors are provided for these control variables when the variables represent information needed or wanted at translation time (e.g., `var`, `varStatus`). For other variables, accessors cannot be provided here since subclasses may differ on their implementations of how those accessors are received. For instance, one subclass might accept a `String` and convert it into an object of a specific type by using an expression evaluator; others might accept objects directly. Still others might not want to expose such information to outside control.

Member Summary

Fields

protected int	begin₂₁₅
protected boolean	beginSpecified₂₁₅
protected	deferredExpression₂₁₅
javax.el.ValueExpressi	
on	

Member Summary

protected int [end](#)₂₁₅
protected boolean [endSpecified](#)₂₁₅
protected [itemId](#)₂₁₅
java.lang.String
protected [statusId](#)₂₁₅
java.lang.String
protected int [step](#)₂₁₅
protected boolean [stepSpecified](#)₂₁₆

Constructors

[LoopTagSupport\(\)](#) ₂₁₆

Methods

int [doAfterBody\(\)](#) ₂₁₆
void [doCatch\(java.lang.Throwable t\)](#) ₂₁₆
void [doFinally\(\)](#) ₂₁₆
int [doStartTag\(\)](#) ₂₁₇
java.lang.Object [getCurrent\(\)](#) ₂₁₇
LoopTagStatus [getLoopStatus\(\)](#) ₂₁₇
protected abstract [hasNext\(\)](#) ₂₁₇
boolean
protected abstract [next\(\)](#) ₂₁₇
java.lang.Object
protected abstract [prepare\(\)](#) ₂₁₈
void
void [release\(\)](#) ₂₁₈
void [setVar\(java.lang.String id\)](#) ₂₁₈
void [setVarStatus\(java.lang.String statusId\)](#) ₂₁₈
protected void [validateBegin\(\)](#) ₂₁₈
protected void [validateEnd\(\)](#) ₂₁₈
protected void [validateStep\(\)](#) ₂₁₉

Inherited Member Summary

Fields inherited from interface **IterationTag**

EVAL_BODY_AGAIN

Fields inherited from interface **Tag**

EVAL_BODY_INCLUDE, EVAL_PAGE, SKIP_BODY, SKIP_PAGE

Fields inherited from class **TagSupport**

id, pageContext

Methods inherited from class **Object**

clone(), equals(Object), finalize(), getClass(), hashCode(), notify(), notifyAll(), toString(), wait(), wait(long), wait(long, int)

Methods inherited from interface **Tag**

doEndTag(), getParent(), setPageContext(PageContext), setParent(Tag)

Inherited Member Summary

Methods inherited from class **TagSupport**

`doEndTag()`, `findAncestorWithClass(Tag, Class)`, `getId()`, `getParent()`,
`getValue(String)`, `getValues()`, `removeValue(String)`, `setId(String)`,
`setPageContext(PageContext)`, `setParent(Tag)`, `setValue(String, Object)`

Fields

begin

protected int **begin**

Starting index ('begin' attribute)

beginSpecified

protected boolean **beginSpecified**

Boolean flag indicating whether 'begin' was specified.

deferredExpression

protected javax.el.ValueExpression **deferredExpression**

The deferred expression if any

end

protected int **end**

Ending index of the iteration ('end' attribute). A value of -1 internally indicates 'no end specified', although accessors for the core JSTL tags do not allow this value to be supplied directly by the user.

endSpecified

protected boolean **endSpecified**

Boolean flag indicating whether 'end' was specified.

itemId

protected java.lang.String **itemId**

Attribute-exposing control

statusId

protected java.lang.String **statusId**

Attribute-exposing control

step

protected int **step**

Iteration step ('step' attribute)

stepSpecified

protected boolean **stepSpecified**

Boolean flag indicating whether 'step' was specified.

Constructors

LoopTagSupport()

public **LoopTagSupport**()

Constructs a new LoopTagSupport. As with TagSupport, subclasses should not implement constructors with arguments, and no-arguments constructors implemented by subclasses must call the superclass constructor.

Methods

doAfterBody()

public int **doAfterBody**()
throws JspException

Continues the iteration when appropriate — that is, if we (a) have more items and (b) don't run over our 'end' (given our 'step').

Specified By: doAfterBody in interface IterationTag

Overrides: doAfterBody in class TagSupport

Throws:

javax.servlet.jsp.JspException

doCatch(Throwable)

public void **doCatch**(java.lang.Throwable t)
throws Throwable

Rethrows the given Throwable.

Specified By: doCatch in interface TryCatchFinally

Throws:

java.lang.Throwable

doFinally()

public void **doFinally**()

Removes any attributes that this LoopTagSupport set.

These attributes are intended to support scripting variables with NESTED scope, so we don't want to pollute attribute space by leaving them lying around.

Specified By: doFinally in interface TryCatchFinally

doStartTag()

```
public int doStartTag()  
    throws JspException
```

Begins iterating by processing the first item.

Specified By: doStartTag in interface Tag

Overrides: doStartTag in class TagSupport

Throws:

javax.servlet.jsp.JspException

getCurrent()

```
public java.lang.Object getCurrent()
```

Retrieves the current item in the iteration. Behaves idempotently; calling getCurrent() repeatedly should return the same Object until the iteration is advanced. (Specifically, calling getCurrent() does **not** advance the iteration.)

Returns: the current item as an object

getLoopStatus()

```
public javax.servlet.jsp.jstl.core.LoopTagStatus211 getLoopStatus()
```

Retrieves a 'status' object to provide information about the current round of the iteration.

Returns: The LoopTagStatus for the current LoopTag.

hasNext()

```
protected abstract boolean hasNext()  
    throws JspTagException
```

Returns information concerning the availability of more items over which to iterate. This method must be provided by concrete subclasses of LoopTagSupport to assist the iterative logic provided by the supporting base class.

See next for more information about the purpose and expectations behind this tag.

Returns: true if there is at least one more item to iterate over, false otherwise

Throws:

See Also: [next\(\)](#) ₂₁₇

next()

```
protected abstract java.lang.Object next()  
    throws JspTagException
```

Returns the next object over which the tag should iterate. This method must be provided by concrete subclasses of LoopTagSupport to inform the base logic about what objects it should iterate over.

It is expected that this method will generally be backed by an Iterator, but this will not always be the case. In particular, if retrieving the next object raises the possibility of an exception being thrown, this method allows that exception to propagate back to the JSP container as a JspTagException; a standalone Iterator would not be able to do this. (This explains why LoopTagSupport does not simply call for an Iterator from its subtags.)

Returns: the java.lang.Object to use in the next round of iteration

Throws:

java.util.NoSuchElementException - if next() is called but no new elements are available

javax.servlet.jsp.JspTagException - for other, unexpected exceptions

prepare()

```
protected abstract void prepare()  
    throws JspTagException
```

Prepares for a single tag invocation. Specifically, allows subclasses to prepare for calls to hasNext() and next(). Subclasses can assume that prepare() will be called once for each invocation of doStartTag() in the superclass.

Throws:

release()

```
public void release()
```

Releases any resources this LoopTagSupport may have (or inherit).

Specified By: release in interface Tag

Overrides: release in class TagSupport

setVar(String)

```
public void setVar(java.lang.String id)
```

Sets the 'var' attribute.

Parameters:

id - Name of the exported scoped variable storing the current item of the iteration.

setVarStatus(String)

```
public void setVarStatus(java.lang.String statusId)
```

Sets the 'varStatus' attribute.

Parameters:

statusId - Name of the exported scoped variable storing the status of the iteration.

validateBegin()

```
protected void validateBegin()  
    throws JspTagException
```

Ensures the "begin" property is sensible, throwing an exception expected to propagate up if it isn't

Throws:

javax.servlet.jsp.JspTagException

validateEnd()

```
protected void validateEnd()  
    throws JspTagException
```

Ensures the "end" property is sensible, throwing an exception expected to propagate up if it isn't

Throws:

`javax.servlet.jsp.JspTagException`

validateStep()

protected void **validateStep()**
throws `JspTagException`

Ensures the “step” property is sensible, throwing an exception expected to propagate up if it isn’t

Throws:

`javax.servlet.jsp.JspTagException`

javax.servlet.jsp.jstl.core StringTokenValueExpression

Declaration

```
public final class StringTokenValueExpression extends javax.el.ValueExpression
```

```
java.lang.Object
|
+--javax.el.Expression
|   |
|   +--javax.el.ValueExpression
|       |
|       +--javax.servlet.jsp.jstl.core.StringTokenValueExpression
```

All Implemented Interfaces: `java.io.Serializable`

Member Summary

Fields

```
protected int i221
java.lang.Integer
protected orig221
javax.el.ValueExpression
```

Constructors

```
StringTokenValueExpression\(javax.el.ValueExpression orig, int i\)221
```

Methods

```
boolean equals\(java.lang.Object obj\)221
java.lang.Class getExpectedType\(\)221
java.lang.String getExpressionString\(\)221
java.lang.Class getType\(javax.el.ELContext context\)221
java.lang.Object getValue\(javax.el.ELContext context\)221
int hashCode\(\)221
boolean isLiteralText\(\)221
boolean isReadOnly\(javax.el.ELContext context\)222
void setValue\(javax.el.ELContext context, java.lang.Object value\)222
```

Inherited Member Summary

Methods inherited from class `Object`

```
clone\(\), finalize\(\), getClass\(\), notify\(\), notifyAll\(\), toString\(\), wait\(\),  
wait\(long\), wait\(long, int\)
```

Fields

i

protected final java.lang.Integer **i**

orig

protected final javax.el.ValueExpression **orig**

Constructors

StringTokenValueExpression(ValueExpression, int)

public **StringTokenValueExpression**(javax.el.ValueExpression orig, int i)

Methods

equals(Object)

public boolean **equals**(java.lang.Object obj)

Overrides: equals in class Object

getExpectedType()

public java.lang.Class **getExpectedType**()

getExpressionString()

public java.lang.String **getExpressionString**()

getType(ELContext)

public java.lang.Class **getType**(javax.el.ELContext context)

getValue(ELContext)

public java.lang.Object **getValue**(javax.el.ELContext context)

hashCode()

public int **hashCode**()

Overrides: hashCode in class Object

isLiteralText()

public boolean **isLiteralText**()

isReadOnly(ELContext)

```
public boolean isReadOnly(javax.el.ELContext context)
```

setValue(ELContext, Object)

```
public void setValue(javax.el.ELContext context, java.lang.Object value)
```


Package

javax.servlet.jsp.jstl.fmt

Description

Class Summary

Classes

LocaleSupport ₂₂₄	Class which exposes the locale-determination logic for resource bundles through convenience methods.
LocalizationContext ₂₂₇	Class representing an I18N localization context.

javax.servlet.jsp.jstl.fmt LocaleSupport

Declaration

```
public class LocaleSupport
```

```
java.lang.Object  
|  
+--javax.servlet.jsp.jstl.fmt.LocaleSupport
```

Description

Class which exposes the locale-determination logic for resource bundles through convenience methods.

This class may be useful to any tag handler implementation that needs to produce localized messages. For example, this might be useful for exception messages that are intended directly for user consumption on an error page.

Member Summary

Constructors

[LocaleSupport\(\)](#) ²²⁴

Methods

static	getLocalizedMessage(javax.servlet.jsp.PageContext
java.lang.String	pageContext, java.lang.String key) ²²⁵
static	getLocalizedMessage(javax.servlet.jsp.PageContext
java.lang.String	pageContext, java.lang.String key, java.lang.Object[] args) ²²⁵
static	getLocalizedMessage(javax.servlet.jsp.PageContext
java.lang.String	pageContext, java.lang.String key, java.lang.Object[] args,
	java.lang.String basename) ²²⁶
static	getLocalizedMessage(javax.servlet.jsp.PageContext
java.lang.String	pageContext, java.lang.String key, java.lang.String
	basename) ²²⁵

Inherited Member Summary

Methods inherited from class **Object**

[clone\(\)](#), [equals\(Object\)](#), [finalize\(\)](#), [getClass\(\)](#), [hashCode\(\)](#), [notify\(\)](#), [notifyAll\(\)](#), [toString\(\)](#), [wait\(\)](#), [wait\(long\)](#), [wait\(long, int\)](#)

Constructors

LocaleSupport()

```
public LocaleSupport()
```

Methods

getLocalizedMessage(PageContext, String)

```
public static java.lang.String getLocalizedMessage(javax.servlet.jsp.PageContext  
    pageContext, java.lang.String key)
```

Retrieves the localized message corresponding to the given key.

The given key is looked up in the resource bundle of the default I18N localization context, which is retrieved from the `javax.servlet.jsp.jstl.fmt.localizationContext` configuration setting.

If the configuration setting is empty, or the default I18N localization context does not contain any resource bundle, or the given key is undefined in its resource bundle, the string “`???<key>???`” is returned, where “`<key>`” is replaced with the given key.

Parameters:

`pageContext` - the page in which to get the localized message corresponding to the given key

`key` - the message key

Returns: the localized message corresponding to the given key

getLocalizedMessage(PageContext, String, String)

```
public static java.lang.String getLocalizedMessage(javax.servlet.jsp.PageContext  
    pageContext, java.lang.String key, java.lang.String basename)
```

Retrieves the localized message corresponding to the given key.

The given key is looked up in the resource bundle with the given base name.

If no resource bundle with the given base name exists, or the given key is undefined in the resource bundle, the string “`???<key>???`” is returned, where “`<key>`” is replaced with the given key.

Parameters:

`pageContext` - the page in which to get the localized message corresponding to the given key

`key` - the message key

`basename` - the resource bundle base name

Returns: the localized message corresponding to the given key

getLocalizedMessage(PageContext, String, Object[])

```
public static java.lang.String getLocalizedMessage(javax.servlet.jsp.PageContext  
    pageContext, java.lang.String key, java.lang.Object[] args)
```

Retrieves the localized message corresponding to the given key, and performs parametric replacement using the arguments specified via `args`.

See the specification of the `<fmt:message>` action for a description of how parametric replacement is implemented.

The localized message is retrieved as in [getLocalizedMessage\(pageContext, key\)](#) ²²⁵.

Parameters:

`pageContext` - the page in which to get the localized message corresponding to the given key

key - the message key

args - the arguments for parametric replacement

Returns: the localized message corresponding to the given key

getLocalizedMessage(PageContext, String, Object[], String)

```
public static java.lang.String getLocalizedMessage(javax.servlet.jsp.PageContext  
    pageContext, java.lang.String key, java.lang.Object[] args,  
    java.lang.String basename)
```

Retrieves the localized message corresponding to the given key, and performs parametric replacement using the arguments specified via args.

See the specification of the <fmt:message> action for a description of how parametric replacement is implemented.

The localized message is retrieved as in [getLocalizedMessage\(pageContext, key, basename\)](#) ²²⁵.

Parameters:

pageContext - the page in which to get the localized message corresponding to the given key

key - the message key

args - the arguments for parametric replacement

basename - the resource bundle base name

Returns: the localized message corresponding to the given key

javax.servlet.jsp.jstl.fmt LocalizationContext

Declaration

```
public class LocalizationContext

java.lang.Object
|
+--javax.servlet.jsp.jstl.fmt.LocalizationContext
```

Description

Class representing an I18N localization context.

An I18N localization context has two components: a resource bundle and the locale that led to the resource bundle match.

The resource bundle component is used by <fmt:message> for mapping message keys to localized messages, and the locale component is used by the <fmt:message>, <fmt:formatNumber>, <fmt:parseNumber>, <fmt:formatDate>, and <fmt:parseDate> actions as their formatting or parsing locale, respectively.

Member Summary

Constructors

```
LocalizationContext() 227
LocalizationContext(java.util.ResourceBundle bundle) 228
LocalizationContext(java.util.ResourceBundle bundle,
java.util.Locale locale) 228
```

Methods

```
java.util.Locale  getLocale() 228
                  getResourceBundle() 228
java.util.ResourceBund
                  le
```

Inherited Member Summary

Methods inherited from class **Object**

```
clone(), equals(Object), finalize(), getClass(), hashCode(), notify(), notifyAll(),
toString(), wait(), wait(long), wait(long, int)
```

Constructors

LocalizationContext()

```
public LocalizationContext()
```

Constructs an empty I18N localization context.

LocalizationContext(ResourceBundle, Locale)

```
public LocalizationContext(java.util.ResourceBundle bundle, java.util.Locale locale)
```

Constructs an I18N localization context from the given resource bundle and locale.

The specified locale is the application- or browser-based preferred locale that led to the resource bundle match.

Parameters:

`bundle` - The localization context's resource bundle

`locale` - The localization context's locale

LocalizationContext(ResourceBundle)

```
public LocalizationContext(java.util.ResourceBundle bundle)
```

Constructs an I18N localization context from the given resource bundle.

The localization context's locale is taken from the given resource bundle.

Parameters:

`bundle` - The resource bundle

Methods

getLocale()

```
public java.util.Locale getLocale()
```

Gets the locale of this I18N localization context.

Returns: The locale of this I18N localization context, or null if this I18N localization context is empty, or its resource bundle is a (locale-less) root resource bundle.

getResourceBundle()

```
public java.util.ResourceBundle getResourceBundle()
```

Gets the resource bundle of this I18N localization context.

Returns: The resource bundle of this I18N localization context, or null if this I18N localization context is empty

Package

javax.servlet.jsp.jstl.sql

Description

Class Summary	
Interfaces	
Result ₂₃₀	This interface represents the result of a <sql:query> action.
SQLExecutionTag ₂₃₄	This interface allows tag handlers implementing it to receive values for parameter markers in their SQL statements.
Classes	
ResultSupport ₂₃₂	Supports the creation of a javax.servlet.jsp.jstl.sql.Result object from a source java.sql.ResultSet object.

javax.servlet.jsp.jstl.sql Result

Declaration

```
public interface Result
```

Description

This interface represents the result of a <sql:query> action. It provides access to the following information in the query result:

- The result rows (`getRows()` and `getRowsByIndex()`)
- The column names (`getColumnNames()`)
- The number of rows in the result (`getRowCount()`)
- An indication whether the rows returned represent the complete result or just a subset that is limited by a maximum row setting (`isLimitedByMaxRows()`)

An implementation of the `Result` interface provides a *disconnected* view into the result of a query.

Member Summary

Methods

java.lang.String[]	getColumnNames() 230
int	getRowCount() 230
java.util.SortedMap[]	getRows() 230
java.lang.Object[][]	getRowsByIndex() 231
boolean	isLimitedByMaxRows() 231

Methods

getColumnNames()

```
public java.lang.String[] getColumnNames()
```

Returns the names of the columns in the result. The order of the names in the array matches the order in which columns are returned in method `getRowsByIndex()`.

Returns: the column names as an array of `String` objects

getRowCount()

```
public int getRowCount()
```

Returns the number of rows in the cached `ResultSet`

Returns: the number of rows in the result

getRows()

```
public java.util.SortedMap[] getRows()
```

Returns the result of the query as an array of `SortedMap` objects. Each item of the array represents a specific row in the query result.

A row is structured as a `SortedMap` object where the key is the column name, and where the value is the value associated with the column identified by the key. The column value is an `Object` of the Java type corresponding to the mapping between column types and Java types defined by the JDBC specification when the `ResultSet.getObject()` method is used.

The `SortedMap` must use the `Comparator java.util.String.CASE_INSENSITIVE_ORDER`. This makes it possible to access the key as a case insensitive representation of a column name. This method will therefore work regardless of the case of the column name returned by the database.

Returns: The result rows as an array of `SortedMap` objects

getRowsByIndex()

```
public java.lang.Object[][] getRowsByIndex()
```

Returns the result of the query as an array of arrays. The first array dimension represents a specific row in the query result. The array elements for each row are `Object` instances of the Java type corresponding to the mapping between column types and Java types defined by the JDBC specification when the `ResultSet.getObject()` method is used.

Returns: the result rows as an array of `Object[]` objects

isLimitedByMaxRows()

```
public boolean isLimitedByMaxRows()
```

Returns true if the query was limited by a maximum row setting

Returns: true if the query was limited by a maximum row setting

javax.servlet.jsp.jstl.sql ResultSupport

Declaration

```
public class ResultSupport
```

```
java.lang.Object  
|  
+--javax.servlet.jsp.jstl.sql.ResultSupport
```

Description

Supports the creation of a javax.servlet.jsp.jstl.sql.Result object from a source java.sql.ResultSet object. A Result object makes it much easier for page authors to access and manipulate the data resulting from a SQL query.

Member Summary

Constructors

[ResultSupport\(\)](#)²³²

Methods

static Result [toResult\(java.sql.ResultSet rs\)](#)²³²

static Result [toResult\(java.sql.ResultSet rs, int maxRows\)](#)²³³

Inherited Member Summary

Methods inherited from class Object

clone(), equals(Object), finalize(), getClass(), hashCode(), notify(), notifyAll(), toString(), wait(), wait(long), wait(long, int)

Constructors

ResultSupport()

```
public ResultSupport()
```

Methods

toResult(ResultSet)

```
public static javax.servlet.jsp.jstl.sql.Result230 toResult(java.sql.ResultSet rs)
```

Converts a ResultSet object to a Result object.

Parameters:

rs - the ResultSet object

Returns: The Result object created from the ResultSet

toResult(ResultSet, int)

```
public static javax.servlet.jsp.jstl.sql.Result230 toResult(java.sql.ResultSet rs,  
int maxRows)
```

Converts maxRows of a ResultSet object to a Result object.

Parameters:

rs - the ResultSet object

maxRows - the maximum number of rows to be cached into the Result object.

Returns: The Result object created from the ResultSet, limited by maxRows

javax.servlet.jsp.jstl.sql SQLExecutionTag

Declaration

```
public interface SQLExecutionTag
```

Description

This interface allows tag handlers implementing it to receive values for parameter markers in their SQL statements.

This interface is implemented by both `<sql:query>` and `<sql:update>`. Its `addSQLParameter()` method is called by nested parameter actions (such as `<sql:param>`) to substitute `PreparedStatement` parameter values for “?” parameter markers in the SQL statement of the enclosing `SQLExecutionTag` action.

The given parameter values are converted to their corresponding SQL type (following the rules in the JDBC specification) before they are sent to the database.

Keeping track of the index of the parameter values being added is the responsibility of the tag handler implementing this interface

The `SQLExecutionTag` interface is exposed in order to support custom parameter actions which may retrieve their parameters from any source and process them before substituting them for a parameter marker in the SQL statement of the enclosing `SQLExecutionTag` action

Member Summary
Methods
<code>void addSQLParameter(java.lang.Object value)</code> ²³⁴

Methods

addSQLParameter(Object)

```
public void addSQLParameter(java.lang.Object value)
```

Adds a `PreparedStatement` parameter value. Must behave as if it calls `PreparedStatement.setObject(int, Object)`. For each tag invocation, the integral index passed logically to `setObject()` must begin with 1 and must be incremented by 1 for each subsequent invocation of `addSQLParameter()`. The `Object` logically passed to `setObject()` must be the unmodified object received in the value argument.

Parameters:

value - the `PreparedStatement` parameter value

Package

javax.servlet.jsp.jstl.tlv

Description

Class Summary

Classes

PermittedTaglibsTLV₂₃₆	A TagLibraryValidator class to allow a TLD to restrict what taglibs (in addition to itself) may be imported on a page where it's used.
ScriptFreeTLV₂₃₈	A TagLibraryValidator for enforcing restrictions against the use of JSP scripting elements.

javax.servlet.jsp.jstl.tlv PermittedTaglibsTLV

Declaration

```
public class PermittedTaglibsTLV extends javax.servlet.jsp.tagext.TagLibraryValidator

java.lang.Object
|
+--javax.servlet.jsp.tagext.TagLibraryValidator
|
+--javax.servlet.jsp.jstl.tlv.PermittedTaglibsTLV
```

Description

A TagLibraryValidator class to allow a TLD to restrict what taglibs (in addition to itself) may be imported on a page where it's used.

This TLV supports the following initialization parameter:

- **permittedTaglibs**: A whitespace-separated list of URIs corresponding to tag libraries permitted to be imported on the page in addition to the tag library that references PermittedTaglibsTLV (which is allowed implicitly).

Member Summary

Constructors

[PermittedTaglibsTLV\(\)](#) 237

Methods

```
void release\(\) 237
validate\(java.lang.String prefix, java.lang.String uri,
    javax.servlet.jsp.tagext.ValidationMessage\[\]
javax.servlet.jsp.tagext.PageData page\\) 237
```

Inherited Member Summary

Methods inherited from class **Object**

[clone\(\)](#), [equals\(Object\)](#), [finalize\(\)](#), [getClass\(\)](#), [hashCode\(\)](#), [notify\(\)](#), [notifyAll\(\)](#), [toString\(\)](#), [wait\(\)](#), [wait\(long\)](#), [wait\(long, int\)](#)

Methods inherited from class **TagLibraryValidator**

[getInitParameters\(\)](#), [setInitParameters\(Map\)](#)

Constructors

PermittedTaglibsTLV()

```
public PermittedTaglibsTLV()
```

Methods

release()

```
public void release()
```

validate(String, String, PageData)

```
public javax.servlet.jsp.tagext.ValidationMessage[] validate(java.lang.String prefix,  
    java.lang.String uri, javax.servlet.jsp.tagext.PageData page)
```

javax.servlet.jsp.jstl.tlv ScriptFreeTLV

Declaration

```
public class ScriptFreeTLV extends javax.servlet.jsp.tagext.TagLibraryValidator

java.lang.Object
|
+--javax.servlet.jsp.tagext.TagLibraryValidator
|
+--javax.servlet.jsp.jstl.tlv.ScriptFreeTLV
```

Description

A TagLibraryValidator for enforcing restrictions against the use of JSP scripting elements.

This TLV supports four initialization parameters, for controlling which of the four types of scripting elements are allowed or prohibited:

- **allowDeclarations**: if true, indicates that declaration elements are not prohibited.
- **allowScriptlets**: if true, indicates that scriptlets are not prohibited
- **allowExpressions**: if true, indicates that top-level expression elements (i.e., expressions not associated with request-time attribute values) are not prohibited.
- **allowRTEExpressions**: if true, indicates that expression elements associated with request-time attribute values are not prohibited.

The default value for all for initialization parameters is false, indicating all forms of scripting elements are to be prohibited.

Member Summary

Constructors

[ScriptFreeTLV\(\)](#) 239

Methods

```
void setInitParameters(java.util.Map initParms) 239
void validate(java.lang.String prefix, java.lang.String uri,
    javax.servlet.jsp.tagext.PageData page) 239
javax.servlet.jsp.tagext.ValidationMessage[]
```

Inherited Member Summary

Methods inherited from class Object

[clone\(\)](#), [equals\(Object\)](#), [finalize\(\)](#), [getClass\(\)](#), [hashCode\(\)](#), [notify\(\)](#), [notifyAll\(\)](#), [toString\(\)](#), [wait\(\)](#), [wait\(long\)](#), [wait\(long, int\)](#)

Methods inherited from class TagLibraryValidator

[getInitParameters\(\)](#), [release\(\)](#)

Constructors

ScriptFreeTLV()

```
public ScriptFreeTLV()
```

Constructs a new validator instance. Initializes the parser factory to create non-validating, namespace-aware SAX parsers.

Methods

setInitParameters(Map)

```
public void setInitParameters(java.util.Map initParms)
```

Sets the values of the initialization parameters, as supplied in the TLD.

Overrides: setInitParameters in class TagLibraryValidator

Parameters:

initParms - a mapping from the names of the initialization parameters to their values, as specified in the TLD.

validate(String, String, PageData)

```
public javax.servlet.jsp.tagext.ValidationMessage[] validate(java.lang.String prefix,  
    java.lang.String uri, javax.servlet.jsp.tagext.PageData page)
```

Validates a single JSP page.

Overrides: validate in class TagLibraryValidator

Parameters:

prefix - the namespace prefix specified by the page for the custom tag library being validated.

uri - the URI specified by the page for the TLD of the custom tag library being validated.

page - a wrapper around the XML representation of the page being validated.

Returns: null, if the page is valid; otherwise, a ValidationMessage[] containing one or more messages indicating why the page is not valid.

Compatibility & Migration

This appendix provides information on compatibility between different versions of JSTL, as well as on how to migrate your web application to take advantage of the new features of the latest JSTL release.

A.1 JSTL 1.2 Backwards Compatibility

JSTL 1.2 is backwards compatible with JSTL 1.1. This means that a web-application that was developed to run with JSTL 1.1 won't require any modification when run with JSTL 1.2.

Note that JSTL is part of the Java EE platform as of the JSTL 1.2 version. A web application therefore does not need to bundle JSTL anymore when it runs on a web container that is Java EE technology compliant. Should JSTL be bundled with a web-application, it will simply be ignored as JSTL provided by the platform always takes precedence (see Section JSP.7.3.2, "TLD resource path" of the JSP specification).

A.2 JSTL 1.1 Backwards Compatibility

JSTL 1.1 is backwards compatible with JSTL 1.0. This means that a web-application that was developed to run with JSTL 1.0 won't require any modification when run with JSTL 1.1. Details explaining how this backwards compatibility is achieved are given in Section A.2.1 below.

If your application executes in an environment that has JSTL 1.1, it is however recommended that you migrate to JSTL 1.1 to take full advantage of the new capabilities it offers. Details on how to migrate your web-application from JSTL 1.0 to JSTL 1.1 are given in Section A.3.

A.2.1 How JSTL 1.1 Backwards Compatibility is Achieved

JSTL 1.0 requires JSP 1.2 (J2EE 1.3 platform). The key difference between JSTL 1.0 and JSTL 1.1 is that the expression language (EL) has moved from the JSTL specification to the JSP specification. The EL is therefore now part of the JSP 2.0 specification, and JSTL 1.1 requires JSP 2.0 (J2EE 1.4 platform).

A web application developed for JSP 1.2 has a servlet 2.3 deployment descriptor (web.xml). JSP 2.0 provides backwards compatibility for JSP 1.2 web applications by disabling by default the EL machinery (i.e. evaluation of EL expressions) when a web application has a servlet 2.3 deployment descriptor. A web application that uses JSTL 1.0 and which is deployed with a servlet 2.3 deployment descriptor therefore runs without any modification in a J2EE 1.4 environment because EL expressions are ignored by JSP 2.0, and JSTL 1.0 keeps evaluating them as was the case with JSP 1.2.

To support backwards compatibility, JSTL 1.1 introduces new URIs that must be specified to use the new capabilities offered in JSTL 1.1. Among these new capabilities is the evaluation of EL expressions being performed by the JSP 2.0 container rather than JSTL itself. The new URIs for JSTL 1.1 are as follows:

JSTL 1.1 Tag Libraries

Functional Area	URI	Prefix
core	http://java.sun.com/jsp/jstl/core	c
XML processing	http://java.sun.com/jsp/jstl/xml	x
I18N capable formatting	http://java.sun.com/jsp/jstl/fmt	fmt
relational db access (SQL)	http://java.sun.com/jsp/jstl/sql	sql

The new URIs are similar to the old JSTL 1.0 EL URIs, except that `jsp/` has been added in front of `jstl`, stressing JSTL's dependency on the JSP specification (which now "owns" the EL). It would have been desirable to move forward with the same EL URIs in JSTL 1.1, however this would have only been possible at the cost of losing full backwards compatibility. The JSTL Expert Group felt that maintaining backwards compatibility was more important than preserving the old URIs.

The JSTL 1.0 URIs are deprecated as of JSTL 1.1. If used, they should normally appear in a web application that has a servlet 2.3 deployment descriptor to disable the JSP 2.0 EL machinery. If used with a servlet 2.4 deployment descriptor, the JSP 2.0 EL machinery must be explicitly disabled for the pages where the JSTL 1.0 tag libraries are used. Consult the JSP specification for details.

A.3 Migrating to JSTL 1.1

To migrate from JSTL 1.0 to JSTL 1.1, so a web application can take advantage of the new features associated with JSTL 1.1, one must do the following:

- Migrate the web application deployment descriptor (web.xml) from servlet 2.3 to servlet 2.4.
 - See Servlet 2.4 specification for details
- Replace all the JSTL 1.0 EL & RT URIs by the new JSTL 1.1 URIs
- Escape all occurrences of “\${” in RT actions and template text.
 - See JSP 2.0 specification for details.

Changes

This appendix lists the changes in the JSTL specification. This appendix is non-normative.

B.1 JSTL 1.2 Maintenance Release

The goal of this maintenance release is to align the JSTL specification with the work done on the JavaServer Pages 2.1 and JavaServer Faces (Faces) 1.2 specifications. Also, as of this release (JSTL 1.2), JSTL is now part of the Java Enterprise Edition platform.

Iteration tags support for nested actions with deferred-values referring to the iteration variable

- The semantics of the standard actions `<c:forEach>` and `<c:forTokens>` are modified to allow the iteration tags to work seamlessly with nested JavaServer Faces actions. More specifically, `<c:forEach>` and `<c:forTokens>` now support nested actions with deferred-values referring to the iteration variable, as long as a deferred value has been specified for the 'items' attribute. See Section 6.2 “`<c:forEach>`” and Section 6.3 “`<c:forTokens>`”.

`<c:set>` support for deferred values

- The semantics of the standard action `<c:set>` have been modified to allow the action to accept a deferred-value. See Section 4.3 “`<c:set>`”.

Generics

- Since JSP 2.1 requires J2SE 5.0, we’ve modified the APIs that can take advantage of generics: `ScriptFreeTLV.setInitParameters()`

Minor corrections

- Example involving `<fmt:parseDate>` in section 9.9 was incorrect. A pattern has been added so the date can be parsed properly.
- Clarified the fact that the output of `<c:url>` won't work for the `url` attribute value of `<c:import>` for context relative URLs (URLs that start with a '/'). (section 7.4).

B.2 JSTL 1.1 Maintenance Release

As already stated in the JSTL 1.0 specification, the specification of the Expression Language (EL) first introduced in JSTL 1.0 is now moving into the JSP 2.0 specification. The primary goal of the JSTL 1.1 maintenance release is to synchronize the JSTL specification with the JSP 2.0 specification which now owns the EL. This maintenance release also addresses clarifications and corrections needed to the initial specification.

Expression Language moved to the JSP specification

- Necessary changes have been made all across the specification to reflect the fact that the Expression Language now belongs to the JSP specification (JSP 2.0). This includes having appendix A removed ("Appendix A - Expression Language Definition"), as well as having examples modified to take advantage of the fact that EL expressions can now be used in template text and do not require the use of the `<c:out>` action (unless the `escapeXml` or default features of `<c:out>` are required).

Compatibility and Migration

- New Appendix A provides information on compatibility between different versions of JSTL, as well as on how to migrate a web application to take advantage of the new features of the latest JSTL release.

Functions

- Since JSP 2.0 introduces EL functions, JSTL 1.1 defines a simple, standard set of functions that has been most often requested by page authors. This includes functions to get the size of a collection, as well as to perform common string manipulations. Functions are defined in the new Chapter 15.

Support for direct transfer from Reader -> out

- With JSP 2.0, displaying the content of a Reader object to "out" has been identified as an important use case, creating the need for a mechanism to handle a direct transfer from reader -> out. This is now provided as an extension of `<c:out>`.

Default values

- New section 2.9 has been added to describe how default values can be handled in a generic way in JSTL.

end attribute < begin attribute in iterator actions

- The spec used to constrain the end attribute to be greater than or equal to the begin attribute. It has now been relaxed to handle this situation according to common practices of modern programming languages (e.g. C++, Java, Perl). If end < begin, the loop will simply not be executed.

Character encoding support in <c:import>

- The way character encoding is handled for <c:import> has been corrected in Section 7.4.

Semantics of locales

- Clarified the fact that the semantics of locales in JSTL are the same as the ones defined by the class `java.util.Locale` (section 8.1). A consequence of this is that, as of J2SE 1.4, new language codes defined in ISO 639 (e.g. `he`, `yi`, `id`) will be returned as the old codes (e.g. `iw`, `ji`, `in`).

Correct the inconsistency between <fmt:message> and <fmt:formatXXX> when <fmt:message> is used with parametric replacement and a locale-less localization context

- If the localization context does not have any locale, the locale of the `java.text.MessageFormat` is set to the locale returned by the formatting locale lookup algorithm in section 9.3, except that the available formatting locales are given as the intersection of the number- and date- formatting locales. If this algorithm does not yield any locale, the locale of the `java.text.MessageFormat` is set to the runtime's default locale.

Null or empty values with formatting actions

- The behavior of <fmt:formatNumber> and <fmt:formatDate> (sections 9.7 and 9.9) has been clarified when value is null or empty.

Connection handling in SQL actions

- Clarifications have been made to the fact that SQL actions in JSTL always release connections to the database as quickly as possible (a connection is always closed by the time execution of the action responsible for opening it completes).

Context for XPath expression evaluations nested within <x:forEach>

- A new description subsection has been added to Section 12.6 to clarify how the context for XPath expression evaluations is obtained within <x:forEach>.

Align behavior of <x:forEach> with <c:forEach>

- Attributes `varStatus`, `begin`, `end`, and `step` have been added.

Default context node for XPath expression evaluations

- New section "11.1.6 Default Context Node" clarifies how the default context node for XPath expression evaluations is obtained.

Replace attributes that start with "xml"

- Names beginning with the string "xml" are reserved by the XML specification. New attribute `doc` has been added to `<x:parse>` to replace attribute `xml` that is now being deprecated. Also, new attributes `doc` and `docSystemId` have been added to `<x:transform>` to replace attributes `xml` and `xmlSystemId` that are now being deprecated.

Response Encoding

- The way formatting actions influence the encoding of the response has been clarified in sections 8.4 and 8.10. Repeated calls to `ServletResponse.setLocale()` will affect the character encoding of the response only if it has not already been set explicitly.

Java APIs

- The specification of the JSTL Java APIs is now generated directly from the Javadoc of the reference implementation and is consolidated within its own chapter (Chapter 16).

Minor corrections

- `status` has been corrected with `varStatus` in section 6.6.
- The resulting locale of examples 1 and 3 in Section 8.3.3 have been corrected.
- The syntax of `<sql:dateParam>` in Section 10.8 has been corrected.

B.3 Changes between Proposed Final Draft and Final Draft

Many typos and clarifications have been made to the specification. Clarifications and modifications worth noting include:

Preface

- Added typographical conventions.

Chapter 2 - Conventions

- When an action is required to throw an exception, there were two choices when no root cause was involved: `JspException` or `JspTagException`. The specification has now standardized on `JspException` everywhere in the spec (instead of `JspException` in some places (with root cause), and `JspTagException` in some others (no root cause)).

- Clarified the proper handling of constraints in section 2.7.
- Constants names now use “_” as word separators (e.g. FMT_FALLBACK_LOCALE)

Chapter 3 - Expression Language Overview

- Fixed example featuring the default attribute in section 3.6.

Chapter 4 - General-Purpose Actions

- Transparent conversion now supported on a value to be set as a bean property.
- Clarified behavior of `<c:set>` when value is null, so it has the same semantics as `<c:remove>`.
- Clarified the behavior of `<c:out>` when value is null.

Chapter 6 - Iterator Actions

- Corrected the name of method `setStatus()` to be `setVarStatus()`, as it should have been.
- Methods `next()`, `hasNext()`, `prepare()` of class `LoopTagSupport` are abstract methods.
- Method `hasNext()` of class `LoopTagSupport` returns boolean.
- Added protected fields `beginSpecified`, `endSpecified`, and `stepSpecified` to class `LoopTagSupport`.

Chapter 8 - I18N Actions

- Left over references to `javax.servlet.jsp.jstl.fmt.bundle` have been changed to `javax.servlet.jsp.jstl.fmt.localizationContext`.
- Added the three constructors to class `LocalizationContext` and clarified the behavior of methods `getResourceBundle()` and `getLocale()`.

Chapter 9 - Formatting Actions

- Clarified how the formatting pattern applies in `<fmt:number>` and `<fmt:parseNumber>`.

Chapter 10 - SQL Actions

- Clarified the handling of auto-commit mode and isolation level in `<sql:transaction>`.
- Clarified the handling of exceptions occurring during the execution of `<sql:transaction>`.
- Added clarification to `<sql:param>` when dealing with `String` values (only works for columns of text type).
- Clarified that if `dataSource` is null, a `JspException` is thrown for `<sql:query>`, `<sql:update>`, `<sql:transaction>`, and `<sql:setDataSource>`.

Chapters 11, 12, 13 - XML Actions

- Clarified “Null & Error Handling” for `<x:parse>` and `<x:transform>`
- In `<x:forEach>`, if `select` is empty, a `JspException` is now thrown.
- Added syntax without body content to `<x:if>`. It is now similar to `<c:if>`.
- Only `String` and `Reader` objects are now allowed for the `xml` attribute of `<x:parse>`.
- Clarified that DOM objects are supported as XPath variables.

Appendix A - Expression Language

- Alternative operators `&&`, `||`, and `!` were missing in some of the tables. They now appear along with their counterpart `and`, `or`, and `not`.
- Clarified the definition of integer and floating point literals.
- Removed division by 0 as an example of exception for arithmetic operators `/` and `%`.

B.4 Changes between Public Draft and Proposed Final Draft

Many typos and clarifications have been made to the specification. Major changes include:

Preface

- Added acknowledgements.

Chapter 1 - Introduction

- Clarified the fact that actions from EL- and RT- based libraries can be mixed together.

Chapter 2 - Conventions

- Clarified how actions throw exceptions.
- “Section 2.8 - Configuration Parameters” has been completely rewritten and is now titled “Configuration Data”. The way configuration data is handled in JSTL has been clarified and will now work properly with containers that implement JSP scopes via a single namespace.

Chapter 4 - Expression Language Support Actions

- Renamed the chapter to “General Purpose Actions”.
- Removed the restriction that the actions in this chapter are only available in the EL-based version of the library.

- Extended the scope of `<c:set>` so it supports setting a property of a target `JavaBeans` or `java.util.Map` object.

Chapter 7 - URL Related Actions

- Improved the error handling behavior of `<c:import>`
- `<c:url>` and `<c:redirect>` now append the context path to any relative URL that starts with `"/"`. Added new attribute `context` to properly handle foreign context URLs.

Chapter 8 - I18N Actions

- In the resource bundle lookup, the locale-less root resource bundle is now supported if neither the preferred locales nor the fallback locale yield a resource bundle match.
- `<fmt:locale>` has been renamed to `<fmt:setLocale>`.
- `<fmt:bundle>` no longer takes `'var'` and `'scope'`. Creating and storing an I18N localization context with a resource bundle in a `'var'` or scoped configuration variable is now done by the new `<fmt:setBundle>`.
- Logging is considered an implementation-specific (deployment) issue and has been removed from `<fmt:message>`'s description.
- A new class `LocalizationContext` has been defined which represents an I18N localization context containing a `java.util.ResourceBundle` and a `java.util.Locale`.
- `javax.servlet.jsp.jstl.fmt.basename` has been replaced with `javax.servlet.jsp.jstl.fmt.localizationContext`.

Chapter 9 - Formatting Actions

- Formatting actions nested inside a `<fmt:bundle>` no longer use that bundle's locale as their formatting locale, but the locale of the enclosing I18N localization context, which is the (possibly more specific) locale that led to the resource bundle match.
- `<fmt:timeZone>` no longer takes `'var'` and `'scope'`. Storing a time zone in a `'var'` or scoped configuration variable is now done by the new `<fmt:setTimeZone>`.
- `<fmt:formatNumber>` no longer uses the `"en"` locale to parse numeric values given as strings, but uses `Long.valueOf()` or `Double.valueOf()` instead.
- In `<fmt:parseNumber>`, `parseLocale`, which used to support string values only, now also supports values of type `java.util.Locale`.
- `<fmt:formatDate>` no longer supports literal values, and no longer has a body. Its `'value'` attribute is no longer optional, meaning the default behaviour of formatting the current time and date is no longer supported.
- In `<fmt:parseDate>`, `parseLocale`, which used to support string values only, now also supports values of type `java.util.Locale`.

- `<fmt:setLocale>`, formerly known as `<fmt:locale>`, now also accepts values of type `java.util.Locale` (in addition to string values).
- The runtime's default locale is no longer used as a fallback, since it is not guaranteed to be among the supported formatting locales.
- `<fmt:timeZone>` and the new `<fmt:setTimeZone>` now also accept values of type `java.util.TimeZone` (in addition to string values).

Chapter 10 - SQL Actions

- The configuration settings now include JDBC parameters.
- `<sql:driver>` has been renamed `<sql:setDataSource>`. It now supports attribute "password" as well as setting configuration variables.
- The keys in the Map objects returned by `Result.getRows()` are now case-insensitive. The motivation for this change is that some databases return column names as all-uppercase strings in the `ResultSet`, while others return them with the same upper/lowercase mix as was used in the `SELECT` statement.
- Method `Result.getRowsCount()` has been renamed to `Result.getRowCount()` to be compatible with naming conventions in J2SE.
- Method `Result.getMetaData()` as well as interface `ColumnMetaData` have been removed because handling of exceptions encountered when caching `ResultSetMetaData` is problematic. New method `Result.getColumnNames()` has been added to still provide easy access to column names.
- Exception message for `<sql:query>` and `<sql:update>` has been improved. It now includes the SQL statement and provides the caught exception as the root cause.
- Warning added in `<sql:transaction>` about the use of commit and rollback.
- JNDI resource path to a data source must now be specified as a relative path, just as is the case in a J2EE deployment descriptor.
- New `<sql:dateParam>` action added to properly support setting the values of parameter markers for values of type `java.util.Date`.
- The algorithm used by the SQL actions (`<sql:query>`, `<sql:update>`, `<sql:transaction>`) to access a database has been modified to support configuration settings for a `DataSource` as well as for the JDBC `DriverManager` facility.

Chapters 11, 12, 13 - XML Actions

- Removed the syntax with body content for `<x:set>`. This was introducing a potentially confusing mechanism for entering "dynamic" XPath expressions.
- URLs specified in `<x:parse>` and `<x:transform>` may now be absolute or relative URLs.
- Clarified the fact that `<x:parse>` and `<x:transform>` do not perform any validation against DTD's or Schemas.

- XPath scopes “page”, “request”, “session”, and “application” have been renamed “pageScope”, “requestScope”, “sessionScope”, and “applicationScope” to be the same as the names of implicit objects in the expression language.

Appendix A - Expression Language

- Implicit objects `page`, `request`, `session`, `application`, have been renamed `pageScope`, `requestScope`, `sessionScope`, `applicationScope`.
- Implicit object `params` has been renamed `paramValues`.
- Added implicit objects `header`, `headerValues`, `cookie`, and `initParam`.
- Coercion rules have been improved.
- New operator “empty” has been added.
- “eq” and “ne” have been added as alternatives to “==” and “!=”
- “&&”, “||”, “!” have been added as alternatives to “and”, “or”, and “not”.

