

Package ‘CSHShydRology’

September 3, 2019

Type Package

Title Canadian hydrological analyses

Version 1.1.0

Date 2019-09-03

Description A collection of user submitted functions to aid in the analysis of hydrological data.

License AGPL-3 | file LICENSE

URL <https://github.com/CSHS-hydRology/CSHShydRology>

Depends R (>= 3.1)

Imports fields,
Kendall,
lubridate (>= 1.3),
plotrix,
timeDate,
stringr,
jsonlite,
curl

Suggests knitr,
testthat,
rmarkdown

VignetteBuilder knitr

LazyData true

RoxygenNote 6.1.1

R topics documented:

CSHShydRology-package	2
Basic_data_manipulation-functions	3
ch_binned_MannWhitney	3
ch_booth_plot	5
ch_fdcurve	6
ch_flow_raster	7

ch_flow_raster_qa	8
ch_flow_raster_trend	9
ch_get_AHCCD_monthly	10
ch_get_peaks	12
ch_get_wscstation	13
ch_hydrograph_plot	14
ch_polar_plot	16
ch_polar_plot_prep	17
ch_read_AHCCD_daily	19
ch_read_AHCCD_monthly	20
ch_read_ECDE_flows	21
ch_regime_plot	21
ch_wtr_yr	22
HYDAT_list	23
StatisticalHydrology-functions	24
Visualization-functions	24
W05AA008	25
Index	26

CSHShydRology-package *Functions for Canadian hydrological analyses*

Description

CSHShydRology is intended for the use of hydrologists, particularly those in Canada. It will contain functions which focus on the use of Canadian data sets, such as those from Environment Canada. The package will also contain functions which are suited to Canadian hydrology, such as the important cold-region hydrological processes. **CSHShydRology** will also contain functions which work with Canadian hydrological models, such as Raven, CRHM, Watflood, and MESH.

This packages has been developed with the assistance of the Canadian Society for Hydrological Sciences (CSHS) <https://cwra.org/en/branches/affiliates/cshs-a> which is an affiliated society of the Canadian Water Resources Association (CWRA) cwra.org.

The **CSHShydRology** will contain functions grouped into several themes, including:

Statistical hydrology trend detection, data screening, frequency analysis, regionalization

Basic data manipulations input/conversion/adapter functions, missing data infilling

Visualization data visualization, standardized plotting functions

Spatial hydrology basin delineation, landscape data analysis, working with GIS

Streamflow measurement analysis rating curve analysis, velocity profiles, naturalization

Network design/analysis homogeneity assessment

Ecohydrology fisheries and ecological analysis

Wrappers/unwrappers between other packages and **CSHShydRology**

References

To cite **CSHShydRology** in publications, use the command `citation("CSHShydRology")` to get the current version of the citation.

Basic_data_manipulation-functions

Basic data manipulation functions

Description

These functions read in or convert values among formats

ch_read_ECDE_flows Reads a file of WSC daily flows from ECDataExplorer

ch_get_wscstation Reads station information from a data file produced by ECDE

ch_get_AHCCD_monthly Downloads monthly Adjusted and Homogenized Canadian Climate Data (AHCCD) values

ch_read_AHCCD_daily Reads file of daily AHCCD values

ch_read_AHCCD_monthly Reads file of monthly AHCCD values

ch_binned_MannWhitney *Compares two time periods of data using Mann-Whitney test*

Description

It bins data based upon a specified size, extracting data for two time periods and tests for change between two such periods. Result can be passed to `ch_polar_plot` for visualization

Usage

```
ch_binned_MannWhitney(mdata, step, range1, range2, ptest = 0.05,
  station_ID = "", station_name = "", variable = "discharge")
```

Arguments

<code>mdata</code>	A data frame of hydrometric data. Must contain the variables Date and Flow.
<code>step</code>	An integer indicating the degree of smoothing eg. 1, 5, 11.
<code>range1</code>	The first and last year of first period, as <code>c(first, last)</code>
<code>range2</code>	The first and last year of second period as <code>codec(first, last)</code>
<code>ptest</code>	The significance level. The default is 0.05.
<code>station_ID</code>	Optional ID of station.
<code>station_name</code>	Optional name of station.
<code>variable</code>	Name of variable. Default is 'discharge'

Value

Returns a list containing:

StationID ID of station

Station_lname Name of station

bin_width Smoothing time step

range1 range1 years

range2 range2 years

p_used p value used

fail TRUE if test failed due to missing values

bin_method method used for binning

test_method Mann-Whitney U

series a data frame containing:

period period numbers i.e. 1:365/step

period1 median values for each bin in period 1

period2 median values for each bin in period 2

mwu Mann Whitney U-statistic for each bin between the two periods

prob probability of U for each period

code significance codes for each bin

Author(s)

Paul Whitfield <paul.h.whitfield@gmail.com>

References

Whitfield, P.H., Cannon, A.J., 2000. Recent variations in climate and hydrology in Canada. Canadian Water Resources Journal 25: 19-65.

See Also

[ch_polar_plot](#) [ch_polar_plot_prep](#)

Examples

```
## Not run:
# fails due to missing data in both periods
range1 <- c(1960,1969)
range2 <- c(1990,1999)
b_MW <- ch_binned_MannWhitney(W05AA008, step=5, range1, range2, ptest=0.05)
## End(Not run)

range1 <- c(1970,1979)
range2 <- c(1990,1999)
b_MW <- ch_binned_MannWhitney(W05AA008, step = 5, range1, range2,
ptest = 0.05, station_ID = "05AA008", station_name= "Crowsnest River at Frank")
```

ch_booth_plot	<i>Create a Booth plot of peaks over a threshold</i>
---------------	--

Description

A Booth plot is a plot of peaks over threshold flood events with duration on the horizontal and either magnitude (default) or volume on the vertical axis

Usage

```
ch_booth_plot(events, threshold, title, type = "mag", colour1 = 1,
              colour2 = 1)
```

Arguments

events	A data frame of POT events from the function <code>ch_get_peaks</code>
threshold	The threshold used by <code>ch_get_peaks</code>
title	Plot title
type	The plot type, either 'mag' (magnitude, the default) or 'vol' (volume)
colour1	A vector of length 12 with line colours of rings or symbols. Defaults to those used by Booth.
colour2	A vector of length 12 with fill colours of rings or symbols. Defaults to those used by Booth.

Value

No value is returned; a standard R graphic is created.

References

Booth, E.G., Mount, J.F., Viers, J.H. 2006. Hydrologic Variability of the Cosumnes River Floodplain. *San Francisco Estuary & Watershed Science* 4:21.

Whitfield, P.H., and J.W. Pomeroy. 2016. Changes to flood peaks of a mountain river: implications for analysis of the 2013 flood in the Upper Bow River, Canada. *Hydrological Processes* 30:4657-73. doi: 10.1002/hyp.10957.

See Also

[ch_get_peaks](#)

Examples

```
threshold <- 0.1 * max(W05AA008$Flow) # arbitrary threshold
peaks <- ch_get_peaks(W05AA008, threshold)
events <- peaks$POTevents
ch_booth_plot(events, threshold, title = "05AA008", type='mag')
ch_booth_plot(events, threshold, title = "05AA008", type='vol')
```

ch_fdcurve

*Plot Flow Duration Curve***Description**

A flow duration curve is a plot of flow magnitude against exceedance probability. The plot may contain the Gustard Curves or they can be omitted. The default is for curves to be plotted against probability, but an option is to plot against the normalized exceedance probability. In that case, the x axis represents a normal distribution.

Usage

```
ch_fdcurve(flow, title = "", normal = FALSE, gust = TRUE)
```

Arguments

flow	Vector containing daily flows
title	The plot title
normal	If normal = TRUE then exceedance probability is normalized. Default is FALSE
gust	If TRUE (the default), adds the curves from Gustard et al 1992

Value

Plots the flow durations and returns a data frame containing the exceedance probability and flow

Author(s)

Paul Whitfield <paul.h.whitfield@gmail.com>

References

Gustard, A., A. Bullock, and J.M. Dixon. 1992. Low flow estimation in the United Kingdom. Institute of Hydrology, 292. Wallingford: Institute of Hydrology.

Vogel, R.M., and N.M. Fennessy. 1994. Flow-duration curves. I: New Interpretation and confidence intervals. Journal of Water Resources Planning and Management ASCE 120:485-504.

Examples

```
flow <- W05AA008$Flow
# plot with Gustard 1992 curves
test <- ch_fdcurve(flow, title = "Station", normal = FALSE, gust = TRUE)

# plot with normalized exceedance probability
test <- ch_fdcurve(flow, title = "Station", normal = TRUE, gust = FALSE)
```

ch_flow_raster	<i>Raster plot of streamflows</i>
----------------	-----------------------------------

Description

Produces a raster plot: years x day of year, showing magnitude of flows. This produces a plot showing the flow data in colours, showing different context than in a hydrograph. High flows are in warm colours

Usage

```
ch_flow_raster(dframe, title = "", rastercolours = c("lightblue",  
  "cyan", "blue", "slateblue", "orange", "red"))
```

Arguments

dframe	A data frame of hydrometric data. Must contain the variables Date and Flow.
title	The (optional) title for the plot
rastercolours	A vector of colours used for the raster plot. The default is c("lightblue", "cyan", "blue", "slateblue", "orange", "red")

Value

No value is returned; a standard R graphic is created.

Author(s)

Paul Whitfield <paul.h.whitfield@gmail.com>

See Also

[ch_flow_raster_trend](#) [ch_flow_raster_qa](#)

Examples

```
ch_flow_raster(W05AA008)
```

ch_flow_raster_qa

Raster plot of streamflows with WSC quality flags

Description

Produces a raster plot of years x day of year showing the flow data in grayscale overlain by the Water Survey of Canada quality flags. Colours are consistent with ECDataExplorer. Raster layout lets the use see the flags in a different context than in a hydrograph. The data flags are:

A (Partial) green

B (Below Ice) blue

D (Dry) yellow

E (Estimated) red

Usage

```
ch_flow_raster_qa(dframe, title = "")
```

Arguments

dframe	A data frame of WSC hydrometric data. Must contain the variables Date, Flow and SYM which is the WSC data flag symbol.
title	The (optional) title for the plot

Value

No value is returned; a standard R graphic is created.

Author(s)

Paul Whitfield <paul.h.whitfield@gmail.com>

See Also

[ch_flow_raster_trend](#) [ch_flow_raster](#)

Examples

```
ch_flow_raster_qa(W05AA008, "Station W05AA008")
```

ch_flow_raster_trend *Raster plot and simple trends of observed streamflows*

Description

Creates a raster plot plus trend plots for day of year, and over time which may be binned by a number of days

Usage

```
ch_flow_raster_trend(date, flow, step = 5, stationID = "",
  title = "", missing = FALSE, colours = c("lightblue", "cyan",
    "blue", "slateblue", "darkblue", "red"))
```

Arguments

date	A numeric vector of the date as an R date. Must be same length as the flow
flow	A numeric vector of daily streamflows
step	An integer indicating the degree of smoothing eg. 1, 5, 11.
stationID	Station ID number, e.g. "05BB001". This value is optional, but is included in the output to help you identify the results.
title	Title of the plot
missing	If FALSE years with missing data are excluded. If TRUE partial years are included.
colours	A vector of colours used for the raster plot. The default is c("lightblue", "cyan", "blue", "slateblue", "darkblue", "red")

Details

The plot contains four panels based upon binned data:

1. The annual maximum, minimum, and median dlow with a trend test number for each period: red arrows indicate decreases, blue arrows indicate increases.
2. The scale bar for the colours used in the raster plot,
3. The rasterplot with a colour for each period and each year where data exist, and
4. A time series plot of the minimum, median, and maximum annual bin values. If there is no trend ($p > 0.05$) the points are black. Decreasing trend are in red, increasing trends are in blue..

Value

a list containing:

stationID Station ID eg 05BB001

missing How missing values were used FALSE=used, TRUE=removed

step number of days in a bin

periods number of periods in a year
period period numbers i.e. 1:365/step
bins values for each period in each year
med_period median for each period
max_period maximum for each period
min_period minimum for each period
tau_period Kendall's Tau for each period
prob_period probability of Tau for each period
year years spanning the data
median_year median bin for each year
max_year maximum bin for each year
min_year minimum bin for each year
tau_median_year value of tau and probability for median_year
tau_maximum_year value of tau and probability for max_year
tau_minimum_year value of tau and probability for min_year

Author(s)

Paul Whitfield <paul.h.whitfield@gmail.com>

See Also

[ch_flow_raster](#)

Examples

```
mdoy <- doys(W05AA008$Date)
mplot <- ch_flow_raster_trend(W05AA008$Date, W05AA008$Flow, step = 5, station = "05AA008")
```

ch_get_AHCCD_monthly *Retrieve AHCCD data from EC datamart*

Description

Retrieve AHCCD data from EC datamart

Usage

```
ch_get_AHCCD_monthly(station, province, variable,
  url = "http://dd.weather.gc.ca/climate/ahccd/geojson/historical/monthly/")
```

Arguments

station	Required. The station number - either as numeric or as a string.
province	Required. Name of province/territory. Must one of AB, BC, MB, NB, NL, NS, NT, NU, ON, PE, QC, SK, YT.
variable	Required. Must be one of variable meaning PCP total precipitation RA rainfall SN snowfall TMAX max air temp TMEAN mean air temp TMIN max air temp PSFC surface air pressure SFCWND surface wind speed SLP sea level pressure
url	Required. The default url currently works to access the data on the Environment Canada server. The url can be changed in case the site is moved.

Value

Returns a data frame with the monthly values and associated variables.

Note

Not all variables are available at all stations. Attempting to retrieve a non-existent variable will result in an error being returned.

Author(s)

Kevin Shook

References

Use of the data must cite *Mekis, E and L.A. Vincent, 2011: An overview of the second generation adjusted daily temperature and precipitation dataset for trend analysis in Canada. Atmosphere-Ocean, 49 (2), 163-177.*

See Also

[ch_read_AHCCD_daily](#) [ch_read_AHCCD_monthly](#)

Examples

```
stoon_monthly_precip <- ch_get_AHCCD_monthly("4057120", "SK", "PCP")
```

ch_get_peaks	<i>Extracts peak flows over a threshold</i>
--------------	---

Description

This function is development code being shared as is. It is expected that the user will be interested in the dataframe returned for POT analysis and for plotting (i.e. Booth_plots).

Usage

```
ch_get_peaks(dataframe, threshold)
```

Arguments

dataframe	a data frame of streamflow data containing columns named 'Date' and 'Flow'
threshold	a value for the threshold. Values above the threshold are tested for peaks.

Details

This function retrieves peaks greater than the prescribed threshold. It returns a dataframe of peak characteristics suitable for subsequent analysis.

The portion under development is the It also returns a list of the flows during an event with the values of the three preceeding dates and three subsequent dates.

Value

a list containing:

POTevents a dataframe contining details of the events

events a vector with the value 0 when the flow is below the threshold and 1 when above.

event_num a vector with the value 0 when the flow is below a threshold or the index of the events when the threshold was exceeded. i.e. 1,2,3, etc

st_date start date of events

case a list of the flows in each individual event (see details for more information)

The POTevents dataframe contains five columns: st_date (starting date), max_date (date of maximum in the event), max (maximum discharge), volume (volume of the event), and duration (in days).

The case list contains the flows during an event and also for three preceeding and subsequent days. The lists range from seven to n days in length.

References

Burn, D.H., Whitfield, P.H., Sharif, M., 2016. Identification of changes in floods and flood regimes in Canada using a peaks over threshold approach. *Hydrological Processes*, 39: 3303-3314. DOI:10.1002/hyp.10861

Whitfield, P.H., and J.W. Pomeroy. 2016. Changes to flood peaks of a mountain river: implications for analysis of the 2013 flood in the Upper Bow River, Canada. *Hydrological Processes* 30:4657-73. doi: 10.1002/hyp.10957.

See Also[ch_booth_plot](#)**Examples**

```
threshold <- 0.9*max(W05AA008$Flow) # arbitrary threshold
my_peaks <- ch_get_peaks(W05AA008, threshold)
str(my_peaks)
```

ch_get_wscstation	<i>Reads station information from a data file produced by ECDE Retrieves station information for an individual Water Survey of Canada site, adds a text string at position 21 that combines key elements for a title.</i>
-------------------	---

Description

Reads station information from a data file produced by ECDE Retrieves station information for an individual Water Survey of Canada site, adds a text string at position 21 that combines key elements for a title.

Usage

```
ch_get_wscstation(stnID, stn)
```

Arguments

stnID	A Water Survey of Canada station number
stn	a data frame of station information from ECDataExplorer. The data frame 'HYDAT_list' is supplied with this package.

Value

Returns a data frame with 21 variables

- Station StationID
- StationName Station Name
- HYDStatus Active or Discontinued
- Prov Province
- Latitude
- Longitude
- DrainageArea km2
- Years # of years with data
- From Start Year
- To End Year

- Reg. Regulated
- Flow if TRUE/Yes
- Level if TRUE/Yes
- Sed if TRUE/Yes
- OperSched Continuous or Seasonal
- RealTime if TRUE/Yes
- RHBN if TRUE/Yes is in the reference hydrologic basin network
- Region if TRUE/Yes is in the reference hydrologic basin network
- Datum if TRUE/Yes is in the reference hydrologic basin network
- Operator if TRUE/Yes is in the reference hydrologic basin network
- Station_Iname Added field combines ID,Name,Province and if RHBN an * is added

Author(s)

Paul Whitfield <paul.h.whitfield@gmail.com>

Examples

```
df <- HYDAT_list
s_info <- ch_get_wscstation("05BB001", df)
title <- s_info[21]
print(title)
```

ch_hydrograph_plot	<i>Plot hydrographs</i>
--------------------	-------------------------

Description

Creates a hydrograph plot for simulated, observed, and inflow hydrograph series, including precipitation if provided. The secondary y axis will be used to plot the precip time series. The function assumes that the supplied time series have the same length and duration in time. If this is not true, then the defined period or period calculated from the first available flow series will be used to determine the plotting limits in time. If the data is taken from output from the **Raven** model, this is not a concern. The supplied time series should be in **xts** format, which can be obtained directly by using the `hyd.extract` function in the package **RavenR**. Note that a plot title is purposely omitted in order to allow the automatic generation of plot titles.

Usage

```
ch_hydrograph_plot(flows = NULL, precip = NULL, prd = NULL,
  winter_shading = FALSE, range_mult_flow = NULL,
  range_mult_precip = 1.5, flow_labels = NULL,
  ylabel = "Flow [m3/s]", precip_label = "Precipitation [mm]",
  leg_pos = NULL, leg_box = NULL, zero_axis = T,
  plot_mode = "base")
```

Arguments

flows	data frame of flows to plot
precip	data frame of precipitation values to plot
prd	period to use in plotting
winter_shading	optionally adds a transparent cyan shading for the December 1st to March 31st period in each year that is plotted. Default is FALSE.
range_mult_flow	range multiplier for max value in hydrograph. This is useful in preventing overlap if precip is also plotted. This value should not be less than 1.0, otherwise the values will be cutoff in the plot.
range_mult_precip	range multiplier for max value in precipitation plot (default 1.5)
flow_labels	string vector of labels for flow values
ylabel	text label for y-axis of the plot (default 'Flow [m3/s]')
precip_label	text label for precipitation y-axis (default 'Precipitation [mm]')
leg_pos	string specifying legend placement on plot e.g. 'topleft', 'right', etc., and is consistent with the legend function options. If NULL, the function will place the legend left, if precip added, on the topleft otherwise).
leg_box	boolean on whether to put legend in an opaque white box or not. If NULL (the default), the function will automatically not use a white box and leave the background of the legend transparent.
zero_axis	fixes the y axis to start exactly at zero (default TRUE). By default, R will plot the values with a small buffer for presentation. Be warned that if this option is set to TRUE, the minimum value is set to zero without checking if any flow values are less than zero. This option should not be used for reservoir stage plotting, since most reservoir stage is typically reported as an elevation.
plot_mode	plot mode as 'base' or 'ggplot'. Currently only 'base' plot type is supported, 'ggplot' is under construction.

Value

Returns TRUE if the function is executed properly.

Author(s)

Robert Chlumsky <rchlumsk@gmail.com>

Examples

```
# example with synthetic random data
dd <- seq.Date(as.Date("2010-10-01"), as.Date("2013-09-30"), by = 1)
x <- abs(rnorm(length(dd)))
y <- abs(rnorm(length(dd))) * x
df <- data.frame("Date" = dd, x, y)
myprd <- "2011-10-01/2012-09-30"
```

```
precip <- data.frame("Date" = dd, "precip" = abs(rnorm(length(dd))) * 10)

# basic hydrograph plot
ch_hydrograph_plot(flows = df, winter_shading = FALSE)

# with different labels
ch_hydrograph_plot(flows = df, winter_shading = FALSE, flow_labels = c("simulated", "observed"))

# with a few more options turned on
ch_hydrograph_plot(flows = df, precip = precip)

# increase the plot ranges to separate flows and precip; add a legend box
ch_hydrograph_plot(flows = df, precip = precip, range_mult_flow = 1.7,
  range_mult_precip = 2, leg_box = TRUE)
```

ch_polar_plot	<i>Polar plot of daily streamflows</i>
---------------	--

Description

Produces a polar plot similar to that used in *Whitfield and Cannon, 2000*. It uses output from the function `ch_binned_MannWhitney` or a data structure created using the function `ch_polar_plot_prep`.

Usage

```
ch_polar_plot(bmw, lcol1 = c("black", "gray50"), lcol2 = c("black",
  "gray50"), lfill = c("yellow", "green"), lsig = c("red", "blue"))
```

Arguments

bmw	output from <code>binned_MannWhitney</code>
lcol1	line colour, default is <code>c("black", "gray50")</code>
lcol2	point colour, default is <code>c("black", "gray50")</code>
lfill	fill colour, default is <code>c("yellow", "green")</code>
lsig	significance symbol colour, default is <code>("red", "blue")</code>

Value

No value is returned; a standard R graphic is created.

Author(s)

Paul Whitfield <paul.h.whitfield@gmail.com>

References

Whitfield, P.H. and A.J. Cannon. 2000. Polar plotting of seasonal hydrologic and climatic data. Northwest Science 74: 76-80.

Whitfield, P.H., Cannon, A.J., 2000. Recent variations in climate and hydrology in Canada. Canadian Water Resources Journal 25: 19-65.

See Also

[ch_binned_MannWhitney](#) [ch_polar_plot_prep](#)

Examples

```
range1 <- c(1970,1979)
range2 <- c(1990,1999)
b_MW <- ch_binned_MannWhitney(W05AA008, step = 5, range1, range2,
ptest = 0.05, station_ID = "05AA008", station_name = "Crowsnest River at Frank")
ch_polar_plot(b_MW)
```

ch_polar_plot_prep	<i>Creates a data structure to be passed to ch_polar_plot.</i>
--------------------	--

Description

Could be used to move data from a different type of analysis different to the binned_MannWhitney function which uses flows. The two series need to be of the same length and their length is related to the step size. For examples 73 periods links to 5 day periods.

Usage

```
ch_polar_plot_prep(station, plot_title, step, x0, x1, stat, prob, test_s,
  variable = "discharge", bin_method = "unstated",
  test_method = "unstated", lline1 = "Period 1", lline2 = "Period 2",
  pvalue = 0.05)
```

Arguments

station	Typically a station number
plot_title	Polar plot title - usually a station name
step	The number of days binned
x0	Time series of length n for a single seasonal cycle
x1	Time series of length n for a single seasonal cycle
stat	Time series of length n for statistical test value for each bin
prob	Time series of length n of probability of test value
test_s	Vector with values of -1, 0, 1 for significance, -1 negative, 1 positive, 0 not significant

<code>variable</code>	Name of variable plotted. Default is "discharge"
<code>bin_method</code>	Default is "unstated"
<code>test_method</code>	Default is "unstated"
<code>l1line1</code>	Names of first period, default is "Period 1"
<code>l1line2</code>	Names of second period, default is "Period 2"
<code>pvalue</code>	Value of p used. Default is 0.05

Value

Returns a list containing:

StationID ID of station

Station_lname Name of station

variable Name of variable

bin_width Smoothing time step

range1 range1 years

range2 range2 years

p_used p value used

fail TRUE if test failed due to missing values

bin_method method used for binning

test_method Mann-Whitney U

series a data frame containing:

period period numbers i.e. 1:365/step

period1 median values for each bin in period 1

period2 median values for each bin in period 2

mwu Mann Whitney U-statistic for each bin between the two periods

prob probability of U for each period

code significance codes for each bin

Author(s)

Paul Whitfield <paul.h.whitfield@gmail.com>

References

Whitfield, P.H. and A.J. Cannon. 2000. Polar plotting of seasonal hydrologic and climatic data. Northwest Science 74: 76-80.

Whitfield, P.H., Cannon, A.J., 2000. Recent variations in climate and hydrology in Canada. Canadian Water Resources Journal 25: 19-65.

See Also

[ch_binned_MannWhitney](#) [ch_polar_plot](#)

ch_read_AHCCD_daily	<i>Reads AHCCD daily file</i>
---------------------	-------------------------------

Description

This program reads an Adjusted and Homogenized Canadian Climate Data (AHCCD) of daily precipitation or temperatures. The values are arranged as month x day, which makes them difficult to read using standard R functions.

Usage

```
ch_read_AHCCD_daily(daily_file)
```

Arguments

daily_file	Required. Name of the file to be read.
------------	--

Value

If successful, returns the values in a dataframe, consisting of the date, the value and the data code.
If unsuccessful, returns the value FALSE.

Author(s)

Kevin Shook

References

Monthly AHCCD data are available from <http://www.ec.gc.ca/dccha-ahccd>. Daily values must be requested. Any use of the data must cite *Mekis, E and L.A. Vincent, 2011: An overview of the second generation adjusted daily precipitation dataset for trend analysis in Canada. Atmosphere-Ocean, 49 (2), 163-177.*

See Also

[ch_read_AHCCD_monthly](#) [ch_get_AHCCD_monthly](#)

Examples

```
## Not run:  
stoon_daily_tmax <- ch_read_AHCCD_daily("dx40657120.txt")  
## End(Not run)
```

ch_read_AHCCD_monthly *Reads AHCCD monthly file*

Description

This program reads an Adjusted and Homogenized Canadian Climate Data (AHCCD) data of precipitation or temperatures. The values are arranged as year x month, which makes them difficult to read using standard R functions.

Usage

```
ch_read_AHCCD_monthly(monthly_file = NULL)
```

Arguments

monthly_file Required. Name of the file to be read.

Value

If successful, returns the values in a dataframe, consisting of the year, the month, the value and the data code. The meanings of the codes can be found in the

Author(s)

Kevin Shook

References

Monthly AHCCD data are available from <https://www.canada.ca/en/environment-climate-change/services/climate-change/science-research-data/climate-trends-variability/adjusted-homogenized-canada-surface-air-temperature-access.html>. Any use of the data must cite Mekis, E and L.A. Vincent, 2011: An overview of the second generation adjusted daily temperature and precipitation dataset for trend analysis in Canada. *Atmosphere-Ocean*, 49 (2), 163-177.

See Also

[ch_read_AHCCD_daily](#) [ch_get_AHCCD_monthly](#)

Examples

```
## Not run:
Stoon_monthly_precip <- ch_read_AHCCD_monthly("mt4057120.txt")
NB_monthly_tmean <- ch_read_AHCCD_monthly("mm4045695.txt")
## End(Not run)
```

ch_read_ECDE_flows	<i>Reads a file of WSC daily flows from ECDataExplorer Reads in a file WSC daily flows as returned from the program ECDataExplorer, and omits the last 3 lines as these contain the data disclaimer.</i>
--------------------	--

Description

Reads a file of WSC daily flows from ECDataExplorer Reads in a file WSC daily flows as returned from the program ECDataExplorer, and omits the last 3 lines as these contain the data disclaimer.

Usage

```
ch_read_ECDE_flows(filename)
```

Arguments

filename	Datafile retrieved from ECDataExplorer
----------	--

Value

Returns a dataframe with the last three rows removed and the Date as Date

Author(s)

Paul Whitfield <paul.h.whitfield@gmail.com>

Examples

```
mfile <- system.file("extdata", "04JD005_Daily_Flow_ts.csv", package = "CSHShydRology")
mdata <- ch_read_ECDE_flows(mfile)
```

ch_regime_plot	<i>Plots the regime of daily streamflows</i>
----------------	--

Description

Produces a regime hydrograph similar to that in the reference. It shows the flow quantiles for each day of the year and the maximum and minimum. Parameters can be set to change colours and fix the y scale to allow plots of same scale to be produced.

Usage

```
ch_regime_plot(date, flow, title = "", wyear = 1, colour = TRUE,
  mx = 1)
```

Arguments

date	Vector of dates
flow	Vector of daily streamflows. Must be the same length as date
title	Text to be used as the graph title
wyear	Beginning month of water year. USe wyear = 10 for October water year, wyear = 1 for calendar year
colour	Logical. If TRUE plot is in colour, if FALSE plot is grayscale
mx	The maximum y value; if mx = 1 then maximum value of the flows is used to set the maximum y-axis value. The value of mx can be specified to produce a series of plots with the same scale.

Value

No value is returned; a standard R graphic is created.

Author(s)

Paul Whitfield

References

MacCulloch, G. and P. H. Whitfield (2012). Towards a Stream Classification System for the Canadian Prairie Provinces. Canadian Water Resources Journal 37: 311-332.

Examples

```
ch_regime_plot(W05AA008$Date, W05AA008$Flow, title = "05AA008", colour = TRUE, wyear = 10)
```

ch_wtr_yr	<i>Designation of the water year</i>
-----------	--------------------------------------

Description

Display water year

Usage

```
ch_wtr_yr(dates, start_month = 10)
```

Arguments

dates	A vector of dates with actual year
start_month	Month in which the year starts (defaults to October)

Value

Year starting in start_month

Source

<http://stackoverflow.com/questions/27626533/r-create-function-to-add-water-year-column>

Examples

```
date <- seq(as.Date("1910/1/1"), as.Date("1912/1/1"), "days")
wtr_yr_date <- ch_wtr_yr(dates=date, start_month=10)
data.frame(wtr_yr_date, date)
```

HYDAT_list

HYDAT_list

Description

A dataframe of station information, as extracted from the EC Data Explorer

Usage

```
HYDAT_list
```

Format

A dataframe with 7791 rows and 20 columns.

Source

Water Survey of Canada

Variables:

- Station StationID
- StationName Station Name
- HYDStatus Active or Discontinued
- Prov Province
- Latitude
- Longitude
- DrainageArea km2
- Years # of years with data
- From Start Year
- To End Year
- Reg. Regulated

- Flow if TRUE/Yes
- Level if TRUE/Yes
- Sed if TRUE/Yes
- OperSched Continuous or Seasonal
- RealTime if TRUE/Yes
- RHBN if TRUE/Yes is in the reference hydrologic basin network
- Region if TRUE/Yes is in the reference hydrologic basin network
- Datum if TRUE/Yes is in the reference hydrologic basin network
- Operator if TRUE/Yes is in the reference hydrologic basin network
- Station_Iname Added field combines ID,Name,Province and if RHBN an * is added

StatisticalHydrology-functions

Statistical analysis functions

Description

These functions perform statistical analyses

ch_binned_MannWhitney Compares two time periods of data using Mann-Whitney test

ch_fdcurve Finds flow exceedence probabilities

ch_get_peaks Finds peak flows over a specified threshold

Visualization-functions

Visualization functions

Description

These functions are primarily intended for graphing, although some analyses may also be done.

ch_booth_plot Plot of peaks over a threshold

ch_flow_raster Raster plot of streamflows

ch_flow_raster_qa Raster plot of streamflows with WSC quality flags

ch_flow_raster_trend Raster plot and simple trends of observed streamflows

ch_hydrograph_plot Plots hydrographs and/or precipitation

ch_polar_plot Polar plot of daily streamflows

ch_regime_plot Plots the regime of daily streamflows

W05AA008	W05AA008
----------	----------

Description

A dataframe of Water Survey of Canada (WSC) daily flows for station W05AA008, CROWSNEST RIVER AT FRANK Alberta.

Usage

W05AA008

Format

A dataframe with 25252 rows and 5 columns spanning the period 1910-2013.

Source

Water Survey of Canada

Variables:

- ID StationID
- PARAMParameter 1=Flow, 2=Level
- DateR date
- FlowDaily flow in m³/s
- SYMWater Survey FLags A, B, D, E

Index

*Topic **datasets**

HYDAT_list, [23](#)

W05AA008, [25](#)

*Topic **hydrograph**

ch_hydrograph_plot, [14](#)

*Topic **plot**

ch_booth_plot, [5](#)

ch_fdcurve, [6](#)

ch_flow_raster_trend, [9](#)

ch_hydrograph_plot, [14](#)

ch_polar_plot, [16](#)

Basic_data_manipulation-functions, [3](#)

ch_binned_MannWhitney, [3](#), [17](#), [18](#)

ch_booth_plot, [5](#), [13](#)

ch_fdcurve, [6](#)

ch_flow_raster, [7](#), [8](#), [10](#)

ch_flow_raster_qa, [7](#), [8](#)

ch_flow_raster_trend, [7](#), [8](#), [9](#)

ch_get_AHCCD_monthly, [10](#), [19](#), [20](#)

ch_get_peaks, [5](#), [12](#)

ch_get_wscstation, [13](#)

ch_hydrograph_plot, [14](#)

ch_polar_plot, [4](#), [16](#), [18](#)

ch_polar_plot_prep, [4](#), [17](#), [17](#)

ch_read_AHCCD_daily, [11](#), [19](#), [20](#)

ch_read_AHCCD_monthly, [11](#), [19](#), [20](#)

ch_read_ECDE_flows, [21](#)

ch_regime_plot, [21](#)

ch_wtr_yr, [22](#)

CSHShydRology-package, [2](#)

HYDAT_list, [23](#)

StatisticalHydrology-functions, [24](#)

Visualization-functions, [24](#)

W05AA008, [25](#)