

# B787 Weather Requirements Quick Reference

Source: Alaska/Hawaiian FOM Rev 123 / 123.1 (Apr 2026). Planning values. Verify against the current Dispatch Release and Jeppesen pages.

## TAKEOFF MINIMUMS

- **Standard:** **1 sm** vis or **RVR 5000** (2 engines or less). FOM 5.4.1.1
- **Higher than standard:** if published mins exceed 1 sm / RVR 5000 and no special procedure (e.g. RNP departure) is prescribed, takeoff below published mins is not allowed. FOM 5.4.1.2
- **Captain required takeoff:** any time vis is at or below **1/4 sm** or **RVR 1600**, the Captain makes the takeoff. FOM 5.4.3
- **Visibility priority:** RVR > RVV > ICAO RVR > prevailing. Runway-specific vis prevails for that runway. FOM 5.4.1

## TAKEOFF ALTERNATE

Required when reported departure wx is below approach landing mins for the runway of intended use (excluding SA CAT I, CAT II/III), or conditions exist that would preclude a return. Wx must meet destination alternate requirements. FOM 5.4.2

**Max distance to a takeoff alternate (787): 393 nm.** FOM 5.4.2

**High-Minimums Captain:** takeoff alternate required if dep wx below published CAT I DH **+100 ft** and CAT I vis **+1/2 sm**. FOM 3.9

## DESTINATION ALTERNATE - NONE REQUIRED (1-2-3)

**Contiguous 48** (and from AK / Mexico / Central America / Canada / Caribbean): none if wx at ETA +/- 1 hr forecasts at least **2000 ft** ceiling and **3 sm** vis (or 2 sm more than the lowest applicable vis min, whichever greater). FOM 8.2.5

**Flag (non-A012):** ceiling at least **1500 ft** above lowest published IAP min or **2000 ft** above field elev (whichever higher; 1500 above circling MDA if circling), and 3 sm or 2 sm more than applicable vis min (whichever greater), ETA +/- 1 hr. FOM 8.2.5

**Always required:** any Flag flight planned over 6 hr; or when TS / volcanic ash forecast at ETA. FOM 8.2.4 / 8.2.5

## ALTERNATE WX MINIMUMS (derived) - C055

**One nav facility** (straight-in non-precision, CAT I, or circling): add **+400 ft** to MDA(H)/DA(H), and **+1 sm** (1600 m) to the landing min. FOM 8.2.4.1

**Two facilities** to different suitable runways (two approach ends): add **+200 ft** to the higher DA(H)/MDA(H), and **+1/2 sm** (800 m) to the higher authorized landing min. FOM 8.2.4.1

Additives apply to the H value, rounded up to the next 100 ft. Jeppesen "For Filing As Alternate" mins do NOT apply. Wind incl gust must be forecast within limits.

## SECOND ALTERNATE (marginal)

Required when the destination ceiling/vis is at or below CAT I mins AND the first alternate is at alternate mins; also when an international destination is missing METAR info. FOM 8.2.4.2

## APPROACH (DESTINATION)

Reported wx must be at or above the vis mins for the approach. Do not begin the final approach segment unless the latest RVR / vis / ceiling (if required) is at or above authorized mins. If a below-min report is received after the FAF is begun, may continue to DA/MDA. FOM 5.6.11

**TDZ RVR controlling** (mid/rollout advisory). RVR > 6000 advisory only. Vis below **1/2 sm** not authorized for approach mins. FOM 5.6.11

## TAKEOFF / LANDING PROHIBITED

- Steady-state wind greater than 50 kt.
- Crosswind exceeds fleet limit (787 per FCOM/AOM).
- Braking action NIL or RWYCC 0 on any portion of runway.
- 787 prepared surface width less than 45 m / 148 ft (contaminated).
- TS at or near airport unless runway + flight path (incl missed) clear of storms.
- Moderate or greater freezing rain (takeoff allowed if LWE-derived HOT available, absent other prohibitor).
- Severe icing reported by similar type or larger aircraft.
- Takeoff only: contaminant depth over 1/2 in wet snow/slush/water, or over 4 in dry snow.

*Most recent report (incl Remarks/conditional language) is controlling. Verbal tower vis/RVV/RVR supersedes METAR/ATIS.* FOM 9.2.1