

B787 Limitations // Memorize Set

FCOM R10, Chapter L.10. 21 items marked for memorization. Number + units + condition; exact wording not required per L.10.1.

#	System	Limitation	Value / Condition	Source
1	Airplane General	Max takeoff and landing tailwind	15 kt	L.10.2
2	Airplane General	HF radios when refueling	Prohibited	L.10.2
3	Airplane General	Severe turb penetration speed	290 KIAS below 25,000 ft; 310 KIAS / .84M (lower) at/above 25,000 ft	L.10.3
4	Airplane General	Weather radar in a hangar	Avoid (test mode exempt)	L.10.3
5	Autoflight	AP min engage altitude after takeoff	200 ft AGL	L.10.8
6	Autoflight	Autoland max airport field elevation	8,400 ft	L.10.8
7	Autoflight	Without LAND 2/3, disengage AP below	135 ft AGL	L.10.8
8	Autoflight	With LAND 2/3 and G/S > 3.25 deg, disengage AP below	100 ft AGL	L.10.8
9	HUD Takeoff	Max headwind	25 kt	L.10.9
10	HUD Takeoff	Max tailwind	15 kt	L.10.9
11	HUD Takeoff	Max crosswind	20 kt	L.10.9
12	Autoland	Max headwind	25 kt	L.10.9
13	Autoland	Max tailwind	15 kt	L.10.9
14	Autoland	Max crosswind	25 kt (15 kt CAT II/III)	L.10.9
15	Autoland	Max glideslope angle	3.25 deg	L.10.9
16	Autoland	Min glideslope angle	2.5 deg	L.10.9
17	Approach	FLCH on final below	Do not use below 1,000 ft AFE	L.10.9
18	Engines	Oil temp for engine start	Greater than -40 deg C	L.10.10
19	Engines	Reverse thrust in flight	Prohibited	L.10.10
20	Engines	Backing with reverse thrust	Prohibited	L.10.10
21	Flight Controls	Rapid/large alternating control inputs	Avoid; structural failure risk at any speed, incl. below VA	L.10.10

Shared scaffolding: HUD takeoff and Autoland share 25 / 15 kt head / tailwind. They split on crosswind (20 vs 25 kt); CAT II/III drops the Autoland crosswind to 15 kt. The reverse-thrust pair both read "prohibited."