

Cockpit Entry:

ARRS
FFLAAP MD
Logbook

DEAD AIRCRAFT:

(Electric Pwr UP Flow: Read & Do Chk)
Batt Sw – On
Hydra Pumps – Off
Wipers – Off
Gr Lever – Dwn
Alt. Flap Swts – Off
External or APU – On

☐ Prelim. Preflt Flow: (Capt or FO)

(I SEE HOP) Logbook
IRS, Status, Eicas, Eng oil, Hyd,
O2, Park Brk
Gnd Air or not?

☐ COMM-ATC: (Capt or FO)

Lagon
KUSA (Allows Flt Cinc to auto upload 30 minutes prior).

☐ PF: COMM – Flt Info –

Request ATIS

☐ PF: CDU (NP.21.2 to NP.21.5)

The following items must be done before the Flt Instrument Check:

Initial Data

-IDENT
-POS INIT

Nav Data

-ROUTE
-DEPT
-ARRIVAL
-FIX
-ANP/RNP
-NAV RAD

☐ PF: CDU PERF Data

The following items must be done prior to the Before Start Checklist:

-ZFW
-Fuel
-CRZ Altitude
-Cost Index
-Step size = 0

☐ PF: COMM-COMPANY

-FLT INIT
-Rqst PRELIMINARY PERFORMANCE
(Rwy T/Off Data)

☐ PM: Walk-around

☐ Individual Cockpit Preflight

Capt FO (Waterfall)

(HUD down = Ready for chklist)

☐ "Preflight Checklist"

☐ ATC Clearance

Domestic - KUSA
HNL - Comm-Flt Info-
Dept Cinc Req

☐ Joint Verbal FMC Route Check:

PF: Reads ATC Cinc
PM: Cxchks Cinc w/RTE page and Rts

☐ Winds loaded: Legs-Rte Data

PROG: Dist + Lndg Fuel

Takeoff Brief:

Flaps, A/T, CG, V-Spds,
Accel/Thrust heights
SID, Threats
Arm VNAV. LNAV?

LCO & TLR: (from printer)

PF: Loads
*Company-Performance-
Takeoff Data pg: LOAD FMC
*CDU Perf Init: ACCEPT
*CDU T/Off pg ½

PM: Verifies entries

☐ Gate Agent/Station Mgr:

Check Fuel on Board
Check EICAS

☐ Flight Attendant:

Cabin Secure
Doors in Auto

☐ EICAS:

(4 / 6)
Nosewheel lockout

Ramp Crew:

-Gnd to Flt Dk. Confirm Brakes set?
-Can we disconnect External/Air?
-“Walk Around Complete”
(Trigger for FO flow)
- “Ready for Push”

Ramp Crew:

-Cleared to Push
-Cleared to Start engines
(After P/back complete)
-Push complete, Set brakes.

Before Taxi Flow: (AFTER receiving salute)

☐ “Flaps __”, “Before Taxi Checklist”: Check 4 generators ONline

☐ Taxi Clearance:

☐ “Before Takeoff Checklist”:
Cabin Ready

-CDU's: T/Off, LEGS pg
-WX, TERR, TCAS

Capt:

-Brakes set.
-Clr to disconnect External/Air?
-Stby for Push Cinc. ↓

☐ Before Start Flow:

(Pumps, Pumps, Beacon, Recall)

☐ “Before Start Checklist”

☐ Call ATC for Push Clearance

-Brakes released.
-Cleared to push (Direction).
-Brakes set.
-Cleared to disconnect towbar.
(After engines started)
-Cleared to disconnect headset.

-ND Display
-TA/RA