

B787 Weather Requirements Quick Reference

Source: Alaska/Hawaiian FOM Rev 123 / 123.1 (Apr 2026). Planning values. Verify against the current Dispatch Release and Jeppesen pages.

TAKEOFF MINIMUMS

- **Standard:** **1 sm** vis or **RVR 5000** (2 engines or less). FOM 5.4.1.1
- **Higher than standard:** if published mins exceed 1 sm / RVR 5000 and no special procedure (e.g. RNP departure) is prescribed, takeoff below published mins is not allowed. FOM 5.4.1.2
- **Captain required takeoff:** any time vis is at or below **1/4 sm** or **RVR 1600**, the Captain makes the takeoff. FOM 5.4.3
- **Visibility priority:** RVR > RVV > ICAO RVR > prevailing. Runway-specific vis prevails for that runway. FOM 5.4.1

TAKEOFF ALTERNATE

Required when reported departure wx is below approach landing mins for the runway of intended use (excluding SA CAT I, CAT II/III), or conditions exist that would preclude a return. Wx must meet destination alternate requirements. FOM 5.4.2

Fleet	Max takeoff-alt dist
787	393 nm
A330	370 nm
A321	360 nm
737	350 nm
717	320 nm

High-Minimums Captain: takeoff alternate required if dep wx below published CAT I DH **+100 ft** and CAT I vis **+1/2 sm**. FOM 3.9

DESTINATION ALTERNATE - NONE REQUIRED (1-2-3)

Contiguous 48 (and from AK / Mexico / Central America / Canada / Caribbean): none if wx at ETA +/- 1 hr forecasts at least **2000 ft** ceiling and **3 sm** vis (or 2 sm more than the lowest applicable vis min, whichever greater). FOM 8.2.5

Flag (non-A012): ceiling at least **1500 ft** above lowest published IAP min or **2000 ft** above field elev (whichever higher; 1500 above circling MDA if circling), and 3 sm or 2 sm more than applicable vis min (whichever greater), ETA +/- 1 hr. FOM 8.2.5

Always required: any Flag flight planned over 6 hr; or when TS / volcanic ash forecast at ETA. FOM 8.2.4 / 8.2.5

ALTERNATE WX MINIMUMS (derived) - C055

One nav facility (straight-in non-precision, CAT I, or circling): add **+400 ft** to MDA(H)/DA(H), and **+1 sm** (1600 m) to the landing min. FOM 8.2.4.1

Two facilities to different suitable runways (two approach ends): add **+200 ft** to the higher DA(H)/MDA(H), and **+1/2 sm** (800 m) to the higher authorized landing min. FOM 8.2.4.1

Additives apply to the H value, rounded up to the next 100 ft. Jeppesen "For Filing As Alternate" mins do NOT apply. Wind incl gust must be forecast within limits.

SECOND ALTERNATE (marginal)

Required when the destination ceiling/vis is at or below CAT I mins AND the first alternate is at alternate mins; also when an international destination is missing METAR info. FOM 8.2.4.2

APPROACH (DESTINATION)

Reported wx must be at or above the vis mins for the approach. Do not begin the final approach segment unless the latest RVR / vis / ceiling (if required) is at or above authorized mins. If a below-min report is received after the FAF is begun, may continue to DA/MDA. FOM 5.6.11

TDZ RVR controlling (mid/rollout advisory). RVR > 6000 advisory only. Vis below **1/2 sm** not authorized for approach mins. FOM 5.6.11

TAKEOFF / LANDING PROHIBITED

- Steady-state wind greater than 50 kt.
- Crosswind exceeds fleet limit (787 per FCOM/AOM).
- Braking action NIL or RWYCC 0 on any portion of runway.
- 787 prepared surface width less than 45 m / 148 ft (contaminated).
- TS at or near airport unless runway + flight path (incl missed) clear of storms.
- Moderate or greater freezing rain (takeoff allowed if LWE-derived HOT available, absent other prohibitor).
- Severe icing reported by similar type or larger aircraft.
- Takeoff only: contaminant depth over 1/2 in wet snow/slush/water, or over 4 in dry snow.

Most recent report (incl Remarks/conditional language) is controlling. Verbal tower vis/RVV/RVR supersedes METAR/ATIS. FOM 9.2.1