

B787 Weather Requirements - Quick Reference

Source: Alaska/Hawaiian FOM Rev 123/123.1 (Apr 2026). Planning values. Verify against current Dispatch Release and Jeppesen pages.

TAKEOFF MINIMUMS

Standard: 1 sm vis or RVR 5000 (2 engines or less). FOM 5.4.1.1

Higher than standard: If published mins exceed 1 sm / RVR 5000 and no special procedure (e.g. RNP departure) prescribed, takeoff below published mins not allowed. FOM 5.4.1.2

Captain required takeoff: Any time vis is at or below 1/4 sm or RVR 1600, the Captain makes the takeoff. FOM 5.4.3

Visibility priority order: RVR > RVV > ICAO RVR > prevailing. Runway-specific vis prevails for that runway. FOM 5.4.1

TAKEOFF ALTERNATE

Required when reported departure wx is below approach landing mins for the runway of intended use (excluding SA CAT I, CAT II/III), or conditions exist that would preclude a return. Wx must meet destination Alternate Airport requirements (below). FOM 5.4.2

Max takeoff-alternate distance	787	A330	737	A321	717
nm	393	370	350	360	320

High-Minimums Captain takeoff alternate: required if dep wx below published CAT I DH +100 ft and CAT I vis +1/2 sm. FOM 3.9

DESTINATION ALTERNATE - WHEN NONE REQUIRED (1-2-3 type)

Contiguous 48 (and from AK/Mexico/Central America/Canada/Caribbean): No alternate if wx at ETA +/- 1 hr forecasts at least 2000 ft ceiling and 3 sm vis (or 2 sm more than lowest applicable vis min, whichever greater). FOM 8.2.5

Flag (non-A012): ceiling at least 1500 ft above lowest published IAP min or 2000 ft above field elev (whichever higher; 1500 above circling MDA if circling), and 3 sm or 2 sm more than applicable vis min (whichever greater), ETA +/- 1 hr. FOM 8.2.5

Alternate always required: any Flag flight planned over 6 hr; or when TS / volcanic ash forecast at ETA. FOM 8.2.4 / 8.2.5

ALTERNATE AIRPORT WEATHER MINIMUMS (derived) - Ops Spec C055

Approach / runway config	Ceiling additive	Visibility additive
One nav facility: straight-in non-precision, or CAT I precision, or circling	Add 400 ft to MDA(H)/DA(H)	Add 1 sm (1600 m) to landing min
Two facilities to different suitable runways (two approach ends)	Add 200 ft to higher DA(H)/MDA(H) of the two	Add 1/2 sm (800 m) to higher authorized landing min of the two

Additives applied to H value rounded up to next 100 ft. Jeppesen 'For Filing As Alternate' mins do NOT apply. Wind incl gust must be forecast within limits. FOM 8.2.4.1

2nd alternate (marginal): required when destination ceiling/vis at or below CAT I mins AND first alternate at alternate mins; also when intl destination missing METAR info. FOM 8.2.4.2

APPROACH (DESTINATION)

Reported wx must be at or above the vis mins for the approach. Do not begin final approach segment unless latest RVR/vis/ceiling (if required) is at or above authorized mins. If below-min report received after FAF begun, may continue to DA/MDA. FOM 5.6.11
TDZ RVR controlling (mid/rollout advisory). RVR > 6000 advisory only. Vis below 1/2 sm not authorized for approach mins. FOM 5.6.11

TAKEOFF / LANDING PROHIBITED - FOM 9.2

- Steady-state wind greater than 50 kt
- Crosswind exceeds fleet limit (787 per FCOM/AOM)
- Braking action NIL or RWYCC 0 on any portion of runway
- 787 prepared surface width less than 45 m / 148 ft (contaminated)
- TS at or near airport unless rwy + flight path (incl missed) clear of storms
- Moderate or greater freezing rain (takeoff still allowed if LWE-derived HOT available, absent other prohibitor)
- Severe icing reported by similar type or larger aircraft
- Takeoff only: contaminant depth over 1/2 in wet snow/slush/water, or over 4 in dry snow

Most recent report (incl Remarks/conditional language) is controlling. Verbal tower vis/RVV/RVR supersedes METAR/ATIS. FOM 9.2.1