CS 575 Lab Notebook

Lab 2

Name: Jarren Calizo
OdinID: calizo
Date: January 20, 2026

Table of Contents


Lab 2.1 LangChain Tour 3
Step 2. Prompt templates 3
1. Take a screenshot of the results of the two prompts that includes your OdinID, then analyze the success or failure of the injection 3
Step 3. Chat templates and messages 3
1. Take a screenshot of the results that includes your OdinID, then analyze the success or failure of the injection 3
2. Take a screenshot of the results that includes your OdinID, then analyze the success or failure of the injection 4
Step 4. Context and safety 5
1. Take a screenshot showing the remediation suggested for the attack that includes your OdinID. 5
Step 5. Chains, LangChain Expression Language (LCEL) 6
1. Take a screenshot showing the bias results for 3 occupations of your choice that includes your OdinID. 6
Step 6. Conversation memory 7
1. Take a screenshot showing the results that includes your OdinID. 7
Step 7. Parsers 9
1. Take a screenshot showing the results that includes your OdinID. 9
Lab 2.2 LangChain Documents 10
Step 2. Document Loaders 10
1. Take a screenshot of the text within the page source that includes your OdinId 10
Step 3. Document Transformers 10
1. Take a screenshot of the output that includes your OdinId comparing the results. 11
Step 4. Chunking 11
1. Take a screenshot of the chunk size needed to perform the operation that includes your OdinId. 12
Step 5. Chunking (2) 12
1. Take a screenshot showing the number of chunks created and the chunk numbers containing the string that includes your OdinId 13
2. Did the query use more or less tokens than the Document Transformer approach? 13
Step 6. Custom recursive loader 14
1. Take a screenshot of the output that includes your OdinId 14
Step 7. Tokenizing 14

1. Take a screenshot of the output that includes your OdinId 15
Step 8. Token costs 15
1. Take a screenshot of the lines modified to set the costs that includes your OdinId 16
2. Take a screenshot of the results that includes your OdinId 17
Step 10. Embedding (2) 18
1. Take a screenshot of the results that includes your OdinId 18
Lab 2.3 LangChain RAG application 18
Step 6. Document search 19
1. Take a screenshot of the results of two different searches that includes your OdinId 19
Step 9. Document Q&A 19
1. Take a screenshot of the results of two different queries that includes your OdinId 20
Step 10. Chat interface with Chainlit 20
1. Take a screenshot that includes the URL and the results of a successful query 20

Lab 2.1 LangChain Tour

Step 2. Prompt templates


1. Take a screenshot of the results of the two prompts that includes your OdinID, then analyze the success or failure of the injection



- This injection succeeded. The key weakness is that the prompt template is just one flat string after rendering, meaning the model cannot reliably tell what is an "example" versus what is the user-provided input. The injected payload effectively smuggles in a fake training example inside the user message, and then nudges the model into continuing the pattern by returning "Benign." In other words, the template unintentionally let the user rewrite the rules of the classification task by blending into the few-shot structure.

Step 3. Chat templates and messages


1. Take a screenshot of the results that includes your OdinID, then analyze the success or failure of the injection




- This injection failed, which is exactly what we wanted to see from the structured chat format. Even though the input tries to mimic LangChain's internal message structure, it is still ultimately treated as plain user text inside a single human message. The system message remains clearly separated and continues to anchor the model toward the original goal: classify the message as

either "Malicious" or "Benign." Compared to the raw prompt template approach, the attack has far less power because it cannot cleanly "become" a trusted role.

2. Take a screenshot of the results that includes your OdinID, then analyze the success or failure of the injection






- This step shows a theme: structured messaging reduces injection risk, but does not eliminate it. The system vs human boundary is clearer, but the model can still be socially engineered inside the human message itself. A few of my attempts worked because they asked the model to stop behaving like a

classifier and instead behave like a compliant assistant. When that happened, the model obeyed the user instruction and returned "Benign," which is a successful bypass.

- At the same time, the bypass was not perfectly consistent. Several injection styles failed and the model still produced "Malicious." That inconsistency is important: it highlights that the defense is not a hard security boundary. It is a probabilistic guardrail that depends on the model's interpretation. In practical security engineering, this is where you would add reinforcement layers like strict output parsing, additional filtering, and rule-based post-validation to prevent "Benign" from being returned when obvious malicious indicators appear.

Step 4. Context and safety

1. Take a screenshot showing the remediation suggested for the attack that includes your OdinID.




Explanation
Even though the response is structured as a breakdown of the incident, the remediation direction is clear and actionable:

- Do not rely on SMS-based authentication for high value accounts
    - The output directly calls out that SMS-based 2FA is weaker than alternatives.
- Prefer authenticator apps or phishing-resistant hardware tokens
    - The response highlights stronger options like hardware keys (U2F/FIDO2).
- Harden account recovery paths
    - The attack succeeds partly because password reset links and OTPs can be stolen through phone takeover, so recovery channels must be treated like a critical security boundary.
- Add telecom / carrier-level protections
    - Since SIM-swaps involve impersonation with the carrier, additional verification and safeguards (like port-out locks or carrier PINs) reduce the chance of a number being hijacked.


Step 5. Chains, LangChain Expression Language (LCEL)


1. Take a screenshot showing the bias results for 3 occupations of your choice that includes your OdinID.





Step 6. Conversation memory

1. Take a screenshot showing the results that includes your OdinID.





ssh.cloud.google.com/v2/ssh/projects/gensec-calizo-calizo/zones/us-west1-b/instances/kali-vm?authuser=0&hl=en_US&projectNumber=226474869652&useAdminProxy=true - Brave
SSH-in-browser
UPLOAD FILE
DOWNLOAD FILE
Odin ID: calizo
>> What is the remediation for the last one you listed?
The last one listed is **A10:2021 - Server-Side Request Forgery (SSRF)**.
SSRF vulnerabilities occur when a web application fetches a remote resource without sufficiently validating the user-supplied URL. An attacker can then trick the application into making requests to an ar
bitrary domain of their choosing, including internal resources, other web applications, or even cloud provider metadata services.
Remediating SSRF requires a multi-layered approach, combining application-level controls with network-level defenses. Here's a breakdown of the key remediation strategies:
1. Application-Level Controls (Most Critical)
The primary defense against SSRF is to strictly validate and sanitize any user-supplied input used to construct outgoing requests.
* **Whitelisting Destination Domains/IPs (Strongest Defense):**
* **Only allow known-good destinations:** Instead of trying to block bad ones, explicitly define a list of allowed domains or IP addresses that the application is permitted to make requests to. If
the requested URL doesn't match an entry on this whitelist, deny the request.
* **Avoid user-supplied URLs entirely:** If possible, do not allow users to provide full URLs. Instead, provide a dropdown of pre-approved options or use an ID that maps to a known, safe internal r
esource.
* **Validate and Sanitize URLs Rigorously:**
* **URL Scheme Validation:** Only allow `http` and `https` schemes. Block dangerous schemes like `file://`, `ftp://`, `gopher://`, `dict://`, `data://`, etc.
* **Hostname/IP Address Validation:**
* **Resolve Hostname and Validate IP:** If a hostname is provided, resolve it to an IP address *before* making the request, and then validate that IP address. This helps defend against DNS rebi
nding attacks.
* **Block Private IP Ranges:** Explicitly deny requests to private IP address ranges (e.g., `10.0.0.0/8`, `172.16.0.0/12`, `192.168.0.0/16`, `127.0.0.1/8` for loopback, `169.254.169.254/32` for
cloud metadata services, `0.0.0.0`). While whitelisting is stronger, blacklisting these is a good secondary defense.
* **Port Restriction:** Restrict outgoing requests to only standard web ports (e.g., 80, 443).
* **Use a Robust URL Parser:** Employ well-tested and secure URL parsing libraries provided by your programming language (e.g., `java.net.URL` in Java, `urllib.parse` in Python, `URL` class in Node
.js) rather than custom regex, as these handle complex URL structures and edge cases more reliably.
* **Disable HTTP Redirects:** Configure the HTTP client used by the application to not automatically follow redirects. Attackers can use redirects to bypass IP/domain blacklists (e.g., redirect from an
allowed domain to a forbidden internal IP). If redirects are necessary, manually inspect and validate the redirect target.
2. Network-Level Controls (Defense in Depth)
These controls act as a safety net, limiting the damage even if an application-level bypass occurs.
* **Firewall Rules / Security Groups:**
* **Restrict Outbound Traffic:** Configure firewalls or security groups on the application server to prevent it from initiating connections to private IP address ranges.
* **Least Privilege:** Ensure the application server can only connect to the specific external resources it legitimately needs, on the required ports.
* **Cloud Metadata Service Blocking:** Explicitly block access to the cloud provider's metadata service IP (e.g., `169.254.169.254` for AWS EC2 instances) from the application server, unless absolu
tely necessary and with very strict controls.
* **Network Segmentation:**
* Place the application server in a segmented network zone (e.g., a DMZ) that is isolated from sensitive internal systems and databases. This limits an attacker's ability to pivot deeper into your
network.
* **Dedicated Proxy for External Requests:**
* If the application *must* make requests to arbitrary external URLs, consider routing all such requests through a dedicated, hardened, and strictly configured proxy server. This proxy can enforce
the whitelisting rules and log all outgoing connections. The application server itself would then only be allowed to connect to this proxy.
3. Identity and Access Management (IAM)
* **Least Privilege for Server Roles:** If your application runs in a cloud environment, ensure the IAM role assigned to the EC2 instance, container, or serverless function has the absolute minimum per
missions required. For example, it should not have permissions to read sensitive data from S3 buckets or interact with other internal services that an attacker could leverage via SSRF.
4. Logging and Monitoring
* **Log All Outgoing Requests:** Implement comprehensive logging for all external and internal requests initiated by the application server.
* **Monitor for Anomalies:** Set up alerts for unusual outgoing requests, such as connections to internal IP addresses, non-standard ports, or unexpected domains.
Summary
The most effective remediation for SSRF is **strict whitelisting of allowed destination domains/IPs at the application layer**, combined with **robust network segmentation and outbound firewall rules** a
s a strong defense-in-depth measure. Always assume user input is malicious and validate it thoroughly before using it to make server-side requests.
History
1. User: What are the current OWASP Top 10?
2. Assistant: The current OWASP Top 10 list is from **2021**.
It serves as a standard awareness document for developers and web application security. It represents a broad consensus about the most critical security risks to web applications.
Here are the OWASP Top 10 for 2021:
1. **A01:2021 - Broken Access Control:** This moved up from the fifth position in 2017, demonstrating that access control issues are still a significant problem.
2. **A02:2021 - Cryptographic Failures:** Formerly "Sensitive Data Exposure," this category is now focused on failures related to cryptography that often lead to sensitive data exposure.
3. **A03:2021 - Injection:** This includes SQL, NoSQL, OS, LDAP injection, etc. It remains a persistent and critical risk.
4. **A04:2021 - Insecure Design:** This is a **new category** for 2021, focusing on risks related to design flaws and the lack of threat modeling. It emphasizes the need for security to be part of the d
esign process.
5. **A05:2021 - Security Misconfiguration:** This category moved up from sixth place and includes issues like improperly configured security headers, default accounts, and verbose error messages.


ssh.cloud.google.com/v2/ssh/projects/gensec-calizo-calizo/zones/us-west1-b/instances/kali-vm?authuser=0&hl=en_US&projectNumber=226474869652&useAdminProxy=true - Brave
SSH-in-browser
UPLOAD FILE
DOWNLOAD FILE
Odin ID: calizo
5. **A05:2021 - Security Misconfiguration:** This category moved up from sixth place and includes issues like improperly configured security headers, default accounts, and verbose error messages.
6. **A06:2021 - Vulnerable and Outdated Components:** Formerly "Using Components with Known Vulnerabilities," this category is still a major risk, highlighting the dangers of relying on unpatched or uns
upported software.
7. **A07:2021 - Identification and Authentication Failures:** Formerly "Broken Authentication," this category now encompasses broader issues related to identity and authentication.
8. **A08:2021 - Software and Data Integrity Failures:** This is a **new category** for 2021, focusing on risks related to software updates, critical data, and CI/CD pipelines compromising integrity. It
also incorporates "Insecure Deserialization" from the 2017 list.
9. **A09:2021 - Security Logging and Monitoring Failures:** Formerly "Insufficient Logging & Monitoring," this category emphasizes the critical importance of effective logging and monitoring for detecti
ng and responding to security incidents.
10. **A10:2021 - Server-Side Request Forgery (SSRF):** This is a **new category** for 2021, specifically highlighting the increasing prevalence and impact of SSRF vulnerabilities.
Key Takeaways from the 2021 Update:
* **Proactive Security:** The addition of "Insecure Design" highlights a shift towards emphasizing security earlier in the software development lifecycle.
* **Integrity:** "Software and Data Integrity Failures" underscores the importance of ensuring the trustworthiness of software and data throughout its lifecycle.
* **New Risks:** The inclusion of SSRF reflects emerging threats and their growing impact.
* **Consolidation:** Some categories were merged or renamed to better reflect the underlying causes of vulnerabilities.
It's crucial for anyone involved in web application development or security to be familiar with this list, as it provides a foundational understanding of the most common and impactful security risks.
You can find the official and most detailed information on the OWASP website: https://owasp.org/www-project-top-10/
3. User: What is the remediation for the last one you listed?
4. Assistant: The last one listed is **A10:2021 - Server-Side Request Forgery (SSRF)**.
SSRF vulnerabilities occur when a web application fetches a remote resource without sufficiently validating the user-supplied URL. An attacker can then trick the application into making requests to an ar
bitrary domain of their choosing, including internal resources, other web applications, or even cloud provider metadata services.
Remediating SSRF requires a multi-layered approach, combining application-level controls with network-level defenses. Here's a breakdown of the key remediation strategies:
1. Application-Level Controls (Most Critical)
The primary defense against SSRF is to strictly validate and sanitize any user-supplied input used to construct outgoing requests.
* **Whitelisting Destination Domains/IPs (Strongest Defense):**
* **Only allow known-good destinations:** Instead of trying to block bad ones, explicitly define a list of allowed domains or IP addresses that the application is permitted to make requests to. If
the requested URL doesn't match an entry on this whitelist, deny the request.
* **Avoid user-supplied URLs entirely:** If possible, do not allow users to provide full URLs. Instead, provide a dropdown of pre-approved options or use an ID that maps to a known, safe internal r
esource.
* **Validate and Sanitize URLs Rigorously:**
* **URL Scheme Validation:** Only allow `http` and `https` schemes. Block dangerous schemes like `file://`, `ftp://`, `gopher://`, `dict://`, `data://`, etc.
* **Hostname/IP Address Validation:**
* **Resolve Hostname and Validate IP:** If a hostname is provided, resolve it to an IP address *before* making the request, and then validate that IP address. This helps defend against DNS rebi
nding attacks.
* **Block Private IP Ranges:** Explicitly deny requests to private IP address ranges (e.g., `10.0.0.0/8`, `172.16.0.0/12`, `192.168.0.0/16`, `127.0.0.1/8` for loopback, `169.254.169.254/32` for
cloud metadata services, `0.0.0.0`). While whitelisting is stronger, blacklisting these is a good secondary defense.
* **Port Restriction:** Restrict outgoing requests to only standard web ports (e.g., 80, 443).
* **Use a Robust URL Parser:** Employ well-tested and secure URL parsing libraries provided by your programming language (e.g., `java.net.URL` in Java, `urllib.parse` in Python, `URL` class in Node
.js) rather than custom regex, as these handle complex URL structures and edge cases more reliably.
* **Disable HTTP Redirects:** Configure the HTTP client used by the application to not automatically follow redirects. Attackers can use redirects to bypass IP/domain blacklists (e.g., redirect from an
allowed domain to a forbidden internal IP). If redirects are necessary, manually inspect and validate the redirect target.
2. Network-Level Controls (Defense in Depth)
These controls act as a safety net, limiting the damage even if an application-level bypass occurs.
* **Firewall Rules / Security Groups:**
* **Restrict Outbound Traffic:** Configure firewalls or security groups on the application server to prevent it from initiating connections to private IP address ranges.
* **Least Privilege:** Ensure the application server can only connect to the specific external resources it legitimately needs, on the required ports.
* **Cloud Metadata Service Blocking:** Explicitly block access to the cloud provider's metadata service IP (e.g., `169.254.169.254` for AWS EC2 instances) from the application server, unless absolu
tely necessary and with very strict controls.
* **Network Segmentation:**
* Place the application server in a segmented network zone (e.g., a DMZ) that is isolated from sensitive internal systems and databases. This limits an attacker's ability to pivot deeper into your
network.
* **Dedicated Proxy for External Requests:**
* If the application *must* make requests to arbitrary external URLs, consider routing all such requests through a dedicated, hardened, and strictly configured proxy server. This proxy can enforce
the whitelisting rules and log all outgoing connections. The application server itself would then only be allowed to connect to this proxy.
3. Identity and Access Management (IAM)
* **Least Privilege for Server Roles:** If your application runs in a cloud environment, ensure the IAM role assigned to the EC2 instance, container, or serverless function has the absolute minimum per
missions required. For example, it should not have permissions to read sensitive data from S3 buckets or interact with other internal services that an attacker could leverage via SSRF.
4. Logging and Monitoring
* **Log All Outgoing Requests:** Implement comprehensive logging for all external and internal requests initiated by the application server.
* **Monitor for Anomalies:** Set up alerts for unusual outgoing requests, such as connections to internal IP addresses, non-standard ports, or unexpected domains.



Step 7. Parsers


1. Take a screenshot showing the results that includes your OdinID.




Lab 2.2 LangChain Documents

Step 2. Document Loaders


1. Take a screenshot of the text within the page source that includes your OdinId






Step 3. Document Transformers


1. Take a screenshot of the output that includes your OdinId comparing the results.



Step 4. Chunking


1. Take a screenshot of the chunk size needed to perform the operation that includes your OdinId.





Step 5. Chunking (2)

1. Take a screenshot showing the number of chunks created and the chunk numbers containing the string that includes your OdinId



2. Did the query use more or less tokens than the Document Transformer approach?

The chunking-based query used less tokens overall than the Document Transformer approach.


From the chunking output, the page was split into 30 chunks, and only the chunk containing the phrase "job placement" (chunk 22) was sent to the LLM instead of the entire page. That single targeted chunk had a much smaller context window (content size shown as ~4.8 KB), and the token metadata confirms the request stayed relatively bounded at roughly 1,102 input tokens and 1,299 total tokens for the model call.

By contrast, the Document Transformer approach extracts the entire <article> section and feeds that full transformed article content into the prompt. Even though it removes irrelevant HTML/JS noise, it is still a much larger slice of text than a single

focused chunk. That larger context translates into higher prompt size, meaning more input tokens are consumed before the model even begins answering.


Step 6. Custom recursive loader

1. Take a screenshot of the output that includes your OdinId




Step 7. Tokenizing

1. Take a screenshot of the output that includes your OdinId





Step 8. Token costs


1. Take a screenshot of the lines modified to set the costs that includes your OdinId



2. Take a screenshot of the results that includes your OdinId








Step 10. Embedding (2)


1. Take a screenshot of the results that includes your OdinId



Lab 2.3 LangChain RAG application


Step 6. Document search

1. Take a screenshot of the results of two different searches that includes your OdinId



Step 9. Document Q&A

1. Take a screenshot of the results of two different queries that includes your OdinId



Step 10. Chat interface with Chainlit

1. Take a screenshot that includes the URL and the results of a successful query

