
PIZZAHUT

Sales Analysis Using SQL







RETRIEVE THE TOTAL NUMBER OF ORDERS PLACED



```sql
select count(*) as total_orders from orders;
```

Result Grid

	total_orders
▶	21350

CALCULATE THE TOTAL REVENUE GENERATED FROM PIZZA SALES.



```sql
SELECT
    ROUND(SUM(order_details.quantity * pizzas.price),
            2) AS total_sales
FROM
    order_details
        JOIN
    pizzas ON pizzas.pizza_id = order_details.pizza_id;
```

Result Grid

	total_sales
▶	817860.05

IDENTIFY THE HIGHEST-PRICED PIZZA



```sql
SELECT
    pizza_types.name, pizzas.price
FROM
    pizza_types
        JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
ORDER BY pizzas.price DESC
LIMIT 1;
```

Result Grid | Filter Rows:

	name	price
▶	The Greek Pizza	35.95

IDENTIFY THE MOST COMMON PIZZA SIZE ORDERED



```sql
SELECT
    pizzas.size,
    COUNT(order_details.order_details_id) AS order_count
FROM
    pizzas
        JOIN
    order_details ON pizzas.pizza_id = order_details.pizza_id
GROUP BY pizzas.size
ORDER BY order_count DESC;
```

Result Grid | Filter Rows:

size	order_count
L	18526
M	15385
S	14137
XL	544
XXL	28

LIST THE TOP 5 MOST ORDERED PIZZA TYPES ALONG WITH THEIR QUANTITIES



```sql
SELECT
    pizza_types.name, SUM(order_details.quantity) AS quantity
FROM
    pizza_types
        JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
        JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY quantity DESC
LIMIT 5;
```

Result Grid | Filter Rows:

name	quantity
The Classic Deluxe Pizza	2453
The Barbecue Chicken Pizza	2432
The Hawaiian Pizza	2422
The Pepperoni Pizza	2418
The Thai Chicken Pizza	2371

JOIN THE NECESSARY TABLES TO FIND THE TOTAL QUANTITY OF EACH PIZZA CATEGORY ORDERED



```sql
select pizza_types.category,
sum(order_details.quantity) as quantity
from pizza_types join pizzas
on pizza_types.pizza_type_id = pizzas.pizza_type_id
join order_details
on order_details.pizza_id = pizzas.pizza_id
group by pizza_types.category order by quantity desc;
```

Result Grid | Filter

	category	quantity
▶	Classic	14888
	Supreme	11987
	Veggie	11649
	Chicken	11050

DETERMINE THE DISTRIBUTION OF ORDERS BY HOUR OF THE DAY



```sql
SELECT
    HOUR(order_time) AS hour, COUNT(order_id)
FROM
    orders AS order_count
GROUP BY HOUR(order_time);
```

Result Grid | Filter Rows:

hour	COUNT(order_id)
11	1231
12	2520
13	2455
14	1472
15	1468
16	1920
17	2336
18	2399
19	2009
20	1642
21	1198
22	663
23	28
10	8
9	1

JOIN RELEVANT TABLES TO FIND THE CATEGORY-WISE DISTRIBUTION OF PIZZAS



```
select category , count(name) from pizza_types
group by category ;
```

Result Grid | Filter Rows:

category	count(name)
Chicken	6
Classic	8
Supreme	9
Veggie	9

GROUP THE ORDERS BY DATE AND CALCULATE THE AVERAGE NUMBER OF PIZZAS ORDERED PER DAY



```sql
SELECT
    ROUND(AVG(quantity), 0) as average_quantity
FROM
    (SELECT
        orders.order_date, SUM(order_details.quantity) AS quantity
    FROM
        orders
    JOIN order_details ON orders.order_id = order_details.order_id
    GROUP BY orders.order_date) AS order_quantity;
```

Result Grid

	average_quantity
▶	138

DETERMINE THE TOP 3 MOST ORDERED PIZZA TYPES BASED ON REVENUE



```sql
SELECT
    pizza_types.name,
    SUM(order_details.quantity * pizzas.price) AS revenue
FROM
    pizza_types
        JOIN
    pizzas ON pizzas.pizza_type_id = pizza_types.pizza_type_id
        JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY revenue DESC
LIMIT 3;
```

Result Grid | Filter Rows:

name	revenue
The Thai Chicken Pizza	43434.25
The Barbecue Chicken Pizza	42768
The California Chicken Pizza	41409.5

CALCULATE THE PERCENTAGE CONTRIBUTION OF EACH PIZZA TYPE TO TOTAL REVENUE.



```sql
select pizza_types.category,
round(sum(order_details.quantity * pizzas.price) /
(select round(sum(order_details.quantity * pizzas.price),2) as total_sales
from order_details join pizzas
on pizzas.pizza_id = order_details.pizza_id) * 100,2) as revenue
from pizza_types join pizzas
on pizza_types.pizza_type_id = pizzas.pizza_type_id
join order_details
on order_details.pizza_id = pizzas.pizza_id
group by pizza_types.category order by revenue desc ;
```

Result Grid | Filter

category	revenue
Classic	26.91
Supreme	25.46
Chicken	23.96
Veggie	23.68

ANALYZE THE CUMULATIVE REVENUE GENERATED OVER TIME



```sql
select order_date,
sum(revenue) over(order by order_date) as cum_revenue
from
(select orders.order_date,
sum(order_details.quantity * pizzas.price) as revenue
from order_details join pizzas
on order_details.pizza_id = pizzas.pizza_id
join orders
on orders.order_id = order_details.order_id
group by orders.order_date) as sales;
```

Result Grid | Filter Rows:

order_date	cum_revenue
2015-01-01	2713.8500000000004
2015-01-02	5445.75
2015-01-03	8108.15
2015-01-04	9863.6
2015-01-05	11929.55
2015-01-06	14358.5
2015-01-07	16560.7
2015-01-08	19399.05
2015-01-09	21526.4
2015-01-10	23990.350000000002
2015-01-11	25862.65
2015-01-12	27781.7
2015-01-13	29831.300000000003

DETERMINE THE TOP 3 MOST ORDERED PIZZA TYPES BASED ON REVENUE FOR EACH PIZZA CATEGORY



```sql
select name, revenue
from
(select category, name , revenue,
rank() over(partition by category order by revenue desc) as rn
from
(select pizza_types.category , pizza_types.name,
sum((order_details.quantity) * pizzas.price) as revenue
from pizza_types join pizzas
on pizza_types.pizza_type_id = pizzas.pizza_type_id
join order_details
on order_details.pizza_id = pizzas.pizza_id
group by pizza_types.category, pizza_types.name) as a ) as b
where rn <= 3 limit 3 ;
```

Result Grid | Filter Rows:

name	revenue
The Thai Chicken Pizza	43434.25
The Barbecue Chicken Pizza	42768
The California Chicken Pizza	41409.5





THANK YOU



