Applying Programming Concepts

ESC108A Elements of Computer Science and Engineering B. Tech. 2017

Course Leaders:

Roopa G.

Ami Rai E.

Chaitra S.



Objectives

- At the end of this lecture, student will be able to
 - follow the best practices for naming of variables, functions, files and projects
 - use the best practices for documentation
 - use the best practices followed by C programmers in creation of a C project



Contents

- Variable and function naming conventions
- Structure naming conventions
- Constant naming conventions
- File and Directory naming conventions
- Documentation conventions



A Question

Can you explain what this structure is used for?

```
struct myStr{
    char *n;
    char *r;
    int a;
}
```



Naming Conventions: Variables

- Give full name
- Start with small letter
- Use upper case for every new word
- If it is a pointer, mention it
- Examples
 - age
 - temporaryStudent
 - myStudentPointer



Naming Conventions: Function

- Give full name
- Start with small letter
- Use upper case for every new word
- name should explain purpose of function
- Examples
 - intAddition
 - linearSearch
 - substringFromString



Naming Conventions: Symbolic Constants

- Give full name
- All letters in capital case
- Use underscore (_) for every new word
- name should explain purpose of function
- Examples
 - PI
 - DEGREE TO RADIANS RATIO



Naming Conventions: File Names

- Have only related functions in one file
- use same convention as variables
- Examples
 - intUtilities.c
 - floatUtilities.h



Types of Errors

- Syntax errors
 - Violation of grammar/rules of programming language
 - E.g., int a

- Logical errors
 - Logical thinking problem
 - Difficult to debug as the system does not display them

- Run-time errors
 - Attempt to run an ambiguous instructions
 - E.g., divide by zero



Documentation

- In each file at the start
 - Header comment
 - Define purpose of code in the file
 - State author name and contact details
 - Give version number
 - Give copyright notice if applicable

- For each function
 - Document its purpose, details of each parameter and the return value expected



Comments

- Single line comment //
- Multiple line comment /* and */

 Comments are ignored by the compiler and do not cause any machine language object code to be generated



Indentation

- Indent the entire body of each function one level of indentation within the braces that define the body of the function
- Emphasizes the functional structure of programs and helps make programs easier to read

```
for(i=0;i<3;i++){
    for(j=0;j<3;j++){
        printf("Enter the elements"):
        scanf("%d",&array[i][j]);
    }</pre>
```



Documentation - Example

```
/*Program to compute the addition of two integer numbers */
#include <stdio.h>
/* function main begins program execution */
int main( void ) {
    int integer1; /* first number to be input by user */
    int integer2; /* second number to be input by user */
    int sum; /* variable in which sum will be stored */
    printf( "Enter first integer\n" ); /* prompt */
    scanf( "%d", &integer1 ); /* read an integer */
    printf( "Enter second integer\n" ); /* prompt */
    scanf( "%d", &integer2 ); /* read an integer */
    sum = integer1 + integer2; /* assign total to sum */
    printf( "Sum is %d\n", sum ); /* print sum */
    return 0; /* indicate that program ended successfully */
}/* end function main */
```



Programming Practices

- Keep your programs simple and straightforward
 - KIS (Keep It Simple)

 Although it is allowed, there should be no more than one statement per line in a program

- Type the beginning and ending braces of compound statements before typing the individual statements within the braces
 - helps avoid omitting one or both of the braces, preventing syntax errors and logic errors



Unary operators should be placed directly next to their operands with no intervening spaces

 Put a blank line before and after each control statement to make it stand out in the program

Try to avoid more than three levels of nesting

 For a loop used to print the values 1 to 10, use the condition as counter<=10



- In expressions using operator &&, make the condition that is most likely to be false the leftmost condition
 - In expressions using operator ||, make the condition that is most likely to be true the leftmost condition

- Don't confuse with = and == operators
 - Logic error

- Function names should effectively express the task
 - Choosing meaningful function names and meaningful parameter names makes programs more readable and helps avoid excessive use of comments



- Although it's not incorrect to do so, do not use the same names for a function's arguments and the corresponding parameters in the function definition
 - helps avoid ambiguity

 Providing more initializers in an array initializer list than there are elements in the array is a syntax error

- Ending a #define or #include preprocessor directive with a semicolon
 - preprocessor directives are not C statements



- Use only uppercase letters for symbolic constant names
 - makes these constants stand out in a program

 Include the letters ptr in pointer variable names to make it clear that these variables are pointers

Choosing a meaningful structure tag name helps make a program self-documenting

 Assigning a structure of one type to a structure of a different type is a compilation error

 When memory that was dynamically allocated is no longer needed, use free to return the memory to the system immediately



Summary

- Code must be written keeping in mind maintainability
- Maintainable code requires that anyone should be able to read the code
- Naming conventions for variables, functions, files, constants and directories are followed to improve readability of code



Further Reading

Kernighan, B. W. and Richie, D. (1992) *The C Programming Language*. 2nd ed., New Delhi:PHI.

