



This documentation is not published yet, this is only a preview. Changes to the publishing settings will reload this page.

# calendly\_clone

It contains following request:-

- Create Host
- Get Host Detail
- Create Call Schedule
- Get Call Availability
- Schedule Call using Google Calender
- Google Auth
- Google Redirect

## POST create-host

http://localhost:2000/user/create-host

### Body raw (json)

json

```
{
  "userId": 6,
  "name": "ruhi",
  "email": "dvf@gmail.com",
  "gender": "female",
  "mobileNo": "098976544",
```

```
{  
  "role": "host"  
}
```

---

## GET get-host

http://localhost:2000/user/get-all-host

---

## POST create-call-schedule

http://localhost:2000/user/create-call-schedule

---

### Body raw (json)

```
json  
  
{  
  "hostId": 3,  
  "userId": 1,  
  "meetingTime": "21:30",  
  "meetingDate": "31-08-1999",  
  "status": "open"  
}
```

---

## GET get-call-availability

http://localhost:2000/user/get-call-availability

**Body** raw (json)

---

```
json
```

```
{  
  "hostId": 2  
}
```

---

**GET** schedule-call-in-google-calender



http://localhost:2000/user/schedule-event

**AUTHORIZATION** Bearer Token

---

**Token**

<token>

---

**GET** google-auth

http://localhost:2000/user/google-auth

---

**GET** google/redirect

http://localhost:2000/user/google/redirect