

# Functional programming, Seminar No. 3

Danya Rogozin  
Lomonosov Moscow State University,  
Serokell OÜ

Higher School of Economics  
Faculty of Computer Science

# Intro

On the previous seminar, we

- studied the basic Haskell syntax
- introduced the notion of a weak head normal form to describe the operational semantics of Haskell
- analysed the regrettable circumstances according to which Haskell doesn't have the Church-Rosser property as a system of typed lambda calculus

# Intro

On the previous seminar, we

- studied the basic Haskell syntax
- introduced the notion of a weak head normal form to describe the operational semantics of Haskell
- analysed the regrettable circumstances according to which Haskell doesn't have the Church-Rosser property as a system of typed lambda calculus

Today we

- investigate the Haskell type system more deeply and overview the advantages of parametric polymorphism
- take a look at bounded polymorphism and discuss type classes

## Motivation

Let us recall the example of a higher order function from the previous seminar:

```
1  changeTwiceBy :: (Int -> Int) -> Int -> Int
2  changeTwiceBy operation value = operation (operation value)
```

It is clear that one may implement the function for Boolean values and strings that have the same behaviour as the function above:

```
1  changeTwiceByBool :: (Bool -> Bool) -> Bool -> Bool
2  changeTwiceByBool operation value = operation (operation value)
3
4  changeTwiceByString :: (String -> String) -> String -> String
5  changeTwiceByString operation value = operation (operation value)
```

## Motivation

Let us recall the example of a higher order function from the previous seminar:

```
1  changeTwiceBy :: (Int -> Int) -> Int -> Int
2  changeTwiceBy operation value = operation (operation value)
```

It is clear that one may implement the function for Boolean values and strings that have the same behaviour as the function above:

```
1  changeTwiceByBool :: (Bool -> Bool) -> Bool -> Bool
2  changeTwiceByBool operation value = operation (operation value)
3
4  changeTwiceByString :: (String -> String) -> String -> String
5  changeTwiceByString operation value = operation (operation value)
```


One needs to have a way to avoid such a boilerplate.

# Parametric polymorphism

The key idea of parametric polymorphism is that the same function might be called on distinct data types. Here are the initial polymorphic examples:

```
1  id :: a -> a
2  id x = x
3
4  const :: a -> b -> a
5  const a b = a
6
7  fst :: (a, b) -> a
8  fst (a, b) = a
9
10 snd :: (a, b) -> b
11 snd = "guess what"
12
13 swap :: (a, b) -> (b, a)
14 swap (a, b) = (b, a)
```

The meme time



## The functions above in the GHCi session

```
Prelude> id 7
7
Prelude> id "string"
"string"
Prelude> const 7 "string"
7
Prelude> const "string" 7
"string"
Prelude> fst (7, 'k')
7
Prelude> snd (7, 'k')
'k'
Prelude> fst (swap (7, 'k'))
'k'
```



## Higher order functions and parametric polymorphism

```
1 infixr 9 .  
2 (.) :: (b -> c) -> (a -> b) -> a -> c  
3 f . g = \x -> f (g x)  
4  
5 flip :: (a -> b -> c) -> b -> a -> c  
6 flip f b a = f a b  
7  
8 fix :: (a -> a) -> a  
9 fix = error "this is your homework"  
10  
11 curry :: ((a, b) -> c) -> a -> b -> c  
12 curry f x y = f (x, y)  
13  
14 uncurry :: (a -> b -> c) -> ((a, b) -> c)  
15 uncurry f p = f (fst p) (snd p)
```

## The functions above in the GHCi session. The composition examples

```
1 incNegate :: Int -> Int
2 incNegate x = negate (x + 1)
3
4 incNegate x = negate $ x + 1
5
6 incNegate x = (negate . (+1)) x
7
8 incNegate x = negate . (+1) $ x
9
10 incNegate = negate . (+1)
```

The functions above in the GHCi session. `curry` and `uncurry`

```
Prelude> uncurry (+) (3,4)
```

```
7
```

```
Prelude> curry fst 3 4
```

```
3
```

```
Prelude> curry snd 3 4
```

```
4
```

```
Prelude> curry id 3 4
```

```
(3,4)
```

```
Prelude> uncurry const (3,4)
```

```
3
```

```
Prelude> uncurry (flip const) (3,4)
```

```
4
```

## The functions above in the GHCi session. The `flip` example

```
1  show2 :: Int -> Int -> String
2  show2 x y = show x ++ " and " ++ show y
3
4  showSnd, showFst, showFst' :: Int -> String
5  showSnd = show2 1
6  showFst  = flip show2 2
7  showFst' = ('show2' 2)
```

## The functions above in the GHCi session. The `flip` example

```
1  show2 :: Int -> Int -> String
2  show2 x y = show x ++ " and " ++ show y
3
4  showSnd, showFst, showFst' :: Int -> String
5  showSnd = show2 1
6  showFst  = flip show2 2
7  showFst' = ('show2' 2)
```

Prelude> showSnd 10  
"1 and 10"  
Prelude> showFst 10  
"10 and 2"  
Prelude> showFst' 42  
"42 and 2"

## Bye-bye boilerplate!

All these functions

```
1  changeTwiceBy :: (Int -> Int) -> Int -> Int
2  changeTwiceBy operation value = operation (operation value)
3
4  changeTwiceByBool :: (Bool -> Bool) -> Bool -> Bool
5  changeTwiceByBool operation value = operation (operation value)
6
7  changeTwiceByString :: (String -> String) -> String -> String
8  changeTwiceByString operation value = operation (operation value)
```

might be replaced to the following ones:

```
1  applyTwice :: (a -> a) -> a -> a
2  applyTwice f a = f (f a)
3
4  applyTwice' :: (a -> a) -> a -> a
5  applyTwice' f a = f . f $ a
6
7  applyTwice'' :: (a -> a) -> a -> a
8  applyTwice'' f = f . f
```

## HOF, polymorphism, and lists

```
1  map    :: (a -> b)    -> [a] -> [b]
2
3  filter  :: (a -> Bool) -> [a] -> [a]
4
5  zipWith :: (a -> b -> c) -> [a] -> [b] -> [c]
6
7  length :: [a] -> Int
```

## HOF, polymorphism, and lists

```
1  map    :: (a -> b)    -> [a] -> [b]
2
3  filter  :: (a -> Bool) -> [a] -> [a]
4
5  zipWith :: (a -> b -> c) -> [a] -> [b] -> [c]
6
7  length :: [a] -> Int
```

We discuss their implementations closely on the next seminar. Here we just take a look at their behaviour.



The functions above in the GHCi session. The composition examples + list functions

```
1 foo, bar :: [Int] -> Int
2 foo patak = length $ filter odd $ map (div 2) $ filter even $ map (div 7) patak
3 bar       = length . filter odd . map (div 2) . filter even . map (div 7)
```

## The functions above in the GHCi session. The composition examples + list functions

```
1 stringsTransform :: [String] -> [String]
2 stringsTransform l = map (\s -> map toUpper s) (filter (\s -> length s == 5) l)
3
4 stringsTransform l = map (\s -> map toUpper s) $ filter (\s -> length s == 5) l
5
6 stringsTransform l = map (map toUpper) $ filter ((== 5) . length) l
7
8 stringsTransform = map (map toUpper) . filter ((== 5) . length)
```

# Restricted strictness

# Bounded polymorphism and type classes

# The Eq type class

# The Show type class

# The Ord type class

# The Num type class



# The Enum type class

# The Fractional type class

# The Bounded type class

# Summary