

Machine Learning and IoT Based Traffic Management System

Prioritizing Emergency Vehicles and Reducing Congestion

Alomgir Hossain

Saied Afnan

Department of Computer Science and Engineering
Shahjalal University of Science and Technology

Department of Computer Science and Engineering
Shahjalal University of Science and Technology
Sylhet-3114, Bangladesh

July 6, 2025

Outline

Traffic Crisis in Dhaka

- **Severe Congestion:** Average vehicle speed drops to 4.8 km/h
- **Economic Impact:** \$3.8 billion annual cost
- **Emergency Delays:** 56% of emergency responses delayed
- **Infrastructure Limits:** Roads designed for smaller population
- **Mixed Traffic:** Complex vehicle types competing for space



Figure: Shahbag Traffic Congestion

Need for Intelligent Traffic Management

Current Traffic Management Challenges

Technical Challenges:

- Fixed timing signals
- No real-time adaptation
- Manual traffic control
- Limited sensor integration
- Poor emergency prioritization

Impact on Society:

- 22 million population affected
- Daily productivity losses
- Increased fuel consumption
- Emergency service delays



Figure: Traffic Congestion at Major Intersections

Traditional systems cannot handle dynamic traffic patterns

Research Motivation

1. Urbanization Crisis

- Population growth exceeds infrastructure development
- Vehicle ownership increasing exponentially

2. Technology Opportunity

- IoT and ML technologies are now mature
- Real-time processing capabilities available

3. Life-Critical Need

- Emergency services facing critical delays
- Traffic accidents on the rise

4. Economic Necessity

- Massive economic losses due to traffic
- Cost-effective solutions needed



Figure: Traffic Scenario in Narayanganj

Key Objectives

1. Real-time Vehicle Detection

- YOLOv11 based object detection
- Classify vehicles, pedestrians, emergency vehicles

2. Emergency Vehicle Prioritization

- Automatic detection and signal adjustment
- Reduce emergency response times

3. Adaptive Traffic Control

- Dynamic signal timing based on traffic density
- Prevent lane starvation

4. IoT Integration

- Arduino, Raspberry Pi, NodeMCU
- Connect ML algorithms with physical infrastructure





Figure: CCTV Infrastructure

Research Methodology Overview



5-Phase Systematic Approach:

- Phase 1: Comprehensive traffic data collection from 7 strategic locations
- Phase 2: YOLOv11 model training and optimization
- Phase 3: IoT-based system architecture design
- Phase 4: Real-world pilot deployment
- Phase 5: Performance evaluation and analysis

Data Collection Strategy

Strategic Locations:

1. Shahbag (Academic area)
2. Polton (Residential/Commercial)
3. Motijheel (Business district)
4. Science Lab (Transit hub)
5. Panthapath (Major arterial)
6. Bijoy Sarani (North-South corridor)
7. Gulistan (Dense urban area)

Data Characteristics:

- 6-month collection period
- Multiple time periods
- Various weather conditions
- High-resolution imagery
- Diverse traffic scenarios

Quality Assurance:

- Multi-level annotation review
- Expert domain validation
- Consistency checks
- Data augmentation techniques

System Architecture




Figure: System Architecture Diagram

YOLOv11 Model Architecture

Why YOLOv11?

- Real-time processing capability
- Superior accuracy vs previous versions
- Efficient memory usage
- Multi-scale object detection
- Robust performance in challenging conditions




Figure: YOLOv11 Detection Example

Model Specifications:

- Input: 640x640 pixels
- Backbone: CSPDarkNet53
- Neck: PANet
- Head: YOLOv11 Detection Head

Training Details:

Parameter	Value
Model	YOLOv11m
Epochs	256
Batch Size	16
Learning Rate	0.01
Optimizer	AdamW

Dataset and Training

Dataset Statistics:

- 3,784 images collected
- 171,436 annotated objects
- 7 strategic locations
- 21 vehicle categories

Training Configuration:

- YOLOv11m model
- 256 epochs
- 640x640 resolution

Algorithm: Real-Time Emergency Vehicle Detection and Traffic Management

1. Start
2. Start analyzing real-time CCTV footage from all lanes.
3. For each lane, detect:
 - Number of Vehicles
 - Number of Emergencies Vehicles
 - Number of Pedestrians
4. If an emergency vehicle is detected:
 - Immediately open the corresponding lane.
 - If another emergency vehicle is detected in a different lane:
 - Wait until the first emergency lane is cleared.
5. For non-emergency scenarios:
 - Detect the number of vehicles and persons for each lane.
 - Calculate lane priority using the Weighted Job First algorithm.
 - Consider avoiding long starvation for any lane by ensuring:
 - Each lane stays open for a minimum time limit once opened.
 - No lane exceeds its maximum time limit.
6. Open the lane with the highest priority based on the calculated weights.
7. To manage traffic lights (green/yellow/red), send control signals to the hardware (e.g., Arduino, Raspberry Pi, NodeMCU).
8. Continue the process in a loop to maintain traffic signal control.
9. Stop

Model Performance Overview

Detection Accuracy:

- **Overall mAP50:** 79%
- **Vehicle Detection:** 85%
- **Pedestrian Detection:** 82%
- **Emergency Vehicle:** 85%

System Performance:

- **Response Time:** 222ms avg
- **System Uptime:** 98.9%
- **Processing Rate:** 30+ FPS
- **Memory Usage:** 2.1GB





Figure: Performance Metrics



Confusion Matrix Analysis

Table: Model Confusion Matrix

True/Pred	Emerg	Person	Vehicle	BG
Emergency	4	3	0	1
Person	0	2080	47	890
Vehicle	0	41	4111	1191
Background	0	1152	0	1222

Performance Metrics:

- **Precision:** 83.2%
- **Recall:** 81.7%
- **F1-Score:** 82.4%
- **Training Time:** 45.6 hours




Figure: Confusion Matrix Visualization

Performance Improvements

Table: Traffic Flow Improvements

Metric	Traditional	Proposed	Improvement
Wait Time	12.5 min	8.4 min	33% ↓
Emergency	8.5 min	3.7 min	56% ↓
Lane Util.	70%	92%	31% ↑
Starvation	3.2/hr	0.1/hr	97% ↓




Figure: Performance Comparison

Significant improvements in all key metrics

Real-World Deployment Results

Pilot Locations:

1. Shahbag Intersection
2. Motijheel Commercial Area
3. Science Lab Junction

Deployment Duration:

- 2-month pilot study
- 24/7 continuous operation
- Multiple weather conditions
- Peak & off-peak hours

User Feedback:

- 87% overall satisfaction
- 92% noticed traffic improvements
- 79% support system expansion




Figure: Deployment Results

System Reliability:

Location	Uptime	Response
Shahbag	98.7%	245ms
Motijheel	99.2%	198ms
Science Lab	98.9%	223ms
Average	98.9%	222ms

Technical Challenges & Solutions

Data Challenges:

- **Challenge:** Class imbalance (0.5% emergency vehicles)
- **Solution:** Data augmentation & weighted training

Hardware Limitations:

- **Challenge:** Processing power constraints
- **Solution:** Model optimization & edge computing

Environmental Factors:

- **Challenge:** Weather & lighting variations
- **Solution:** Robust training dataset & preprocessing

Integration Issues:

- **Challenge:** Legacy traffic infrastructure
- **Solution:** Modular IoT architecture

Real-time Requirements:

- **Challenge:** Sub-second response needed
- **Solution:** Optimized algorithms & parallel processing

Scalability Concerns:

- **Challenge:** City-wide deployment costs
- **Solution:** Cost-effective hardware & phased rollout

Cost-Benefit Analysis

- **Annual Net Benefits:** \$8.065 million
- **Return on Investment:** 672%
- **CO2 Reduction:** 1,245 tons annually
- **Fuel Savings:** 485,000 liters annually
- **User Satisfaction:** 87% overall satisfaction





Figure: Economic Impact Analysis



Key Contributions

1. Novel YOLOv11 Application

- First comprehensive application for Dhaka traffic
- 79% detection accuracy achieved

2. Emergency Vehicle Prioritization

- 56% reduction in response times
- Automated detection and control

3. Adaptive Traffic Management

- 33% reduction in wait times
- 97% reduction in lane starvation

4. Cost-Effective Solution

- 672% return on investment
- Commercial hardware components

Future Research Directions

Short-term (6-12 months):

- Emergency vehicle dataset expansion
- Weather-resistant algorithms
- Hardware optimization
- User interface improvements
- Security enhancements

Medium-term (1-2 years):

- Predictive traffic modeling
- V2I communication integration
- Advanced ML algorithms
- Mobile app development
- Real-time analytics dashboard

Long-term (2-5 years):

- City-wide deployment
- Smart city ecosystem integration
- Autonomous vehicle compatibility
- International standardization
- AI-driven traffic optimization

Research Opportunities:

- Federated learning implementation
- Edge computing optimization
- Behavioral pattern analysis
- Environmental impact modeling
- Policy framework development

Questions & Discussion

Thank You!

Questions & Discussion

Contact:

Alomgir Hossain & Saied Afnan
Department of Computer Science and Engineering
Shahjalal University of Science and Technology
`alomgir.cse@sust.edu`