Shaping a Swarm Using Wall Friction and a Shared Control Input

Shiva Shahrokhi and Aaron T. Becker

Abstract—Micro- and nano-robots can be manufactured in large numbers. Large numbers of micro robots are required in order to deliver sufficient payloads, but the small size of these robots makes it difficult to perform onboard computation. Instead, these robots are often controlled by a global, broadcast signal. In our previous work we focused on a block-pushing task, where a swarm of robots pushed a larger block through a 2D maze. One surprising result was that humans that only knew the swarm's mean and covariance completed the task faster that humans who knew the position of every robot [?]. Inspired by that work, we proved that we can control the mean position of a swarm and that with an obstacle we can control the swarm's position variance (σ_x and σ_y). We then wrote automatic controllers which could complete a block pushing task, but these controllers had some limitations [?]. One of the limitations was that we could only compress our swarm along the world x and y axes, and could not navigate workspaces with narrow corridors with other orientations. One solution to these problems would be a controller that regulates the swarm's position covariance, σ_{xy}. For controlling σ_{xy}, we prove that the swarm position covariance σ_{xy} is controllable given boundaries with non-zero friction. We then prove that two orthogonal boundaries with high friction are sufficient to arbitrarily position a swarm of robots. We conclude by designing controllers that efficiently regulate σ_{xy}.

I. Introduction

## II. Theory

III. Simulation

Fig. 1. Several real vascular networks exist in real world, which navigating a swarm with a global input would be a challenge because of the branches in the way.


Simulation: box2d example showing controlling the covariance of a swarm of 200 robots

Missing figure

Fig. 2. We can control covariance of the swarm by using friction.

S. Shahrokhi and A. Becker are with the Department of Electrical and Computer Engineering, University of Houston, Houston, TX 77204-4005 USA {sshahrokhi2, atbecker}@uh.edu

Algorithm 1 GenerateDesired$x$-spacing(s_1, s_2, e_1, e_2, L)

Require: Knowledge of starting (s_1, s_2) and ending (e_1, e_2) positions of two robots. $(0,0)$ is bottom corner, s_1 is topmost robot, L is length of the walls. Current position of the robots are (r_1, r_2).

Ensure: $r_{1y} - r_{2y} \equiv s_{1y} - s_{2y}$

1: $\Delta s_x \leftarrow s_{1x} - s_{2x}$
2: $\Delta e_x \leftarrow e_{1x} - e_{2x}$
3: $r_1 \leftarrow s_1,\ r_2 \leftarrow s_2$
4: **if** $\Delta e_x < 0$ **then**
5:      $m \leftarrow (L - \max(r_{1x}, r_{2x}), 0)$ ▷ Move to right wall
6: **else**
7:      $m \leftarrow (-\min(r_{1x}, r_{2x}, 0)$ ▷ Move to left wall
8: **end if**
9: $m \leftarrow m + (0, -\min(r_{1y}, r_{2y}))$ ▷ Move to bottom
10: $r_1 \leftarrow r_1 + m,\ r_2 \leftarrow r_2 + m$ ▷ Apply move
11: **if** $\Delta e_x - (r_{1x} - r_{2x}) > 0$ **then**
12:      $m \leftarrow (min(\|\Delta e_x - \Delta s_x\|, L - r_{1x}), 0)$ ▷ Move right
13: **else**
14:      $m \leftarrow (-min(\|\Delta e_x - \Delta s_x\|, r_{1x}), 0)$ ▷ Move left
15: **end if**
16: $m \leftarrow m + (0, \epsilon)$ ▷ Move up
17: $r_1 \leftarrow r_1 + m,\ r_2 \leftarrow r_2 + m$ ▷ Apply move
18: $\Delta r_x = r_{1x} - r_{2x}$
19: **if** $\Delta r_x \equiv \Delta e_x$ **then**
20:      $m \leftarrow (e_{1x} - r_{1x}, e_{1y} - r_{1y})$
21:      $r_1 \leftarrow r_1 + m,\ r_2 \leftarrow r_2 + m$ ▷ Apply move
22:      **return** (r_1, r_2)
23: **else**
24:      **return** GenerateDesired$x$-spacing(r_1, r_2, e_1, e_2, L)
25: **end if**

Algorithm 2 Getting desired Y-space

Require: Knowledge of the starting and ending positions of the two robots s_1 (right robot) & s_2 (left robot) & e_1 & e_2 and L length of the walls. Current position of the robot will be showed as r.

Ensure: $\Delta x(t) = \Delta x(0)$

1: $e_{1y} - e_{2y} = \Delta e_y$
2: $s_{1y} - s_{2y} = \Delta s_y$
3: **if** $\Delta e < 0$ **then**
4:      Move almost to up wall
5: **else**
6: Move almost to down wall
7: **end if**
8: Move to right
9: **if** $\Delta e_y - \Delta s_y > 0$ **then**
10:      Update current position of the robots: r_1 , r_2
11:      Go right for $min(\|\Delta e_y - \Delta s_y\|, L - r_{1y})$
12: **else**
13: Go left for $-min(\|\Delta e - \Delta s_y\|, r_{1y})$
14: **end if**
15: Move ϵ left
16: Update current position of the robots: r_1 , r_2
17: $\Delta r_y = r_{1y} - r_{2y}$
18: **if** $\Delta r_y = \Delta e_y$ **then**
19:      Go to e_1, e_2
20:      Return
21: **else**
22: Do the algorithm again with the inputs of r_1, r_2, e_1, e_2
23: **end if**

Time-lapse collage of 2 robots changing their relative positions

Experiment: image of testing environment: show table, 101 robots, camera, and 2 lights.

Time-lapse collage of robots changing covariance

Algorithm 3 Getting desired Space

Require: Knowledge of the starting and ending positions of the two robots s_1 & s_2 & e_1 & e_2 and L length of the walls. Current position of the robot will be showed as r.

1: $e_{1x} - e_{2x} = \Delta e_x$
2: $e_{1y} - e_{2y} = \Delta e_y$
3: $s_{1x} - s_{2x} = \Delta s_x$
4: $s_{1y} - s_{2y} = \Delta s_y$
5: **if** $\Delta s_x < \Delta s_y$ **then**
6:     Do XSpace
7:     Do YSpace
8: **else**
9:     Do YSpace
10:   Do XSpace
11: **end if**

Fig. 3. Using friction to move two robots from the starting point to their end point.