Carrier Connectivity & Audio Quality

Built specifically for Indian telecom realities. Engineered to eliminate latency, handle noisy real-world backgrounds (traffic, market chatter), and deliver crisp, natural voice exchanges.

Sub-100ms Turnaround — TARGET LATENCY

Optimized pipeline with dedicated streaming audio chunking. Eliminates unnatural 2-3 second robotic lag common in generic cloud voice bots.

Indian Ambient Filtering — 8KHZ / 16KHZ

Adaptive neural noise suppression tuned for Indian background acoustics: vehicle horns, ceiling fans, street markets, and low-bandwidth 2G/4G coverage.

Hindi & Hinglish Fluency — NATIVE ACOUSTIC

Native comprehension of code-mixed Hindi-English sentences, regional inflections, colloquial terms, and Indian numerical formats (Lakhs, Crores).

Carrier Interconnects — SIP / PSTN

Direct SIP trunking and cloud PSTN routing across Bharti Airtel, Reliance Jio, Vodafone Idea, Tata Tele Business Services, Exotel, and Twilio.

AUDIO LATENCY & NETWORK BENCHMARKING

PERFORMANCE METRIC	GENERIC CLOUD BOT	TRADITIONAL IVR	VAAKRITI ENTERPRISE
Response Latency	1,800ms - 3,200ms	Keypress Driven (Manual)	**< 100ms Streaming**
Voice Interruption (Barge-In)	Clipped / Unstable	Unsupported	**Instant Full-Duplex**
Audio Jitter Management	Noticeable crackles	Static circuit	**Adaptive Anti-Jitter Buffer**
Hinglish Code-Mixing	Frequent misunderstandings	Restricted to numbers	**Native Colloquial Accuracy**