

Exercise 4

Compilation 0368:3133

Due 24/1/2018

1 Introduction

Congratulations, you have made it to the final step of building an entire compiler for RioMare programs. Remember that the entire specification of RioMare appears inside the relevant folder of the course website. In order to make this document self contained, all the information needed to complete the fourth exercise is brought here again.

2 Programming Assignment

The fourth (and last) exercise implements the code generation phase for RioMare programs. The chosen destination language this year is MIPS assembly, favoured for its straightforward syntax, complete toolchain and available tutorials. The exercise can be roughly divided into three parts as follows: (1) recursively traverse the AST to create an intermediate representation (IR) of the program. (2) Translate IR to MIPS instructions, but use an unbounded number of temporaries instead of registers. (3) Perform liveness analysis, build the interference graph, and allocate those hundreds (or so) temporaries into 8 physical registers. The input for this last exercise is a (single) text file, containing a RioMare program, and the output is a (single) text file that contains the translation of the input program into MIPS assembly.

3 The RioMare Semantics

This section describes the semantics of RioMare, and provides a multitude of example programs.

3.1 Binary Operations

Integers in RioMare are artificially bounded between -2^{15} and $2^{15} - 1$. The semantics of integer binary operations in RioMare is therefore somewhat different than that of standard programming languages. It is presented in Table 1, and to distinguish RioMare operators from the usual arithmetic signs, we shall use a RioMare subscript inside brackets: $(*_{[RioMare]}, +_{[RioMare]}$ etc.)

$a *_{[RioMare]} b = \begin{cases} -2^{15} & \text{when } a * b \in (-\infty, -2^{15}] \\ a * b & \text{when } a * b \in (-2^{15}, 2^{15} - 1] \\ 2^{15} - 1 & \text{otherwise} \end{cases}$
$a +_{[RioMare]} b = \begin{cases} -2^{15} & \text{when } a + b \in (-\infty, -2^{15}] \\ a + b & \text{when } a + b \in (-2^{15}, 2^{15} - 1] \\ 2^{15} - 1 & \text{otherwise} \end{cases}$
$a -_{[RioMare]} b = \begin{cases} -2^{15} & \text{when } a - b \in (-\infty, -2^{15}] \\ a - b & \text{when } a - b \in (-2^{15}, 2^{15} - 1] \\ 2^{15} - 1 & \text{otherwise} \end{cases}$
$a /_{[RioMare]} b = \begin{cases} -2^{15} & \text{when } \lfloor a/b \rfloor \in (-\infty, -2^{15}] \\ \lfloor a/b \rfloor & \text{when } \lfloor a/b \rfloor \in (-2^{15}, 2^{15} - 1] \\ 2^{15} - 1 & \text{otherwise} \end{cases}$

Table 1: Semantics of RioMare binary operations between integers

Strings can be concatenated with binary operation $+$, and tested for (contents) equality with binary operator $=$. When concatenating two (null terminated) strings $\{s_i\}_{i=1}^2$, the resulting string s_1s_2 is allocated on the heap, and should be null terminated. The result of testing contents equality is either 0 when they are equal, or 1 otherwise.

3.2 If and While Statements

While statements behave similar to (practically) all programming languages: before executing their body, their condition is evaluated. If it equals 0, the body is ignored, and control is transferred to the statement immediately after the body. Otherwise, the body is executed, then the condition is evaluated again, and so forth.

If statements behave similar to (practically) all programming languages: before executing their body, their condition is evaluated. If it equals 0, the body is ignored, and control is transferred to the statement immediately after the body. Otherwise, the body is executed exactly once, then control is transferred to the statement immediately after the body.

3.3 Function Calls and Order of Evaluation

When calling a function with more than one input parameter, the evaluation order matters. You should evaluate the sent parameters from left to right, so for example, the following code should print 32766:

```
CLASS counter { int i := 32767; }
counter c := NEW counter;
void inc(){ c.i := c.i + 1; }
void dec(){ c.i := c.i - 1; }
int foo(){ return c.i; }
void main()
{
    PrintInt(foo(inc(),dec()));
}
```

Table 2: Evaluation order of a called function's parameters matters.

When evaluating global variables order matters, and it should be the same as the order of appearance in the original program. Note that before entering main, all global variables with initialized values should be evaluated.

Initializing class data members should occur during the construction of the object. The order in which you evaluate the data members initializations is irrelevant.

3.4 Runtime Checks

RioMare enforces three kinds of runtime checks: division by zero, invalid pointer dereference and out of bound array access.

Division by zero should be handled by printing “Division By Zero”, and then exit gracefully by using the exit system call. The following code will result in such behaviour:

```
int i:= 6; while (i+1) { int j := 8/i; i := i-1; }
```

Invalid pointer dereference can occur when trying to access data members or methods of uninitialized class variable. For example, here:

```
CLASS Father { int i; int j; } Father f; int i := f.i;
```

Similarly, assigning NIL to `f` should clearly trigger the same behaviour:

```
CLASS Father { int i; int j; } Father f := NIL; int i := f.i;
```

When an invalid pointer dereference occurs, the program should print “Invalid Pointer Dereference” and then then exit gracefully by using the exit system call.

Out of bound array access should be handled by printing “Access Violation” and then exit gracefully by using the exit system call. The following code demonstrates an illegal array access:

```
ARRAY IntArray = int[] IntArray A := NEW int[6]; int i := A[18];
```

3.5 System Calls

MIPS supports a limited set of system calls, out of which we will need only four: printing an integer, printing a string, allocating heap memory and exit the program.

system call example	MIPS code	Remarks
PrintInt(17)	li \$a0,17 li \$v0,1 syscall	
string s:="abc" PrintString(s)	.data myLovelyStr: .asciiz "abc" .text main: la \$a0,myLovelyStr li \$v0,4 syscall	Printed string must be null terminated. It can be allocated inside the text section, or in the heap.
Malloc(17)	li \$a0,17 li \$v0,9 syscall	allocated address is returned in \$v0
Exit()	li \$v0,10 syscall	Make sure every MIPS program ends with exit.

Table 3: Relevant MIPS system calls.

Program	::=	dec ⁺
dec	::=	funcDec varDec classDec arrayDec
varDec	::=	ID ID [ASSIGN exp] ';'
funcDec	::=	ID ID '(' [ID ID [',' ID ID]*] ')' '{' stmt [stmt]* '}'
classDec	::=	CLASS ID [EXTENDS ID] '{' cField [cField]* '}'
arrayDec	::=	ARRAY ID = ID '[' ']'
exp	::=	var
	::=	'(' exp ')'
	::=	exp BINOP exp
	::=	[var ','] ID '(' [exp [',' exp]*] ')'
	::=	'[-]' INT NIL STRING NEW ID NEW ID '[' exp ']'
var	::=	ID
	::=	var '.' ID
	::=	var '[' exp ']'
stmt	::=	varDec
	::=	var ASSIGN exp ';'
	::=	RETURN [exp] ';'
	::=	IF '(' exp ') '{' stmt [stmt]* '}'
	::=	WHILE '(' exp ') '{' stmt [stmt]* '}'
	::=	[var ','] ID '(' [exp [',' exp]*] ')' ';'
cField	::=	varDec funcDec
BINOP	::=	+ - * / < > =
INT	::=	[1 - 9][0 - 9]* 0

Table 4: Context free grammar for the RioMare programming language.

4 Input

The input for this exercise is a single text file, the input RioMare program.

5 Output

The output is a single text file that contains the translation of the input program into MIPS assembly.

Precedence	Operator	Description	Associativity
1	<code>:=</code>	assign	
2	<code>=</code>	equals	left
3	<code><, ></code>		left
4	<code>+, -</code>		left
5	<code>*, /</code>		left
6	<code>[</code>	array indexing	
7	<code>(</code>	function call	
8	<code>.</code>	field access	left

Table 5: Binary operators of RioMare along with their associativity and precedence. 1 stands for the lowest precedence, and 9 for the highest.

6 Submission Guidelines

The skeleton code for this exercise resides (as usual) in subdirectory EX4 of the course repository. COMPILATION/EX4 should contain a makefile building your source files to a runnable jar file called COMPILER (note the lack of the .jar suffix). Feel free to use the makefile supplied in the course repository, or write a new one if you want to. Before you submit, make sure that your exercise compiles and runs on the school server: *nova.cs.tau.ac.il*. This is the formal running environment of the course.

Execution parameters compiler receives 2 input file names:

InputRioMareProgram.txt
OutputMIPS.s