

Informe sobre la red local

Hecho por Darien Ruben Suazo De Jesus

Objetivos y como lograrlo

Mi objetivo con este informe es recopilar y explicar de manera resumida como escanear la red local, encontrar vulnerabilidades, puertos abierto, etc de un equipo. Como hacerlo y cual comando usar.

Ip,broadcast y netmask.

- Con el comando ifconfig este te dara la ip,broadcast y netmask de tu equipo.
- La ip: 192.168.10.12
- Netmask: 255.255.255.0
- Broadcast: 192.168.10.255

```
(kali@kali)-[~]  
$ ifconfig  
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500  
    inet 192.168.10.12 netmask 255.255.255.0 broadcast 192.168.10.255  
    inet6 fe80::e30b:1ef2:7118:604d prefixlen 64 scopeid 0x20<link>  
    ether 08:00:27:63:b0:05 txqueuelen 1000 (Ethernet)  
    RX packets 194422 bytes 11866322 (11.3 MiB)  
    RX errors 0 dropped 1 overruns 0 frame 0  
    TX packets 724130 bytes 43461164 (41.4 MiB)  
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0  
  
lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536  
    inet 127.0.0.1 netmask 255.0.0.0  
    inet6 ::1 prefixlen 128 scopeid 0x10<host>  
    loop txqueuelen 1000 (Local Loopback)  
    RX packets 15360 bytes 675968 (660.1 KiB)  
    RX errors 0 dropped 0 overruns 0 frame 0  
    TX packets 15360 bytes 675968 (660.1 KiB)  
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

La ip del route y la ip de red

- Usando el comando `netstat -r -n` es como conseguimos la dirección del route.
- ip-router: 192.168.10.110
- Ip-de-red: 192.168.10.0

```
(kali@kali)-[~]  
$ netstat -r -n  
Kernel IP routing table  
Destination Gateway Genmask Flags MSS Window irtt Iface  
0.0.0.0 192.168.10.110 0.0.0.0 UG 0 0 0 eth0  
192.168.10.0 0.0.0.0 255.255.255.0 U 0 0 0 eth0
```

Como sacar el prefijo de red

- Primero que todo que es un prefijo de red? Un prefijo de red indica cuántos bits (de los 32 en IPv4 o 128 en IPv6) se utilizan para identificar la red, separados por una barra diagonal (ej. /24). Define la parte de red de una dirección IP, permitiendo el enrutamiento eficiente y la división en subredes al especificar qué bits son fijos para todos los hosts.
- Para sacar simplemente hay que multiplicar el 255 que aparece en el netmask por 8. esto quiere decir que si hay dos 255 entonces el prefijo es /16. en nuestro caso tiene tres entonces seria 8x3 que seria igual a 24 y ese seria nuestro prefijo.

```
netmask 255.255.255.0
```

Ip totales, asignables y disponibles.

- Con el comando arp-scan podemos saber la cantidad de ip totales y asignables.
- Como se puede ver tenemos 256 ip y 249 ip asignables.
- Ademas podemos ver que hay 7 ip activas.

```
(kali@kali)-[~]  
$ sudo arp-scan -I eth0 --localnet  
[sudo] password for kali:  
Interface: eth0, type: EN10MB, MAC: 08:00:27:63:b0:05, IPv4: 192.168.10.12  
WARNING: Cannot open MAC/Vendor file ieee-oui.txt: Permission denied  
WARNING: Cannot open MAC/Vendor file mac-vendor.txt: Permission denied  
Starting arp-scan 1.10.0 with 256 hosts (https://github.com/royhills/arp-scan)  
192.168.10.1    b0:22:7a:34:e2:2b    (Unknown)  
192.168.10.3    94:b3:f7:12:5d:3e    (Unknown)  
192.168.10.6    1a:0e:16:23:35:0f    (Unknown: locally administered)  
192.168.10.4    78:d8:40:9e:b6:d4    (Unknown)  
192.168.10.7    82:1d:96:9c:9d:75    (Unknown: locally administered)  
192.168.10.8    7e:05:ba:3d:ef:42    (Unknown: locally administered)  
192.168.10.110  98:f9:cc:47:4f:e9    (Unknown)  
  
7 packets received by filter, 0 packets dropped by kernel  
Ending arp-scan 1.10.0: 256 hosts scanned in 1.825 seconds (140.27 hosts/sec). 7 responded
```

Ip vulnerable

- Para ver las ips vulnerables se tiene que usar el comando nmap para ver cuales ip están vulnerable.
- Como se puede en esta red no hay ip vulnerables

```
(kali@kali)-[~]  
$ sudo nmap -sCV -p 135,139,445 -vvv 192.168.10.110/24  
Starting Nmap 7.98 ( https://nmap.org ) at 2026-02-02 21:58 -0500  
NSE: Loaded 158 scripts for scanning.  
NSE: Script Pre-scanning.  
NSE: Starting runlevel 1 (of 3) scan.  
Initiating NSE at 21:58  
Completed NSE at 21:58, 0.00s elapsed  
NSE: Starting runlevel 2 (of 3) scan.  
Initiating NSE at 21:58  
Completed NSE at 21:58, 0.00s elapsed  
NSE: Starting runlevel 3 (of 3) scan.  
Initiating NSE at 21:58  
Completed NSE at 21:58, 0.00s elapsed  
Initiating ARP Ping Scan at 21:58  
Scanning 255 hosts [1 port/host]  
Completed ARP Ping Scan at 21:58, 4.91s elapsed (255 total hosts)  
Initiating Parallel DNS resolution of 5 hosts. at 21:58  
Completed Parallel DNS resolution of 5 hosts. at 21:58, 2.01s elapsed
```

```
PORT      STATE SERVICE REASON  VERSION  
135/tcp   filtered msrpc   no-response  
139/tcp   filtered netbios-ssn no-response  
445/tcp   filtered microsoft-ds no-response  
MAC Address: B0:22:7A:34:E2:2B (HP)  
  
Nmap scan report for 192.168.10.3  
Host is up, received arp-response (0.084s latency).  
Scanned at 2026-02-02 21:58:44 EST for 7s  
  
PORT      STATE SERVICE REASON  VERSION  
135/tcp   closed msrpc   reset ttl 64  
139/tcp   closed netbios-ssn reset ttl 64  
445/tcp   closed microsoft-ds reset ttl 64  
MAC Address: 94:83:F7:12:5D:3E (Hui Zhou Gaoshengda Technology)  
  
Nmap scan report for 192.168.10.7  
Host is up, received arp-response (0.12s latency).  
Scanned at 2026-02-02 21:58:44 EST for 7s  
  
PORT      STATE SERVICE REASON  VERSION  
135/tcp   closed msrpc   reset ttl 64  
139/tcp   closed netbios-ssn reset ttl 64  
445/tcp   closed microsoft-ds reset ttl 64  
MAC Address: 82:1D:96:9C:9D:75 (Unknown)  
  
Nmap scan report for 192.168.10.8  
Host is up, received arp-response (0.29s latency).  
Scanned at 2026-02-02 21:58:44 EST for 7s  
  
PORT      STATE SERVICE REASON  VERSION  
135/tcp   closed msrpc   reset ttl 64  
139/tcp   closed netbios-ssn reset ttl 64  
445/tcp   closed microsoft-ds reset ttl 64  
MAC Address: 7E:05:BA:3D:EF:42 (Unknown)  
  
Nmap scan report for dahuawifi.com (192.168.10.110)  
Host is up, received arp-response (0.0018s latency).  
Scanned at 2026-02-02 21:58:44 EST for 7s  
  
PORT      STATE SERVICE REASON  VERSION  
135/tcp   closed msrpc   reset ttl 64  
139/tcp   closed netbios-ssn reset ttl 64  
445/tcp   closed microsoft-ds reset ttl 64  
MAC Address: 98:F9:CC:47:4F:E9 (Zhejiang Dahua Technology)
```

Puertos abiertos

- Con el comando de nmap pude ver todo los puertos abierto que tiene los dispositivo.
- Como se puede ver tengo 17 puertos abiertos.

```
(kali㉿kali)-[~]  
$ sudo nmap -p- --open -vvv 192.168.10.110/24
```

PORT	STATE	SERVICE	REASON
5040/tcp	open	unknown	syn-ack ttl 128
5357/tcp	open	wsdapi	syn-ack ttl 128
7680/tcp	open	pando-pub	syn-ack ttl 128
9993/tcp	open	palace-2	syn-ack ttl 128

PORT	STATE	SERVICE	REASON
6466/tcp	open	unknown	syn-ack ttl 64
6467/tcp	open	unknown	syn-ack ttl 64
6553/tcp	open	unknown	syn-ack ttl 64
8008/tcp	open	http	syn-ack ttl 64
8009/tcp	open	ajp13	syn-ack ttl 64
8443/tcp	open	https-alt	syn-ack ttl 64
9000/tcp	open	cslistener	syn-ack ttl 64
16330/tcp	open	unknown	syn-ack ttl 64
33173/tcp	open	unknown	syn-ack ttl 64
44281/tcp	open	unknown	syn-ack ttl 64

PORT	STATE	SERVICE	REASON
53/tcp	open	domain	syn-ack ttl 64
80/tcp	open	http	syn-ack ttl 64
52881/tcp	open	unknown	syn-ack ttl 64

Mucha gracias por leer el
informe

Que tengan un buen dia