



Pre-trained Models for Natural Language Processing: A Survey

自然语言处理预训练模型综述

周梅、周雨慧、陈悦

2021年10月28日

CONTENTS



1. Introduction



2. Classification




3. Main models



4. Conclusion






1. Introduction



1. Introduction

1.1 为什么需要预训练模型

- 从CV领域中来
- 标注数据昂贵
- 性能极大提升




- 在庞大的无标注数据上进行预训练可以获取更通用的语言表示，并有利于下游任务
- 为模型提供了一个更好的初始化参数，在目标任务上具备更好的泛化性能、并加速收敛
- 是一种有效的正则化手段，避免在小数据集上过拟合（一个随机初始化的深层模型容易对小数据集过拟合）

1. Introduction

1.2 词嵌入 (word embedding)

	o_ENE	o_ESE	o_East	o_NE	o_NNE	o_NNW	o_NW	o_North	o_SE	o_SSE	o_SSW	o_SW	o_South	o_Variable	o_WSW
0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0
1	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0
2	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
4	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0
5	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0
6	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
8	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0
10	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0

One-Hot



Projection of the embedding vectors to 2-D

- 机器学习时代：矩阵分解（SVD）、LSA、LDA
- 深度学习时代：Word2Vec、Bert、GPT

1.3 预训练模型两大范式

1. 浅层词嵌入（Non-Contextual Embeddings）

词嵌入	训练目标	全局/局部语料
NNLM	语言模型	局部语料
word2vec	非语言模型 (窗口上下文)	局部语料
Glove	非语言模型 (词共现矩阵)	全局语料

浅层词嵌入的主要缺陷为：词嵌入与上下文无关，每个单词的嵌入向量始终是相同，因此不能解决一词多义的问题。


2. 预训练编码器（Contextual Embeddings）


编码器	PTMs代表	计算方式
MLP	NNLM/word2vec	前馈+并行
CNNs		前馈+并行
RNNs	ELMO	循环+串行
Transformer	GPT (Decoder) BERT (Encoder)	前馈+并行
Transformer-XL	XLNet	循环+串行
长距离依赖建模能力		

预训练编码器通常采用LSTM和Transformer两种特征提取器

1. Introduction

1.4 PTMs的发展历程





2. Classification



2. Classification


2.1 预训练任务类型


Task	Loss Function	Description
LM	$\mathcal{L}_{\text{LM}} = - \sum_{t=1}^T \log p(x_t \mathbf{x}_{<t})$	$\mathbf{x}_{<t} = x_1, x_2, \dots, x_{t-1}$.
MLM	$\mathcal{L}_{\text{MLM}} = - \sum_{\hat{x} \in m(\mathbf{x})} \log p(\hat{x} \mathbf{x}_{\setminus m(\mathbf{x})})$	$m(\mathbf{x})$ and $\mathbf{x}_{\setminus m(\mathbf{x})}$ denote the masked words from \mathbf{x} and the rest words respectively.
Seq2Seq MLM	$\mathcal{L}_{\text{S2SMLM}} = - \sum_{t=i}^j \log p(x_t \mathbf{x}_{\setminus \mathbf{x}_{i:j}}, \mathbf{x}_{i:t-1})$	$\mathbf{x}_{i:j}$ denotes an masked n-gram span from i to j in \mathbf{x} .
PLM	$\mathcal{L}_{\text{PLM}} = - \sum_{t=1}^T \log p(z_t \mathbf{z}_{<t})$	$\mathbf{z} = \text{perm}(\mathbf{x})$ is a permutation of \mathbf{x} with random order.
DAE	$\mathcal{L}_{\text{DAE}} = - \sum_{t=1}^T \log p(x_t \hat{\mathbf{x}}, \mathbf{x}_{<t})$	$\hat{\mathbf{x}}$ is randomly perturbed text from \mathbf{x} .
DIM	$\mathcal{L}_{\text{DIM}} = s(\hat{\mathbf{x}}_{i:j}, \mathbf{x}_{i:j}) - \log \sum_{\tilde{\mathbf{x}}_{i:j} \in \mathcal{N}} s(\hat{\mathbf{x}}_{i:j}, \tilde{\mathbf{x}}_{i:j})$	$\mathbf{x}_{i:j}$ denotes an n-gram span from i to j in \mathbf{x} , $\hat{\mathbf{x}}_{i:j}$ denotes a sentence masked at position i to j , and $\tilde{\mathbf{x}}_{i:j}$ denotes a randomly-sampled negative n-gram from corpus.
NSP/SOP	$\mathcal{L}_{\text{NSP/SOP}} = - \log p(t \mathbf{x}, \mathbf{y})$	$t = 1$ if \mathbf{x} and \mathbf{y} are continuous segments from corpus.
RTD	$\mathcal{L}_{\text{RTD}} = - \sum_{t=1}^T \log p(y_t \hat{\mathbf{x}})$	$y_t = \mathbf{1}(\hat{x}_t = x_t)$, $\hat{\mathbf{x}}$ is corrupted from \mathbf{x} .

¹ $\mathbf{x} = [x_1, x_2, \dots, x_T]$ denotes a sequence.

2. Classification

2.2 预训练模型分类





3. Main models




3. Main models

3.1 AllenNLP ELMo: Embeddings from Language Models



- ✓ Embedding size: 512
 - ✓ 2048 character n-gram convolutional filters
- ✓ BiLSTM layers: 2
- ✓ BiLSTM hidden states : 4096
- ✓ Residual Connection

分别训练前向语言模型和反向语言模型



3. Main models

3.2 自注意力 (Self-Attention)



3.3 Transformer: 可能是目前为止最适合NLP的模型


◆ 广义的**Transformer**指一种基于自注意力的全连接神经网络

□ 核心组件

- 自注意力（Self-Attention）


□ 仅仅自注意力还不够，包括其它操作

- 位置编码
- 层归一化
- 直连边
- 逐位的FNN



3. Main models



3.3 Transformer完整结构



3. Main models

3.4 OpenAI GPT: Generative Pre-Training

- ✓ BPE tokens: 7,000
- ✓ Embedding size: 512
- ✓ Transformer layers: 12
- ✓ Attention heads: 12
- ✓ Attention hidden states: 768
- ✓ FFN hidden states : 3072



Radford A, Narasimhan K, Salimans T, et al. Improving language understanding by generative pre-training. 2018.

3. Main models

3.4 GPT-3: Language Models are Few-Shot Learners

The three settings we explore for in-context learning

Zero-shot

The model predicts the answer given only a natural language description of the task. No gradient updates are performed.

```
1 Translate English to French:  ← task description
2 cheese =>                   ← prompt
```

One-shot

In addition to the task description, the model sees a single example of the task. No gradient updates are performed.


```
1 Translate English to French:  ← task description
2 sea otter => loutre de mer    ← example
3 cheese =>                    ← prompt
```

Few-shot

In addition to the task description, the model sees a few examples of the task. No gradient updates are performed.



```
1 Translate English to French:  ← task description
2 sea otter => loutre de mer    ← examples
3 peppermint => menthe poivrée ←
4 plush girafe => girafe peluche ←
5 cheese =>                    ← prompt
```

Dataset	Quantity (tokens)	Weight in training mix	Epochs elapsed when training for 300B tokens
Common Crawl (filtered)	410 billion	60%	0.44
WebText2	19 billion	22%	2.9
Books1	12 billion	8%	1.9
Books2	55 billion	8%	0.43
Wikipedia	3 billion	3%	3.4



3. Main models

3.5 Bert



3.5 Bert

Task1. Masked Language Model


- 80%: my dog is hairy -> my dog is [mask]
- 10%: my dog is hairy -> my dog is apple
- 10%: my dog is hairy -> my dog is hairy

Task2. Next Sentence Prediction


目的是让模型理解两个句子之间的联系。训练的输入是句子A和B，B有一半的几率是A的下一句，输入这两个句子，模型预测B是不是A的下一句。

3.5 Bert


- ◆ 单个序列文本分类任务(SST-2, CoLA)
- ◆ 两个序列文本分类任务(MNLI, QQP, QNLI, STS-B, MRPC, RTE)
- ◆ 阅读理解任务(SQuAD)
- ◆ 序列标注任务(CoNLL-2003 NER)




(a) Sentence Pair Classification Tasks:
MNLI, QQP, QNLI, STS-B, MRPC,
RTE, SWAG



(b) Single Sentence Classification Tasks:
SST-2, CoLA




(c) Question Answering Tasks:
SQuAD v1.1



(d) Single Sentence Tagging Tasks:
CoNLL-2003 NER

3. Main models


3.6 T5——Seq2Seq Masked Language Modeling



Text-to-Text Transfer Transformer (T5)

3. Main models

3.7 XLNet—Permutation Language Modeling



	x_1	x_4	x_2	x_3
x_1	●			
x_4	●	●		
x_2	●	●	●	
x_3	●	●	●	●



ELNet

	x_1	x_2	x_3	x_4
x_1	●			
x_2	●	●		●
x_3	●	●	●	●
x_4	●			●

Yang Z, Dai Z, Yang Y, et al. Xlnet: Generalized autoregressive pretraining for language understanding. Advances in neural information processing systems. 2019.

3. Main models

3.7 XLNet




Figure 2: (a): Content stream attention, which is the same as the standard self-attention. (b): Query stream attention, which does not have access information about the content x_{z_t} . (c): Overview of the permutation language modeling training with two-stream attention.

3. Main models

3.7 XLNet

阅读理解 (RACE) : 性能比较

RACE	Accuracy	Middle	High
GPT [25]	59.0	62.9	57.4
BERT [22]	72.0	76.6	70.1
BERT+OCN* [28]	73.5	78.4	71.5
BERT+DCMN* [39]	74.1	79.5	71.8
XLNet	81.75	85.45	80.21

Bert效果

XLNet效果: 效果提升明显

阅读理解 (SQuAD) : 性能比较

SQuAD1.1	EM	F1	SQuAD2.0	EM	F1
Dev set results without data augmentation					
BERT [10]	84.1	90.9	BERT† [10]	78.98	81.77
XLNet	88.95	94.52	XLNet	86.12	88.79
Test set results on leaderboard, with data augmentation (as of June 19, 2019)					
Human [27]	82.30	91.22	BERT+N-Gram+Self-Training [10]	85.15	87.72
ATB	86.94	92.64	SG-Net	85.23	87.93
BERT* [10]	87.43	93.16	BERT+DAE+AoA	85.88	88.62
XLNet	89.90	95.08	XLNet	86.35	89.13

较长文档: 效果提升明显

综合NLP任务 (GLUE) : 性能比较

Model	MNLI	QNLI	QQP	RTE	SST-2	MRPC	CoLA	STS-B	WNLI
Single-task single models on dev									
BERT [2]	86.6/-	92.3	91.3	70.4	93.2	88.0	60.6	90.0	-
XLNet	89.8/-	93.9	91.8	83.8	95.6	89.2	63.6	91.8	-
Single-task single models on test									
BERT [10]	86.7/85.9	91.1	89.3	70.1	94.9	89.3	60.5	87.6	65.1
Multi-task ensembles on test (from leaderboard as of June 19, 2019)									
Snorkel* [29]	87.6/87.2	93.9	89.9	80.9	96.2	91.5	63.8	90.1	65.1
ALICE*	88.2/87.9	95.7	90.7	83.5	95.2	92.6	68.6	91.1	80.8
MT-DNN* [18]	87.9/87.4	96.0	89.9	86.3	96.5	92.7	68.4	91.1	89.0
XLNet*	90.2/89.7†	98.6†	90.3†	86.3	96.8†	93.0	67.8	91.6	90.4

重点看这组数据: 效果也有提升

3. Main models

3.7 XLNet

文本分类任务：性能比较

Model	IMDB	Yelp-2	Yelp-5	DBpedia	AG	Amazon-2	Amazon-5
CNN [14]	-	2.90	32.39	0.84	6.57	3.79	36.24
DPCNN [14]	-	2.64	30.58	0.88	6.87	3.32	34.81
Mixed VAT [30, 20]	4.32	-	-	0.70	4.95	-	-
ULMFIT [13]	4.6	2.16	29.98	0.80	5.01	-	-
BERT [35]	4.51	1.89	29.32	0.64	-	2.63	34.17
XLNet	3.79	1.55	27.80	0.62	4.49	2.40	32.26

重点看这组数据：效果有提升，幅度不算大

信息检索任务：性能比较

Model	NDCG@20	ERR@20
DRMM [12]	24.3	13.8
KNRM [8]	26.9	14.9
Conv [8]	28.7	18.1
BERT [†]	30.53	18.67
XLNet	31.10	20.28

重点看这组数据：效果有提升，幅度不算大

3.7 XLNet

1. 与Bert采取De-noising Autoencoder方式不同的新的预训练目标: **Permutation Language Model(简称PLM)**; 打开了NLP中两阶段模式潮流的一个新思路。

2. 引入了Transformer-XL的主要思路: 相对位置编码以及分段RNN机制。实践已经证明这两点对于长文档任务是很有帮助的;

3. 加大增加了预训练阶段使用的数据规模; Bert使用的预训练数据是BooksCorpus和英文Wiki数据, 大小13G。XLNet除了使用这些数据外, 另外引入了Giga5, ClueWeb以及Common Crawl数据, 并排掉了其中的一些低质量数据, 大小分别是16G,19G和78G。


XLNet与Bert纯粹模型比较: 性能比较

#	Model	RACE	SQuAD2.0		MNLI m/mm	SST-2
			F1	EM		
1	BERT-Base	64.3	76.30	73.66	84.34/84.65	92.78
2	DAE + Transformer-XL	65.03	79.56	76.80	84.88/84.45	92.60
3	XLNet-Base ($K = 7$)	66.05	81.33	78.46	85.84/85.43	92.66
4	XLNet-Base ($K = 6$)	66.66	80.98	78.18	85.63/85.12	93.35
5	- memory	65.55	80.15	77.27	85.32/85.05	92.78
6	- span-based pred	65.95	80.61	77.91	85.49/85.02	93.12
7	- bidirectional data	66.34	80.65	77.87	85.31/84.99	92.66
8	+ next-sent pred	66.76	79.83	76.94	85.32/85.09	92.89

与Bert相比: 长文档阅读理解提升幅度大, 其它任务还好

哈工大讯飞联合实验室 (HFL) ——中文XLNet: <https://github.com/ymcui/Chinese-XLNet>


3.8 小结



3. Main models

3.8 小结

PTMs	Architecture [†]	Input	Pre-Training Task	Corpus	Params	GLUE [‡]	FT? [#]
ELMo [14]	LSTM	Text	BiLM	WikiText-103			No
GPT [15]	Transformer Dec.	Text	LM	BookCorpus	117M	72.8	Yes
GPT-2 [58]	Transformer Dec.	Text	LM	WebText	117M ~ 1542M		No
BERT [16]	Transformer Enc.	Text	MLM & NSP	WikiEn+BookCorpus	110M ~ 340M	81.9*	Yes
InfoWord [55]	Transformer Enc.	Text	DIM+MLM	WikiEn+BookCorpus	=BERT	81.1*	Yes
RoBERTa [43]	Transformer Enc.	Text	MLM	BookCorpus+CC-News+OpenWebText+ STORIES	355M	88.5	Yes
XLNet [49]	Two-Stream Transformer Enc.	Text	PLM	WikiEn+ BookCorpus+Giga5+ClueWeb+Common Crawl	≈BERT	90.5 [§]	Yes
ELECTRA [56]	Transformer Enc.	Text	RTD+MLM	same to XLNet	335M	88.6	Yes
UniLM [44]	Transformer Enc.	Text	MLM [‡] + NSP	WikiEn+BookCorpus	340M	80.8	Yes
MASS [41]	Transformer	Text	Seq2Seq MLM	*Task-dependent			Yes
BART [50]	Transformer	Text	DAE	same to RoBERTa	110% of BERT	88.4*	Yes
T5 [42]	Transformer	Text	Seq2Seq MLM	Colossal Clean Crawled Corpus (C4)	220M ~ 11B	89.7*	Yes
ERNIE(THU) [76]	Transformer Enc.	Text+Entities	MLM+NSP+dEA	WikiEn + Wikidata	114M	79.6	Yes
KnowBERT [77]	Transformer Enc.	Text	MLM+NSP+EL	WikiEn + WordNet/Wiki	253M ~ 523M		Yes
K-BERT [78]	Transformer Enc.	Text+Triples	MLM+NSP	WikiZh + WebtextZh + CN-DBpedia + HowNet + MedicalKG	=BERT		Yes
KEPLER [80]	Transformer Enc.	Text	MLM+KE	WikiEn + Wikidata/WordNet			Yes
WKLM [57]	Transformer Enc.	Text	MLM+ERD	WikiEn + Wikidata	=BERT		Yes
CoLAKE [81]	Transformer Enc.	Text+Triples	MLM	WikiEn + Wikidata	=RoBERTa	86.3	Yes



4. Prospect



4.1 如何对预训练模型进行迁移学习？

1) 选择合适的预训练任务：

语言模型PTM是最为流行的预训练任务；预训练任务有其自身的偏置，并且对不同的任务会产生不同的效果。例如，NSP任务可以使诸如问答（QA）和自然语言推论（NLI）之类的下游任务受益。

2) 选择合适的模型架构：

例如BERT采用的MLM策略和Transformer-Encoder结构，导致其不适合直接处理生成任务。

3) 选择合适的数据：

下游任务的数据应该近似于PTMs的预训练任务，现在已有有很多现成的PTMs可以方便地用于各种特定领域或特定语言的下游任务。

4) 选择合适的layers进行transfer：

主要包括Embedding迁移、top layer迁移和all layer迁移。如word2vec和Glove可采用Embedding迁移，BERT可采用top layer迁移，Elmo可采用all layer迁移。

5) 特征集成还是fine-tune？

对于特征集成预训练参数是freeze的，而fine-tune是unfreeze的。特征集成方式却需要特定任务的体系结构，fine-tune方法通常比特征提取方法更为通用和方便。

4.2 预训练模型还有哪些问题需要解决？

1、PTMs的上限

大多数的PTMs可通过使用更长训练步长和更大数据集来提升其性能。

2、面向任务的预训练和模型压缩

在实践中，不同的目标任务需要 PTMs 拥有不同功能。而 PTMs 与下游目标任务间的差异通常在于两方面：模型架构与数据分布。

3、PTMs的架构设计

对于PTMs，Transformer 已经被证实是一个高效的架构。然而 Transformer 最大的局限在于其计算复杂度（输入序列长度的平方倍）。

4、finetune中的知识迁移

finetune是目前将 PTM 的知识转移至下游任务的主要方法，但效率却很低，每个下游任务都需要有特定的 finetune 参数。

5、PTMs 的解释性与可靠性

PTMs 的可解释性与可靠性仍然需要从各个方面去探索，它能够帮助我们理解 PTM 的工作机制，为更好的使用及性能改进提供指引。



Pre-trained Models for Natural Language Processing: A Survey
自然语言处理预训练模型综述

Thanks!