

```

METHOD /iwbsp/if_mgw_appl_srv_runtime~create_deep_entity.
**TRY.
*CALL METHOD SUPER->/IWBEP/IF_MGW_APPL_SRV_RUNTIME~CREATE_DEEP_ENTITY
*   EXPORTING
**       iv_entity_name           =
**       iv_entity_set_name       =
**       iv_source_name           =
*       IO_DATA_PROVIDER          =
**       it_key_tab               =
**       it_navigation_path       =
*       IO_EXPAND                 =
**       io_tech_request_context =
** IMPORTING
**       er_deep_entity           =
*
*
** CATCH /iwbsp/cx_mgw_busi_exception .
** CATCH /iwbsp/cx_mgw_tech_exception .
**ENDTRY.

DATA:
ls_so_all TYPE zcl_zso_creation_mpc_ext=>ty_so_all.
DATA:
lo_msg_container TYPE REF TO /iwbsp/if_message_container.

DATA:
ls_header_in  TYPE bapisdhd1,
ls_header_inx TYPE bapisdhd1x,
lt_items      TYPE TABLE OF bapisditm,
lt_itemsx     TYPE TABLE OF bapisditmx,
lt_partners   TYPE TABLE OF bapiparnr,
lt_schedules  TYPE TABLE OF bapischdl,
lt_schedulesx TYPE TABLE OF bapischdlx,
lt_return     TYPE TABLE OF bapiret2.

DATA:
lv_vbeln TYPE vbeln_va.

*-----
* Read Payload
*-----

io_data_provider->read_entry_data(
    IMPORTING
        es_data = ls_so_all ).

*-----
* Create only
*-----

IF ls_so_all-vbeln IS INITIAL.

*-----
* Header
*-----

ls_header_in-doc_type   = ls_so_all-auart.
ls_header_in-sales_org  = ls_so_all-vkorg.
ls_header_in-distr_chan = ls_so_all-vtweg.
ls_header_in-division   = ls_so_all-spart.
ls_header_in-doc_date   = '20250627'.

ls_header_inx-updateflag = 'I'.

```

```
ls_header_inx-doc_type   = 'X'.
ls_header_inx-sales_org  = 'X'.
ls_header_inx-distr_chan = 'X'.
ls_header_inx-division   = 'X'.
ls_header_inx-doc_date   = 'X'.
```

```
* -----
* Partner
* -----
```

```
APPEND VALUE bapiparnr(
  partn_role = 'AG'
  partn_num  = ls_so_all-kunnr ) TO lt_partners.
```

```
* -----
* Items
* -----
```

```
LOOP AT ls_so_all-toitem INTO DATA(ls_item).
```

```
  APPEND VALUE bapisditm(

    itm_number = ls_item-posnr
    material   = ls_item-matnr
    target_qty = ls_item-zmeng
    target_qu  = ls_item-meins
    plant      = ls_item-werks
    store_loc  = ls_item-lgort
    short_text = ls_item-arktx
```

```
  ) TO lt_items.
```

```
  APPEND VALUE bapisditmx(

    itm_number = ls_item-posnr
    updateflag = 'I'
    material   = 'X'
    target_qty = 'X'
    target_qu  = 'X'
    plant      = 'X'
    store_loc  = 'X'
    short_text = 'X'
```

```
  ) TO lt_itemsx.
```

```
* -----
* Schedule Lines
* -----
```

```
APPEND VALUE bapischdl(

  itm_number = ls_item-posnr
  sched_line = '0001'
  req_qty    = ls_item-zmeng
  req_date   = '20250627'
```

```
  ) TO lt_schedules.
```

```
APPEND VALUE bapischdlx(

  itm_number = ls_item-posnr
```

```
    sched_line = '0001'  
    updateflag = 'I'  
    req_qty    = 'X'  
    req_date   = 'X'
```

```
) TO lt_schedulesx.
```

```
ENDLOOP.
```

```
*-----  
* Create Sales Order  
*-----
```

```
CALL FUNCTION 'BAPI_SALESORDER_CREATEFROMDAT2'
```

```
EXPORTING
```

```
    order_header_in    = ls_header_in  
    order_header_inx   = ls_header_inx
```

```
IMPORTING
```

```
    salesdocument      = lv_vbeln
```

```
TABLES
```

```
    return             = lt_return  
    order_items_in     = lt_items  
    order_items_inx    = lt_itemsx  
    order_partners     = lt_partners  
    order_schedules_in = lt_schedules  
    order_schedules_inx = lt_schedulesx.
```

```
*-----  
* Error Check  
*-----
```

```
READ TABLE lt_return WITH KEY type = 'E'  
    TRANSPORTING NO FIELDS.
```

```
IF sy-subrc <> 0.
```

```
    READ TABLE lt_return WITH KEY type = 'A'  
        TRANSPORTING NO FIELDS.
```

```
ENDIF.
```

```
*-----  
* Success  
*-----
```

```
IF sy-subrc <> 0.
```

```
CALL FUNCTION 'BAPI_TRANSACTION_COMMIT'
```

```
EXPORTING
```

```
    wait = 'X'.
```

```
ls_so_all-vbeln = lv_vbeln.
```

```
LOOP AT ls_so_all-toitem ASSIGNING FIELD-SYMBOL(<fs_item>).
```

```
    <fs_item>-vbeln = lv_vbeln.
```

```
ENDLOOP.
```

```
lo_msg_container =
```

```
me->/iwbep/if_mgw_conv_srv_runtime-get_message_container( ).
```

```
lo_msg_container->add_message(
```

```

iv_msg_type      = 'S'
iv_msg_id        = '00'
iv_msg_number    = '398'
iv_msg_v1        = |Sales Order { lv_vbeln } Created Successfully|
iv_add_to_response_header = abap_true ).

```

```

" 3. Pass processing structures back through the pipeline channel safely with 'me->'
me->copy_data_to_ref(
  EXPORTING
    is_data = ls_so_all
  CHANGING
    cr_data = er_deep_entity ).

```

```

* -----
* Error
* -----

```

ELSE.

```
CALL FUNCTION 'BAPI_TRANSACTION_ROLLBACK'.
```

```

lo_msg_container =
me->/iwbep/ifu_mgw_conv_srv_runtime~get_message_container( ).

```

```
LOOP AT lt_return INTO DATA(ls_return).
```

```

  lo_msg_container->add_message(

    iv_msg_type = ls_return-type
    iv_msg_id   = ls_return-id
    iv_msg_number = ls_return-number
    iv_msg_v1    = ls_return-message_v1
    iv_msg_v2    = ls_return-message_v2
    iv_msg_v3    = ls_return-message_v3
    iv_msg_v4    = ls_return-message_v4 ).

```

ENDLOOP.

```

RAISE EXCEPTION TYPE /iwbep/cx_mgw_busi_exception
  EXPORTING
    message_container = lo_msg_container.

```

ENDIF.

```

* -----
* Update Not Allowed
* -----

```

ELSE.

```

DATA(lo_msg) =
me->/iwbep/ifu_mgw_conv_srv_runtime~get_message_container( ).

```

```

lo_msg->add_message(
  iv_msg_type = 'E'
  iv_msg_id   = '00'
  iv_msg_number = '001'
  iv_msg_text  = 'Update scenario is not implemented.' ).

```

```

RAISE EXCEPTION TYPE /iwbep/cx_mgw_busi_exception
  EXPORTING

```

```
message_container = lo_msg.
```

```
ENDIF.
```

```
ENDMETHOD.
```