

Kubernetes

Lab1

- 1- Create a pod with the name “imperative-nginx” and with the image nginx and latest tag. using Imperative command (not yaml).

```
controlplane $ kubectl run imperative-nginx --image=nginx
pod/imperative-nginx created
controlplane $ kubectl get pod
```

NAME	READY	STATUS	RESTARTS	AGE
imperative-nginx	1/1	Running	0	24s

- 2- Create a pod with the name webserver and with the image “nginx123” Use a pod-definition YAML file.

```
apiVersion: v1
kind: Pod
metadata:
  name: webserver
spec:
  containers:
  - name: nginx
    image: nginx123
```

```
controlplane $ vim pod-definition.yaml
controlplane $ kubectl apply -f pod-definition.yaml
pod/webserver created
controlplane $ kubectl get pod
```

NAME	READY	STATUS	RESTARTS	AGE
imperative-nginx	1/1	Running	0	7m3s
webserver	0/1	ContainerCreating	0	3s

- 3- What is the nginx pod status?

State: ImagePullBackOff

- 4- Change the nginx pod image to “nginx” check the status again

```
controlplane $ vim pod-definition.yaml
controlplane $ kubectl apply -f pod-definition.yaml
pod/webserver configured
controlplane $ kubectl get pod
```

NAME	READY	STATUS	RESTARTS	AGE
imperative-nginx	1/1	Running	0	12m
webserver	1/1	Running	0	5m50s

- 5-How many pods are running in the system? Type the command to show this

```
controlplane $ kubectl get pod
```

NAME	READY	STATUS	RESTARTS	AGE
imperative-nginx	1/1	Running	0	14m
webserver	1/1	Running	0	7m19s

- 6- What does READY column in the output of get pods command indicate?

Ans: it shows how many containers in a pod are considered ready

- 7- Delete the first pod named imperative-nginx you just created. Type the command to do this

```
controlplane $ kubectl delete pod/imperative-nginx
pod "imperative-nginx" deleted
controlplane $ kubectl get pod
NAME          READY   STATUS    RESTARTS   AGE
webserver     1/1     Running   0           13m
```

- 8- Which node is pod named webserver running on (list two commands to do this)

```
controlplane $ kubectl get pod -o wide
NAME          READY   STATUS    RESTARTS   AGE   IP          NODE    NOMINATED NODE   READINESS GATES
webserver     1/1     Running   0           15m   192.168.1.4 node01    <none>           <none>
controlplane $ kubectl describe pod webserver
Name:         webserver
Namespace:    default
Priority:      0
Service Account: default
Node:         node01/172.30.2.2
Start Time:   Mon, 16 Jan 2023 11:34:02 +0000
Labels:       <none>
```

- 9- Get a shell to the running container i.e ssh into it (figure out the command)
- 10- Run cat /etc/os-release inside the container
- 11- Exit from the shell (/bin/bash) session

```
controlplane $ kubectl exec -it webserver -- /bin/bash
root@webserver:/# cat /etc/os-release
PRETTY_NAME="Debian GNU/Linux 11 (bullseye)"
NAME="Debian GNU/Linux"
VERSION_ID="11"
VERSION="11 (bullseye)"
VERSION_CODENAME=bullseye
ID=debian
HOME_URL="https://www.debian.org/"
SUPPORT_URL="https://www.debian.org/support"
BUG_REPORT_URL="https://bugs.debian.org/"
root@webserver:/# exit
exit
```

- 12- Get logs of pod, what are logs and what they are used for?

```
controlplane $ kubectl logs webserver
/docker-entrypoint.sh: /docker-entrypoint.d/ is not empty, will attempt to perform configuration
/docker-entrypoint.sh: Looking for shell scripts in /docker-entrypoint.d/
/docker-entrypoint.sh: Launching /docker-entrypoint.d/10-listen-on-ipv6-by-default.sh
10-listen-on-ipv6-by-default.sh: info: Getting the checksum of /etc/nginx/conf.d/default.conf
10-listen-on-ipv6-by-default.sh: info: Enabled listen on IPv6 in /etc/nginx/conf.d/default.conf
/docker-entrypoint.sh: Launching /docker-entrypoint.d/20-envsubst-on-templates.sh
/docker-entrypoint.sh: Launching /docker-entrypoint.d/30-tune-worker-processes.sh
/docker-entrypoint.sh: Configuration complete; ready for start up
2023/01/16 12:11:56 [notice] 1#1: using the "epoll" event method
2023/01/16 12:11:56 [notice] 1#1: nginx/1.23.3
2023/01/16 12:11:56 [notice] 1#1: built by gcc 10.2.1 20210110 (Debian 10.2.1-6)
2023/01/16 12:11:56 [notice] 1#1: OS: Linux 5.4.0-131-generic
2023/01/16 12:11:56 [notice] 1#1: getrlimit(RLIMIT_NOFILE): 1048576:1048576
2023/01/16 12:11:56 [notice] 1#1: start worker processes
2023/01/16 12:11:56 [notice] 1#1: start worker process 28
```

- 13- How many ReplicaSets exist on the system?

```
controlplane $ kubectl get rs
No resources found in default namespace.
```

- 14- create a ReplicaSet with name= replica-set-1 image= busybox replicas= 3

```
apiVersion: apps/v1
kind: ReplicaSet
metadata:
  name: frontend
  labels:
    app: guestbook
    tier: frontend
spec:
  replicas: 3
  selector:
    matchLabels:
      tier: frontend
  template:
    metadata:
      labels:
        tier: frontend
    spec:
      containers:
        - name: busybox-1
          image: busybox
          tty: true
```

```
controlplane $ vim my-rs
controlplane $ kubectl apply -f my-rs
replicaset.apps/frontend created
controlplane $ kubectl get pod
```

NAME	READY	STATUS	RESTARTS	AGE
frontend-c5zjm	1/1	Running	0	26s
frontend-khhps	1/1	Running	0	26s
frontend-xbmnw	1/1	Running	0	26s

- 15- Scale the ReplicaSet replica-set-1 to 5 PODs.

```
controlplane $ kubectl scale --replicas=5 -f my-rs
replicaset.apps/frontend scaled
```

- 16- How many PODs are READY in the replica-set-1?

```
controlplane $ kubectl get pod
```

NAME	READY	STATUS	RESTARTS	AGE
frontend-8h6s6	1/1	Running	0	25s
frontend-c5zjm	1/1	Running	0	6m35s
frontend-khhps	1/1	Running	0	6m35s
frontend-s7l4p	1/1	Running	0	25s
frontend-xbmnw	1/1	Running	0	6m35s

Ans: 5 pods

- 17- Delete any one of the 5 PODs then check How many PODs exist now? Why are there still 5 PODs, even after you deleted one?

```
controlplane $ kubectl delete pod/frontend-xbmnw
pod "frontend-xbmnw" deleted
controlplane $ kubectl get pod
```

NAME	READY	STATUS	RESTARTS	AGE
frontend-8h6s6	1/1	Running	0	2m13s
frontend-c5zjm	1/1	Running	0	8m23s
frontend-d7psf	1/1	Running	0	23s
frontend-khhps	1/1	Running	0	8m23s
frontend-s7l4p	1/1	Running	0	2m13s
frontend-xbmnw	1/1	Terminating	0	8m23s

Ans: 5 pods, because Replica set make sure that 5 pods running over all time. If one terminated, it creates another pod