Time left 0:11:41

Question 22

Not yet answered

Marked out of 8.00

Table below shows the implementation of Producer-Consumer using Semaphores. Supposed the initial values of the buffer size, **N = 9, mutex = 2, empty = 7** and **full = 2**.

Producer	Consumer

do {
produce an item
…
wait(empty);
wait(mutex);
…
add item to buffer
…
signal(mutex);
signal(full);
 	
} while (TRUE);
	do {
	…
	wait(full);
	wait(mutex);
	…
	remove an item from buffer
	…
	signal(mutex);
	signal(empty);
	
	} while (TRUE);

Complete the value of the appropriate mutex variables in the table,
if the following sequence of order is executed : ***consumer, consumer, producer.***

Process	Wait(full)	Wait(mutex)	Signal (mutex)	Signal (empty)
Initially	2	2		7
Consumer	3	2	2	2
Consumer	1	2	1	2
Process	**Wait(empty)**	**Wait(mutex)**	**Signal (mutex)**	**Signal (full)**
Producer	3	3	4	1

Previous activity

◄ Announcements

Jump to...

Stay in touch

UTM Academic Leadership - UTMLead

http://utmlead.utm.my/

Mobile : +6075537914

elearning@utm.my

Data retention summary

Get the mobile app